Appearance Similarity Learning for Multi-Person Tracking and Re-Identification

by

María José Gómez Silva

A dissertation submitted by in partial fulfillment of the requirements for the
degree of Doctor of Philosophy in
Electrical Engineering, Electronics and Automation

Universidad Carlos III de Madrid

Advisors:

Prof. José María Armingol Moreno

Prof. Arturo de la Escalera Hueso

Tutor:

Prof. José María Armingol Moreno

November 2019

A mis padres

Declaration

I hereby declare that except where specific reference is made to the work of others, the contents of this thesis are my original work toward the degree of Doctor of Philosophy at Universidad Carlos III de Madrid. This thesis is my own work and contains nothing which is the outcome of work done in collaboration with others, except as specified in the text.

María José Gómez Silva
November 2019

Agradecimientos

Gracias a mis directores de tesis por toda su dedicación y ayuda. Gracias por confiar en mí y por brindarme la oportunidad de vivir experiencias únicas, que me han hecho crecer profesional y personalmente. Gracias por hacer que trabajar en lo que más me gusta sea posible.

Gracias a mis compañeros por convertir esta etapa un camino interesante a la par que divertido. Gracias por hacer que forme parte de este gran equipo.

Gracias a todas esas personas que siempre me han animado a cumplir mis metas, a los que me han apoyado para lograrlas y a aquellos que fueron fuente de inspiración.

Gracias a Dani por cambiar mi forma de concebir el mundo, por sacar lo mejor de mí, por darme fuerzas, por estar siempre ahí. Gracias a ti por compartir. Compartir momentos, ideas, ilusiones, penas y alegrías, compartir una vida. Gracias por hacerme feliz.

Gracias a mi hermano por cuidar de mí, soportarme, entenderme, ser mi consejero, por ser mi compañero de batalla durante esta etapa, y un ejemplo a seguir. Gracias por contagiarme de alegría. Gracias por ser como eres.

Gracias a mis padres por TODO, por traerme hasta aquí y hacer esto posible. Mi suerte es el reflejo de su trabajo. Gracias por dejarme volar y ser la red que da seguridad. Gracias por enseñarme. Gracias por hacer que viva mis sueños y llenar mi memoria de recuerdos bonitos.

Published and Submitted Content

Published journal articles ¹:

1. **Gómez-Silva, M. J.**, Izquierdo, E., Escalera, A. D. L., and Armingol, J. M. (2019). Transferring learning from multi-person tracking to person re-identification. Integrated Computer-Aided Engineering, (Preprint), 1-16.IOS Press. DOI: 10.3233/ICA-190603, [132].

This article has been partially included in this thesis, in Chapters 2, 4 and 6. The inclusion in the thesis of material from this source is specified in a footnote to each chapter where an inclusion occurs. The material from this source included in this thesis is not singled out with typographic means and references.

2. **Gómez-Silva, M. J.**, Armingol, J. M., and de la Escalera, A. (2019). Balancing people re-identification data for deep parts similarity learning. Journal of Imaging Science and Technology. Journal of Imaging Science and Technology, Volume 63, Number 2, March 2019, pp. 20401-1-20401-14(14), Society for Imaging Science and Technology, DOI: <https://doi.org/10.2352/J.ImagingSci.Technol.2019.63.2.020401>, [131].

This article has been partially included in this thesis, in Chapters 2, 4 and 6. The inclusion in the thesis of material from this source is specified in a footnote to each chapter where an inclusion occurs. The material from this source included in this thesis is not singled out with typographic means and references.

3. Al-Kaff, A., **Gómez-Silva, M. J.**, Moreno, F. M., de la Escalera, A., and Armingol, J. M. (2019). An Appearance-Based Tracking Algorithm for Aerial Search and Rescue Purposes. Sensors, 19(3), 652. Multidisciplinary Digital Publishing Institute, <https://doi.org/10.3390/s19030652>, [3].

This article has been partially included in this thesis, in Chapter 5. The inclusion in the thesis of material from this source is specified in a footnote to each chapter where an inclusion occurs. The material from this source included in this thesis is not singled out with typographic means and references.

¹ Articles' authors are listed by relative contribution. The name of this thesis's author is marked in bold to easily describe her participation.

4. **Gómez-Silva, M. J.**, García, F., Martín, D., de la Escalera, A., and Armingol, J. M. (2015). Intelligent surveillance of indoor environments based on computer vision and 3D point cloud fusion. *Expert Systems with Applications*, 42(21), 8156-8171, Elsevier. <https://doi.org/10.1016/j.eswa.2015.06.026>. [125].

This article has been partially included in this thesis, in Chapters 1 and 2. The inclusion in the thesis of material from this source is specified in a footnote to each chapter where an inclusion occurs. The material from this source included in this thesis is not singled out with typographic means and references.

Published conference articles¹:

5. **Gómez-Silva, M. J.**, Armingol, J. M., and de la Escalera, A. (2018). Deep Parts Similarity Learning for Person Re-Identification. In *Proceedings of the 13th International Conference on Computer Vision Theory and Applications (VISIGRAPP 2018) (5: VISAPP)* (pp. 419-428). DOI: 10.5220/0006539604190428, ISBN: 978-989-758-290-5. [129].

This article has been partially included in this thesis, in Chapters 2, 4 and 6. The inclusion in the thesis of material from this source is specified in a footnote to each chapter where an inclusion occurs. The material from this source included in this thesis is not singled out with typographic means and references.

6. **Gómez Silva, M. J.**, Armingol, J. M., and de la Escalera, A. (2018). Re-identificación de personas mediante la distancia de Mahalanobis. *Actas de las XXXIX Jornadas de Automática*, Badajoz, 5-7 de Septiembre de 2018. Universidad de Extremadura. URI: <http://hdl.handle.net/10662/8794>. [130].

This article has been partially included in this thesis, in Chapters 2, 4 and 6. The inclusion in the thesis of material from this source is specified in a footnote to each chapter where an inclusion occurs. The material from this source included in this thesis is not singled out with typographic means and references.

7. Morales-Álvarez, W., **Gómez-Silva, M. J.**, Fernández-López, G., García-Fernández, F., and Olaverri-Monreal, C. (2018). Automatic Analysis of Pedestrian's Body Language in the Interaction with Autonomous Vehicles. In *2018 IEEE Intelligent Vehicles Symposium (IV)*, Changshu, China. (pp. 1-6). IEEE. DOI: 10.1109/IVS.2018.8500425, ISSN: 1931-0587. [241].

This article has been partially included in this thesis, in Chapter 5. The inclusion in the thesis of material from this source is specified in a footnote to each chapter

where an inclusion occurs. The material from this source included in this thesis is not singled out with typographic means and references.

8. **Gómez-Silva, M. J.**, Armingol, J. M., and de la Escalera, A. (2017). Multi-object tracking errors minimisation by visual similarity and human joints detection. 25-30. 8th International Conference on Imaging for Crime Detection and Prevention (ICDP 2017), Madrid, Spain. IET. DOI: 10.1049/ic.2017.0044, ISBN: 978-1-78561-687-7. [127].

This article has been partially included in this thesis, in Chapters 2, 5 and 6. The inclusion in the thesis of material from this source is specified in a footnote to each chapter where an inclusion occurs. The material from this source included in this thesis is not singled out with typographic means and references.

9. **Gómez-Silva, M. J.**, Armingol, J. M., and de la Escalera, A. (2017). Deep part features learning by a normalised double-margin-based contrastive loss function for person re-identification. In Proceedings of the 12th International Conference on Computer Vision Theory and Applications (VISIGRAPP 2017) (Vol. 7, pp. 277-285). SCITEPRESS. DOI: 10.5220/0006167002770285, ISBN: 978-989-758-227-1. [128].

This article has been partially included in this thesis, in Chapters 2, 4 and 6. The inclusion in the thesis of material from this source is specified in a footnote to each chapter where an inclusion occurs. The material from this source included in this thesis is not singled out with typographic means and references.

10. **Gómez-Silva, M. J.**, Armingol, J. M., and de la Escalera, A. (2016). Multi-object tracking with data association by a similarity identification model. 25-6. 7th International Conference on Imaging for Crime Detection and Prevention (ICDP 2016), Madrid, Spain. IET. DOI: 10.1049/ic.2016.0093, ISBN: 978-1-78561-400-2. [126].

This article has been partially included in this thesis, in Chapters 2, 5 and 6. The inclusion in the thesis of material from this source is specified in a footnote to each chapter where an inclusion occurs. The material from this source included in this thesis is not singled out with typographic means and references.

Submitted conference articles¹:

- II. **Gómez-Silva, M. J.**, Armingol, J. M., and de la Escalera, A. (Under revision). Triplet Permutation Method for Deep Learning of Single-Shot Person Re-Identification. 9th International Conference on Imaging for Crime Detection and Prevention (ICDP 2019), London, UK.

This article has been partially included in this thesis, in Chapters 2, 5 and 6. The inclusion in the thesis of material from this source is specified in a footnote to each chapter where an inclusion occurs. The material from this source included in this thesis is not singled out with typographic means and references.

Other Research Merits

1. Grant from the Ministry of Education's University Faculty Training programme of the Spanish Government (FPU14/02143). From the 9th of September of 2015 to the 9th of September of 2019.
2. International Research Stay at MultiMedia Research Group from Queen Mary University of London, with a grant from the Ministry of Education's Short stays and temporary transfers programme. From the 9th of April of 2018 to the 8th of July of 2018.
3. Deep Learning Specialization, composed by the courses: Neural Networks and Deep Learning; Improving Deep Neural Networks: Hyperparameter tuning, Regularization and Optimization; Structuring Machine Learning Projects; Convolutional Neural Networks; Sequence Models . Certificated by Coursera, with a score of 100%. February of 2018.
4. Accesit at the Infaimon Prize for Best Computer Vision Work among those presented in the Jornadas de Automática 2018, for the work "Re-identificación de personas mediante la distancia de Mahalanobis", by María José Gómez Silva, José María Armingol Moreno and Arturo de la Escalera Hueso. The 7th of September of 2018.
5. Best Student Paper Prize at 8th International Conference on Imaging for Crime Detection and Prevention (ICDP 2017), for the work "Multi-Object Tracking Errors Minimisation by Visual Similarity and Human Joints Detection", by María José Gómez Silva, José María Armingol Moreno and Arturo de la Escalera Hueso. The 15th of December of 2017.
6. Best Poster Presentation Prize at 7th International Conference on Imaging for Crime Detection and Prevention (ICDP 2016), for the work "Multi-Object Tracking with Data Association by a Similarity Identification Model", by María José Gómez Silva, José María Armingol Moreno and Arturo de la Escalera Hueso. The 25th of November of 2016.

Abstract

In a changing world, where the presence of video-surveillance sensors is a continuously growing phenomenon, the research on Intelligent Surveillance Systems has been prompted by the necessity of automatically managing the huge amount of captured data. These systems assist or even replace traditional surveillance based on a human operator's observation, with the ultimate purpose of increasing the monitoring effectiveness and reducing costs.

The automation of the simultaneous tracking of multiple individuals within a wide monitoring area, and even, through several non-overlapping camera views, poses a challenging landmark, whose achievement is essential for the Surveillance endeavour in distributed networks of cooperative cameras.

Due to the unavailability of fine-biometrics cues, and the difficulty to establish temporal and spatial constraints in a network of non-overlapped and distant sensors, people tracking relies on visual data, posing a demanding goal for computer vision and artificial intelligence.

Besides that, the presence of frequent individuals' occlusions and interactions, in unconstrained and crowded scenarios, makes insufficient the use of algorithms relying only on motion cues and turns the individuals' appearance into valuable information to recognise people across a sequence of frames from the same or multiple camera views.

This thesis states and discuss the approach of addressing Multi-Person Tracking (MOT) and Re-Identification (Re-Id) through the learning of the Degree of Appearance Similarity (DoAS).

Instead of individually modelling every individual's appearance, the proposed DoAS model treats the identification problem as a pair-wise binary classification task. The DoAS model compares two images and determines whether they belong to the same person or not, so it is able to identify any unknown individual, which is an essential capacity given the unpredictable nature of the surveillance task in real unstructured scenarios.

The capacity of the DoAS metric to identify a person from only a pair of images has been exploited to perform both, Single-Shot Person Re-Identification, and online (frame-by-frame) data association for Multi-Object Tracking (MOT).

The properties of the Degree of Appearance Similarity measurement make it suitable for performing the data association process of a tracking algorithm, i.e. the assignment of identities to the people detected in every frame. The DoAS function has been integrated into a novel cascade data

association method, based on the hierarchical proposal of multiple global assignment hypotheses. This method is the core of a developed Multi-Object Tracking algorithm and provides the ability to manage multiple agents, and to deal with crossings, changing trajectory individuals, and partial and total occlusions for short and long term.

Furthermore, with the aim of coping with long-term disappearances and multiple-camera settings, a Re-identification module has also been designed, under the paradigm of Single-Shot recognition from only a pair of images, in order to reduce the quantity of data transmitted among co-operative sensors.

The Degree of Appearance Similarity has been modelled by Deep Convolutional Neural Networks, following a Siamese and a Triplet Architecture.

The recognition of a person by means of an appearance neural model arises incipient barriers due to its intrinsically unbalanced nature, given the lack of data about the people to identify and the huge number of possible false assignments with surrounding agents. This results in the over-fitting and the collapse of the deep neural models used to render the visual appearance. These problems have been appalled by the formulation of novel data feeding techniques, including the Triplet Permutation method, and the innovative idea of transferring learning from MOT to Re-iD domain.

Resumen

En un mundo cambiante, donde la presencia de sensores de videovigilancia es un fenómeno en continuo crecimiento, la investigación en sistemas de vigilancia inteligentes es promovida por la necesidad de gestionar automáticamente la enorme cantidad de datos capturados. Estos sistemas ayudan o incluso reemplazan los sistemas tradicionales basados en la observación de un operador humano, con el propósito final de aumentar la efectividad de la monitorización y reducir los costos.

La automatización del seguimiento simultáneo de múltiples individuos dentro de una amplia área de monitorización, e incluso, a través de varias cámaras con campos de visión no superpuestos, plantea un hito desafiante, cuyo logro es esencial para las labores de vigilancia en redes distribuidas de cámaras cooperativas.

Dada la falta de disponibilidad de signos biométricos precisos y la dificultad para establecer restricciones espaciotemporales en redes de sensores distantes y con vistas no superpuestas, el seguimiento de personas se ampara en datos visuales, lo que plantea una meta exigente para la visión por computador y la inteligencia artificial.

Además de esto, la presencia de frecuentes oclusiones e interacciones entre individuos, en escenarios no estructurados y concurrenciosos, hace que el uso de algoritmos basados en movimiento sea insuficiente y presenta la apariencia como una información valiosa para reconocer personas a través de fotogramas de la misma o múltiples cámaras.

Esta tesis establece y discute el enfoque consistente en abordar el seguimiento de múltiples personas (Multi-Object Tracking, MOT) y su re-identificación (Person Re-Identification, Person Re-Identification (Re-Id)) a través del aprendizaje del grado de similitud de apariencia, (Degree of Appearance Similarity, Degree of Appearance Similarity (DoAS)).

En lugar de modelar la apariencia de cada individuo independientemente, el modelo propuesto trata el problema de la identificación como una tarea de clasificación binaria por pares. El modelo DoAS compara dos imágenes y determina si pertenecen a la misma persona o no, por lo tanto, es capaz de identificar cualquier individuo desconocido, lo cual es una capacidad esencial dada la naturaleza impredecible de la tarea de vigilancia en escenarios no estructurados.

La capacidad de la medida DoAS para identificar a una persona a partir de solamente un par de imágenes ha sido explotada para realizar tanto re-identificación con una sola captura, como

asociación de datos online (fotograma a fotograma) para un algoritmo de seguimiento de múltiples personas.

Las propiedades de la medida del grado de similitud de apariencia hacen que esta métrica sea apropiada para realizar el proceso de asociación de datos de un algoritmo de seguimiento, o lo que es lo mismo, la asignación de identidades a las personas detectadas en cada fotograma. La función DoAS ha sido integrada en un novedoso método de asignación de datos en cascada, basado en la propuesta jerárquica de múltiples hipótesis de asignaciones globales. Este método es el núcleo del algoritmo de seguimiento desarrollado y le proporciona la habilidad para gestionar múltiples agentes y lidiar con cruces entre individuos, personas con trayectorias cambiantes, y oclusiones totales o parciales durante cortos y largos intervalos de tiempo.

Además, con el objetivo de hacer frente a desapariciones duraderas y a configuraciones de múltiples cámaras, un módulo de re-identificación ha sido diseñado bajo el paradigma del reconocimiento a partir de una única captura, para reducir la cantidad de datos transmitidos entre sensores cooperativos.

El grado de similitud de apariencia se ha modelado con redes neuronales convolucionales profundas siguiendo las arquitecturas siamesa y trilliza.

El reconocimiento de una persona por medio de un modelo neuronal de apariencia implica ciertas dificultades debido a su naturaleza intrínsecamente desequilibrada, dada la falta de datos sobre las personas a identificar y la enorme cantidad de posibles falsas asignaciones con los agentes que las rodean. Esto da como resultado, el sobreajuste y el colapso de los modelos neuronales profundos usados para representar la apariencia visual. Estos problemas han sido paliados con la formulación de novedosas técnicas para alimentar los modelos, entre las que se encuentra el método de permutación de ternas y la idea innovadora de transferir el aprendizaje del ámbito del seguimiento de personas al ámbito de la re-identificación.

Table of contents

List of acronyms	xxv
List of figures	xxxii
List of tables	xxxvii
1 Introduction	I
1.1 Social, Economical and Political Context	I
1.1.1 European Research Programmes	5
1.2 Research and technological background	7
1.2.1 Intelligent Surveillance Systems	7
1.2.2 Deep Learning	9
1.3 Problem Statement	II
1.3.1 Multi-Object Tracking Challenges	12
1.3.2 Person Re-identification Challenges	13
1.4 Motivation	15
1.5 Objectives	16
1.6 Outline of the dissertation	17
2 Literature Review	19
2.1 Multi-Object Tracking	19
2.1.1 Tracking-by-Detection	20
2.1.2 Person Detectors	21
2.1.3 State Estimation and Gating	23
2.1.4 Data Association Method	24
2.1.5 Cost Functions	28
2.1.6 Modelling People	29
2.1.7 Temporal Consistency	32
2.1.8 Multi-Target Multi-Camera Tracking	33

2.1.9	Conclusion	34
2.2	Person Re-Identification	36
2.2.1	Person Re-identification as a Pair-wise Classification Task	37
2.2.2	Features Designing	37
2.2.3	Metric Learning	39
2.2.4	Deep Re-Identification Neural Models	43
2.2.5	Siamese and Triplet model	44
2.2.6	Supervised vs Unsupervised Learning for Re-Identification	45
2.2.7	Transfer Learning	46
2.2.8	Facing Over-fitting	48
2.2.9	Balancing Re-Identification Data	49
2.2.10	Conclusion	50
2.3	Contributions	51
2.3.1	Research contribution on Multi-Object Tracking field	52
2.3.2	Research contribution on Person Re-Identification field	56
3	Methodology	63
3.1	Approach: Learning the Degree of Appearance Similarity (DoAS)	63
3.2	Development Framework	64
3.2.1	Concepts	64
3.2.2	Development Framework Architecture	65
3.2.3	Programming Tools	67
3.3	Datasets	68
3.3.1	Re-Identification Datasets	68
3.3.2	Multi-Object Tracking datasets	72
3.4	Data Generation Module	74
3.5	Training and Testing Framework	75
3.5.1	Feature Computation Module	76
3.5.2	Learning Algorithm	76
3.6	Applications	79
4	Person Re-Identification	81
4.1	Deep Convolutional Neural Network Architecture	82
4.2	Siamese Model	84
4.2.1	Siamese Architecture	85
4.2.2	Normalised Double-Margin-based Contrastive Loss Function	86
4.2.3	Pairs Mini-Batch Learning	89

4.3	Balancing Re-Identification Data	92
4.4	Triplet Model	93
4.4.1	Triplet Loss and Architecture	93
4.4.2	Triplet Mini-Batch Learning	95
4.4.3	Triplets Selection	97
4.4.4	Triplet Loss vs. Contrastive Loss	99
4.4.5	Model Over-fitting	100
4.5	Triplet Feeding	101
4.5.1	Triplets Permutation	101
4.5.2	Data Shuffling	107
4.5.3	Data Augmentation	107
4.6	Regularization	110
4.6.1	Loss Regularization	110
4.6.2	Dropout	113
4.6.3	Early Stopping	113
4.6.4	Normalisation	113
4.7	Transfer Learning	115
4.7.1	Transfer learning from Multi-Object Tracking domain	118
4.7.2	Transfer Learning from Cross-Re-Identification Dataset	119
4.8	Human Shape Partition	120
4.8.1	Three independently learnt part-features	121
4.8.2	Nine jointly learnt part-features	125
4.8.3	Three jointly learnt part-features	129
4.9	Mahalanobis Distance as the Distance Metric	132
4.9.1	Discriminative Mahalanobis Matrix Estimation	132
4.9.2	Mahalanobis Matrix Learning	137
4.9.3	Integration of the Mahalanobis distance computation as the distance metric into the feature learning process	140
4.10	Other Applications	141
4.10.1	Facial Recognition	141
4.10.2	Multi-Object Tracking	142
5	Multi-Object Tracking	143
5.1	Multi-Object Tracking Algorithm Architecture	144
5.2	Multi-Agent Management	146
5.2.1	Structures	146
5.2.2	Creation and Removal of an Agent	148

5.2.3	Updating Rule	151
5.3	Detection	152
5.4	State Estimation	153
5.5	Data Association	155
5.5.1	Individual Data Association	157
5.5.2	Global Data Association	157
5.5.3	Cascade Data Association	159
5.5.4	Global Hypotheses Generator	166
5.6	Degree of Appearance Similarity, DoAS	172
5.6.1	Hand-Crafted Single-Shot DoAS	173
5.6.2	Deeply Learnt Single-Shot DoAS	177
5.6.3	Deeply learnt Multi-Shot DoAS	178
5.6.4	Deeply learnt Single-Shot Multi-View DoAS, Single-Shot Multi-View Degree of Appearance Similarity (SS-MV-DoAS)	186
5.7	Skeleton Analysis	186
5.7.1	Skeleton attribute	188
5.7.2	Human Joints Detection Algorithm	189
5.7.3	Human Shape Validation (HSV)	189
5.7.4	Detection-by-tracking (DBT)	190
5.8	Multi-Target Multi-Camera Tracking	190
5.9	Other Applications	191
5.9.1	Appearance-Based Tracking for Aerial Search and Rescue	191
5.9.2	Analysis of Pedestrian's Body Language in the Interaction with Autonomous Vehicles	193
6	Experimental Results	195
6.1	Orthogonalization methodology	195
6.2	Person Re-identification Experiments	195
6.2.1	Datasets Protocol	196
6.2.2	Methodology to Evaluate the Learning Process	197
6.2.3	Methodology to evaluate the Re-Id performance	200
6.2.4	Experimental results	201
6.2.5	Final results	235
6.2.6	Results Comparison and Discussion	244
6.2.7	Computational time	249
6.3	Multi-Object Tracking Experiments	249
6.3.1	Datasets Protocols	250

6.3.2	Methodology to Evaluate the Appearance Model	251
6.3.3	Methodology to Evaluate the Multi-Object Tracking Performance . . .	252
6.3.4	Experimental results of evaluating the Appearance models	254
6.3.5	Experimental results of evaluating the Multi-Object Tracking	263
6.3.6	Results Comparison and Discussion	269
6.3.7	Computational time	272
6.4	Experiments on other applications	273
6.4.1	Facial Recognition Experiments	274
6.4.2	Aerial Search and Rescue Experiments	278
7	Conclusions and Future Work	281
7.1	Conclusions	281
7.2	Future Work	284
	References	287
	Appendix A Notation	315
A.1	Deep Learning notation	315
A.2	Multi-Agent Tracking algorithm notation	316
	Appendix B Architecture of the three jointly learnt parts-features model.	319
	Appendix C MOT algorithm Architecture	321

List of acronyms

ACF Aggregate Channel Features

ADVISOR Annotated Digital Video for Intelligent Surveillance and Optimized Retrieval

AI Artificial Intelligence

aPRDC attributes Probabilistic Relative Distance Comparison

ARGUS-IS Autonomous Real-Time Ground Ubiquitous Surveillance Imaging System

ARMOT Aerial Rescue Multi-Object Tracking

BAIR Berkeley AI Research

BoW Bag-of-Words

BTF Brightness Transfer Function

CAGR Compound Annual Growth Rate

Caffe Convolutional architecture for fast feature embedding

CAVIAR Context Aware Vision using Image-based Active Recognition

CCTV Closed-Circuit Television

CLEAR CLassification of Events, Activities and Relationships

CMC Cumulative Matching Characteristic

CNN Convolutional Neural Network

CPM Convolutional Pose Machine

CRAFT Camera coRrelation Aware Feature augmenTation

- CRC** Cascaded Rejection Classifiers
- CUHK** Chinese University of Hong Kong
- DARPA** Defense Advanced Research Projects Agency
- DBN** Deep Belief Network
- DBT** Detection-By-Tracking
- DCNN** Deep Convolutional Neural Network
- DDC** Descriptive and Discriminative Classification
- DETER** Detection of Events for Threat Evaluation and Recognition
- DFL** Decision Function Learning
- DoAS** Degree of Appearance Similarity
- DPF** Decentralized Particle Filter
- DPM** Deformable Part Model
- DPSL** Deep Parts Similarity Learning
- EIML** Efficient Impostor-based Metric Learning
- ELF** Ensemble of Localized Features
- EMD** Earth Mover's Distance
- EU** European Union
- EWMA** Exponentially Weighted Moving Average
- FC** Fully Connected
- FIFO** First In, First Out
- FPR** False Positive Rate
- GD** Gradient Descent
- GFI** Global Feature Importance
- GNN** Global Nearest Neighbor

GoP Group of Personalities

GPU Graphic Processing Unit

GRID underGround Re-IDentification

HCSS-DoAS Hand-Crafted Single-Shot Degree of Appearance Similarity

hGPLVM hierarchical Gaussian Process Latent Variable Model

HOG Histogram of Oriented Gradients

HSV Human Shape Validation

ICT Implicit Camera Transfer

i-LIDS Imagery Library for Intelligent Detection Systems

ISS Intelligent Surveillance System

ITML Information Theoretic Metric Learning

JPDAF Joint Probabilistic Data Association Filters

KISSME Keep It Simple and Straightforward Metric

LADF Locally Adaptive Thresholding Function

LBP Local Binary Patters

LDA Linear Discriminant Analysis

LDML Logistic Discriminant Metric Learning

LMNN Large Margin Nearest Neighbor

LMNN-R Large Margin Nearest Neighbor with Rejection

LRN Local Response Normalization

LSTM Long-Short Term Memory

MCMC Markov Chain Monte Carlo

MHT Multiple Hypotheses Tracking

MOT Multi-Object Tracking

MOTA Multi-Object Tracking Accuracy

MOTP Multi-Object Tracking Precision

MPEG Moving Picture Experts Group

MRank Manifold Ranking

MS-CNN Multi-Scale Convolutional Neural Network

MSCR Maximally Stable Color Regions

MS-DoAS Multi-Shot Degree of Appearance Similarity

MTMCT Multi-Target Multi-Camera Tracking

MWIS Maximum Weighted Independent Set

NCA Neighborhood Component Analysis

N₂MCL Normalised Double-Margin-based Contrastive Loss

OTHR Over-The-Horizon Radar

PAL Phase Alternating Line

PASR Preparatory Action in the field of Security Research

PCA Principal Component Analysis

PCCA Pairwise Constrained Component Analysis

PDAF Probabilistic Data Association Filters

PLS Partial Least Squares

PPV Positive Predictive Value

PRDC Probabilistic Relative Distance Comparison

PRID₂₀₁₁ Person Re-IDentification 2011

PRISMATICA PRo-active Integrated systems for Security MAnagement by Technological Institutional and Communication Assistance

PS Pictorial Structures

PSFI Prototype-Sensitive Feature Importance

QMUL Queen Mary University of London

RankSVM Ranking Support Vector Machine

RCD Region Covariance Descriptor

Re-Id Person Re-Identification

ReLU Rectified Linear Unit

R-CNN Region-based Convolutional Neural Network

RJMCMC Reversible Jump Markov Chain Monte Carlo

RNN Recurrent Neural Network

ROC Relative Operating Characteristic

RPN Region Proposal Network

RTD Research and Technological Development

SAC Switcher-Aware Classifier

SDALF Symmetry-Driven Accumulation of Local Features

SDP Scale Dependent Pooling

SGD Stochastic Gradient Descent

SOT Single Object Tracking

SPPNet Spatial Pyramid Pooling Network

SSD Single-Shot Detector

SS-DoAS Single-Shot Degree of Appearance Similarity

SS-MV-DoAS Single-Shot Multi-View Degree of Appearance Similarity

SVM Support Vector Machine

TCA Transfer Component Analysis

TFLDA Transference to Fisher Linear Discriminant Analysis

TPR True Positive Rate

USD United States Dollar

VGG Visual Geometry Group

VIPeR Viewpoint Invariant Pedestrian Recognition

VLBP Volume Local Binary Patterns

VSAM Video Surveillance and Monitoring

XQDA Cross-view Quadratic Discriminant Analysis

List of figures

1.1	What are the main risk/threats for the European Union in the coming years? (% - EU). Source:Eurobarometer 464b [68], QA6.	2
1.2	What are the main risk/threats for the European Union in the coming years? (% - the most mentioned answer by country). Source:Eurobarometer 464b [68], QA6.	3
1.3	What do you think are the most important issues facing (OUR COUNTRY) at the moment? (% - EU). Source: Standard Eurobarometer 90 [70], QA3a.	3
1.4	Scale driving Deep Learning Progress graph, recreated from [249].	10
1.5	Tracking errors. Colours of individuals' silhouettes render their identities, and the colours of the bounding boxes, the identities given by a hypothetical tracker algorithm.	13
2.1	Stages of a multi-object tracking-by-detection algorithm.	20
2.2	Summarising chart of data association methods for MOT. Methods listing is shaded. Benefits are indicated with symbol '+' and drawbacks with '-', in white column.	34
2.3	Summarising chart of modelling methods for MOT. Methods listing is shaded. Benefits are indicated with symbol '+' and drawbacks with '-', in white column.	35
2.4	Examples of matched pairs belonging to PRID2011 (a), and VIPeR dataset (b).	36
2.5	Summarising chart of data association methods for Single-Shot Re-Id. Methods listing is shaded. Benefits are indicated with symbol '+' and drawbacks with '-', in white column.	50
3.1	Development framework architecture	66
3.2	Example images of the PRID2011 dataset. Each column renders a person's pair of images.	69
3.3	Example images of the VIPeR dataset. Each column renders a person's pair of images.	70

3.4	Example images of the CUHK dataset. Each column renders a person's pair of images.	70
3.5	Example images of the GRID dataset. Each column renders a person's pair of images.	71
3.6	Example images of the i-LIDS-VID dataset. Each column renders a person's pair of images.	72
3.7	Architecture of the Data Generation module.	74
4.1	Re-identification method.	82
4.2	Architecture of the Siamese model.	85
4.3	Loss contribution of a positive, e_p , and negative, e_n , single pair sample to the contrastive loss function (Eq. 4.3), with $m=1.5$	87
4.4	Loss contribution of a positive, e_p , and negative, e_n , single pair sample to the N2MCL function (Eq.4.7): a) without normalisation and $m_1 = 1$ and $m_2 = 2$ and b) with normalisation and $m_1 = 0.3$ and $m_2 = 0.7$	88
4.5	Loss function evaluated over a validation set of samples throughout the training process: a) using the traditional contrastive loss function, (Eq. 4.3); and b) using the double-margin contrastive loss function, (Eq.4.7).	89
4.6	Pair samples (at every column) from PRID2011 dataset.	93
4.7	Architecture of the Triplet model.	94
4.8	Learning curves for Siamese and Triplet model over PRID2011 and VIPeR datasets.	99
4.9	Training triplet sets generation, according to three formulations (Eq. 4.34, 4.35 and 4.36), from PRID2011 dataset.	103
4.10	Undesirable situations (a), (b), (c), and (d), represented in the feature space.	105
4.11	Solving of the undesirable situations s_a, s_b, s_c and s_d by imposing constraints c_1, c_2, c_3 and c_4 , all rendered in the feature space. In (0) no constraint is imposed. In (1), (2), (3), (4) constraints c_1, c_2, c_3 and c_4 are consecutively added.	107
4.12	L1 (a) and L2 (b) representation for the case of having only two weights to fix (W_1, W_2).	111
4.13	Contribution of the source (blue) and target (yellow) datasets on the learning of the weights of the different layers for an example model, and for given values of l_T and l_U	116
4.14	Triplet samples generated from MOT17 dataset.	118
4.15	Re-Identification Method Architecture based on three parts division.	121
4.16	Re-Identification Method Architecture based on the extraction of nine body-parts.	125
4.17	Body parts extracted before being resized.	126
4.18	Re-Identification Method Architecture based on three jointly learnt parts.	130

4.19	Siamese model to simultaneously train a DCNN and estimate the Mahalanobis Matrix.	133
4.20	Triplet model to simultaneously train a DCNN and estimate the Mahalanobis Matrix.	134
5.1	Multi-Object Tracking Algorithm Architecture.	145
5.2	Automatic agent's management mode.	149
5.3	Selection of candidates for a tracked agent. The predicted head location is rendered by a yellow point, and the detections selected as candidates are bounded by red boxes.	157
5.4	Architecture of the Cascade Data Association algorithm.	159
5.5	Agents classification.	161
5.6	Computation of the Appearance Similarity Descriptor	175
5.7	Extraction of training samples. Positive samples are joint by a green line, and negative samples, by a red line.	176
5.8	Computation of Multi-Shot Degree of Appearance Similarity, Multi-Shot Degree of Appearance Similarity (MS-DoAS), between a measurement, m_j , and an agent, a_i	179
5.9	MS-DoAS learning architecture.	180
5.10	Generation of Feature Tracklets Blobs.	182
5.11	Examples of the images from which tracklets of the set X_I are generated. Positive tracklets are underlined in green, and negatives, in red. f renders the number of the frame from which the first tracklet component was extracted, in the sequences of the MOT17 dataset.	183
5.12	MOT algorithm with Human Shape Validation and Detection-by-Tracking modules.	187
5.13	Skeleton attribute visualisation.	188
5.14	Computation of pose dissimilarity measure $f_j a_i m_j$: a) poses of an agent, $J a_i$, and a taken measurement, $J m_j$; b) rotated poses of the agent, $RJ a_i$, and the measurement, $RJ m_j$; c) rotated pose of the agent, $RJ a_i$, and rotated and translated pose of the measurement, $RTJ m_j$; d) joints distances	192
6.1	Loss function evaluated over a validation set of samples throughout the training process: a) using the traditional contrastive loss function, (Eq. 4.3); and b) using the double-margin contrastive loss function, (Eq.4.7).	203

6.2	Three-dimensional representation of learnt descriptors, in green for positive samples, and in red for the negative samples for a test set in the cases of training with: (a) One Margin Contrastive Loss function, (Eq. 4.3), and (b) Double-Margin Contrastive Loss function, (Eq. 4.7).	203
6.3	Cumulative Matching Characteristic (CMC) curves for the models learnt by three different Contrastive Loss functions.	204
6.4	CMC curves for the use of two balancing settings from a)PRID2011 and b)VIPeR dataset.	207
6.5	Learning curve and soft accuracy during the training with a proportion of 1 : 4 positive over negative samples.	208
6.6	CMC curves for the use of two learning models over a)PRID2011 and b)VIPeR dataset.	209
6.7	Learning curves for Siamese and Triplet model over PRID2011 and VIPeR datasets.	210
6.8	Learning curves for level 0 and 4 of transfer learning, using PRID2011 as target dataset.	211
6.9	Learning curves for level 0 and 4 of transfer learning, using VIPeR as target dataset.	211
6.10	CMC curves for six levels of transfer learning, over a) PRID2011 and b) VIPeR dataset.	212
6.11	Comparison of the learning process evolution for two Deep Convolutional Neural Networks (DCNNs) architectures (VGG16 and VGG11) over PRID2011 dataset.	214
6.12	Comparison of the learning process evolution for two DCNNs architectures (VGG16 and VGG11) over VIPeR dataset.	215
6.13	CMC curves for different DCNN architectures trained on PRID2011 dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).	215
6.14	CMC curves for different DCNN architectures trained on VIPeR dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).	216
6.15	CMC curves for VGG11 model with and without Local Response Normalization (LRN) cell over PRID2011 dataset,for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).	216
6.16	CMC curves for VGG11 model with and without LRN cell over VIPeR dataset,for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).	217
6.17	Comparison of the learning process evolution using training sets I, II and III over PRID2011 dataset.	218
6.18	Comparison of the learning process evolution using training sets I, II and III over VIPeR dataset.	219

6.19	CMC curves of models trained with different Triplets Permutation formulations from PRID2011 dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).	220
6.20	CMC curves of models trained with different Triplets Permutation formulations from VIPeR dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).	220
6.21	Comparison of the learning process evolution using data augmentation techniques I, II and II over PRID2011 dataset.	221
6.22	Comparison of the learning process evolution using data augmentation techniques I, II and II over VIPeR dataset.	222
6.23	CMC curves of models learnt by applying different data augmentation techniques on PRID2011 dataset, for the first 100 ranks (a), and detailed for the first 25 ranks (b).	223
6.24	CMC curves of models learnt by applying different data augmentation techniques on VIPeR dataset, for the first 100 ranks (a), and detailed for the first 25 ranks (b).	223
6.25	Comparison of the learning process evolution using L2 and L1 regularization with different weight decay values, wd , over PRID2011 dataset.	225
6.26	Comparison of the learning process evolution using L2 and L1 regularization with different weight decay values, wd , over VIPeR dataset.	226
6.27	CMC curves of models learnt by applying different regularization settings on PRID2011 dataset, for the first 100 ranks (a), and detailed for the first 25 ranks (b).	227
6.28	CMC curves of models learnt by applying different regularization settings on VIPeR dataset, for the first 100 ranks (a), and detailed for the first 25 ranks (b).	227
6.29	CMC curves of DCNN models with and without parts partition on PRID2011 dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).	229
6.30	CMC curves of DCNN models with and without parts partition on VIPeR dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).	229
6.31	Comparison of the learning process evolution using different Mahalanobis distance learning methods, over PRID2011 dataset.	231
6.32	Comparison of the learning curves using (a) ot not (b) the triplets selection layer.	232
6.33	CMC curves of models using Euclidean and Mahalanobis distance on PRID2011 dataset.	233
6.34	Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of PRID2011 dataset.	237
6.35	Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of VIPeR dataset, where correct match is found within the top 10 ranks.	238

6.36	Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of VIPeR dataset, where correct match is found between the top 11 and 20 ranks.	239
6.37	Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of CUHK-01 dataset, where correct match is found within the top 10 ranks.	240
6.38	Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of CUHK-01 dataset, where correct match is found between the top 11 and 20 ranks.	241
6.39	Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of GRID dataset.	242
6.40	Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of i-LIDS-VID dataset.	243
6.41	MOTA values for four different Hand-Crafted Single-Shot Degree of Appearance Similarity (HCSS-DoAS) models.	256
6.42	Relative Operating Characteristic (ROC) curves for Single-Shot Degree of Appearance Similarity (SS-DoAS) learnt with a Triplet and a Siamese model.	258
6.43	ROC curves from the evaluation of every MS-DoAS model on five different test sets (a), and zoomed region (b).	260
6.44	ROC curves from five different evaluations conducted for each one of the MS-DoAS models (a), and zoomed region (b).	261
6.45	People detectors comparison.	265
6.46	Comparison of data association methods.	266
6.47	Effect of Detection-By-Tracking (DBT) and Human Shape Validation (HSV) modules on the <i>MOTA</i> .	267
6.48	Examples of true positive pairs of faces images from FEI face dataset.	275
6.49	Examples of true negative pairs of faces images from FEI face dataset.	275
6.50	Examples of false positive pairs of faces images from FEI face dataset.	276
6.51	Examples of false negative pairs of faces images from FEI face dataset.	276
6.52	ROC curves of the face recognition model over two different test sets.	277
B.1	Architecture of the three jointly learnt parts-features model.	320
C.1	Architecture of Cascade Global Hypotheses Association-based Multi-Object Algorithm.	322
C.2	Architecture of Agent Management module.	323
C.3	Architecture of Association module.	324

List of tables

3.1	Details of the PRID2011, VIPeR, GRID, i-LIDS, and CUHK datasets. $\#probe$ and $\#gallery$ indicate the number of identities in these sets.	68
3.2	Details of the CAVIAR and MOT17 datasets. $\#seq$, $\#f$, $\#id$ indicate the number of sequences, total frames and total identities	72
4.1	Structure of the used VGG16-based model. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, or $\#outputs$ for FC layers.	83
4.2	Structure of the used VGG11-based model. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, or $\#outputs$ for FC layers.	84
4.3	Structure of the used VGG11LRN-based model. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, or $\#outputs$ for FC layers.	115
4.4	Set-up values for l_T and l_U , for every level of transfer learning.	117
4.5	Neural network architecture for the fist image division (head). The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, or $\#outputs$ for FC layers.	123
4.6	Neural network architecture for the fist image division (body). The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, or $\#outputs$ for FC layers.	123
4.7	Neural network architecture for the fist image division (legs). The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, or $\#outputs$ for FC layers.	124
4.8	Head neural network architecture. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, or $\#outputs$ for FC layers.	127

4.9	Arm neural network architecture. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, <i>stride</i> , or <i>#outputs</i> for FC layers.	128
4.10	Legs neural network architecture. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, <i>stride</i> , or <i>#outputs</i> for FC layers.	128
4.11	Weighting network structure. Dimensions are described in $\#rows \times \#cols \times \#filters$	129
4.12	VGG5 head DCNN architecture. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, <i>stride</i> , and <i>#outputs</i> for the FC layer.	130
4.13	VGG5 body DCNN architecture. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, <i>stride</i> , and <i>#outputs</i> for the FC layer.	131
4.14	VGG5 legs DCNN architecture. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, <i>stride</i> , and <i>#outputs</i> for the FC layer.	131
4.15	Weighting network structure. The sizes are described in $\#rows \times \#cols \times \#filters$	131
5.1	Tigger factors for the creation and destruction of an agent in each working mode.	149
5.2	DoAS Metrics.	173
5.3	SVM parameters.	176
6.1	Experiments settings to evaluate the effects of different contrastive loss functions.	202
6.2	CMC scores (%) for the models learnt by three different Contrastive Loss functions.	204
6.3	Experiments settings to evaluate different feature embeddings.	205
6.4	CMC scores (%) for different feature embeddings, over PRID2011 dataset.	205
6.5	Experiments settings to evaluate the effects of balancing the training data.	207
6.6	CMC scores (%) of models trained on two balance settings from PRID2011 and VIPeR dataset.	207
6.7	Experiments settings to evaluate the effects of Siamese and Triplet model.	209
6.8	CMC scores (%) for neural networks trained with two learning models on PRID2011 and VIPeR dataset.	209
6.9	Experiments settings to evaluate transfer learning technique.	211
6.10	CMC scores (%) for six levels of transfer learning, over PRID2011 and VIPeR.	212
6.11	Experiments settings to evaluate the effects of reducing the neural depth.	213
6.12	CMC scores (%) for different DCNN architectures trained on PRID2011 and VIPeR datasets.	214

6.13	CMC scores (%) of VGG11 with and without LRN, over PRID2011 and VIPeR dataset.	216
6.14	Experiments settings to evaluate the Triplet Permutation method.	217
6.15	CMC scores (%) for models trained on sets generated by different Triplets Permutation formulations from PRID2011 and VIPeR dataset.	219
6.16	Experiments settings to evaluate three data augmentation methods.	221
6.17	CMC scores (%) for models learnt by applying different data augmentation techniques over PRID2011 and VIPeR dataset.	223
6.18	Experiments settings to evaluate the effects of different regularization methods.	224
6.19	CMC scores (%) for models learnt by applying different regularization settings on PRID2011 and VIPeR dataset.	227
6.20	Experiments settings to evaluate the effects of partitioning the human shape.	228
6.21	CMC scores (in [%]) for DCNN models with and without parts partition on PRID2011 and VIPeR dataset.	228
6.22	Experiments settings to evaluate different distance metrics and methods to learn them.	230
6.23	CMC scores (in [%]) for models learnt by applying different Mahalanobis estimation methods on PRID2011 dataset.	233
6.24	CMC scores (in [%]) for models using Euclidean and Mahalanobis distance metric on PRID2011 dataset.	233
6.25	Experiments settings to evaluate the effects of training on a Cross-Re-Id dataset.	234
6.26	CMC scores (in [%]) for models learnt by applying different fine-tuning steps, evaluated over different Re-Id datasets.	234
6.27	Final re-identification strategies settings	236
6.28	CMC scores (in [%]) for the Re-Id models (each one trained and evaluated over the same datasets).	236
6.29	Comparison of CMC rates (in [%]) of Re-Id methods on PRID2011 dataset, ‘-’ indicates no result was reported.	244
6.30	Comparison of CMC rates (in [%]) of Re-Id methods on VIPeR dataset, ‘-’ indicates no result was reported.	245
6.31	Comparison of CMC rates (in [%]) of Re-Id methods on CUHK-01 dataset, ‘-’ indicates no result was reported.	245
6.32	Comparison of CMC rates (in [%]) of Re-Id methods on GRID dataset, ‘-’ indicates no result was reported.	246
6.33	Computational time of Re-Id models, ‘-’ indicates no result was calculated.	249

6.34	Precision (in [%]) of every classifier trained with $N = 1, 4, 7, 10$ over every test set ($n = 1 : 10$).	255
6.35	Recall (in [%]) of every classifier trained with $N = 1, 4, 7, 10$ over every test set ($n = 1 : 10$).	255
6.36	Experiments settings to evaluate the effects of training with different learning models.	257
6.37	Binary classification metrics for the SS-DoAS network learnt with a Siamese model.	257
6.38	Binary classification metrics for the SS-DoAS network learnt with a Triplet model.	258
6.39	Experiment settings to evaluate the effects of five different training sets of tracklets.	259
6.40	Maximum $F1$ score value (in [%]) for every MS-DoAS model, evaluated over five different test sets, and th value where it is achieved.	262
6.41	Maximum Accuracy, A , value (in [%]) for every MS-DoAS model, evaluated over five different test sets, and th value where it is achieved.	262
6.42	MOT algorithm settings.	264
6.43	Experiments settings to evaluate the effects of two different data association methods on the MOT performance	265
6.44	Experiments settings to evaluate the effects of DBT and HSV modules on the MOT performance	266
6.45	Detectors and MOT errors rates.	267
6.46	Multi-Object Tracking performance of algorithm MOT.2 over MOT17 dataset. $MOTA$, $MOTP$, FP , FN and ID_{sw} values.	268
6.47	Multi-Object Tracking performance of algorithm MOT.2 over MOT17 dataset. IDF_1 , FAF , MT , ML , and $Frag$ values.	269
6.48	MOT.1 results comparison.	270
6.49	Comparison of Multi-Object Tracking performance of MOT.2 with top 3 benchmarking algorithms over MOT17 dataset.	271
6.50	Comparison of Multi-Object Tracking performance of MOT.2 with top 3 online benchmarking algorithms over MOT17 dataset.	271
6.51	Computation time measurements (average values per iteration in seconds) for different stages and enhancements of the MOT system design, for MOT17-01-DPM sequence.	273
6.52	Binary classification metrics for the face recognition model.	274
6.53	Binary classification metrics for the face recognition model, tested on frontal and well-illuminated images.	277
6.54	Aerial Rescue Multi-Object Tracking (ARMOT) dataset.	278
6.55	Multi-Object Tracking metrics values for the sequences 1, 2, 3 and 4.	279

Chapter I

Introduction

In the last decades, the presence of surveillance systems has been continuously increasing in outdoor and indoor environments and public and private places, with the aim of protecting citizens against multiple threats. Concretely, a massive amount of security cameras has been deployed to monitor critical infrastructures such as military bases, airports, power plants, banking, or campuses.

Manual video-surveillance by a human operator is an inefficient solution, due to the expensive cost of labour and the limited attention span. Intelligent Surveillance Systems (ISSs) are emerging to automatically monitor the environment with less or without human intervention. Their monitoring tasks include automatically detecting and tracking people to perform further analysis of their behaviour. Therefore, ISSs are a powerful tool to identify not authorised individuals and activities, and their demand is rising, in quality and quantity, in order to guarantee the citizens' security.

Researching on image processing and artificial intelligence techniques are the leading force to boost the development of such intelligent systems.

This chapter discusses the social and economic impact of developing ISSs. It also presents the research and technological background and the challenges that motivate this dissertation, concluding with the targets set¹.

I.1 Social, Economical and Political Context

In the 21st century, security awareness has deeply changed. This is the result of the evolving global situation and some alarming events, such as the terrorist attacks of 11 September 2001 in the United States. Furthermore, Europe's security environment has also changed in recent years due to the

¹This Chapter includes contents from item 4 of "Published and Submitted Content" list.

increasing threat of terrorism. Terrorist attacks in March 2004 in Madrid, and more recently, in November 2015 in Paris, in March 2016 in Brussels and in August 2017 in Barcelona and the considerable media coverage they have received have subsequently influenced both citizens and policy-makers' concerns.

According to the Special Eurobarometer 464b of June 2017 about Europeans attitudes towards security [68], a large majority of European citizens (90%) feel secure in their immediate city and neighbourhood but they are less convinced that the European Union (EU) is a secure place to live in. The proportion of those who consider that the EU is a secure place to live in (68%) has decreased significantly in comparison with the ratio in 2015 (79%). Moreover, a large majority of respondents regard terrorism, organised crime and cybercrime as fundamental challenges to EU security (95%, 93% and 87%, respectively).

Fig. 1.1 collects the response of the Europeans to the question of “What are the main risk/threats for the EU in the coming years?” and Fig 1.2 presents the most mentioned response per-country. The results show that terrorist attacks are the main concern of citizens, both in general and for most of the European countries, including Spain.

Nevertheless, when the scope of action is reduced to a national level, citizens show more concern about issues which affect its daily lives. In that regard, terrorism alarm is overcome by the concern about crime (12%), according to the Standard Eurobarometer 90 of November 2018 [70]. This trend is shown in Fig. 1.3, which collects the response of the Europeans to the question of “What do you think are the most important issues facing our country at the moment?”.

Fig. 1.1 What are the main risk/threats for the European Union in the coming years? (% - EU). Source: Eurobarometer 464b [68], QA6.

Fig. 1.2 What are the main risk/threats for the European Union in the coming years? (% - the most mentioned answer by country). Source: Eurobarometer 464b [68], QA6.

Fig. 1.3 What do you think are the most important issues facing (OUR COUNTRY) at the moment? (% - EU). Source: Standard Eurobarometer 90 [70], QA3a.

One of the immediate reactions to these threats and citizens' concerns is the growing implantation of video surveillance systems. These systems have long been used to prevent and detect a wide variety of types of crime, such as robbery, theft, burglary and inter-personal crime, like bullying, harassment and assault in work environment, public places and transport, [301].

The value of video-surveillance not only as prevention but also as investigative tools has been endorsed by the crucial role of Closed-Circuit Television (CCTV) in crime fight [10]. Besides, the increasing threat of terrorism and cross border intrusions have led Governments to impose stringent standards pertaining to the safety of nations, resulting in the expansion of the surveillance market across the world.

From an economic point of view, the Global Surveillance market is continuously growing. According to the Market Research Report published in November of 2017 by Market and Market, [229], the size of the global perimeter security market was valued at 15,326.8 million of United States Dollar (USD) in 2016. Moreover, a new Market Research Report published on May of 2019 by Grand View Research [275] claimed that this market was valued at USD 17.7 billion in 2018 and it is expected to expand at a Compound Annual Growth Rate (CAGR) of 7.7% until 2025.

The development of smart cities and infrastructure is essential to boost the growth of the perimeter security market, as well as, Government support for deploying security systems at critical locations. Therefore, nowadays, the market growth is driven by the increasing demand for Intelligent Surveillance Systems (ISSs) (described in Section 1.2.1), which can be used for analysing trends and learning patterns. The development of ISS is presented as a potential niche market, which is expected to continue rising in the fore-coming years. Concretely, the video-surveillance segment, within the global perimeter security market, was valued at USD 6.2 billion in 2018.

Video-surveillance is a very common technology used in public transport for security purposes. For example, the early study presented in [338] in 1992, already suggested that CCTV was effective at reducing robberies at London Underground stations. Since then, the monitoring of transport infrastructures has kept rising across the world. Concretely, between 2015 and 2018, the average number of cameras per system has increased by almost 70%, according to the Statistics Brief, [319] of the International Association of Public Transport (UITP), together with industry expert Axis Communications, performed in 2018. The statics show a marked trend towards the digitalisation of video surveillance networks.

Furthermore, the phenomenon of the rising implantation of video-surveillance systems in public areas, especially in transport infrastructures, receives high citizens' acceptance. There exists a big awareness about personal data and privacy issues. However, the statistics reveal that the increase in security from video surveillance outweighs the loss of privacy for a rising majority of travellers. Concretely, citizens' support for video surveillance has grown since 2015, from 65% to 73% in 2018, according to [319].

This might be due to the fact that investigation into some recent high-profile incidents was assisted with the sequences recorded by video surveillance systems located in public transport infrastructures. For instance, information captured by surveillance systems was helpful to identify

the metro bomber and an accomplice in the attacks in Brussels in March 2016. Video surveillance systems were also used in the police investigation after the truck ramming in Berlin in December 2016 and in Stockholm in April 2017.

Increasing concerns over public safety and the use of video analytics in criminal investigations are positively impacting on the demand for video analytics solutions. Concretely, the size of the global video analytics market is expected to reach USD 9.4 billion by 2025, registering a 22.8% CAGR, according to [275].

In Europe, the general security awareness has led to a comprehensive security approach that addresses internal as well as external security and can combine civil and military means. However, the evolving situation also modifies the types of emerging threats. Political, social and technological developments have created a security environment where risks and vulnerabilities are more diverse and less visible. This results in new threats for European interests, which are able to cross the state borders.

Therefore, in today's global society, the EU faces opportunities, as well as, new dangers. The EU must protect its population and simultaneously defend its commitment to a pluralist, open and liberal society. For that reason, at the beginning of the 21st century, the EU undertook a far-reaching process of transformation towards its globalisation, to augment and reinforce the links with the rest of the world. In addition, at that time, the Common Foreign and Security Policy (CFSP) and the European Security and Defence Policy (ESDP) announced the active contribution of the EU to ensure a global state of peace.

As a result of the changing social-economical frame, in the last two decades, the EU policies encouraged an appropriate degree of security in all Member States and mobilised the necessary resources to tackle risks and vulnerabilities that concern European societies as a whole.

1.1.1 European Research Programmes

To address the emerging dangers and overcome the security deficiencies, in the last decades, Europe policies have increased its funding and improved the coherence of its efforts.

The European Council recognized the arising threats in December 2003 with the adoption of the EU Security Strategy published in the Report of the Group of Personalities (GoP), called "A secure Europe in a better world" [66], in March of 2004. The main objective of the GoP in the field of Security Research was to propose principles and priorities of a European Security Research Programme, which were aligned with the EU's objectives about foreign, security and defence policies, in order to guarantee freedom, security and justice.

Furthermore, the Preparatory Action in the field of Security Research (PASR) on "Enhancement of the European industrial potential (2004-2006)" was centred on the development of a European security research agenda to bridge the gap between civil research, as supported by Eu-

ropean Commission Framework Programmes, and national and intergovernmental security research initiatives.

Subsequently, given the importance of security awareness and in light of the successful implementation of the PASR, Security Research was an integral part of the 7th Research and Technological Development (RTD) Framework Programme (2007-2013) (FP7), which offered a total budget of roughly €1.35 billion.

To achieve the established economical and societal objectives, the new Research Programmes proposed to take advantage of the European's technological strengths to analyse risks and to design effective protection or even neutralisation means. The development of novel technology trends offers new opportunities as well as the synergies between different research areas, such as security and defence, whose systems commonly rely on similar technologies.

With the goal of fostering innovation and bringing ideas from the lab to the market, a Research and Innovation programme was created, the H2020 programme. This is the biggest research investment of the EU ever, with nearly €80 billion of funding available over 7 years (from 2014 to 2020), in addition to the investment from private entities that this project attracts.

The Secure Societies Programme, with a budget of about €1700 million was established as part of the Horizon 2020 program to undertake the research and innovation activities regarding the protection of the European citizens, society, economy, infrastructures and services, prosperity, political stability and well-being.

The major mission of this programme is to reduce the gap between research output and market uptake, caused by the misalignment between demand and supply and the limits of existing funding schemes. Research is not a stand-alone process, but part of a wider process, the Capability Development Process, which involves five main actors: Researchers, Policymakers, Practitioners, Industry and Citizens. This fact was reflected in the Mission letter written by Julian King, the Commissioner for the Security Union, in October 2016, where the necessity of support between different actors was highlighted.

In the fight against the security threats research action plays an essential role, which has been highlighted by different European institutions. For instance, In April 2015 European Agenda on Security [67] defined the priority actions at EU level to ensure an effective response to security threats over the period 2015-2020, where the importance of research was declared: "Research and innovation is essential if the EU is to keep up-to-date with evolving security needs. Research can identify new security threats and their impacts on European societies. It also contributes to creating social trust in research-based new security policies and tools. Innovative solutions will help to mitigate security risks more effectively by drawing on knowledge, research and technology".

Moreover, in December 2018, the Section on EU Security Research of the Seventeenth Progress Report towards an effective and genuine Security Union [69] said: "EU security research is one

of the building blocks of the Security Union enabling innovation in technologies and knowledge crucial for developing capabilities to address today's security challenges, anticipating tomorrow's threats and contributing to a more competitive European security industry". This report also strengthened the idea of collaborating among different security actors: "Given the particular nature of the security sector (in which the market is represented mainly by public authorities), appropriate uptake of research output can be guaranteed only if research is acknowledged as one of the building blocks of a wider capability development process bringing together policy-makers, practitioners, industry and academia".

In conclusion, in today's evolving world, which is driven by knowledge and technology, the capability to face the new security challenges highly relies on the research action.

1.2 Research and technological background

At present, Intelligent Surveillance Systems (ISSs) are increasingly receiving attention because of the growing demand on the safety and security sectors. This section exposes the background to the research field of Intelligent Surveillance where this thesis is framed, whose development has been boosted by the success of Artificial Intelligence in computer vision.

1.2.1 Intelligent Surveillance Systems

In the last decades, the development of surveillance systems has been boosted by the necessity of detect, prevent and neutralize the emerging threats, in order to guarantee the citizens' security.

The traditional and most common modality of surveillance system (first generation) is simply formed by visible cameras in a Closed-Circuit Television, CCTV. It has long been in use to monitor environments, people, events and activities. These systems consist of video recording and its later analysis, or the monitoring over a live video by human operators.

The complete involving of human operators in these systems presents disadvantages, like high manpower costs, operators' limited capacity to monitor a certain number of screens, or their lack of attention after several work hours [313].

In recent years, the number of deployed surveillance cameras for security purposes has risen dramatically in airports, train stations, and shopping centres. This fact causes an increase in the workload of the operators to manually analyse and understand video content, to monitor long term activity and to characterise people's behaviour in a scene. The necessity of managing all the visual information captured by the sensors, in a more effective, profitable and faster way, has boosted the development of automatic surveillance systems provided with a certain degree of autonomy and artificial intelligence.

Intelligent Surveillance Systems (ISSs) are surveillance systems that have the intelligent capability to automatically analyse video sequences and perform necessary actions such as generating alarm or warning, without or with limited human intervention. Therefore, ISSs [271, 162], can supplement (second generation) [111] or even replace (third generation) traditional systems. These intelligent systems aim to monitor a determinate environment in real-time, providing an automatic interpretation of the scene and predicting the individuals' actions and interactions, basing on the data acquired by sensors.

ISS is an interdisciplinary topic that involves electronic (sensing device), computer vision, pattern recognition, artificial intelligence (machine learning), networking, communication and other areas. ISS is promising to be implemented in a wide variety of environments. Some typical applications are home security [17, 18] and intrusion detection [43], home care and safety [77], public transport area such as airport, seaport, bus/train terminal [314], public area [268] such as colleges, campuses, governmental buildings, traffic monitoring [52], crown management and analysis [170], pedestrian detection and autonomous cars [95, 91], and remote military surveillance, border monitoring, and perimeter surveillance for power plants and companies.

Some examples of surveillance systems that have been previously studied or developed are VSAM (Video Surveillance and Monitoring) [63], W4 [304], ADVISOR (Annotated Digital Video for Intelligent Surveillance and Optimized Retrieval) [302] and PRISMATICA (PRo-active Integrated systems for Security MAnagement by Technological Institutional and Communication Assistance) [314, 326] that has been proposed to improve passenger security and safety in the public transport system.

Another impressive surveillance system is ARGUS-IS (Autonomous Real-time Ground Ubiquitous Surveillance Imaging System) [197] developed by Defense Advanced Research Projects Agency (DARPA). This is a 1.8 Gigapixels video system, which is capable of tracking every moving object within 40 square kilometres using a single platform. Furthermore, some commercially available ISS products are DETER (Detection of Events for Threat Evaluation and Recognition) [243] and those offered by the company DETEC AS [85].

The reliability of the ISSs has long been increased by modelling the environmental constraints from the previous knowledge of the context [230], or using multi-media data [76], and combining different sensor technologies, such as adding an audio stream, [271], or information from laser scanners [114] to the visual data. Moreover, in [179] biometrics is used to identify people in a scene. However, these fine cues are not always available for real-time monitoring of multiple people in wide areas, and in most of the scenarios, security must be guaranteed by visual surveillance systems.

The new research branches seek to increase the wideness of the monitored scenes, as well as the robustness and flexibility of the surveillance systems by means of the design of novel architectures. The cooperative sensors networks [62] forms the key infrastructure for the new generation of

surveillance systems. The current trend is to design ISSs, with distributed architecture to obtain scalability and robustness [324].

In distributed surveillance systems, every sensor works as a non-centralised and relatively autonomous entity, which interacts with the others in a dynamic environment, leading to a network, where each cooperative camera utilises vision algorithms, besides of the data from the neighbour cameras. The efficient data management, provided by these systems' architecture, allows an increase in the number of sensors, geographically distributed in several monitoring points. The aim of these systems is to monitor wider and wider areas, like in PRISMATICA [326] and ADVISOR [302] projects.

As their name suggests, distributed systems are based on the distribution of the processing capacity over the sensors network and the use of embedded devices to process images at every monitoring point. The recent developments in computer vision and machine learning have an essential role in enabling the automatisation of such intelligent visual systems.

1.2.2 Deep Learning

Learning algorithms are continuously used by people in daily tasks since they are present in many common applications, such as a web search engine, email anti-spam filter, or photo tagging.

Machine learning is a field that had grown out of the field of Artificial Intelligence (AI). Arthur Samuel described Matching Learning as “the field of study that gives computers the ability to learn without being explicitly programmed”. Then, a more precise definition was given by Tom Mitchell: “A computer program is said to learn from experience E with respect to some class of tasks T and performance measure P , if its performance at tasks in T , as measured by P , improves with Experience E ”.

There are a number of tasks that can not be explicitly programmed because humans neither know how to solve it. There was a realisation that the only way to do these things was by means of machines that learn to do it by themselves. Consequently, machine learning emerged as a new capability for computers and nowadays it is involved in many sectors of industry and science. Machine learning is applied to a wide range of problems, including autonomous robotics, computational biology, database mining, machinery applications, and artificial perception. Consequently, Artificial Intelligence is bringing about an equally big society transformation as electricity did it about 100 years ago.

Concretely, Deep Learning is a part of AI that is advancing rapidly and generating a lot of developments. It has already transformed internet businesses, like web search and advertising, by enabling brand new products and services, from better health-care to even self-driving cars.

Deep learning is a type of machine learning in which a model learns to perform tasks directly from image, time-series or other types of raw data, and it is usually implemented using Neural

Networks. A neural network is a model, originally motivated by the goal of having machines that can mimic the brain, which gives a way of defining a complex, non-linear form of hypotheses with parameters that can fit the data, even when the input data space is large.

The basic technical ideas behind Neural Networks were originated many decades ago. These models were very widely used in the 80s and the early 90s and their popularity diminished in the late 90s. However, Neural Networks have suffered a recent resurgence, becoming the state-of-the-art technique for many applications.

Andrew Ng shared a conceptual graph [249] (Fig. 1.4) illustrating how the effectiveness of deep learning improves as the networks are fed with more data. The resurgence of the interest in Neural Networks is mainly due to a large amount of data available through the digitisation of the society, as well as, other facts like the innovation in the development of neural network algorithms and their faster computation.

Deep learning is a software model where even trillions of connections between neurons are trained, this is why it is called “deep”. For that reason, Graphic Processing Units (GPUs) are presented as the convenient processor to train networks since they perform the parallelisation of the process, allowing researchers to train networks 10 or 20 times faster, according to [196]. Moreover, from 2013 to 2016, the development of the technology of GPUs has provided 60 times faster training in only three years, according to [231].

In summary, the reason for the success of Deep Learning is the availability of bountiful and inexpensive computation, storage, and data.

Fig. 1.4 Scale driving Deep Learning Progress graph, recreated from [249].

Deep Learning algorithms are evolving towards “self-taught learning”, a.k.a. unsupervised feature learning, which is the Artificial Intelligence dream. Under this paradigm, algorithms will

be fed with a large amount of unlabelled data from which to learn a good feature representation of the input. Consequently, massive amounts of unlabelled data will be easily obtained and used to train, avoiding labelling costs.

However, at the present time, the vast majority of the economic value produced by machine learning has been generated by neural networks trained with supervised learning. In supervised learning, the network is fed not only with input samples but also with their labels, that is the correct outputs, under the assumption that there exists a relationship between the input and the output.

Historically, it has been much harder for computers to make sense of unstructured data, like images, compared to structured data (databases). However, thanks to deep learning, computers are now much better at interpreting unstructured data as compared to just a few years ago. In that way, neural networks have improved supervised learning. This fact creates opportunities for many emerging applications that use speech recognition, natural language processing on text, or computer vision.

In particular, Deep Convolutional Neural Networks (DCNNs) have demonstrated to provide successful results in various vision problems, such as image recognition or classification [147, 184, 303], objects detection [239], optical flow estimation [106], face verification [315, 333], and even by bio-inspired computations [347].

In general terms, two types of DCNN models are commonly employed in computer vision. The first type is the classification model, which is used in image classification [184] and object detection [121]. The second is the Siamese model using image pairs [325] or triplets [289] as input, which consists of two or three DCNNs branches, sharing parameters and joined in the last layer, where the loss function performs a pairwise verification. This last model is usually used to contrast images in applications like face recognition.

In the last years, the training of DCNNs has turned into a popular choice for end-to-end learning of image representations due to their accuracy and scalability and the demonstrated capacity of deep learning techniques to automatically find salient high-level features from the pixels of an image, which is highly useful in intelligent surveillance applications.

1.3 Problem Statement

The trend of installing large-scale distributed networks of cooperative cameras has open a research branch dedicated to designing Multi-Target Multi-Camera Tracking algorithms (MTMCT) to automatically perform the monitoring of multiple people through different camera views. These algorithms require the development of efficient Multi-Object Tracking (MOT) methods and Person Re-Identification (Re-Id) models.

Without the support of a central system to save the monitoring points configuration in a global map, these algorithms only can use local visual information, since cameras are often placed far apart to reduce costs, and their fields of view do not always overlap. This results in extended periods of occlusion and large changes of viewpoint and illumination across different fields of view. In that sense, the complete automatisation of visual surveillance is highly challenging due to the real-time constraint and some practical and real-world issues, which are described in the following sections.

1.3.1 Multi-Object Tracking Challenges

Multi-Object Tracking (MOT) task consists of visually finding the location of multiple objects from their visual measurements and conserving their identities in an image sequence.

In video surveillance applications, the term object refers to each individual in a monitored area. Therefore, in that scope Multi-Object Tracking is also known as Multi-Person, Multi-Target and Multi-Agent Tracking. The term agent has been taken from the artificial intelligence theory and defines an artificial object with independent actions and states. In [271] an agent represents the state of an individual and its interactions with others. The tracking of multiple agents allows monitoring of several events, which constitutes the base of intelligent surveillance.

The currently predominant approach to MOT is tracking-by-detection, where a pre-trained detector and a tracker are coupled. So, the inputs to the tracking module are people detections.

Traditionally, the tracking module has been constituted by a filter stage and a data association process, as it is explained in detail in Section 2.1. A large variety of filters has long been used in tracking algorithms to predict agents' trajectories. Moreover, the data association process usually is performed by an optimization method to find the assignment between the captured detections, at a certain frame, and their corresponding identities, tracked along a sequence.

In real unconstrained scenarios, the tracking of multiple individuals is hampered by a wide variety of challenging situations: fast-moving people or moving camera platforms, presence of crowds, crossing people, people with changing-trajectories, partially or total occlusions along short or long term, people disappearing from the monitored area, or new individuals entering in the field of view of the surveillance camera.

For that reason, the application of tracking-by-detection approaches in complex surveillance scenes produces certain tracking errors. There are three main types of tracking errors:

- I. False negatives or missed target individuals.
- II. False positives caused by the association of an identity to some object different from the people to track.

III. Identity switches, due to the association of a wrong identity to a person.

The definition of these errors and the protocol used to measure them are established in [27]. A visual example of these errors over a certain frame is given in Fig. 1.5.

Fig. 1.5 Tracking errors. Colours of individuals' silhouettes render their identities, and the colours of the bounding boxes, the identities given by a hypothetical tracker algorithm.

Very often, the number of false negatives and false positives is highly increased by the lack of precision inherited from the used detector. Therefore, robust tracking algorithms are required to face this daunting frame.

In addition, the number of people is typically not known in advance, and no information about the agents appearing in the scene is available. Under these assumptions, the tracking of multiple unknown individuals in crowded scenarios is a notoriously difficult problem, since they must be recognised among a high number of observations. Therefore, the amount of data to process is enormous. Although MOT methods have been reviewed intensively, [27], it remains a challenging problem.

1.3.2 Person Re-identification Challenges

Person Re-Identification (Re-Id) consists of visually recognising an individual through images from non-overlapping camera views. A good Re-Id performance is necessary to extend the functionalities of an intelligent surveillance system through several cameras views at different times and locations. For that reason, Re-Id task plays an essential role in the developing of large scale distributed multi-camera surveillance systems.

Usually, in real-world surveillance scenarios, fine bio-metric cues are unavailable. For that reason, the research has been mainly focused on re-identification models that only use the visual data from surveillance images. The visual appearance Re-Id paradigm entails several computer vision challenges.

The Re-Id task has attracted great attention in the last decade since it is one of the most arduous problems in intelligent video surveillance. Even though many research efforts from the computer vision field have been focused on solving the Re-Id problem [133], it remains unsolved, [384]. The reason is that visual-based Re-Identification becomes a daunting task in unconstrained scenarios, due to the presence of inter-class ambiguities, intra-class variations, and the lack of data about every person to identify.

Inter-class ambiguities are produced by the presence of different people with a similar appearance. The existence of different individuals with almost identical shape and wearing similar clothes and hairstyles turn the discrimination and recognition of their identities into an extremely difficult goal to attain.

On the other hand, the challenge of person re-identification is to match images of the same person captured by different non-overlapping camera views against significant and unknown cross-view feature distortion. The differences between the camera characteristics and point of view of two different monitoring points cause large changes in perspective, illumination, background, pose, scale and resolution. This results in dramatically different appearances and consequently different representations of the same person, which are called intra-class variations.

Moreover, variations of viewpoints and poses cause misalignment in the compared human shapes. Dealing with misaligned features also implies another challenge for features design in the Re-Id task.

Another important adversity to deal with in Re-Id research is the data problem. The identification performed in access controls is based on contrasting an individual measurement on a finite and previously collected database, containing data about a certain number of authorised individuals. Conversely, the objective of person re-identification is to extend the monitoring of any anonymous individual across different camera views. Therefore, there is no previous knowledge about the queried individual, but only the current captures from the different views.

Moreover, the re-identification task is characterised by the unbalanced nature of the underlying Re-Id data. Indeed, in this particular task, the number of instances of a query identity is very limited, specifically when compared with the vast quantity of potentially available different people representations.

Furthermore, in contrast to large-scale search problems, typically no accurate temporal and spatial constraints can be exploited to ease the Re-Id task, due to the distant location of the involved cameras.

1.4 Motivation

This dissertation has been motivated, in the first place, by the need for research on Intelligent Surveillance Systems (ISSs) to ensure the citizens' security against emerging and already existing threats. Such research activity has been even encouraged by European Government's policies through significant investment programmes, and it has powerful applications in the substantial and continuously growing market niche of video-surveillance, as it was explained in Section 1.1.

Subsequently, within the ISS discipline, a new generation of large-scale distributed networks of cooperative sensors is arising to automatically monitor wide areas. This automatism seeks to reduce the response time against a detected dangerous or unauthorised event, in comparison with a human operator (Section 1.2.1). Otherwise, surveillance systems will be only forensic instruments to analyse saved videos.

These distributed systems state the necessity of efficient algorithms to perform Multi-Object Tracking (MOT) and Person Re-Identification (Re-Id) in order to monitor multiple individuals across different and distant camera views.

Typically, temporal and spatial constraints are difficult to establish, and fine bio-metric cues cannot be acquired from distant sensors. Therefore the tracking of individuals across multiple cameras relies on visual data, posing a demanding goal for computer vision. The remaining challenges of MOT and Re-Id tasks, described in Section 1.3, keep the research on them open and active, which motivates the contribution of this thesis to addressing such unsolved problems.

The presence of frequent individuals' occlusions and interactions, in unconstrained and crowded scenarios, makes insufficient the use of algorithms relying only on motion cues, which boosts the research on modelling individuals' appearance.

Although deep learning has been proven to provide successful results in many fields of application, as Section 1.2.2 explains, its potential to learn a unique appearance model, able to represent any anonymous individual in a scene, has not yet been sufficiently exploited. This research gap has brought a new branch of study whose development is addressed by this thesis, as well as, each subsequently challenges derived from this approach.

The recognition of a person by means of an appearance neural model presents an intrinsically unbalanced nature, given the lack of data about the people to identify and the huge number of possible false assignments with surrounding agents. This results in the over-fitting and collapse of the neural models used to render the visual appearance. Facing such problems has motivated the research work on deep learning techniques throughout this dissertation.

Therefore, the ultimate motivation of this dissertation is to develop methods to learn a unique appearance model using neural networks with surveillance purposes. Such a significant undertaking demands a deep study and innovation, not only in the field of surveillance algorithms development but also in the science of deep learning.

1.5 Objectives

The imperative research to solve the computer vision challenges which are entailed by solving MOT and Re-Id from visual data and the boosting provided by the development of Deep Neural Networks Learning have inspired this dissertation: Appearance Similarity Learning for Multi-Object Tracking and Person Re-Identification.

In video surveillance, the tracking of a person in a sequence, especially after occlusions, and its re-identification through different camera views involve the recognition of its identity from visual features among all detected people in the scene. Instead of individually modelling the appearance of every agent in a scene, this dissertation proposes the learning of a model to measure the Degree of Appearance Similarity, DoAS, which is able to compare two images and determine whether they belong to the same individual or not.

Therefore, the objective of this thesis is to propose, explain, evaluate and discuss the approach of addressing Multi-Person Tracking and Re-Identification through the learning of the DoAS measurement.

This method is meant to be integrated into a future distributed and cooperative sensors network to perform Intelligent Surveillance. Although this further application is beyond the purposes of this thesis, it conditions the characteristics of the method, whose development implies the achievement of some important milestones, listed as follows:

- Formulating an efficient neural model to learn the Degree of Appearance Similarity, DoAS.
- Designing and implementing an online MOT method mainly based on the data association performed by a universal model to measure the DoAS between every new detection and its previous track, without relying on future observations.
- Automatically learning a Single-Shot Re-Id model to extend the tracking of a person after temporary occlusions and through different cameras views, by means of only two snapshots of each individual with the aim of reducing the stream of information between sensors.
- Reviewing the previous and state-of-the-art methods to solve Multi-Person Tracking and Re-Identification to establish the foundations on which the taken research decisions are based.
- Implementing a development framework, to design and evaluate appearance models, learning techniques and tracking algorithms through an extensive battery of experiments, to provide comparative results and concluding remarks.

1.6 Outline of the dissertation

The thesis is structured as follows:

Chapter 2 reviews the relevant state-of-the-art methods to solve Multi-Object Tracking and Person Re-identification. The content of this chapter focus on the application of emerging Deep Learning techniques to model human appearance, and the problematic of this approach. This chapter also exposes the contributions of this dissertation to both fields of research: Multi-Object Tracking and Person Re-Identification.

Chapter 3 introduces the general approach adopted to address the surveillance objective, whose core is the learning of a Degree of Appearance Similarity (DoAS) model. Besides, this chapter describes the development methodology followed to formulate and evaluate effective appearance models, learning techniques, and tracking algorithms. The datasets, software and hardware resources employed throughout the development of this dissertation are also exposed in chapter 3.

Chapter 4 describes the Deep Neural Networks models used to re-identify people, as well as, the designed layers, functions, and learning techniques to improve not only the Re-Id performance but also the convergence of the model learning.

Chapter 5 presents a Multi-Object Tracking architecture, where appearance models measurements are integrated. This chapter is focused on describing the formulated method to perform identity assignment, which is the core of the proposed tracking method.

The description of the conducted experiments, and the evaluation metrics used to validate the proposed methods are given in Chapter 6. This chapter also presents the obtained results, their comparison with other state-of-the-art methods and the discussion of the achieved improvements.

Finally, conclusions and future work ideas are exposed in Chapter 7.

Chapter 2

Literature Review

An analysis of previous and state-of-the-art methods to solve Multi-Person Tracking and Re-Identification has been conducted as the foundation of the research approach presented in this thesis: learning a visual similarity measurement to address both surveillance tasks.

This chapter presents a review of the literature related to these two branches of research: Multi-Object Tracking and Person Re-Identification, in the following two sections. Finally, the last section states the contributions of this dissertation to the scientific community¹.

2.1 Multi-Object Tracking

Multi-Object Tracking (MOT), a.k.a. Multi-Target, Multi-Person or Multi-Agent Tracking, consists of visually finding the location of multiple individuals from their visual measurements and conserving their identities in an image sequence.

Nowadays, the development of Single-Object Tracking algorithms is considerably mature, unlike Multi-Object Tracking methods, which are still under development. Multi-Object Tracking in video sequences is one of the most important research areas in the field of computer vision, since it is widely used in military and civil applications, such as sports players tracking and analysis [217, 250, 354], biology (e.g., birds [224], ants [176], fish [110, 310, 311] and cells [198, 234] tracking), robot navigation [94, 96], and autonomous driving vehicles [98, 264].

Multi-Object Tracking has become a branch of research deeply studied by the scientist community due to its prominent application to Intelligent Surveillance Systems. Indeed, in the last decades, the development of ISSs has been boosted by the necessity of automating and optimising the management of the visual data captured by a continuously rising number of cameras, installed for security purposes. In that respect, tracking multiple people is one of the essential modules of an

¹This Chapter includes contents from items 1, 2, 4, 5, 6, 8, 9, 10 and 11 of "Published and Submitted Content" list.

ISS, since many other surveillance applications rely on the tracking, such as the action recognition or behaviour analysis of an individual.

Furthermore, MOT through video streams from multiple cameras, known as Multi-Target Multi-Camera Tracking (MTMCT), is essential to enable some applications including suspicious activity and anomaly detection, and crowd behaviour analysis in a distributed surveillance system.

2.1.1 Tracking-by-Detection

In the literature, tracking problem is commonly solved by selecting a detector and feeding a tracker with it, resulting in a wide range of approaches, which has long been encompassed under the paradigm called “tracking-by-detection”, e.g. [25, 33, 56, 97, 188, 238, 269]. Fig.2.1 illustrates the general stages of an exemplary tracking-by-detection algorithm.

Fig. 2.1 Stages of a multi-object tracking-by-detection algorithm.

In a first step, object detectors provide potential locations of the objects of interest in the form of bounding boxes. The work in [244] presents a review of different tracking-by-detection approaches and compares their performance, providing evidence that the choice of a detector can substantially alter the performance of a tracker.

Once a set of reliable detections is collected, the task of the tracker translates into a data association problem, where the visual measurements from the detections at every new frame are assigned to their corresponding tracked identity. Identity is given to every trajectory that describes the path of an individual instance, hereinafter called agent, over time.

The data association process relies on the modelled representations of both sets, agents and detections. Therefore, relevant cues, about motion or appearance, are usually encompassed in a model to provide a powerful representation of the tracked people and their new detections.

In addition, in tracking-by-detection algorithms is really common the addition of a state estimation step before the data association stage. In that way, the state of every agent is estimated

by a filter algorithm providing a more approached vision of its representation in the next frame. Therefore, this is a predicting stage which eases the association process.

Finally, the data association method is mainly composed of a cost function and an optimization method. The cost of matching a detection with a certain identity is computed by a cost metric. Subsequently, an optimization algorithm is in charge of seeking the assignment that minimizes the matching cost.

A lot of research has been developed in order to improve the performance of the MOT task by means of enhancing one or several of these five key parts: the provided detections, the association method used to match the detections with their identities, the formulation of the matching cost, the agents state estimation, and the way in which each identity is represented or modelled. A review of the existing literature related to each one of these tracking concerns has been performed and it is exposed in the following sections. Moreover, Section 2.1.4 is summarised by Fig. 2.2 and Sections 2.1.5, 2.1.6 and 2.1.7 are summarised by Fig. 2.3, presented in the final section (Section 2.1.9), where the extracted conclusions are given.

2.1.2 Person Detectors

Many efforts have been focused on the enhancement of the human detection methods to avoid the loss of some tracks and prevent from starting to track non-human objects. Both circumstances, badly affect the performance of the tracking-by-detection approaches, increasing the number of false negatives and false positive agents, respectively.

One of the classical detectors is the one based on Histogram of Oriented Gradients (HOG), denoted as HOG-SVM, that Dalal and Triggs presented in 2005, [78]. HOG-SVM detector computes local histograms of the gradient orientation on a dense grid and uses linear Support Vector Machine (SVM) as a classifier. Although it is not currently the best person detector, historically has been the de facto benchmark detector, and it works well with the presence of contrasting background that clearly helps delimit the boundaries of people. Indeed, its constituent HOG features have demonstrated to be one of the most discriminant features, and for that reason, a vast quantity of state-of-art detectors include HOG features or its variants, like the work presented in [91].

Then, in 2010 Felzenszwalb et al. proposed the Deformable Part Model (DPM) detector, [102], which improved the detection accuracy by a human partition-based approach. DPM aggregates evidence of different parts of a body to detect a person in an image. This detector is characterized by the combination of strong low-level features based on HOG, efficient matching algorithms for deformable part-based models (pictorial structures) and the use of Latent-SVM as a classifier to perform discriminative learning with latent variables. Its trained model is divided into different parts, such as the head, upper body, and lower body, and every detected area has its own score. Therefore, a person's model is made up of parts sub-models. Since this detector relies on parts,

and not only on a full body, it is able to detect partially occluded people. Additionally, it also offers better localization accuracy as it infers bounding box based on detected body parts. The popular DPM detector [102] was used as the public detector for MOTChallenge² sequences [194, 236, 276] and in labelling Re-Id datasets [382, 383].

In 2014, Dollar et al., [89], proposed the Aggregate Channel Features (ACF) based detector. This is characterised by the use of aggregates (summed over blocks) of features represented as channels. Some examples of used features are the normalized amplitude of the gradient, the histograms of oriented gradients and colour channels. Then, the detector was trained with a variant of Boosted classifier. This is a fast detector that has proved high performance on multiple benchmarking sequences. In general terms, the ACF detector performance highlights in outdoor environments, e.g., a camera mounted on a vehicle, whereas the DPM outperforms whenever the dataset contains partially occluded person instances.

In the last decade, with the boosting of Deep Learning techniques, person detectors based on the training of deep neural models have outperformed the traditional ones. The MOT17² challenge shows that trackers rise their accuracy by utilizing detectors based on deep learning. These include Faster Region-based Convolutional Neural Network (R-CNN) [274], Single-Shot Detector (SSD) [218], or pose-based detectors, like OpenPose [42] which has shown good performance on Multi-Target Multi-Camera Tracking [276].

The advances in these object detection networks were driven by the success of R-CNNs [121] and region proposal methods (e.g., [322]). Although R-CNNs were computationally expensive as originally developed in [121], their cost has been drastically reduced thanks to sharing convolutions across proposals [146, 120], through advances like Spatial Pyramid Pooling Network (SPPNet) and Fast R-CNN, exposing region proposal computation as a bottleneck.

The Deep Neural Networks detection models depend on region proposal algorithms to hypothesize object locations. In 2015, Ren et al. proposed the Faster R-CNN, [274], which solve the region proposal time problem by introducing a Region Proposal Network (RPN) that shares global-image neural features with the detection model, enabling region proposals with an almost null cost. A RPN is a fully convolutional network that provides object bounds and scores of finding an object at each position, simultaneously. The RPN is trained end-to-end to generate high-quality region proposals, which feed the detection performed by Fast R-CNN. In summary, the RPN and Fast R-CNN were merged into a single network by sharing their convolutional features.

Yang et al. investigated two new strategies to detect objects accurately and efficiently using a DCNN, in the work [361] published in 2016. These strategies were: Scale Dependent Pooling (SDP) and layer-wise cascaded rejection classifiers. The SDP method improves detection accuracy

²MOTChallenge is a Multiple Object Tracking Benchmark which provides a unified framework to standardise the evaluation of MOT methods. This includes a variety of rankings, such as MOT17Det and MOT17 challenges. This is published under: <https://motchallenge.net/>

by exploiting appropriate convolutional features according to the scale of the objects proposed as candidates. The cascaded rejection classifiers (CRC) effectively utilise convolutional features and remove negative proposals in cascade, which largely accelerates the detection while maintaining high accuracy.

The previously mentioned detectors, HOG-SVM, DPM, ACF, Faster R-CNN and SDP, have marked the superiority benchmarks on progressive detectors eras, as they were consecutively published on 2005, 2010, 2014, 2015, and 2016 respectively. In addition, with the exception of HOG-SVM, these detectors are still among the best twenty detectors, according to the MOT17Det challenge². In fact, the last three mentioned detectors, DPM, Faster R-CNN, and SDP, are used to provide three sets of detections for each sequence of the MOT17 challenge².

Currently, the person detector occupying the top position on the MOT17Det rank was proposed by Cai et al. [39], for fast multi-scale object detection. This detector is constituted by a unified deep neural network, called Multi-Scale Convolutional Neural Network (MS-CNN), that combines a proposal and a detection sub-network. To reduce the memory and computation costs, they trained the unified network end-to-end, by optimizing a multi-task loss and performing feature upsampling by deconvolution, as an alternative to input upsampling.

An alternative solution to improve the detection stage in a tracking algorithm, apart from the enhancement of the detector model itself, is the detection-by-tracking approach. People detectors have been presented capacity for locating people even in complex scenarios scenes, but false positives and false negatives have remained frequent. In [8], the combination of the advantages of both detection and tracking in a single framework is proposed. Prior knowledge on possible articulations for each person and temporal coherency within a walking cycle are modelled using a hierarchical Gaussian Process Latent Variable Model (hGPLVM), and the results are used to improve both, detection and tracking, simultaneously.

2.1.3 State Estimation and Gating

Traditionally, Multi-Object Tracking has been defined as the task of predicting the trajectories of all object instances in a video sequence. Therefore, the tracking module used to be mainly composed of a state estimation stage together with the first detection step. Indeed, data association methods based on the location of the detections are usually improved by the previous estimation of the state of the tracked agents.

The current state of every object tracked is estimated by a filter algorithm, at every time that a measurement is received. This task has been commonly addressed by two steps: prediction and updating. The prediction step propagates state forward in time, taking process noise into account (translate, deform, and spread). Then, once the data association has been conducted, in the updat-

ing step, modifications based on current measurement are performed over the prediction. Bayes theorem has been traditionally used in the filters to perform the updating step.

The literature presents two main configurations for filter algorithms: decentralised one, which assigns a tracker to each object, and centralised one, where all the agent states form a single representation. Some examples of decentralised filters are the Decentralized Particle Filter (DPF) [116], and the Kalman filter [172].

Kalman Filter, presented in 1960, has been widely used to estimate the state of an agent with a set of measurements over time. The work presented in [266] proposes a system for tracking people in video sequences, outputting their body and head locations. This system comprises a variation of Stauffer's adaptive background algorithm with a spatio-temporal adaptation of the learning parameters and a Kalman filter in a feedback loop. Moreover, Weng et al. [345] proposed a video moving object tracking method based on the use of the Kalman filter to track the dominant colour of the moving targets. In addition, constant velocity motion prediction has been demonstrated to greatly improve the quality of matching in situations where objects are closely spaced, and appearance cues are not strong.

On the other hand, some examples of centralised filters are Tracker Hierarchy [371], and Reversible Jump Markov Chain Monte Carlo (RJMCMC) Particle Filter [176].

Moreover, the literature shows that performing gating around each predicted target location, before the data association process, is a common practice in MOT algorithms. Gating is a method to determine possible matching observations and prune matches that are geometrically unlikely from the start. This technique allows decomposing matching into smaller sub-problems, reducing the matching complexity.

2.1.4 Data Association Method

Data association process is an essential component of numerous computer vision applications, including MOT as one of the most prominent examples. The task of the data association module in a tracking-by-detection algorithm is matching the people detected in each frame with their identities over time to form trajectories for each individual across frames.

The existing association methods can be grouped into two categories according to the use or not of future observations to perform every assignment, arising the offline and the online tracking approaches groups, respectively.

a) Online data association methods

Online methods, e.g. [34, 57, 97, 260, 269], perform a frame-by-frame data association under the assumption that one agent generates a single visual measurement for each frame. Online methods

immediately associate detections of the incoming frame to existing trajectories and because of that, they are appropriate for real-time applications. However, these systems find difficulties in dealing with complex interacting situations, with occlusions, overlaps, and similar appearances between agents, which causes missed and faulty detections and bounding boxes for a merged group. For that reason, the top positions at the rank of MOT17 challenge² are mainly occupied by offline algorithms instead of online ones.

Online methods commonly treat the data association as a linear assignment problem, between measurements from two frames, assuming that N objects from one image, and M from another, are given. The linear assignment problem can be expressed by an $N \times M$ table of match scores, and also as a weighted bipartite graph, with two layers of nodes [176, 251, 252, 260, 261, 350]. Nodes of each layer render the detections on one of two frames (usually consecutive frames). The edges between nodes are weighted by matching scores [5, 124].

Then, the task of finding a one-to-one correspondence that maximises the sum of match scores or minimises the match costs is solved by an optimisation algorithm. The optimisation algorithm gives a solution under the permutation matrix constraint, which ensures that only one object from each row and from each column is matched up.

One of the earlier optimisation methods in the literature to solve the linear assignment is the Kuhn-Munkres, a.k.a. Hungarian algorithm, [185, 246], which has been translated into one of the most extensively used solutions. For instance, the work proposed in [353] is based on the Hungarian method, and in [161] also part of the data association is solved by the Hungarian method, where the cost is obtained from the locations of the detections.

The main virtue of this algorithm is that exact solution to the linear assignment problem can be found in polynomial time. In addition, most implementations of the Hungarian algorithm allow using a rectangular matrix of matching costs, rather than a square matrix, to handle the case of having a different number of tracks than observations. Hungarian method provides a number of associations as possible. However, this can produce mismatching associations when there are new detections (without previous tracking), or missed identities (not detected). This is a typical situation in surveillance scenes, where people are appearing and disappearing, so some observations may not match any track, and some tracks may not have any observations.

The bipartite graph assignment could be also solved by a min-cut or max flow algorithm, instead of an optimization algorithm. However, assignment problem is not a general max-flow problem, due to the restriction that only one internal edge per node can be turned on. That means that a correct matching is formed by a set of edges such that no two edges share a vertex. This imposed constraint makes the max-flow algorithm inefficient to solve the linear assignment.

The linear assignment approach is a global approach since every possible match is considered to optimise the assignment. Instead of this global vision, other online association methods, per-

form the identity assignment independently for every detection. They independently propose hypotheses for every tracked identity and select the most probable one.

The literature present independent algorithms based on Bayesian probability, where the states predicted by a filter are updated by means of evaluating the likelihood between the states and detections using a model. An example is Joint Probabilistic Data Association Filters (JPDAF) method, which is the adaptation of the Probabilistic Data Association Filters (PDAF) [20] to handle multi-target tracking. The original PDAF was designed to track a single target in the presence of false alarms and missed detections with a statistical approach, base on the minimum mean square error estimation. The first real-world application of the PDAF was probably in the Jindalee Operational Radar Network, [20] which is an Australian Over-The-Horizon Radar (OTHR) network.

Another example of independent online association method is the Global Nearest Neighbor (GNN) algorithm [112], which evaluates each observation in a gating region, independently for each track. This algorithm presents the problematic of ending up with contention for the same observations when individuals are crossing. This is known as the merge and split problem.

b) Offline data association methods

While online methods only have access to the past and current observations, offline approaches, a.k.a. batch approaches, e.g. [9, 25, 37, 161, 265, 372], also consider future frames.

Batch methods, which perform multi-frame generalization, are based on longer tracklets (i.e. trajectories fragments) or even the whole sequence at once and on a hierarchical global data association [372], where all the detections are gradually connected after these have been collected for a huge set of frames.

Batch tracking systems can handle complex scenes, presenting high accuracy and robustness, since their advantage resides in the temporal context, allowing for more robust predictions. However, they are unsuitable for real-time applications, where a frame-by-frame association is needed.

Three main types of batch association methods can be found in the literature, those based on the Greedy paradigm, Min-Cost Network Flow approaches and Multidimensional Assignment algorithms.

Greedy paradigm encompasses those algorithms that follow the heuristic procedure of choosing the locally optimal solution at each stage with the intent of finding a global optimum. This is a global data association method that extends a partial solution, frame-by-frame, sequentially forwards in time. The Greedy strategy does not usually find an optimal solution in multiple problems, but it may produce locally optimal solutions that approximate the global one in a reasonable amount of time. Therefore, this has been widely used to solve MOT, like in [34], where Greedy method is used with a predefined model. The main drawback of Greedy approach is that

once matches have been done, they cannot be undone if later information shows them to be sub-optimal.

Apart from Greedy paradigm, there have been several attempts to learn MOT data association in a supervised way, either through recurrent neural networks for end-to-end prediction of trajectories [237] or by learning data association by back-propagating through a network-flow solution [290]. Network Flow-based methods [25, 37, 265, 372] have recently become a standard formulation of the association problem including birth and death of trajectories [193, 195, 372], due to their computational efficiency and optimisation. These methods have been pushing in the right direction even though they haven't yet topped single-camera tracking benchmarks.

These approaches were motivated by the idea of seeking a globally optimal solution by considering observations over all frames in "batch" mode. These methods extend the two-frame min-cost formulation (from a bipartite graph), by adding observations from all frames into the network. In recent years, efficient inference algorithms to find the globally optimal solution [25, 372] or approximate solutions [265] have been introduced. Some works add push-relabel methods to the Network Flow solution, such as [372]. Other works used a successive shortest path algorithm, like the presented by Berclaz et al. [25] and Pirsiavash et al. [265], these both include approximate dynamic programming solutions.

However, despite the benefits of polynomial-time computation, flow-based approaches come with a important drawback: the cost function can contain nothing but unary and pairwise terms. Pairwise costs are very restrictive in representing constant velocity or other higher-order motion and appearance models. In fact, Collins [61] mathematically demonstrated that the Multidimensional Assignment problem is a more complete representation of the MOT problem than the Network Flow formulation.

The Multidimensional Assignment formulation is a generalisation of the bipartite graph assignment problem to a k-frame assignment. Therefore, the observations are rendered as nodes in a k-partite graph, and hyper-edges contain one node from each partite set. Each hyper-edge has an associated cost or weight and a binary decision variable. According to the permutation constraint implicit in the multi-target assignment task, the solution must be a set of disjoint hyper-edges (i.e. each node can only be part of one matched edge) with the minimum cost. In contrast to Network Flow, there is no limitation in the formulation of the cost function.

Classical algorithms to solve Multidimensional Assignment are Multiple Hypotheses Tracking (MHT) [75, 142, 258, 273] and Markov Chain Monte Carlo (MCMC) [176, 251]. MHT is one of the earliest successful MOT algorithms, originally proposed in 1979 by Reid [273]. For each candidate target, it generates a tree of potential track hypotheses, providing a systematic solution to the data association problem. It calculates the likelihood of each and selects the most probable combination of tracks. Therefore, Multiple Hypotheses Tracking (MHT) is ideally suited

to exploit high-level representations for long-term motion and appearance, since the whole track hypothesis can be considered when computing the probability.

While MCMC provides asymptotic guarantees, MHT has the ability to scan the solution space more profoundly. Andriyenko [9] proposed a discrete-continuous optimization method to jointly solve trajectory estimation and data association, and Segal [293] proposed a related approach based on a message-passing algorithm. These methods, just like MHT, directly optimize global energy with no guarantees on solution quality. But in practice, MHT is more effective in identifying high-quality solutions.

MHT has been popular in the radar target tracking community [29]. Nonetheless, in visual tracking domain, it is generally considered to be memory intensive and slow. MHT has traditionally been hindered by the exponential growth in the number of hypotheses and the need for efficient pruning methods, such as propagating only the n -best hypotheses [75]. Its performance strongly depends on the ability to prune branches in the search tree quickly and reliably, to keep the number of hypotheses manageable. For that reason, while there was considerable interest in MHT in the vision community during the 90s, for the past years it has not been a mainstream approach for tracking. However, Kim et al. [178] address the limitations of MHT algorithm by the development of effective feature representations through discriminative appearance modelling by means of convolutional neural networks [121, 184].

Moreover, MHT has long been approached not only as a multidimensional assignment problem but also as a Maximum Weight Independent Set (MWIS) problem. The work in [258] provides a qualitative comparison of both approaches, concluding that both formulations are equivalent within the context of a MHT algorithm, but the MWIS implementation is simpler.

In general, formulations with polynomial-time solutions consider evidence along paths of time-consecutive edges [25, 41, 109, 166, 167, 265, 329, 372, 374] and some build on bipartite matching [35, 38, 49, 79, 187, 298, 346]. Methods that use all the pairwise terms, not only those which are time-consecutive, are significantly more accurate but NP-hard [46, 61, 80, 82, 186, 277, 295, 316–318]. Unary terms are sometimes added for completeness [82, 316]. Higher order terms have also been used [37, 344] but with sharply diminishing returns. To trade off computational cost for simplicity of formulation and accuracy, techniques as correlation clustering [19, 276–278] or graph multi-cuts [83, 317] are applied to the data association method.

2.1.5 Cost Functions

In the past decades, important research progress has been made in solving the data association problem [1, 189, 298, 372]. However, the final Multi-person tracking performance is limited by the person representation design and the cost function. Therefore, independently from the association mechanism, a proper design of the cost function is crucial for good tracking performance.

Cost functions were hand-crafted and carefully designed in most prior works. For instance, the cost functions presented in [195, 236, 269] only rely on detection confidences and spatial (i.e., bounding box differences) and temporal distances, and Zhang et al. [372] and Zamir et al. [367] included appearance information via colour histograms.

Other works explicitly learn affinity or similarity metrics from data. For instance, Li et al. [204] present a hierarchical association approach where increasingly longer tracklets are combined into trajectories. The similarity between tracklets is learned by a boosting formulation from several hand-crafted inputs including the length of trajectories and colour histograms. Leal-Taixe et al. [193] train a Siamese neural network to compare the appearance of two detections and combine this with spatial and temporal differences in a boosting framework. These works are characterised by the use of a cost metric in their tracking formulation, once the metric has been learnt, but they do not consider the actual inference model during the learning phase. They either do not treat the problem as a whole and only optimise parts of the costs [193, 204, 350, 372].

The work in [188] proposes an extension of the approach in [204] to online learning for each sequence. Similarly, Bae and Yoon [15] learn affinities on-line with a variant of linear discriminant analysis. Song et al. [309] train appearance models online for individual trajectories when they are isolated, and then they are used to disambiguate from other trajectories in difficult situations like occlusions or interactions.

Moreover, Wang et al. [334] and Schuster et al. [290] proposed methods based on learning arbitrary parametrised cost functions for all variables of the association problem in an end-to-end manner. The work in [334] presents a formulation to jointly learn all costs in a Network Flow graph with a structured SVM. However, the employed structured SVM limits the cost functions to a linear parametrisation. To overcome this disadvantage, the method proposed in [290] relies on bi-level optimisation [31, 64] and is more flexible, allowing for non-linear differentiable cost functions as neural networks do.

Similar to these works, there are others that also include the full inference model in the training phase. For instance, structured SVMs [320] have recently been used in the tracking context to learn costs for bipartite graph matching in an online tracker [180], a divide-and-conquer tracking strategy [306] and a joint graphical model for activity recognition and tracking [59].

2.1.6 Modelling People

Many research efforts have been focused on improving the data association techniques to solve the optimal identities assignments. However, a significant part of their performance relies on the model used to render both the tracked identities and the detections. Affinity scores for determining the correspondence of detections across frames is based on feature similarity between them.

Some of the most commonly used features are related to individuals' motion, such as location, or velocity, and even the interactions between agents. In addition, recently, the individuals' visual appearance is also widely exploited in tracking systems.

a) Motion Models

Motion is a crucial cue for MOT, since knowing the likely position of targets in future frames will reduce the search space and hence increase the appearance model accuracy. Trajectories have been typically treated as state-space models, like in Kalman [172] or particle filters [135].

Popular motion models used in MOT are divided into linear and non-linear motion models. Linear models track a movement with constant velocity along a sequence. This simple motion model is one of the most popular models in MOT [33, 238, 254, 294, 366]. However, there are many cases where linear motion models cannot deal with long-term occlusions; to remedy this, non-linear motion models are proposed to produce a more accurate prediction [86, 359, 360]. Moreover, in crowded scenes, a location or motion-based online association method, such as the one presented in [233], could find problems to deal with changing-trajectory and crossing agents. In [15, 16], trajectories are clustered as a means to learn motion patterns.

Furthermore, another approach is to develop more complex motion models to better predict future trajectories. For instance, Fan et al. [100] used DCNNs to predict the location and scale of an individual for tracking.

There exists also important research on models that consider interactions among humans [9]. In fact, the simplifying assumption that each person has an independent motion model can be problematic in crowded scenes. To overcome that, the interaction between different individuals in a scene can be modelled [148, 157, 343]. Two of the most extended interaction models are the social force models introduced by [148] and the crowd motion pattern model [157]. Social force models, a.k.a. group models, render each target's reactions caused by interactions with other people through forces (repulsion or attraction), e.g. [4, 58, 260, 261, 279, 292, 358]. Crowd motion pattern models are inspired by the crowd simulation problematic [369, 307], and they are applicable to over-crowded scenes [182, 242, 277, 280, 381].

The main disadvantage of most of these models is that they are limited to a few hand-crafted force terms, such as group attraction or collision avoidance. Recently, Alahi et al. [4] proposed the social Long-Short Term Memory networks to jointly reason across multiple individuals. It predicts people's trajectories based on their past positions using Long-Short Term Memory (LSTM) networks, assuming that the number of people in a scene is known a priori. However, Narayan et al. [248] eliminate this restriction.

b) Appearance Models

There is a vast number of works that exploit appearance information to solve data association and to overcome the dependency on the motion cues. Therefore, a primary task in people tracking is converting raw pixels into a higher-level representations.

Some simple appearance models are based on raw pixel template representation for simplicity, e.g. [6, 255, 260, 348, 358]. Many objects trackers, like [37] rely on extracting appearance information from the object pixels using hand-crafted features, where including appearance information via colour histogram [38, 47, 49, 50, 80, 192, 317, 329, 367] and texture descriptors [38, 49, 79, 187, 373, 374] are the most popular representation for appearance modelling in MOT.

Moreover, the use of hue data with tracking purposed has long been exploited in algorithms like Mean-shift [65] and Cam-shift [99]. Lighting variations are commonly addressed through colour normalisation, [38], exemplar-based approaches, [49], or brightness transfer functions learned, with [80, 167], or without supervision, [47, 119, 373, 374]. Other approaches use covariance matrix representation, pixel comparison representation and SIFT-like features, or pose features [156, 165, 177, 247, 367]. For instance, Shu et al. [298] present an edgelet-based part model for describing the appearance of objects.

Recently, deep neural network architectures have been used for modelling appearance [149, 193, 368]. In these architectures, high-level features are extracted by DCNN trained for a specific task. For example, in [178] the feature extraction is directly learnt by using a convolutional pipeline that can be completely trained on a vast number of samples.

In many association methods, models to compare two observations are learnt. Therefore, the pairwise terms, which relate two observations, can be weighted by offline trained appearance templates or a simple distance metric between appearance features, as in the network-flow-based method proposed in [296] and [372], respectively. In contrast, in [142], a simple fixed appearance model is incorporated into a standard MHT framework.

On the other hand, some tracking algorithms get improvements by means of modelling every tracked agent independently, e.g. [15, 16, 362]. Since there is no previous knowledge about the people to track, the dedicated models are trained online. The works presented in [34, 309] train a classifier for each target and use the classification score for Greedy data association or Particle filtering. The drawback of these approaches is that a certain time is needed until the online learning catches enough number of samples of a person to learn a reliable pattern.

c) Integration of describing people models into the data association method

The recent trend in Multi-Target tracking is the online learning of people models (based on motion, appearance or both) along the data association process. This integration of the people fea-

tures learning into the association scheme has been extended for the two main groups of data association methods: Multidimensional Assignment and Network Flow.

For example, MHT method can be extended to include online learned discriminative appearance models for each track hypothesis. Online discriminative appearance modelling is a standard method for addressing appearance variation [305].

On the other hand, in [290], features for Network Flow-based data association are learnt via back-propagation, by expressing the optimum of a smoothed network Flow problem as a differentiable function of the pairwise association costs. However, the flow-based methods have limited capability to model the complex appearance changes of a target, and even to represent it through a linear motion model.

d) Multimodal Models

Although an appearance model is an essential cue to track a single target, relying only on appearance can be problematic in MOT task, especially when the scene is highly crowded or when individuals present a similar appearance. Some works have been focused on improving the appearance model, e.g. [33, 136], while other works have combined the dynamics and interactions between targets with the target appearance, e.g. [4, 58, 260, 261, 279, 292, 358]. Kim et al., [178], demonstrated that combining motion and appearance is highly effective in pruning the hypothesis space of MHT efficiently and accurately.

Although architectures based on neural networks have become an essential instrument to face perception tasks, with almost human-level accuracy to classify images [145, 147], their performance on the MOT problem is still far from matching human performance [286, 350]. This is mainly because it is difficult for neural networks to capture the inter-relation of targets in time and space using multi-modal cues, such as appearance, motion, and interactions. To overcome that, the designing or learning of a multimodal cost function (see Section 2.1.5) is required to properly combine independently learnt cues. For instance, Sadeghian et al. [284] proposed the learning of three different cues in separate recurrent networks, and a fourth global neural setting to combine them.

2.1.7 Temporal Consistency

Many of the research efforts, focused on reducing the tracking errors, exploit the temporal consistency by the extraction of people tracklets. Unfortunately, the availability of reliable tracklets cannot be guaranteed due to the propagation of mistakes. This effect is pronounced in network flow-based association methods due to their limited capacity to model complex appearance changes. An alternative is to define pairwise costs between tracklets, i.e. short object tracks that can be reliably computed [35, 160, 217, 297].

In tracklet association, several works [15, 188, 189, 360] train discriminative appearance models of tracklets with the aim of learning an improved affinity score function. In Brendel et al. [35], tracklets association is solved by the Maximum Weighted Independent Set (MWIS) method. Kim et al. [178] also adopt MWIS but follow the classical formulation presented in [258] and focus on the incorporation of appearance modelling.

Other methods add temporary consistency to the data association process by using Long Short-Term Memory (LSTM) models. For instance, Sadeghian et al. [284] propose a LSTM model which learns to predict similar motion and appearance pattern, and Gordon et al. [134], to track generic objects with robotic applications.

LSTM models were introduced by [155], and they are a special kind of Recurrent Neural Network (RNN) capable of learning long-term dependencies. All recurrent neural networks present a chain structure of repeating modules. In standard RNNs, the repeating module has a simple architecture, such as a single tanh layer. LSTM models also have a main chain structure, but the repeating module is constituted by four neural layers interacting to acquire information from a larger collection of data.

LSTM cells were explicitly designed to avoid the long-term dependency problem and have been successfully applied to visual recognition and description [92]. Indeed, a continuously growing research interest has been focused on solving such a problem. For example, Grid LSTM networks have been introduced by Kalchbrenner, et al. [171], and other researchers use RNNs in generative models, such as Gregor, et al. [139], Chung, et al. [60], or Bayer and Osendorfer [21].

2.1.8 Multi-Target Multi-Camera Tracking

The objective of Multi-Target Multi-Camera Tracking (MTMCT) is to track multiple people through video streams, taken by several non-overlapping cameras.

The first approaches to address MTMCT were inspired by the idea of connecting the tracking of the individuals from one sequence to the other by means of analysing the relationship between the cameras from which they were captured. Spatial relations between cameras have been either explicitly mapped in 3D [47, 373], learned by tracking known identities [40, 167, 329], or obtained by comparing entry/exit rates across pairs of cameras [38, 187]. Moreover, preprocessing methods have been used to fuse data from partially overlapping views [374], while some systems rely on completely overlapping and unobstructed views [12, 25, 32, 173].

However, when the views are not overlapped, some works explicitly model people entry and exit points on the ground [38, 47, 187, 228] or image plane [119, 329]. Furthermore, travel time have been also modelled, either parametrically [329, 373] or not [47, 167, 187]. For instance, Ristani et al. [278] use time constraints to rule out unlikely inter-camera associations. In [278] and [276] correlations are decayed to zero as the time distance between observations increases. This

ensures that timely distant observations are associated, provided that they are connected by positive correlations. With similar purpose other works, like [318], employ lifted multicuts into the data association process.

Nevertheless, not always the relationships among the cameras is available or known. For that reason, there is an increasing trend of approaches mainly based on the appearance re-identification of the individuals to addressing MTMCT. In that way, MTMCT involves having to continuously employ tracking within cameras and a separate process of re-identification for individuals crossing the camera boundaries. Ristani et al. [278] propose the learning of features for both MTMCT and Re-Id with a convolutional neural network. They couple a triplet Re-Id loss function with a training method based on hard-data mining.

Other approaches reformulate the tracking problem as a Re-Id problem at every new frame, since tracking essentially involves linking detections. The inherent advantage of such a reformulation lies in the ability of the tracking algorithm to effectively handle temporal discontinuities in multi-camera environments. This unification of the two disjoint tasks, MTMCT and Re-Id, presents a much clearer and simpler solution which has the advantage of not requiring temporally contiguous sequences of video frames for tracking. For instance, Nayaran et al. [248] present a novel approach to the person tracking within the context of entity association, exploiting the appearance-based features to improve the performance of data associations for re-identification.

2.1.9 Conclusion

An overview of the recent literature related to MOT is provided by the following summarising charts, Fig. 2.2 and Fig. 2.3.

ONLINE	INDIVIDUAL	e.g. GNN [112] JPDAF [20]	- Merge and split problem		+ Real-time applications
	GLOBAL Linear assignment in a Matrix NxM or bipartite graph	Optimisation algorithm e.g. Kuhn-Munkres [185, 246]	+ Polynomial time - Problem of appearing and disappearing individuals		- Poor performance in complex scenes
		Max-flow	- Non-efficient under restrictions		- No temporal consistency
OFFLINE	GREEDY e.g. [34]		+ Polynomial time - Irreversible mistakes		+ Can handle complex scenes + Temporal consistency
	MIN-COST NETWORK FLOW e.g.[25, 37, 265, 372]		+ Polynomial time - The cost function can only contain unary and pairwise terms		
	MULTIDIMENSIONAL ASSIGNMENT	MCMC [176, 251]	- Asymptotic guarantees.	+ No limitation in the formulation of the cost function - NP-hard -needs pruning	- No real-time applications
		MHT [273]	+ High quality solutions		

Fig. 2.2 Summarising chart of data association methods for MOT. Methods listing is shaded. Benefits are indicated with symbol '+' and drawbacks with '-', in white column.

MOTION	Linear		+ Simple - Problems with long-term occlusions		- Problems with changing trajectory and crossing agents	
	Non-linear		+ More accurate prediction			
INTERACTIONS	Social force models [148] and Crowd motion pattern [157]		- Limited by a few hand-crafted force terms			
	Social LSTM [4]		- Known number of people in the scene			
APPEARANCE	Hand-crafted features e.g.[38, 47, 50, 192]		- Previous feature designing		+ Avoid motion dependence - Problem with agents with similar appearance	
	DCNN models	Online individual models e.g [15,16,362]		-Time to get a reliable pattern		
		Offline pairwise model e.g. [178]	Non-recurrent networks	- No temporary consistency		+ no knowledge about individuals is required
			LSTM	+temporary consistency		- Previous training
		Online pairwise model	Through MHT [305]	- Computationally expensive		
			Through network flow [296]	+ Models and association jointly learnt + Temporal consistency - Limited capacity to model complex appearance changes		
MULTIMODAL	Learning of a DCNN multi-modal model, e.g.[286, 350]		- Difficulty to capture the interrelation of targets with multi-modal cues.			
	Cost function designing	Hand-crafted e.g.[195]		- Previous cost function designing		
Offline learning of similarity metrics e.g.[193, 204]		- Previous training - Not considering the actual inference model during the learning phase.				
Online learning e.g.[15,188,309]		+ no previous training is required				
Joint and online learning of models, cost function and association e.g.[31, 64, 290, 334]		+ Considering the actual inference model during the learning phase.				

Fig. 2.3 Summarising chart of modelling methods for MOT. Methods listing is shaded. Benefits are indicated with symbol '+' and drawbacks with '-', in white column.

The main extracted conclusions, which inspire this dissertation are: firstly, modelling appearance with LSTM cells and using them into an online data association method brings together the advantages of allowing a real-time algorithm with temporal consistency. This approach arises a new and extensive branch of research. Secondly, many efforts have been dedicated to the Multiple Hypothesis Tracking approach, which is a batch method, but there is a lack of hypotheses generators algorithms for online data association. Concretely, with a global hypotheses generator for the frame-to-frame association, the advantages of enabling real-time and avoiding the “merge and split problem” of individual association methods. Thirdly, by learning an appearance similarity model offline, no knowledge about individuals is required and neither time to adapt the model to them, and any known agent can be tracked. Then, the problems to deal with people with sim-

ilar appearance can be prevented by the design of an adaptative cost formulation, according to different types of agents, which is a non-exploited approach.

These remarks are the main foundations for the contributions of this dissertation to the Multi-Object Tracking field, which are described in detail in Section 2.3.1

2.2 Person Re-Identification

Person Re-Identification (Re-Id) consists of visually recognising an individual through images from non-overlapping camera views at different locations and time. It has become one of the most studied tasks in intelligent video-surveillance due to the fact that many other applications, like tracking or behaviour analysis, rely on solving the Re-Id problem [327]. A good Re-Id performance is necessary to extend the functionalities of an ISS through several cameras views, which is the base of large scale distributed multi-camera surveillance systems.

Usually, in real-world surveillance scenarios, fine biometric cues are unavailable. For that reason, the research has been mainly focused on developing visual appearance-based methods. In this context, the literature presents two main Re-Id modes: Multi-Shot and Single-Shot.

Multi-Shot recognition is performed by matching two groups of images, which are obtained from two separate tracks, e.g. [44, 175, 203, 308, 356]. If only an image pair is matched, the method is considered as a Single-Shot recognition method.

Following this premise, two different types of Re-Id datasets can be found in order to address a Multi-Shot or a Single-Shot re-identification. Therefore, in Multi-Shot Re-Id datasets, a tracklet of every individual (i.e. small sequence of images) from each camera view is available. In contrast, for Single-Shot scenarios, [245], only one image per person and per view is given. Fig. 2.4 shows examples of matched pairs (in each column) from two Single-Shot datasets: PRID2011 [154], and VIPeR [138]. Every pair is formed by one image captured from each one of the two different cameras views (cam a and cam b).

Fig. 2.4 Examples of matched pairs belonging to PRID2011 (a), and VIPeR dataset (b).

This thesis is focused on the Single-Shot case, where the aim of the Re-Id task is to identify the person represented by an image from one view, called probe image, among all the images of different people from the other view, called gallery images.

Following sections provide a review of Re-Id methods from the literature, which are summarised by Fig. 2.5, presented in the final section (Section 2.2.10), where some remarks are given.

2.2.1 Person Re-identification as a Pair-wise Classification Task

The objective in Single Shot Re-Identification task is to match the person appearing in an image (probe), with its corresponding representation among a set of images captured from a different view (gallery). Hence, the comparison of two images must provide a prediction of whether they belong to the same identity or not. A pair of images of the same person is hereinafter called a matched or positive pair. Analogously, a pair of images of different people is denoted as mismatched or negative pair.

Therefore, the Person Re-Identification problem can be treated as a pairwise binary classification task, composed of two main components: features extraction and the learning of their optimal combination to discriminate positive and negative pairs.

Consequently, earlier methods for Re-Id generally fall into two categories. Firstly, approaches focused on enhancing the person features design to represent the most discriminant aspects of an individual's appearance, e.g. [101, 232, 363, 380]. Then, other methods were meant to learn an effective discriminative distance to optimally combine the previously extracted visual features, e.g. [154, 181, 211, 227, 235, 355, 376, 387]. Some works, like [207], addressed both objectives.

2.2.2 Features Designing

With the aim of solving the Re-Id problem, many works have been dedicated to the design of novel features able to represent the most discriminant visual aspects of an individual's appearance, followed by a matching step by means of a standard distance. For instance, in [153], the Euclidean distance is used to compare colour and texture-based features.

The earlier works made use of handcrafted features, based on colour, texture and shape. Popular representations of people's appearance include low-level local features based on RGB or HSV histograms, [22, 138], principal axis histogram [158], rectangle region histogram [90], Gabor filters [377] HOG-based signatures [253], graph [117] and spatial co-occurrence representations [336].

Subsequently, some approaches, like [282], reduce the dimensionality of the computed features using the Principal Component Analysis (PCA) method. An alternative to the dimensionality reduction is the integration of several types of features into a global descriptor. Since the

elementary features, like colour, shape and texture, capture different aspects of the information contained in images, they are often combined to give a richer signature.

Some works use multiple features-based representations [101, 138]. For example, [270] combined 8 colour features with 21 texture filters (Gabor and differential filters). Bazzani et al. [22] and Cheng et al. [53] combined Maximally Stable Color Regions (MSCR) descriptors with weighted Color Histograms. Others proposed the integration of several types of features with complementary nature, like the ones used in [101] into a global signature, such as Bag-of-Words (BoW) models. In [226], BoW model is improved by means of using the Fisher Vector, [285], which encodes higher order statistics of local features.

Other relevant methods to fuse different modalities of features are the ones based on covariance descriptors, extensively used in feature-oriented approaches, such as the method proposed in [74]. Moreover, in [377], Gabor features and Local Binary Patterns (LBP) are combined to form a covariance descriptor which handles the difficulties of varying illumination, viewpoint changes, and non-rigid body deformations.

In addition to handcrafted feature designs and their combinations, many research efforts have been focused on learning salient features for Re-Id task. General image saliency has been extensively studied [123], however, in the context of Person Re-Identification, human saliency is different from general image saliency in the way of drawing visual attention. In [379], Zhao et al. presented an unsupervised saliency learning method to exploit discriminative features, and in [380], they proposed the learning of mid-level features from hierarchical clusters of patches.

Concretely, for describing Re-Id images there exist two types of visual features that are desirable to learn: invariant and discriminative ones.

Invariant visual features, e.g., [22, 152, 336], are both, distinctive and stable under changing viewing conditions between different cameras, i.e. they are invariant to pose, scale and illumination. However, the large intraclass appearance variations, make the computation of these features often impossible under realistic conditions.

To overcome this limitation, discriminative methods take advantage of class information to exploit the discriminative information to find a more distinctive representation, e.g. [73, 138, 152, 291]. However, such methods tend to suffer from over-fitting. Moreover, they are often based on local image descriptors, which might be a severe disadvantage. The dependence on salient local attributes makes impossible the re-identification of a person in two images if the salient attribute is not visible in both captures.

Moreover, to increase their representative capability, both invariant and discriminative features have been designed to carry spatial information, like in [138]. For instance, Farenzena et al. [101] proposed a method called Symmetry-Driven Accumulation of Local Features (SDALF). This exploits the symmetry property in pedestrian images to handle view variation, making the

method robust to background clutter. Then, in [23], a symmetry-based silhouette partition was used to detect salient body regions.

Then, the regions can be described by their area, centroid, second-moment matrix, and average colour. Furthermore, the Region Covariance Descriptor (RCD) has also been widely used for representing regions. In RCD, the pixels of a region are firstly represented by a feature vector which captures their intensity, texture, and shape statistics. Secondly, these feature vectors are encoded by a covariance matrix. Interestingly, RCD can be generalised to any type of images (intensity, colour, or even infrared). Another method designed to handle illumination change and background variations is the one presented in [225]. This work developed the BiCov descriptor based on the Gabor filters and a covariance descriptor. In [22] and [53], MSCR are extracted, by making small stable clusters of pixels with similar colour.

In addition, to make the features invariant to pose and robust against partial occlusions, region-based methods were exploited. They usually split the human body into different articulated parts and extract features for each part. In that way, spatial information is also integrated into the feature representation. The body configuration-based pictorial structure features have also been well studied to cope with individual variations [210, 357]. Lu et al. [357] employed assembly of part templates to handle the articulation of the human body. Cheng et al. [55] utilised the Pictorial Structures to estimate human body configuration and computed visual features based on different body parts to cope with pose variations. Then, in [54], a pose estimation stage, based on Pictorial Structures, [103], was presented, from which traditional features were subsequently computed.

The tendency in the research stream dedicated to person feature design is to learn a lower number of high-level representations to describe a person. This research advances in the direction of extracting attributes from person images. Attributes-based approaches allow a description semantically meaningful for humans. For instance, in [191] attributes as hair or clothing style are combined with low-level features.

2.2.3 Metric Learning

On the other hand, instead of designing high dimensional feature representations to capture all relevant information, another widely extended Re-Id stream is composed of methods to optimally combine and quantify visual features. The learning of a metric to optimally combine some visual descriptors can boost the Re-Id performance using quite simple hand-crafted features.

Some approaches address such goal through feature selection, others seek to embed a camera-to-camera transition function, [282], and others learn a novel distance metric to compare features from two person images, like in [81].

a) Feature selection methods

Feature selection has been used to improve the discriminative power of the distance function by evaluating the discriminative importance of different types of features to properly weight them, as it is presented in [214].

In [138], Gray et al. used boosting to select features. Concretely, a weighted ensemble of likelihood ratio tests, obtained with AdaBoost, was used to select the most relevant features. Similarly, in [73] Haar-like features are extracted from the whole body and the most discriminative ones were selected by AdaBoost.

Prosser et al. [270] formulated Person Re-Identification as a ranking problem and learned global feature weights based on an ensemble of Ranking Support Vector Machines (RankSVMs). RankSVM optimises over the pairwise differences. Beside AdaBoost and RankSVM, Partial Least Squares (PLS) and multiple instances learning [287, 288] have also been applied to Person Re-Identification, with the same idea of improving the performance.

In order to properly weight previously extracted features, discriminative classification methods can be also applied to Re-Id domain, such as Linear Discriminant Analysis (LDA) and Logistic Discriminant Metric Learning (LDML). The objective of the LDA method is to compute a linear classification, or a linear combination of features, to characterise and separate two different classes. This method is a generalisation of Fisher's linear discriminant method [108], which is also used in image classification [285]. LDML methods, [140], follows the same approach as LDA from a probabilistic point of view.

Once the extracted features have been properly weighted to generate a person descriptor, pairs of these descriptors are compared by a distance metric to measure the similarity between the images that they are rendering. In [153], Hirzer et al. used the Euclidean distance, also referred to as L2-norm in [158]. Moreover, L1-norm is used in [336].

However, in [226] the idea of that different representations need different distance metrics (similarity functions) to properly re-identify people is discussed. For example, representations based on histograms can be compared with Bhattacharyya distance [22, 24, 55] or Earth Mover's Distance (EMD) [13, 14]. When the dimensionalities of the representations to be compared are different, EMD can also be used as it allows many-to-many association [253]. Using a non-Euclidean distance even less distinctive features, which do not need to capture the visual invariances between different cameras, are sufficient for getting considerable matching results.

In [282] a generative standard Mahalanobis distance learning is presented. On the other hand, RankSVM is used to learn an independent weight for each feature, and the Probabilistic Relative Distance Comparison (PRDC), [386], outputs an orthogonal matrix that encodes the global importance of each feature. Instead of that, Mahalanobis metric learning optimizes a full matrix that

relates the features computed from one of the view sets, with those calculated from the other view set of images, to code the view-to-view transitions.

b) Transformation function learning methods

Using labelled samples, transitions in feature space between two camera views can be modelled.

To account for the appearance changes between non-overlapping cameras some early methods modelled the transfer of colours associated with the two specific cameras [167, 168, 206], which can be understood as inter-camera colour calibration. Following the work of Porikli [267], designed for overlapping cameras, these early studies proposed different ways to estimate a Brightness Transfer Function (BTF). The BTF approach for modelling the appearance transfer between two cameras has some limitations. First, it assumes that a perfect foreground-background segmentation is available for both, the training set and at real-time when the re-identification decision should take place, and second, it is not always sufficient for modelling all the variability in the possible appearance changes.

On the other side, the Implicit Camera Transfer (ICT) method [11] introduces a novel way of modelling the camera-dependent transfer. The camera transfer is modelled by a binary relation that provides a generalised representation of the variabilities of the changes in appearance, without relying on high-level features or previous background subtraction. Instead of that, the figure-ground separation is performed implicitly by automatic feature selection.

In addition, Mahalanobis matrix learning [282] exploits the structure of the data under the assumption that the classes present the same distribution. Therefore, this can be employed to code the view-to-view transitions, so that, the cross-view variations are reduced.

The embedding of cross-view transforms can also be used to deal with the misaligned features problem (described in Section 1.3.2). Indeed, Li and Wang [199] learned a mixture of cross-view transformations, and features are projected into a common space that allows its alignment.

c) Distance metric learning methods

Furthermore, another important research direction in Re-Id is distance learning. There is a vast variety of supervised methods encompassed under the paradigm of Metric Learning algorithms. They learn a distance metric from pairs of images from different views. Therefore, the training stage is necessary. Metric learning approaches use training data to learn effective distance metrics to properly combine features. It means that these methods search for strategies that combine given features maximising inter-class variation whilst minimising intra-class variation.

These approaches do not pay too much attention to the feature representation. In fact, in practice, metric learning techniques use very simple features. But once the metric is learned, these

approaches are very efficient during evaluation since, apart from the feature extraction and the matching, they only calculate a linear projection.

Some widely used metric learners are, Probabilistic Relative Distance Comparison (PRDC), [386], Large Margin Nearest Neighbor (LMNN) [342], Information Theoretic Metric Learning (ITML) [81], Logistic Discriminant Metric Learning (LDML) [140], and Pairwise Constrained Component Analysis (PCCA) [235]. These learner algorithms have been applied to diverse visual classification tasks, beside Re-Identification. Moreover, there are also a number of general distance learners that have been rarely exploited in the context of Re-Id problem, e.g. [81, 340, 349, 352].

Zheng et al. [386] formulated the distance learning as a PRDC model to maximise the likelihood so that correctly matched pairs will have a smaller distance between them than incorrectly matched pairs. Weinberger et al. presented the LMNN method, which minimises the distance between each training point and its k -nearest similarly labelled neighbours while maximising the distance between all differently labelled points which are closer than the aforementioned neighbours' distances plus a constant margin. In addition, Mignon and Jurie [235] proposed PCCA to project the original data into a lower-dimensional space in which the distance between pairs has the desired properties. Li et al. introduced a Locally Adaptive Thresholding Function (LADF) to metric learning models and reported that it achieved good performance on Re-Id task [205].

These metric learning algorithms are based on complex optimisation schemes, with high computational cost and memory requirements, making them unfeasible in practice. Moreover, these algorithms treat a multi-class classification problem, which is not the case of the Re-Id task that is commonly treated as a pair-wise binary classification problem. Indeed, there are only a few methods, like for instance those presented in [7, 118], which directly intend learning a metric from data pairs.

For that reason, some metric learners have been modified to provide a metric adapted to the Re-Id task, e.g. [137, 385]. In [213], attribute-sensitive importance was integrated into some metric learners, such as PRDC. In [87], the authors improved the LMNN with rejection and successfully applied their method to Person Re-Identification, resulting in the Large Margin Nearest Neighbor with Rejection (LMNN-R) method.

Moreover, some metric learning algorithms have been developed in particular for Person Re-Identification, such as Efficient Impostor-based Metric Learning (EIML), [154], and Keep It Simple and Straightforward Metric (KISSME), [181].

In general, metric learners model a global weighting, i.e. a vector of generic weights, which are invariant to the population. The global weighting reflects the stability of each feature component across two cameras so they can be grouped under the paradigm of Global Feature Importance (GFI) methods, e.g. [223]. In contrary, in [214], a Prototype-Sensitive Feature Impor-

tance (PSFI) based method is proposed to adaptively weight features according to different clusters of population.

Furthermore, most existing methods [87, 201, 235, 270, 386] match pedestrian images by directly comparing misaligned features vectors, which causes significant information loss and errors. Conversely, Li and Wang [199] learned a mixture of cross-view transforms and projected features into a common space for alignment. In contrast, in [378], the problem of feature misalignment is handled through patch matching. Concretely salience matching is integrated with patch matching, and both show robustness to spatial variation and misalignment. Moreover, Liu et al. [212] allowed user's feedback in the learning procedure, which achieved significant improvement over metric learning methods, and [213] integrates attribute-sensitive importance into some metric learners, such as PRDC.

Most of the metric learning approaches presented above optimise a linear function to properly weight the absolute difference between the images features of a pair, after those features have been computed for a dataset, treating the features selection and the distance learning as two independent stages. Instead of that, deep Re-Id neural models allow jointly learning person features and a metric distance.

2.2.4 Deep Re-Identification Neural Models

Recently, there are some works of literature applying neural models to address the Re-Id problem. This recently adopted approach has been boosted by the success of Deep Convolutional Neural Networks in various vision problems, such as image recognition or classification [147, 184, 303], objects detection [239], face identification [333], or even by bio-inspired computations [347].

Moreover, the training of Convolutional Neural Networks (CNNs) to solve Re-Id has been inspired by the demonstrated capacity of deep learning techniques to automatically find salient high-level features from the pixels of an image.

In general, two types of CNN models are commonly employed in computer vision. The first type is the classification model, which is used in image classification [184] and object detection [121]. The second is the Siamese model that is used to perform a pair-wise binary classification. This last category includes a new paradigm of methods based on the learning of Deep Re-Id neural models, which has been originated by the adaptation or generation of Neural Networks with a Re-Id purpose, e.g. [2, 53, 88, 202, 215, 323, 325, 351, 364].

Most of these approaches treat the Re-Id as a pairwise binary classification to discriminate between matched and mismatched pairs of images. These approaches follow a supervised learning framework, [215], whose overall network architecture is a Siamese network [202, 364], with two branches or a Triplet model [289], with three branches. On the other hand, Xu et al. [357] adopted a cluster sampling algorithm [209] for re-identifying persons with templates.

2.2.5 Siamese and Triplet model

The first two works in Person Re-Identification to use deep learning, [202, 364], employed a Siamese neural network to model the similarity between a pair of images and determine if both images belong to the same identity. Therefore, they applied a deep neural network to learn pair-wise similarity. Indeed, the Siamese network had been earlier used to verify signatures [36].

Siamese Networks consist of two DCNNs branches, sharing parameters and joined in the last layer, where the loss function performs a pairwise verification [2, 323, 325, 364]. The loss function leads the whole network to discriminate between pairs of similar or dissimilar images. Each branch computes the feature representation for one of the images of a pair. The distance between the learnt features measures the degree of similarity between the images so the objective is to make the distances for positive pairs smaller than that for negative ones, achieving a binary classification in the distance space.

Traditionally, Siamese networks have been used the Contrastive Loss function, proposed in [141]. This function forces the distance between matched pairs of images to be lower than a set margin, and higher for mismatched pairs.

Yi et al. [364] added an additional cost function in the network and divided the person images into three overlapping body parts. They trained three independent networks, finally fused at the score level, while Li et al. [202] used a finer body partitioning.

Later, Ahmed et al. [2] improved the Siamese model by including a layer that computes cross-input neighbourhood differences to capture local relationships between the mid-level features of both images, and a patch summary layer to get high-level features. This method compares the features from one image to features in surrounding locations of another image.

Liu et al. [216] presented a Set-Label Model, which applies Deep Belief Network (DBN) and Neighborhood Component Analysis (NCA) on the proposed concatenated features of the images to improve the Re-Id performance. They proposed a deep learning framework for learning filters to automatically encode the photometric transforms across cameras.

Another variation of the Siamese network is the one known as Triplet model. The basics of the Triplet loss computation are presented in [289], where face recognition is addressed. This model has been widely used to automatically find salient high-level representations from raw images, like in the works presented in [53, 150, 388].

In the Triplet model, each training input is a set of three samples, instead of two. Two of the three images are rendering the same person and the third one, a different identity. Therefore, this model allows the comparison between a matched and a mismatched pair from each triplet input, so the objective function can maximise the relative distance between them.

For that reason, some works [332, 88] extend the triplet-based model to the Re-Id problem with an efficient learning algorithm and a triplet generation scheme. Wang et al. [332] proposed

a model which involved learning features for fine-grained image retrieval. They pre-trained the neural network designed by Krizhevsky et al. [184], using soft-max loss function, but they did not clarify whether their triplet model can be effective without pre-training techniques. Then, Ding et al. [88] demonstrated the effectiveness of their model without pre-training techniques using a relatively simple network.

Many works build each branch of the triplet model with neural architectures that were previously designed for different purposes, like the VGG architectures, introduced in [303], by Oxford's Visual Geometry Group (VGG). For instance, Zhuang et al. [388] chose the VGG16 model to learn representative features to solve Face Re-Identification with a triplet model, and Liu et al. [218] to address Person Re-Identification. Liu et al. also added LSTM networks to provide temporary consistency, since they adopted a Multi-Shot Re-Id approach. In [284], a combination of LSTM and VGG networks are also used to solve people tracking.

2.2.6 Supervised vs Unsupervised Learning for Re-Identification

The performance of deep supervised learning methods highly relies on the quantity and variety of the training data, so that, the training on vast datasets prevent from high variance problem without damaging the high bias fighting.

The requirement of a large amount of labelled data to learn a non-over-fitted model which is able to generalise the solution with unknown samples severely limits its scalability in real-world applications. With the aim of overcoming this limitation, some methods use unlabelled data from people detection, e.g. [101, 331]. Loy et al. proposed the Manifold Ranking (MRank) method [221], which propagates key features along with unlabelled data.

Nevertheless, compared to supervised learning approaches, unsupervised models are less effective in learning discriminative features. This is because without pairwise identity labels, existing unsupervised models cannot exploit cross-view identity-discriminative information, i.e. without labelled matching pairs across camera views, they are not capable of learning what makes a person recognisable under severe appearance changes. Therefore, the matching performance of unsupervised approaches is generally lower than that for supervised learning methods.

On the other hand, Person Re-Identification poses a unique challenge to deep supervised learning, since a highly layered model, with millions of parameters, must be trained on an extremely limited training set. Therefore, deep Re-Id models are prone to over-fit the training data, and incapable to provide a general solution to identify unknown samples.

The lack of training data is particularly acute in the Single-Shot Re-Id case. Single-Shot Re-Id datasets, such as PRID2011 [152] or VIPeR [138], provide only two images for each identity. This is also the reason that deep Re-Id networks mainly focus on Siamese and Triplet model, treating the Re-Id task as a pairwise binary classification.

2.2.7 Transfer Learning

Given the inefficiency of unsupervised methods in Person Re-Identification and the insufficiency of labelled data to apply supervised ones, transferring the models learned from a larger auxiliary dataset becomes necessary.

The literature presents Transfer Learning from other domains, also called domain adaptation, [257], as a widely applied tool in deep Re-Id model learning, where the target task is short of labelled data. Indeed, Transfer Learning has been considered in most existing deep Re-Id works.

The most common deep Transfer Learning strategy is fine-tuning [365]: firstly, a base network is trained on a large source data, then the weights corresponding to the first n layers are copied in the target network, and the remaining layers are randomly initialised; and secondly, fine-tuning is performed over these layers or over all layers, by training on the target dataset. Usually, the models are pre-trained with a Re-Id dataset that is larger than the target dataset, and the target dataset is subsequently used to fine-tune the models.

In principle, domain adaptation can be carried out by any unsupervised method, such as, auto-encoder [151] and dictionary learning [183], which can be integrated as the later layers of a CNN network [332]. The method presented in [262] transfers a pre-trained model to solve Person Re-Identification on an unlabelled target dataset. In addition, soft-label self-training based deep unsupervised learning has become popular recently [159]. In [115], a novel co-training based unsupervised domain adaptation method is proposed, in [219] a semi-supervised approach is presented, and in [44], both supervised and unsupervised settings are proposed to perform a two-stepped fine-tuning strategy.

On the other hand, to keep the advantages of supervised models and to cope with the lack of labelled training data, some recent works use auxiliary source datasets from a different domain, taking a multi-task joint training approach.

These methods go beyond existing Re-Id datasets and consider much larger sources, like classification datasets. An example of a vast object categorisation dataset is ImageNet dataset [84], which contains millions of images of thousands of object categories. This has been shown useful as source dataset for model pre-training in a variety of visual recognition tasks [92], as well as for Re-Id, [115]. In [115], the ImageNet dataset is employed in a two-stepped fine-tuning strategy, to solve a Re-Id model.

However, transferring knowledge from a classification model to a Re-Id one has a number of drawbacks, due to the differences in the tasks for which they were meant, and the dissimilarities in their input data. Indeed, the inputs of a Re-Id model are person detection images, which have very different aspect ratios and much lower resolutions than classification images. Consequently, the architectures used to train models with them are quite different. That implies the modification and adaptation of the traditional Re-Id architectures to be able to receive the knowledge transferred

from the classification models. For example, in [115], several model architecture modifications, and various loss formulations are proposed, to bring together the learning on two different domains.

Other methods, like [256] and [300], address the alleviation of the gap between source and target domains. Pan et al. [256] perform domain adaptation via Transfer Component Analysis (TCA), and Si et al. [300] propose a new form of regularization, which transfers the knowledge gained in source samples to target samples.

Some methods aim to minimise the discrepancy between the marginal [113, 375] or joint [220] distributions of the source and target datasets, by blurring the domain boundary [113], with a cross-domain loss. However, these methods for minimising discrepancies are unsuitable when the source and target domains have completely different tasks, like in [115]. A systematic study is presented in [365] which examines how transferable features of different layers are between the source and target domains. This work concludes that the generalisation ability decreases when the discrepancy between the source and target tasks increases.

In order to use a unique architecture, other works use different Re-Id datasets as the source and target datasets. This cross-dataset transfer learning has been recently adopted for Re-Id models with the aim of providing transferable discriminative information from other Re-Id labelled data to a given target dataset.

Among the existing cross-dataset transfer learning works, the literature presents [190], where a SVM multi-kernel Transfer Learning strategy is adopted, and [227, 337], where multi-task metric learning models are employed. Many Re-Id models are pre-trained with a Re-Id dataset that is larger than the target dataset, for example, in [351], a single model is learnt across multiple Re-Id datasets before the fine-tuning in each one of them.

All of these works are supervised, and they need a large number of labelled samples in the source and the target dataset. This requirement is difficult to achieve using only Re-Id datasets. The size of the training data, even when it is formed by a combination of Re-Id datasets, is relatively small, which tends to over-fit a camera-pair-specific model. In consequence, that model cannot be directly transferred to solve Person Re-Identification in a target dataset which contains people who never appeared in the source datasets and which were captured from a new camera pair.

The use of existing Re-Id labelled datasets to pre-train a model allows learning the view-invariant features of a person's appearance since each dataset was captured from camera pairs with different viewing conditions. However, the differences between the source and target domains, due to the drastically different camera viewing conditions could result in a negative transfer [262]. This is the main drawback of using multiple Re-Id datasets, besides the fact that the size of the training data resulting from combining multiple datasets is not large enough.

2.2.8 Facing Over-fitting

Given the inefficiency of unsupervised methods, the insufficiency of labelled data to apply supervised ones, and the drawbacks of the existing Transfer Learning approaches, the application of some over-fitting reduction strategies becomes necessary.

To reduce the over-fitting problem, a.k.a. a high-variance problem, two main approaches can be adopted: simplifying the model, i. e. reducing the number of parameters to learn, and increasing the quantity and variety of training data. These are the foundations of some commonly used techniques, like regularization and data augmentation, respectively. Indeed, a combination of several techniques is usually conducted, e.g. [202].

Transfer learning approach, previously described, can be considered as a technique halfway between simplifying the model and augmenting the data, since it adopts some parameters values, which were learnt in a different domain with a larger dataset. Therefore, it also reduces model over-fitting.

a) Regularization methods

The number of parameters (network weights) to train can be reduced by choosing less deep network architectures, meaning a smaller number of layers. The deeper the network, more complex and discriminative features it can model. However, the simpler the model, the less prone to be over-fitted it is. Therefore, a trade-off solution must be found. To avoid the use of too simple architecture, incapable of modelling discriminative features, regularization has been extensively applied over deep neural networks.

Regularization is a technique which effectively limits the number of free parameters in a neural model in order to palliate the over-fitting. It prevents the network weights, W , from fitting so perfectly to over-fit the model, by adding an extra term to the loss function. This term is called regularization term and it penalises large weights. In that way, weights tend to take small values.

Two of the most common regularization terms are L_2 regularization (also called L_2 norm, or Ridge regularization) [259] and L_1 regularization (also called L_1 norm or Lasso regularization) [72]. These regularization methods are non-specialised methods since they can be applied over almost any loss function.

On the contrary, in [299] specific regularization formulation is presented for each one of three distance metric learning algorithms: Large Margin Nearest Neighbors (LMNN) [341], Linear Discriminant Analysis (LDA) [108], and Decision Function Learning (Decision Function Learning (DFL)) [174]. In [370], an adaptive distance metric learning method for local distance comparison is proposed to overcome the over-fitting problem in Multi-Shot Re-Id.

On the other hand, instead of performing weights penalisation on the loss function, dropout technique, [312], randomly ignore neurons during training. Hence, at every training iteration, a

different network is considered, and always with fewer parameters than the original one. Therefore, the dropout technique can be understood as an adaptive regularization method [328]. The work in [351] presents Re-Id model learning from multiple domains, with domain guided dropout, that is a method of muting non-related neurons for each domain.

b) Data augmentation methods

As it is mentioned above, apart from simplifying the model, other approaches to solve over-fitting consists of increasing the quantity of training data. However, collecting new matching pairs of person images in a camera network is a notoriously difficult task. For each pair of cameras, eye-balling the two views to annotate correctly matching pairs among hundreds of impostors is a tough job even for humans so the labelling cost would be prohibitively high. For that reason, data augmentation techniques have been extensively used, since they are based on slight transformations of the already existing labelled samples. In that way, the training data is augmented by adding the modified samples.

In [51] instead of data augmentation, feature augmentation is performed relying on a specific pair of camera views. They propose a view-specific method called Camera coRelation Aware Feature augmenTation (CRAFT). This method relies on a specific pair of camera views.

2.2.9 Balancing Re-Identification Data

Single-Shot Re-Id datasets are characterised by their unbalanced nature, since the number of images of a certain person is very limited, especially when it is compared against to the huge amount of different people representations, among which a person must be identified. So, the number of available positive pairs is much smaller than that of negative ones.

For that reason, the training process is mainly dominated by the last group, hampering the learning of a similarity measurement to identify a person in two different images. A certain compensation in both groups sizes is necessary to avoid that the learning process ends up ignoring the positive pair's contributions and collapse.

The triplet model, where a positive and a negative pair are taken at the same time, guarantees the learning from an absolutely balanced dataset since the same number of positive and negative samples are taken as input. However, given the lack of samples of each individual, this forced balance only can lead to the consideration of a reduced number of mismatched samples, or the redundancy of the matched ones, until achieving the balance between them.

Another alternative to balance data is that presented in [208], where an asymmetric weighting in the loss layer is used to balance the quantity of available positive pairs with respect to the negative ones.

2.2.10 Conclusion

A overview of the recent literature related to Re-Id is provided by the following summarising chart, Fig. 2.5.

Separate designing	Features designing	Hand-crafted features		RGB and HSV histograms [22, 138], Gabor filters [377], HOG signatures [253]		- Hand-crafted design				
		Global descriptors		MSCR [53], BoW [226], Covariance descriptors [74]						
		Saliency learning		e.g.[379,380]		- General image saliency techniques are not applicable				
		Discriminative methods		e.g. [73, 138, 152, 291]		+ exploit discriminative information - over-fitting problem - dependence on salient local attributes				
		Region-based methods		SDALF [101] Pictorial Structures [103]		+ Features invariant to pose and robust against partial occlusions + spatial information				
		Attributes		e.g. [191]		± semantically meaningful for humans				
	Metric learning	Feature selection	Adaboost [138], RankSVM [270], LDA [108], LDML [140]			+ improve discriminative power of the distance function		- Two different training processes - Linear function optimisation		
			Distance choice	L1 [336], Euclidean [153], Bhattacharyya[22], EMD [13], Mahalanobis [282]			- different representations needs different distance metrics			
		Learning of transformation	Intercamera colour calibration and BTF [167, 168, 206]			- Needs perfect fore-background segmentation - Not sufficient for modelling all the possible appearance changes			+ modelling of non-overlapping cameras transition	
			ICT [11]			+independent from background extraction				
			Mahalanobis matrix learning [282]			+ reduction of cross-view variations				
		Distance Metric Learning	GFI	General	ITML [81], PCCA [235], LMNN [342], LADF [205], PRDC [386]		-High computational and memory costs -Unfeasible in practise -Multi-class purpose		+ no need for high-level feature representations	
				Re-Id specialised	aPRDC [213], LMNN-R [87], EIML [154], KISSME [181]		+ Pair-wise purpose		- Need for a training stage - Misalignment	
			PSFI [214]			± weighting according clusters of population				
	Patch matching and saliency matching [378]			+ alignment						
	Joint leaning of Deep Re-Id Neural Models	Unsupervised	e.g. Mrank [221], auto-encoder [151]				+ no data restrictions + no labelling costs - poor effectivity in learning discriminative features		+ One learning process + automatic search of salient features	
Supervised		Learning a Re-Id model	Siamese [202, 364]			+ Fixed boundary	+Pair-wise classification			
			Triplet [289]			+ Relative distance				
		Transfer Learning Domain Adaptation (fine-tuning)	From Classification e.g. [115]			+ Lots of data - Different input data - Architecture modifications	+ Reduce over-fitting			
			Cross-dataset e.g. [190, 351]			+ unique architecture - Lack of data - Negative transfer				
		Facing over-fitting	Regularization: L1[72], L2[259], dropout[312]			+ Reduce over-fitting				
			Data augmentation e.g. CRAFT [51]			+ Prevent from labelling costs + Reduce over-fitting				
		Balancing data	Triplet model [289]			- Positive samples redundancy				
			Asymmetric weighting [208]			- Modification of loss function				

Fig. 2.5 Summarising chart of data association methods for Single-Shot Re-Id. Methods listing is shaded. Benefits are indicated with symbol '+' and drawbacks with '-', in white column.

The main extracted conclusions, which inspire this dissertation are: firstly, the transference of learning from MOT domain to the Re-ID task has not been exploited yet. This approach allows feeding the Re-id model with a huge amount of person images from MOT sequences. Therefore, it brings together the advantage of using a unique model (like in cross-dataset transfer) and the availability of lots of data (like transferring from classification domain). Secondly, the idea of augmenting, not the quantity of re-id images, but their possible combinations, has not been sufficiently developed. So, there is a lack of data combination tools in order to face both the model over-fitting and its collapse by data balancing. This approach arises an extensive branch of research, not only to designing feeding formulations according to the characteristics of a certain learning model (Siamese or Triplet) but also to adapt the learning process to that. Thirdly, large efforts have been dedicated to designing region-based features, in contrast to the use of body parts dedicated DCNN, which encourages the study of novel architectures to jointly and automatically extract body parts, their features, and their combination and comparison metric to avoid misalignments. Finally, metric learning has been deeply researched and addressed by a wide assortment of methods, but the parameters of a distance by means of neural networks has not been addressed yet. This novel approach aims to automatically model the cameras transition and the proper comparison of features jointly with the features learning in a unique process.

These remarks are the main foundations for the contributions of this dissertation to the Person Re-Identification field, which are described in detail in Section 2.3.2

2.3 Contributions

This thesis proposes the learning of a model to measure the Degree of Appearance Similarity (DoAS) between two-person images, with applications on multi-person tracking and re-identification.

Many learning techniques, architectures and novel layers have been developed to obtain the DoAS model. And eventually, a surveillance system architecture has been designed to manage multiple agents. The DoAS model has been integrated into this system, where the tracking and re-identification of multiple individuals are performed.

A developing framework has been designed and implemented to train, validate and test the DoAS model. To evaluate the proposed methods and hypothesis, many experiments have been conducted on this developing framework. It also allows testing the performance of the final surveillance system where the trained models are integrated. The implementation of such a developing framework implies the creation of tools with different purposes, such as generating datasets in the

required formats³, interpreting learnt models in different programming languages⁴, and measuring evaluation metrics. Most of these tools have been publicly delivered.

Therefore, the main contribution of this research work is the design of a method to perform Multiple-People Tracking and Re-Identification based on the measure of the Degree of Appearance Similarity between people images. Besides of that, multiple contributions have been made on the specific research fields of Multi-Object Tracking and Person Re-Identification, which are exposed in the two following subsections.

2.3.1 Research contribution on Multi-Object Tracking field

This thesis proposes a MOT method where the association of the individuals' observations through different frames is mainly based on a visual similarity appearance model.

The architecture of a tracking-by-detection system to manage the multiple tracked agents have been designed, where several novel modules have been integrated. Therefore, contributions have been made on several stages of MOT, which are depicted in the following list and explained above.

- a) Cascade Data Association method
- b) Global Hypotheses Generator
- c) Multi-modal Cost Function
- d) Similarity Appearance model
- e) Temporary consistency
- f) Multi-Agent management strategy
- g) Human skeleton analysis
- h) Re-identification

a) Cascade Data Association method

An online Cascade Data Association method has been formulated to perform a frame-to-frame identities assignment. The association process has been divided into different and consecutive levels. Through this hierarchical association, a specialised solution is provided to different critical situations in the tracking process, such as the intersection of agents, their occlusion, disappearances, and the birth of new tracks.

³Functions to generate data are publicly available under *https : github com magomez dataset_factory*

⁴A C++ class to interpret several network architectures and pre-trained weights is publicly available under *https : github com magomez feature_computation*

Instead of modelling the intersections among the agents' trajectories or their interactions [284], concurrency points have been detected. The tracks involved in concurrency regions are consequently redirected to their corresponding level of association, to be properly treated. This strategy avoids the problem of merged and split observations [112], caused by crossing agents.

With the aim of performing an online tracking, the selection of a batch approach, [330, 178], based on future frames observations, has been discarded. Instead of that, the proposed association method performs a frame-to-frame assignment where temporary consistency is provided by modelling the agents' appearance with a LSTM network. In that way, the propagation of punctual association mistakes is avoided, without requiring extending the association process through multiple future frames, like it is done in multi-dimensional alignment algorithms [273] or network flow-based methods [290, 265, 25, 37, 372].

b) Global Hypotheses Generator

A mechanism to generate multiple global matching hypotheses has been formulated.

Instead of proposing multiple hypotheses for every track [273], hypotheses of how a whole set of detections is matched with the set of tracked identities are generated. The term "global" refers to the fact that each hypothesis describes a global matching that encompasses all the identities assignments at once. Therefore, the cost of a hypothesis corresponds to the sum of the costs of every identity assignment described by it. This global approach prevents from possible identities switches since each agent assignment is conditioned by the rest of the associations in a frame.

Many methods use pruning methods [178] to filter the generated hypotheses in order to reduce the number of probable ones after their generation. Instead, the proposed method is implicitly conditioned by a previously calculated mask of impossible associations. In that way, only the notably probable hypotheses are generated and proposed, reducing the computational time. Moreover, the computation cost of measuring the DoAS between detections and agents is independent of the number of generated hypotheses.

The proposed formulation is capable of performing linear assignment without relying on a squared matrix, [185], so, the problematic situation of having a different number of agents and detections have been solved. Besides, the possibility of new tracks births is considered by the hypotheses generation method.

c) Multi-modal Cost Function

A novel formulation to measure the cost of matching a certain identity with a detection has been designed. This thesis defines a multi-modal cost function based on motion and visual appearance cues. The weighing and fusion of these features present an adaptive formulation. Ambiguities due to the presence of crowds, crossing agents, occlusions, and missed and redundant detections

are detected and, consequently considered by the cost function. That means that the matching cost can take different formulations according to the presence of certain ambiguous situations.

Trackers based on only targets dynamics, such as [233], are not able to handle agents with varying trajectories or rapid changes in motion. On the other hand, relying only on appearance models can be problematic when the scene is highly crowded or when individuals present a similar appearance. The literature presents many works solving these problems by means of learning a combination of multi-modal features to render the person observations [279, 4, 358, 58, 261, 178]. Instead of that, the affinity cues provided by three independently learnt models have been integrated into a multi-modal cost function, in this thesis.

The motion of every agent has been independently tracked and predicted by a Kalman filter which considers the position, velocity and acceleration of the person's head location. Tracking the head location has demonstrated to be more reliable than measuring other body parts positions. Even when agents are partially occluded, the head is one of the most visible parts due to the almost zenith setting of most of the surveillance monitoring points. In addition, the head movements mostly follow the person trajectories, unlike limbs with unpredictable movements.

Moreover, similarity appearance between different observations has been measured by a neural network model, which is able to identify any known agent, even after temporary disappearances.

The training of the appearance models independently from the motion cues has been motivated by the fact that neural networks still find difficult to capture the inter-relation of targets in time and space using multi-modal cues [286, 350]. Therefore, the classification power of deep neural models has been exploited to recognise the similarity between agents, and the motion prediction has been subsequently added into the cost function formulation.

d) Similarity Appearance model

The Degree of Appearance Similarity, DoAS, between two images has been modelled as a binary classifier to discriminate between pairs of representations of the same person or different people.

Instead of learning a number of specified patterns for each one of the tracked agents, e.g. [15, 16, 34, 309, 362], a unique model has been pre-trained to identify the appearance similarity between different images of the same person, allowing the tracking of multiple people using the same model for all of them. In that way, unlike online-learning models approaches, the developed method does not require previous knowledge about the scene and neither a large number of frames to learn a robust model for an agent's appearance. The proposed agent's identification presents the same accuracy performance from the first frame of the tracking.

Three appearance models have been designed and implemented. Firstly, a handcrafted descriptor to compare pairs of images was designed. This is based on a variant of Volume Local Binary Patterns (VLBP), that uses hue data to compare two aligned person images. The obtained descriptor

value is subsequently classified by a pre-trained SVM. This model offers a good discriminative capacity when detections of an agent are available in consecutive frames, but the performance decays when there are missed detections due to detection errors, occlusions or temporal disappearances.

Secondly, in order to deal with partial-term occlusions, and missed detections, a Siamese neural model has been trained on a wide variety of pair of images to obtain a robust DoAS measurement able to re-identify detections after temporal disappearances.

In addition, a third model has been developed by adding Long-Short Term Memory (LSTM) cells to the previous neural model. This model relies on the temporal consistency of the agent's appearance by analysing the visual features measured in previous frames. In that way, temporary consistency is added to the DoAS measurement, which is even able to deal with failed associations in previous frames, preventing from the further transmission of the error.

e) Temporary consistency

A model based on LSTM neurons has been used to give temporary consistency to the features learnt by a previously trained Siamese network. In that way, every detection is compared by a model that consider not only the last saved observations but also those from previous frames.

Instead of using a batch association method [25, 37, 9, 265, 372], the proposed LSTM-based DoAS model allows an online tracking algorithm, with a frame-to-frame association. The temporary consistency is given by the observations of every agent in previous frames, but not by the future ones.

The proposed neural model has been optimised to be able to cope with short-term disappearances of the agents, missed detections, and occlusions. Moreover, this model is also capable of dealing with failed associations in previous frames, preventing from further propagation of the identities mismatching. These capabilities have been acquired by the training on a variate set of tracklets (fragments of tracks), especially generated with such purposes by deliberately introducing temporal steps between some people detections, as well as, intruders' detections⁵. In that way, the model has been trained to face complex real surveillance situations.

f) Multi-Agent management strategy

Dedicated structures have been created to manage all the employed tracking cues, as well as, their identities assignments and state updating.

An attributes-oriented representation has been adopted. Therefore, every track is rendered by a set of attributes to save its visual appearance, associated motion filter, location, and even some

⁵The tracklets generation tool has been implemented as a set of C++ functions, which are publicly available under: http://github.com/magomez/dataset_factory/tree/master/data_factory_from_mot

features measured in previous frames, giving short-term memory to the track. These representations serve to a multi-agent management strategy, which is able to generate newly appearing tracks, update the already existing identities, and re-identify the temporarily disappeared agents.

g) Human skeleton analysis

To deal with the herein errors from the detection stage, which causes missed and false positive agents, two strategies based on the geometrical analysis of human skeletons have been designed.

Firstly, the inference of the localisation of missed agents has been performed by a detection-by-tracking approach. A Convolutional Pose Machine (CPM), [339], is used to search a human shape in the location where each missed agent is expected to be found.

Secondly, a filter to validate the human shapes of the detected objects has been designed. This filter geometrically analyses the structured described by the joints detected by the CPM, to determine whether this corresponds or not to a human skeleton⁶.

h) Re-identification

A Re-Identification module has been designed in order to get Multi-Target Multi-Camera Tracking by connecting tracks from the same agent. The inherent advantage of such a formulation lies in the ability of the tracking algorithm to effectively handle temporal discontinuities in single or multi-camera surveillance settings. This module consists of an association process scored by a Single-Shot Re-Id model, made of neural networks, whose developing novelties are exposed in the following section.

2.3.2 Research contribution on Person Re-Identification field

This thesis proposes a Re-Id model, where salient person features, their optimal weighting and the metric to compare them have been automatically and jointly learnt, through the training of DCNNs.

Novel methods and layers formulations have been proposed to learn the Re-Id model. Therefore, contributions are been made on multiples parts of the Re-Id learning, from the generation and augmentation of the training data to the designing of new connection and loss functions and novel architectures, as it has been collected in the following list and explained above in more detail.

- a) Normalised Double-Margin-based Contrastive loss function
- b) Balancing data

⁶The functions to detect human joints is publicly available under <http://github.com/magomez/CPMclass>

- c) Triplet Mini-batch Stochastic Gradient Descent
- d) Transfer Learning from Multi-Person Tracking to person Re-identification domain
- e) Triplets and Data Augmentation
- f) Architectures and body parts partitioning
- g) Mahalanobis Distance Learning

a) Normalised Double-Margin-based Contrastive loss function

The contrastive loss function, [141], originally employed in Siamese networks has been improved with a new formulation based on two margins instead of only one. Subsequently, a second enhancement has been achieved by means of implicitly including the normalisation of the features contrasted by the loss function⁷.

b) Balancing data

The unbalanced nature of the Re-Id data turns into an important challenge in the Single-Shot version, where only two instances of a certain individual are available against the high number of different people.

A comparative study of the effects of the learning model choice (Siamese or Triplet) and its training data in palliating this data problem has been conducted. This study provides a comparison between the use of a totally and a partially balanced dataset, which has been possible thanks to the design of a data generation tool to artificially balance the Re-Id data in the desired measure⁸.

On difference to the asymmetric weighting loss performed in [208], this thesis presents a training data generation tool that allows setting the desired proportion between the quantity of positive and negative pairs to feed a Siamese model. This generation tool also allows exploiting the way of feeding the Triplet architecture to appalled the unbalanced data problem by comparing every available positive pair, with all the possible negative ones.

The performed comparative study has demonstrated the following hypotheses:

- I. A certain compensation in the sizes of both groups, positive and negative pairs, is necessary to avoid that the learning process ends up ignoring the positive pairs' contributions, and collapsing.

⁷The Normalised Double-Margin-based Contrastive Loss function is implemented in a python layer which is publicly available under: <http://github.com/magomez/N2M-Contrastive-Loss-Layer>

⁸Pairs Balancing has been implemented as a set of C++ functions, which are publicly available under: http://github.com/magomez/dataset_factory/tree/master/data_factory_from_reid

- II. Training a Re-Id Siamese model with partially balanced training set provides better results than doing it with an absolutely balanced set, where there is the same number of positive than negative pairs.
- III. The Triplet model, where a positive and a negative pair are taken at the same time, guarantees the learning from a balanced dataset and improves the Re-Id performance in comparison to the Siamese model.

c) Triplet Mini-batch Stochastic Gradient Descent

The triplet model learning proposed in [289], has been adapted to the Single-Shot Re-Id task by the formulation of a mini-batch triplet-based gradient descent algorithm.

The triplet objective formulation, presented in [289], establishes a relative distance relationship. For each person sample taken as anchor image, this formulation ensures that the distance from this anchor's descriptor to the descriptor of every image rendering the same person is smaller (by a predefined margin) than the distances to the descriptors of images rendering different people.

However, in the Single-Shot Re-Id challenge, there is only one positive sample for every anchor image. So, the available data is not enough to adopt an individual-meant approach, which clusters the samples of the same person close from each other and distant to another person identity cluster. On the contrary, the proposed method treats all the possible positive pairs as a set rendering the condition of similarity. In the same way, negative pairs represent the dissimilarity situation. The discrimination between similarity and dissimilarity is learnt by means of comparing every positive pair with all the negative pairs generated from the same anchor, taking advantage of the triplet model architecture for that.

The formulation of a mini-batch-based learning algorithm has made possible the proposed training approach, which is based on the learning of two classes, similarity and dissimilarity, through a vast quantity of samples for both.

d) Transfer Learning from Multi-Person Tracking to person Re-identification domain

Two general streams can be found in the literature to transfer learning to the Re-Id domain: the works transferring knowledge from a different domain as classification, and those pre-training the Re-Id models on combinations of Re-Id datasets different from the target one.

On the one hand, the first group has to deal with the differences in the model architectures employed in the source and the target domain. However, Yosinski et al. [365] examined how transferable features are between different domains, concluding that the generalisation ability decreases when the discrepancy between the source and target tasks increases.

On the other hand, the second stream presents the drawback of the negative transfer produced by the pre-training of a model in different Re-Id datasets. This is caused by the learning of camera-to-camera transitions that cannot be extrapolated from one dataset to another captured from a different pair of cameras.

Conversely, this thesis proposes transferring the learning previously acquired on the MOT domain to a Re-Id model. A data generation tool, which has been publicly delivered, has been designed to create a source Re-Id dataset from MOT sequences⁹. The intuition under this approach is that the most representative features of a person are automatically learnt on a MOT dataset. From the set of learnt descriptors, the low-level ones, which are learnt in the earlier layers of the network model, are kept. Then, the most high-level representations, coded in the further layers, are fine-tuned on a Re-Id target dataset to make them more discriminative.

The proposed method presents the following benefits:

- I. The Re-Id network architecture does not require any modification to transfer learning from MOT to Re-Id domain since the resolution and aspect ratio of the person representations in both domains are quite similar. The MOT sequences have been adapted to feed a Re-Id network, by extracting people images, so the advantages of using an auxiliary Re-Id dataset are retained, but with the possibility of getting a larger training dataset.
- II. The unbalanced nature of the Re-Id data is attenuated. In the proposed source dataset, many detections of the same person are extracted, making easier the convergence of the learning process.
- III. Samples from different MOT sequences are coupled in the source dataset. This setting helps to avoid the dependence on the characteristics of a certain camera view, and consequently, to alleviate the negative transfer of learning.

Moreover, this thesis presents the implementation and evaluation of different stages of Transfer Learning. This analysis provides experienced knowledge about the best configuration for transferring learning from MOT to Re-Id domain, which is applicable beyond the presented experiments.

e) Triplets and Data Augmentation

In order to reduce the over-fitting of a deep Re-Id triplet model, a novel approach, called “Triplets Permutation” method has been proposed. This method formulates different modes to combine

⁹The data generation tool has been implemented as a set of C++ functions, which are publicly available under: http://github.com/magomez/dataset_factory/tree/master/data_factory_from_mot.

the person images of a Re-Id dataset to generate triplets. The implementation of such a combination has originated a triplets generation tool, which is able to create multiple training sets under different constraints, depending on the outcome that is sought to obtain. This tool, which has been publicly delivered, has allowed increasing the variety of triplets obtained from a certain Re-Id dataset¹⁰. In that way, the problems of insufficient data for Person Re-Identification are appalled, and consequently, also the over-fitting of the model.

In addition, two new neural layers have been designed to perform online data augmentation, so that the creation of new samples is integrated into the learning process. In that way, no previous offline stage is required to create new data and neither memory space to save it. Concretely, these layers have been coded as Caffe [169] python layers, since Caffe framework (see Section 3.2.3) allows the customization of layers without modifying the Caffe core code¹¹. One of the presented layers performs rectangular cropping, which is not provided by Caffe libraries. In addition, this cropping is randomly padded, in contrast to [53], where central cropping is performed. The second layer simulates random illumination variations on the samples, provided the human shape and aspect of people in the images are not altered.

Moreover, some recent works are focused on improving the effectiveness of regularization and data augmentation techniques by specialising them for a certain metric, or a pair of camera views, e.g. [51, 299]. In contrast, the proposed augmentation techniques are suitable for any dataset and independent from the used metric.

f) Architectures and body parts partitioning

A comparative study of different existing networks architectures has been performed. Two different VGG architectures have been evaluated, one with sixteen layers, VGG16, and the other one, with eleven, VGG11. The effects of shortening the network architecture have been analysed, concluding that the simpler the model, the less prone to be over-fitted it is.

Besides that, three new neural architectures have been developed. They are based on different human shapes partitions to integrate spatial information into the modelled descriptors, to make them robust against pose and background variations and to deal with the misaligned features problem of Re-Id task.

Firstly, a novel three-dimensional representation to describe the similarity between two images was proposed. This model roughly divides the human shape into three parts corresponding to the head, body, and legs by considering a fixed human proportion. For each part, a deep Siamese Network has modelled the DoAS between two people. The result is the learning of three similarity

¹⁰Triplets Permutation has been implemented as a set of C++ functions, which are publicly available under: http://github.com/magomez/dataset_factory/tree/master/data_factory_from_reid

¹¹Data augmentation layers are available under: https://github.com/magomez/data_augmentation_layers

distances (one per body part) whose computation gives the value of each one of the three components of a descriptor. Finally, with the aim of obtaining a single value metric, the comparison between the two images is calculated as the module of the three-dimensional descriptor.

Secondly, a unified approach, which has been denoted as Deep Parts Similarity Learning (DPSL), was proposed. In this model, body-parts features and their combination are jointly learnt by training DCNNs. This architecture divides the human shape into nine body parts, two for each limb and the head. Instead of the symmetry-based silhouette partition, presented in [23], or the Pictorial Structures used in [103], this work proposes the integration of a Convolutional Pose Machine (CPM), [339], into the learning framework¹².

The features corresponding to each body part are parallelly learnt in the same process. The proper weighting of the learnt features has been also addressed by deep learning, allowing the automatic search of the most discriminative person descriptor. All the stages, body parts extraction, and feature and weighting learning are integrated into a unified learning framework.

Finally, an approach that fusions the advantages of the two previous ones has been designed. This is based on a partition of the input images in three parts, from which features are jointly learnt by a unified triplet model.

g) Mahalanobis Distance Learning

The use of the Mahalanobis distance as a connection function to measure the similarity between two-person features has been proposed. The intuition under this approach is that a Mahalanobis matrix can be learnt to embed camera-to-camera transitions in order to deal with the intra-class variations.

Some Re-Id algorithms evaluate the discriminative importance of every feature others learn a distance to implicitly compute the transformations between two views, like [214] and [140, 282] respectively. Nevertheless, in this thesis, both functions are performed by the Mahalanobis matrix estimation.

In contrast to previous works, where the Mahalanobis matrix is estimated from a set of previously computed features, such as [285, 140], this dissertation proposes the integration of an estimation process into the features learning process, affecting on the features learning evolution, and improving it simultaneously. With that purpose, two different methods have been formulated and implemented as novel neural layers¹³.

The first proposed method estimates the Mahalanobis matrix by a discriminative data analysis process by exploiting the structure of the data under the assumption that both sets of images

¹²Parts extraction layer is publicly available under <http://github.com/magomez/CPMclass>

¹³Layers to learn Mahalanobis matrix are publicly available under: <http://github.com/magomez/MahalanobisMatrixLearning>

present the same distribution. This estimation has been optimized by the adaptively learning of the covariance matrices of two features spaces, the similar and dissimilar ones.

The second method automatically learns a Mahalanobis matrix. The estimation of the matrix is not only integrated into the learning of the features, but it is simultaneously learnt. The elements of the matrix are considered as new neural weights, and the implemented layer codes a new triplet loss function, using Mahalanobis distance, and its derivatives to perform backwards propagation.

Chapter 3

Methodology

This thesis asserts that both Multi-Person Tracking and Re-Identification can be faced through a similarity appearance model. Indeed, Person Re-Identification has been addressed by measuring the degree of visual appearance similarity between an image and a set of possible candidates, and the core of the proposed Multi-Target Tracking method is a data association mechanism based on taking the degree of appearance similarity as a matching score between two observations.

The Degree of Appearance Similarity (DoAS) has been modelled by a deep neural network, whose parameters must be properly trained. This chapter describes the approach and development methodology followed to formulate effective appearance models, learning techniques, and algorithms to track and re-identify multiple people.

3.1 Approach: Learning the Degree of Appearance Similarity (DoAS)

With the aim of exploiting the visual appearance of a target individual to track and re-identify him/her among multiple people, an appearance model has been developed.

Given the unpredictable nature of the surveillance task in unstructured scenarios, an essential capacity for MOT and Re-Id algorithms is the versatility to be applied to any unknown individual.

To achieve that, the idea of independently modelling any of the appearing individuals' appearance has been discarded. Instead of that, a universal model has been designed to measure the degree of similarity between two person images. This model predicts whether the images correspond to the same person or not. Consequently, an input pair formed by images of the same person is considered as a positive pair, and a pair consisting of images of different people is taken as a negative pair. Hence, instead of modelling a specific individual's appearance pattern, the situations of sim-

ilarity and dissimilarity are discriminated in two classes. Each one of these classes is the absence of the other.

Therefore, the measurement of the Degree of Appearance Similarity (DoAS) has been formulated as a pair-wise binary classification problem. Due to the contrastive essence of a pair-wise approach, the proposed appearance model measures a comparative distance between two person images. This distance value can be understood as the probability of a pair of images belongs to the dissimilarity class. And the complementary probability, that of belonging to the similarity class, is taken as the DoAS.

Instead of computing the distances directly over the raw images, these are calculated from representative feature arrays of the person images. Therefore, it is necessary to model an embedding $F(I)$, to map an input image I to a feature space, such that the distances between samples rendering the same person are small and larger between different people in that feature space.

In this thesis, the feature embedding has been modelled by a Deep Convolutional Neural Network (DCNN). Therefore, the feature representation for an image, I , is given by the output of the DCNN, $F_W(I)$, which depends on its weights values, W .

Next section describes the framework designed to develop these network models, and the surveillance algorithms where the models are applied.

3.2 Development Framework

A development framework has been implemented to train and test neural models and to evaluate the final applications into which they are integrated. This framework states the basics to try different architectures and learning techniques in order to solve MOT and Re-Id. Therefore, this has been used as a platform to conduct experiments.

This framework is formed by a variate set of tools to perform multiple tasks, which are needed to develop algorithms and learning techniques. These tools include, programmes to create specific datasets, to visualise a learning process evolution, to compute evaluation metrics, and to interpret the learnt model in different programming languages.

The architecture of this platform and the programming resources used to implement it are described in the following subsections, but previously, a set of concepts definitions are given.

3.2.1 Concepts

There are several confusing terminologies in the field of Neural Network learning. This section defines the concepts that they refer to, throughout this dissertation.

Neuron. This is a simple computational unit that has weighted input signals and produces an output signal using an activation function. It's a building block of a neural network.

Layer. This is a set of neurons. Neural networks are typically organised in layers. The neurons of a layer are not connected amongst themselves, but they are with the neurons of the next or previous layer.

Network architecture. This is the structure of a neural network, and it is defined by the number and types of its layers and the pattern of connectivity between neurons, that is the way in which its neurons are linked together.

Model. It is the set of trained parameters of a network architecture, W , i.e. the values to weight every connection between neurons.

Learning model. This is the configuration or structure used to train a neural network. Two examples of widely used learning models to train deep Re-Id networks are Siamese and Triplet model. The Siamese model duplicates the query network in two identical branches and the Triplet model triplicates it in three branches. These learning models structures are determined by the loss function formulation.

Loss function. This function measures how much error is incurred in predicting a certain output value for a particular model, according to an established objective. This function is also called cost, penalty or objective function.

Learning algorithm. This is the procedure used to optimise the loss function, which means to find the values of the neural network weights (model) that minimise the loss value.

Hyper-parameters. This term refers to the parameters that govern the learning algorithm, the loss function or the whole learning process. This term does not refer to the parameters trained by the learning algorithm (network weights). Hyper-parameter symbols are listed in the Appendix A.

3.2.2 Development Framework Architecture

The structure of the development framework is illustrated in Fig. 3.1, where its main modules are rendered.

A series of datasets have been collected and divided into two different groups: developing and evaluation datasets. The developing datasets are treated in the data generation framework to create training, validation and test samples, in the proper format to feed the neural models.

The training framework uses a learning algorithm with a learning model to train the parameters of a certain network architecture, resulting in the learning of a model. The learning is a supervised offline process.

The selection of different hyper-parameters values results on different models, whose convergence is validated over the validation data by means of the validation tool.

The testing framework measures the performance of a model. The network architecture weights receive the learnt values, saved in the model. The predictions given by the network for the samples of the test set are used to measure the value of certain performance metrics.

Moreover, the learnt models are used to perform both Multi-Object tracking and Person Re-identification, by means of using the network output as a measurement of the DoAS between two images. The evaluation framework measures the performance of the developed surveillance applications over the evaluation datasets.

In this dissertation, the term test has been used to refer to the measurement of the performance of the trained neural models. On the other hand, the term evaluation refers to the measurement of the performance of the final surveillance application, where the models are integrated.

Further sections describe the programming tools and the datasets used to conduct experiments, and the details of each module of the developing framework: Data Generation, Training and Testing Framework. Finally, the last section presents the addressed surveillance applications.

Fig. 3.1 Development framework architecture

3.2.3 Programming Tools

To design and training neural network models Caffe libraries have been employed (Caffe: Convolutional architecture for fast feature embedding). Caffe is a deep learning framework meant to provide speed and modularity. Caffe project was created by Yangqing Jia [169] and is developed by Berkeley AI Research (BAIR) and by community contributors.

In the last years, Caffe libraries have been widely used by the computer vision research community. Many authors have delivered Caffe implementations of their network architectures and layer formulations and even pre-trained models.

In addition, the modular essence of Caffe framework allows the creation and the integration of new layers in a neural model. In this thesis, several new Caffe layers have been designed. They have been programmed using Python language (version 2.7). Python [281] provides easy management of the inputs and outputs of the neural layers as matrices of data.

Moreover, once the neural models have been learnt, they are integrated into a surveillance application, to perform MOT and Re-Id. These algorithms and their evaluation tools have been implemented using C++ language [71], which is a programming language designed by Bjarne Stroustrup in the middle 80s. It was meant to expand the C language with mechanisms to handle objects. Therefore, C++ is a hybrid or multi-paradigm language that allows structured and object-oriented programming. Objects are abstracted through classes that possess their own identity, attributes and methods or functions.

Therefore, C++ is a suitable language to implement the architecture of the proposed MOT algorithm, and the tools to evaluate it. The proposed multi-agent management strategy, based on the creation of agent instances to manage every individual's attributes is efficiently coded by C++ classes and structures.

In addition, many of the processing stages over the surveillance sequences have been implemented with OpenCV libraries (version 2.4). OpenCV libraries [164, 163] were designed to provide computational efficiency in real-time applications, and they include hundreds of computer vision algorithms coded in several programming languages. In this thesis, both C++ and Python functions of OpenCV have been employed.

As long as the hardware is concerned, two GPUs have been used to train neural models: Nvidia GeForce GTX Titan X Pascal 12GB GDDR5 and Nvidia GeForce Titan Xp 12GB GDDR5X. The final applications are executed by an Intel Core i7-4790K processor with 4.0Ghz and 4 cores, together with the GPU Nvidia Gigabyte GeForce GTX 960 OC WindForce 4GB DDR5.

3.3 Datasets

In order to obtain the data to conduct experiments, previously, an assortment of datasets have been collected. Bench-marked datasets, widely used in both fields of research, Person Re-identification and Multi-Object Tracking, have been selected.

Due to the supervised character of the performed training, all the employed datasets are accompanied by ground truth files with labels. Their ground truth information is also used in the processes of validation, test and evaluation to measure the performance of the proposed solutions.

3.3.1 Re-Identification Datasets

Person Re-identification datasets are usually composed of two groups of samples, probe and gallery sets, captured from non-overlapping camera views. Single-Shot datasets provide a maximum of one sample in each group for every identity. Each sample is a person image, and the individuals represented by probe images must be recognised among the gallery samples, captured from a different camera view. Not always, every individual has representation in both groups. Indeed some datasets add distraction samples which do not form matched pairs.

Five publicly available Single-Shot Re-Id datasets are used in the presented development framework: PRID2011 [152], VIPeR [138], CUHK-02 [200, 201], GRID [223] and i-LIDS-VID [385]. Table 3.1 presents the details of these datasets.

Table 3.1 Details of the PRID2011, VIPeR, GRID, i-LIDS, and CUHK datasets. #probe and #gallery indicate the number of identities in these sets.

Name	Environment	Resolution	#probe	#gallery	Challenges
PRID2011 ¹	Outdoor	64x128	385	749	Severe lighting change
VIPeR	Outdoor	48x128	632	632	Viewpoint and illumination changes
CUHK-02 (P1)	Outdoor	60x160	971	971	Viewpoint and illumination changes
GRID ²	Underground station	An average of 70x180	250	1025	Inter-object occlusions and viewpoint variations
i-LIDS-VID	Indoor airport arrival hall	An average of 60x150	300	300	Viewpoint and illumination changes and inter-object occlusion

¹ 200 matched pairs in both views

² 250 matched pairs in both views

These are some of the most widely used datasets for evaluating Re-Id approaches since they are composed of person images captured from two camera views with remarkable differences in camera characteristics, illumination, person's poses, and background. For that reason, all these datasets have been used, as evaluation datasets in this dissertation.

However for developing models and algorithms two of them has been selected: PRID2011 and ViPeR dataset, since they are representative examples of datasets acquired from a fixed camera pair, and from multiple viewpoints, respectively. In PRID2011 all the images from the probe set were captured from the same camera view, and all the samples from the gallery were acquired from a second camera view different from the first one. However, in ViPeR, the images were captured from many different views, even inside the same set, but maintaining the assumption that the representation of a person in the probe set was captured from different camera view than that from which its representation in the gallery was captured.

a) PRID2011

The PRID2011¹ dataset (Person Re-IDentification 2011) was captured from two different, static surveillance cameras, placed outdoors, in 2011. This thesis uses the single-shot version in which each person is only associated with one picture in a camera set. The two sets contain 385 and 749 individuals separately. 200 of the individuals are rendered in both sets. The images contain viewpoint and pose changes and a stark difference in illumination, background and camera characteristics. Therefore, the challenge lies in severe lighting changes caused by the sunlight. Example images of this dataset are shown in Fig. 3.2

Fig. 3.2 Example images of the PRID2011 dataset. Each column renders a person's pair of images.

b) ViPeR

The ViPeR² dataset (Viewpoint Invariant Pedestrian Recognition), released in 2007, contains 632 pedestrian image pairs taken from arbitrary viewpoints under varying illumination condi-

¹PRID2011 dataset is publicly available under: <https://www.tugraz.at/institute/icg/research/team-bischof/lrs/downloads/prid11/>

²ViPeR dataset is publicly available under: <https://vision.soe.ucsc.edu/node/178>

tions. Hence, each person has two images, captured in two different outdoor views. The dataset is demanding due to large appearance differences between the images of most of the matched pairs caused by viewpoint and pose variations and large illumination changes at an outdoor environment. Example images of this dataset are shown in Fig. 3.3.

Fig. 3.3 Example images of the VIPeR dataset. Each column renders a person's pair of images.

c) CUHK-02

The CUHK-02³ dataset, created by the Chinese University of Hong Kong in 2013, contains 1816 identities, 7264 images manually cropped and captured from five pairs of disjoint camera views (P1-P5). These camera-pair subsets have 971, 306, 107, 193 and 239 persons respectively. In this thesis, subset P1, also called CUHK-01 dataset has been used to test and the rest of the sets, for training. Each identity presents two images per camera view. The dataset is challenging due to viewpoint and pose variations and illumination changes at an outdoor environment. Example images of this dataset are shown in Fig. 3.4

Fig. 3.4 Example images of the CUHK dataset. Each column renders a person's pair of images.

³CUHK dataset is available for the academic purpose under:
http://www.ee.cuhk.edu.hk/xgwang/CUHK_identification.html

d) GRID

The GRID⁴ dataset (underGround Re-IDentification), created by Queen Mary University of London (QMUL) in 2009, was captured from eight disjoint camera views installed in a busy underground station, [222]. The probe set contains 250 individuals, whilst the gallery set contains 1 025 individuals, where 775 of them are not rendered by any of the images of the probe set, so are distraction samples. This dataset is challenging due to severe inter-object occlusions, large viewpoint and pose variations, colours and lighting changes and poor image quality. Low spatial resolution and noisy artefacts due to video transmission and compression make the dataset more challenging. Example images of this dataset are shown in Fig. 3.5.

Fig. 3.5 Example images of the GRID dataset. Each column renders a person's pair of images.

e) i-LIDS-VID

The i-LIDS-VID⁵ dataset (Imagery Library for Intelligent Detection Systems) was captured in a busy airport arrival hall, and it was released in 2014. It involves 300 different pedestrians observed across two disjoint camera views in public open space. The average number of images per person is 73 (from 23 to 192). Therefore, this is a Multi-Shot Re-Id dataset. To perform the evaluation of a Single-Shot based person Re-Id method, some images have been randomly selected from the available static-images-based version, as Section 6.2.1 describes.

The i-LIDS-VID dataset is very challenging due to clothing similarities among people, lighting and viewpoint variations across camera views, cluttered background and severe inter-object occlusions. Most of the people are carrying bags or suitcases. These accessories can be profitably used to match their owners, but they introduce a lot of occlusions which usually act against the matching. In addition, the taken images present different qualities (in terms of resolution, zoom level, noise),

⁴GRID dataset is publicly available under:

http://personal.ie.cuhk.edu.hk/ccloy/downloads_qmul_underground_reid.html

⁵i-LIDS-VID dataset is publicly available under:http://www.eecs.qmul.ac.uk/xiatian/downloads_qmul_iLIDS VID VID_ReID_dataset.html

making very challenging the Re-Id task over this dataset. Example images of this dataset are shown in Fig. 3.6.

Fig. 3.6 Example images of the i-LIDS-VID dataset. Each column renders a person's pair of images.

3.3.2 Multi-Object Tracking datasets

Multi-Object Tracking datasets are usually composed by a collection of surveillance video-sequences, together with a ground truth file for each one of them. The ground truth file contains the location and identity of every individual at every frame of the sequence. The identity of every person is denoted by an identification number whose value is maintained through the video.

Two publicly available MOT datasets are used in the presented development framework. They are CAVIAR and MOT17 dataset. Table 3.2 presents their details.

Table 3.2 Details of the CAVIAR and MOT17 datasets. #seq, #f, #id indicate the number of sequences, total frames and total identities

Name	#seq	Scenario	Resolution	#f	#id
CAVIAR ¹	26	Indoor	384x288	36303	258
MOT17	14	12 outdoor sequences 2 indoor sequences	1920x1080 in 12 sequences 640x480 in 2 sequences	11235	546

¹ Corridor view sequences of the 2nd set of CAVIAR

a) CAVIAR

The CAVIAR⁶ dataset [107] (Context Aware Vision using Image-based Active Recognition) consists of two sets of video clips, which were released in 2005. The first set was filmed with a wide-angle sensor in the reception of the INRIA Labs at Grenoble, France. The second set, also acquired by a wide-angle lens, was filmed along and across the hallway in a shopping centre in Lisbon. For each sequence, there are two timely synchronised videos, one of them with the view across and

⁶CAVIAR dataset is publicly available under: <http://homepages.inf.ed.ac.uk/rbf/CAVIARDATA1/>

the other along the hallway. All the videos have half-resolution PAL standard (384 x 288 pixels, 25 frames per second) and they have been compressed using MPEG2. Generally, the sizes of the MPEG files are between 6 and 12 MB (up to 21 MB).

This thesis uses those videos with the view across the corridor from the second CAVIAR set. They have been divided to form developing and evaluation datasets. These sequences include people walking alone, meeting with others, window shopping, entering and exiting shops, producing some of the most challenging situation for the tracking: people crossing between them, changing-trajectory individuals, groups, partial-term occlusions and people re-appearing in the scene.

b) MOT₁₇

The MOT₁₇ dataset belongs to the MOTchallenge⁷ and includes fourteen variate real-world surveillance sequences, meant to train and test Multi-Person Tracking algorithms, which were released in 2017. The MOT₁₇ dataset contains the same set of sequences as MOT₁₆ [236], but with an extended more accurate ground truth.

The sequences of MOT₁₇ dataset are split into two groups of seven sequences. The sequences of the first group are labelled. These have been used as developing sequences in this thesis, whose content, in turn, has been divided into train, validation and test data. These data sets have used to learn, validate and test appearance neural models. Moreover, the unlabelled sequences of the second set have been used as evaluation sequences. The designed surveillance algorithms have been executed over these sequences. Since the ground truth of these sequences is not publicly available, the evaluation process is performed by submitting the algorithms' outputs to a public platform provided by the MOTchallenge, where the comparison with the ground truth is made.

In contrast to CAVIAR dataset, MOT₁₇ dataset provides the location of the detected people at every frame. In that way, only tracking performance is evaluated, without requiring the implementation of a previous detection stage. For every sequence, the detections given by three different people detectors (DPM, Faster-R-CNN, and SDP) are provided. Therefore, three different versions of every sequence are available, resulting in 21 sequences for every group, the labelled and the unlabelled one.

This benchmark contains challenging video sequences in unconstrained environments filmed with both static and moving cameras.

⁷MOTChallenge is a Multiple Object Tracking Benchmark which provides a unified framework to standardise the evaluation of MOT methods. This includes a variety of rankings, such as MOT₁₇Det and MOT₁₇ challenges. This is published under: <https://motchallenge.net/>

3.4 Data Generation Module

With the aim of training a similarity appearance model, two different learning models have been tried: Siamese and Triplet. These models compare pairs and triplets of images, respectively. Moreover, to give temporal consistency to these models, Long Short Term Memory (LSTM) cells have been added to them. LSTM cells take information from a sequence of images (tracklets). Therefore pairs, triplets and tracklets of person images must be created to feed these learning models (deeply described in Chapters 4 and 5).

Data generation module is in charge of dividing the datasets into train, validation and test sets, and creating pairs, triplets, and tracklets of images from each one of them. The stages of Data Generation module⁸, rendered in Fig. 3.7, are coded in independent python modules and sh scripts.

Fig. 3.7 Architecture of the Data Generation module.

This module transforms the data to the format required by Caffe framework. Caffe layers take data in a format called blob. A blob is a kind of data matrix defined by these parameters:

⁸The functions composing the data generation module are publicly available under [https : github com magomez dataset_factory](https://github.com/magomez/dataset_factory)

- Batch size, B , is the number of taken samples at every learning iteration.
- Channel, K , is the number of colour channels of the input images in the initial layer, and K renders the features dimension in further layers.
- Height, H , is the number of rows.
- Width, W , is the number of columns.

Therefore, the dimension of a blob is $B \times K \times H \times W$.

Both Re-Id and MOT datasets are composed by sets of images (person images, or sequences of frames respectively) and ground truth files containing the identities of the rendered people. The ground truth information is considered by the data generation module in order to properly combine person images to create matched and mismatched pairs, for example. In addition, the identities information is also packaged into label blobs.

In the case of creating blobs from frames, the detections on them must be previously extracted to provide samples of person images. The information required for that is available in the ground truth of MOT sequences. This samples extraction stage is not required when blobs are created from Re-Id datasets since person images samples are already provided.

3.5 Training and Testing Framework

The DoAS between person images is obtained by comparing the features computed for each one of them. These features are computed by a certain DCNN, whose parameters have been learned with supervised training using Caffe libraries [169]. The input of the Training Framework is a set of blobs that encompasses the training data (samples and labels), which have been obtained with the Data Generation module.

The presented training framework supports the learning of different neural networks. Therefore, the training output is a model which is the set of learned parameters values for a certain architecture (see Fig. 3.1). The obtained model is, in turn, taken by the validation tool and the testing framework. Every certain number of learning iterations, the validation tool evaluates the model during its training, in order to check the model behaviour over a set of samples different from the training ones. The testing framework computes metrics to measure the final model performance over the test set. Analogously to the train set, the validation and the test sets are blobs given by the Data Creation module.

To compute the output given by a neural network for a certain input sample, it is necessary to use the network architecture, with the parameters values that are given by the model and compute

every layer operation. This computation is performed by a tool that has been called the feature computation module since the output of a neural network is a feature array.

The feature computation tool is used to test the learned models, and to integrate them into the final surveillance algorithm. Besides that, it is also needed to train some complicated architectures, as it will be explained in further chapters. The feature computation tool, as well as, the theoretical foundations of the employed learning algorithms are exposed in the following sections.

3.5.1 Feature Computation Module

The proposed MOT algorithm is based on the agents' appearance. Therefore, the computation of the appearance features has been integrated into the final application code.

The feature computation tool is in charge of obtaining a person representation, by means of computing the output of a certain neural network, once its weights have been trained. The network input is a person image, and the output is a feature array.

In this thesis, different network architectures have been implemented, but all of them using Caffe library layers. The architecture of a neural network is defined in a "prototxt" file, where the relationships between the Caffe layers are established. A trained model is saved in a "caffemodel" file, which contains the learnt weights for this architecture. These files are the inputs of the feature computation module.

The programs where feature computation is integrated, i.e. the surveillance application, and evaluation framework, are coded in C++ language. Therefore, the feature computation module, composed of C++ functions⁹, is a bridge between C++ code and Caffe files. This module transforms the images data to the Caffe format, interprets the network architecture and its trained weights, and offers the net output as a feature array.

3.5.2 Learning Algorithm

The objective of the learning algorithm is to optimise the loss function, which means to find the values of the weights of the neural network that minimise the loss value.

The computation of a neural network outputs a feature array. For correct performance, this feature must present a certain range of values, defined by objective thresholds. The objectives of a neural network are defined by a loss (or cost) function. At the same time, the loss function penalises the deviation of the network's outputs with respect to the objectives. The output of the network depends on the values of its weights, which are trained by the learning algorithm. Hence,

⁹The C++ class needed to interpret several network architectures and pre-trained weights is publicly available under https://github.com/magomezsf/feature_computation

in summary, the learning algorithm fits the parameters of the network, given a training set, so that, the cost function is minimised.

Due to the non-linearity and high-dimensionality of the feature formulation that DCNNs provide, a numerically analytic method is not applicable. The loss value is calculated by a multi-dimensional function that depends on every parameter. Given the huge number of parameters (millions) in a DCNN, it is impossible to analytically localise the minimum in the loss function. For that reason, optimisation methods are used with that purpose. An example of optimisation method is Gradient Descent (GD) method, which has been employed in this thesis.

To minimise the loss value, $f_L W$, as a function of the set of parameters, W , an optimisation method, such as Gradient Descent, need two inputs at every iteration, t :

- The loss function value, $f_L W^t; X_i$, for a set of parameters, W , and an input sample, X_i .
- The partial derivatives terms with respect to every parameter, which is the gradient vector of the cost function, $\frac{\partial f_L W^t; X_i}{\partial W_j^t}$.

The loss value is obtained by forward propagation, which is the process of computing the network's output by performing the operations defined by its neurons. Each neuron computes and outputs a value called activation. Therefore, the activations are forward-propagated from the network input to its output.

The derivatives are obtained by the back-propagation (backward propagation) [283] method. The errors (deviation with respect to the objective) of the network's output are computed, and distributed backwards throughout the network's layers, by using the derivative chain rule to iteratively compute gradients for each layer.

Then, the Gradient Descent algorithm outputs the set of updated parameters, computed by the Delta rule (Eq. 3.1), where η is the learning rate. The direction in which the cost function decreases, with a negative slope, is given by the gradient term. In that way, in every step, the set of weights are approached to the values that make the cost function decreases, until achieving a minimum. Gradient descent is susceptible to local optima.

$$W^{t+1} = W^t - \eta \frac{\partial f_L W^t; X_i}{\partial W_j^t} \quad (3.1)$$

The Gradient Descent algorithm is an iterative training method. Therefore, first, network weights, W , are randomly initialised, and then forward propagation, back-propagation and weights updating are recursively computed for every training sample. This cycle can be repeated through several epochs. An epoch is one training cycle (forward and backward) of the complete training set. The main procedures of Gradient Descent algorithm are shown by Algorithm 1.

Algorithm 1 Stochastic Gradient Descent algorithm (1 epoch)**Require:** Training samples, $X = X_i$.**Ensure:** The network parameters $W = W_j$.

- 1: $W^0 = \{w_j^0\}$
- 2: $\frac{\partial f_L(W^t; X_i)}{\partial W^t} = 0$;
- 3: **for all** training triplet X_i **do**
- 4: Calculate $f_L(W^t; X_i^t)$ by forward propagation;
- 5: Calculate $\frac{\partial f_L(W^t; X_i^t)}{\partial W_j^t}$ by back-propagation.
- 6: Update parameters according to Eq. 3.1.
- 7: **end for**

GD method is the optimisation algorithm most commonly used to train neural networks. At the same time, there exist various algorithms and methods to optimise GD, such as momentum [272], Adagrad [93], or regularization.

When using Caffe libraries, the selected optimisation algorithm is specified in a file called solver. The solver file also saves the values for the needed hyper-parameters, like the learning rate, α . The symbol for every hyper-parameter referred to in this dissertation is defined in Appendix A.

Furthermore, there are three variants of GD: batch, mini-batch and stochastic. They differ in the number of samples used to compute the gradient of the objective function. The selection of this amount of data brings a trade-off between the accuracy of the parameter update and the time it takes to perform an update.

Algorithm 1 presents the Stochastic Gradient Descent (SGD) (or simply Gradient Descent, GD), where the gradient of the cost function w.r.t. to the parameters W is computed for every new training sample.

Batch GD computes the gradient for the entire training dataset at once. Batch GD ensures the convergence to the global minimum for convex cost surfaces. Nonetheless, often in practice, the computation of the loss and gradient value for the entire training set can be very slow and even intractable on a single machine if the training set is too large to fit in the available memory. Moreover, it does not allow an easy way to incorporate new data in an ‘online’ setting.

Mini-Batch GD performs an update for every mini-batch of B training examples. The batch size, B is an extra hyper-parameter. Mini-batch gradient descent is the most commonly used algorithm when training a neural network [30] and the term Stochastic Gradient Descent usually is also employed when mini-batches are used (but not in this dissertation). The reason for the extended use of Mini-Batch GD is twofold: first, this reduces the variance in the parameter update, caused by SGD, and can lead to more stable convergence. Second, this allows a faster computation than Batch GD. Moreover, a well-vectorized computation of the loss and gradient values can

make Mini-Batch GD even faster than SGD. In this thesis Mini-Batch GD has been employed, also motivated by the limitations in processing memory resources. The chosen batch size was that as large as the available memory resources make possible.

3.6 Applications

The final purpose of creating a development framework is to provide a platform where surveillance applications can be designed, implemented and evaluated.

The developed application in this thesis is a Multi-Object Tracking algorithm, which is able to manage multiple agents, and capable to deal with crossings, changing trajectory individuals, and partial and total occlusions for short and long term. With the aim of cope with long-term disappearances and multiple-camera settings, a Re-identification module is also integrated on the application.

Both MOT and Re-Id methods are based on visual appearance models to measure the similarity between agents. The models are developed on the Training and Testing framework, and integrated into the application with the Feature Computation module (see Fig. 3.1).

However, the model learning depends on its final purpose: tracking a person through contiguous frames or re-identify an individual on timely and locally separated captures. Each one of these tasks needs to deal with different requirements, challenges, and training data. This lead to the design of different and specified learning techniques, models and architectures. They are described in the following Chapters. Chapter 4 describes methods to learn an efficient Re-Id model, and Chapter 5 the whole MOT architecture, where appearance models are integrated.

The evaluating protocols and metrics are also different for both algorithms, MOT and Re-Id, and they are described in Chapter 6.

Chapter 4

Person Re-Identification

The Person Re-Identification (Re-Id) problem consists of visually recognising people across non-overlapping camera views at different locations and time. It is assumed that person images have been previously detected in both camera views. This thesis presents the research conducted to improve the Single-Shot Re-Id task, where a person is re-identified by means of only one capture from each one of two different cameras.

Single-Shot Re-Id allows reducing the quantity of data transmitted between neighbours cameras, with respect to Multi-Shot Re-Id which relies on the previous tracking of an agent to obtain a tracklet formed by consecutive detections. Therefore, Single-Shot Re-Id speeds up communications in a distributed network of cooperative surveillance sensors.

Considering Single-Shot Re-Id task as an isolated module, its objective is to identify the person represented by an image from one view, called probe image, among a set of images from the other view, denoted as gallery images.

This is achieved by calculating the distances between the probe image and all the gallery images and selecting as correct match that gallery image presenting the smallest distance. However, the distances are not computed directly over the raw images but over a representative feature array.

Therefore, it is necessary to learn a certain distance metric and an embedding $F: I \rightarrow \mathcal{F}$ from an image I into a feature space, such that the distances between samples corresponding to the same person are smaller than that to different people. In that way, the Re-Id algorithm consists of the computation of features for a pair of person images and its comparison through a connection function, a.k.a. distance metric, dm , as Fig. 4.1 shows.

The Degree of Appearance Similarity, DoAS, between two images is defined as the probability that the pair of images render the same person. Conversely, dm , whose value has been normalised from zero to one, provides the probability of a pair of images render different people since similar images comparisons produce small values for the distance between their descriptors, and dissimilar

images comparison cause just the opposite effect. Therefore, the distance metric, dm , and the DoAS between two images are complementary values, as Eq. 4.1 defines.

In that way, the Single-Shot Re-Id problem can be treated as a pairwise binary classification, where the DoAS value discriminates positive and negative pairs.

Fig. 4.1 Re-identification method.

$$DoAS = 1 - dm \quad (4.1)$$

The feature embedding has been modelled by a DCNN, using the presented Learning Framework (Section 3.2). The learning of such feature embedding, $F(I)$, requires of the definition of the architecture of the DCNN used to model it, and the learning model and algorithm employed to train its weights (see Fig. 3.1). This chapter describes them, as well as, the designed methods to improve both, the learning process and the Re-Id capacity of the resulting model.

A basic network architecture used to model the person feature array is presented in Section 4.1. Moreover, two different learning models have been employed to train that network architecture, Siamese and Triplet. The loss functions that define these models and the learning algorithms formulated for using them are described in Sections 4.2 and 4.4. The techniques designed to feed the Siamese and Triplet model are explained in Sections 4.3 and 4.5, respectively. Then, Sections 4.6 and 4.7 presents some methods implemented for improving the Re-Id model learning. In addition, both, the feature embedding and the distance metric used to compare two person features have been improved. Consequently, the design of different network architectures based on human shape partition, and the learning of the Mahalanobis distance are proposed in Section 4.8 and 4.9. Finally, Section 4.10 presents the application of the designed models and learning techniques to different visual tasks, as proof of their versatility¹.

4.1 Deep Convolutional Neural Network Architecture

The transformation of every image, I , to its corresponding representation in the feature space, $F_W(I)$, is performed by a Deep Convolutional Neural Network, DCNN. Therefore, the feature representation for an image is given by the output of the DCNN, which depends on the values of its weights, W .

¹This Chapter includes contents from items 1, 2, 5, 6, 9 and 11 of "Published and Submitted Content" list.

Choosing the number of layers of this DCNN is critical to get an effective Re-Id model. The deeper the network is, i.e. the higher the number of its layers is, the higher the level of complexity of the representations that it is able to model. Therefore, a high-layered network could embed salient and discriminative high-level features. Nevertheless, the increase in the number of neural layers implies a larger number of parameters to train, boosting its over-fitting. Hence, achieving a trade-off solution is required to get discriminative features while avoiding model over-fitting.

The initial experiments of this thesis have been conducted using adapted versions of two well-known architectures. Concretely, a 16-layered network, hereafter called VGG16, presented as the D version of a set of Very Deep CNNs in [303], and an 11-layered network, henceforth, VGG11, presented as the A version in the same work. Therefore, two similar network architectures, but differently layered, have been trained. The layers specifications for the proposed VGG16 and VGG11-based embeddings are listed in Tables 4.1 and 4.2, respectively.

Table 4.1 Structure of the used VGG16-based model. The input and output sizes are described in *#rows x #cols x #filters*; the kernel, in *#rows x #cols x #filters, stride*, or *#outputs* for FC layers.

Layer	Input size	Output size	Kernel
Conv-1-1	128 x 64 x 3	128 x 64 x 64	3 x 3 x 3
Conv-1-2	128 x 64 x 64	128 x 64 x 64	3 x 3 x 64
Pool-1	128 x 64 x 64	64 x 32 x 64	2 x 2 x 64, 2
Conv-2-1	64 x 32 x 64	64 x 32 x 128	3 x 3 x 64
Conv-2-2	64 x 32 x 128	64 x 32 x 128	3 x 3 x 128
Pool-2	64 x 32 x 128	32 x 16 x 128	2 x 2 x 128, 2
Conv-3-1	32 x 16 x 128	32 x 16 x 256	3 x 3 x 128
Conv-3-2	32 x 16 x 256	32 x 16 x 256	3 x 3 x 256
Conv-3-3	32 x 16 x 256	32 x 16 x 256	3 x 3 x 256
Pool-3	32 x 16 x 256	16 x 8 x 256	2 x 2 x 256, 2
Conv-4-1	16 x 8 x 256	16 x 8 x 512	3 x 3 x 256
Conv-4-2	16 x 8 x 512	16 x 8 x 512	3 x 3 x 512
Conv-4-3	16 x 8 x 512	16 x 8 x 512	3 x 3 x 512
Pool-4	16 x 8 x 512	8 x 4 x 512	2 x 2 x 512, 2
Conv-5-1	8 x 4 x 512	8 x 4 x 512	3 x 3 x 512
Conv-5-2	8 x 4 x 512	8 x 4 x 512	3 x 3 x 512
Conv-5-3	8 x 4 x 512	8 x 4 x 512	3 x 3 x 512
Pool-5	8 x 4 x 512	4 x 2 x 512	2 x 2 x 512, 2
FC-6	4 x 2 x 512	1 x 1 x 4096	4096
FC-7	1 x 1 x 4096	1 x 1 x 4096	4096
FC-8	1 x 1 x 4096	1 x 1 x 1000	1000

Table 4.2 Structure of the used VGG11-based model. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, *stride*, or *#outputs* for FC layers.

Layer	Input size	Output size	Kernel
Conv-1-1	128 x 64 x 3	128 x 64 x 64	3 x 3 x 3
Pool-1	128 x 64 x 64	64 x 32 x 64	2 x 2 x 64, 2
Conv-2-1	64 x 32 x 64	64 x 32 x 128	3 x 3 x 64
Pool-2	64 x 32 x 128	32 x 16 x 128	2 x 2 x 128, 2
Conv-3-1	32 x 16 x 128	32 x 16 x 256	3 x 3 x 128
Conv-3-2	32 x 16 x 256	32 x 16 x 256	3 x 3 x 256
Pool-3	32 x 16 x 256	16 x 8 x 256	2 x 2 x 256, 2
Conv-4-1	16 x 8 x 256	16 x 8 x 512	3 x 3 x 256
Conv-4-2	16 x 8 x 512	16 x 8 x 512	3 x 3 x 512
Pool-4	16 x 8 x 512	8 x 4 x 512	2 x 2 x 512, 2
Conv-5-1	8 x 4 x 512	8 x 4 x 512	3 x 3 x 512
Conv-5-2	8 x 4 x 512	8 x 4 x 512	3 x 3 x 512
Pool-5	8 x 4 x 512	4 x 2 x 512	2 x 2 x 512, 2
FC-6	4 x 2 x 512	1 x 1 x 4096	4096
FC-7	1 x 1 x 4096	1 x 1 x 4096	4096
FC-8	1 x 1 x 4096	1 x 1 x 1000	1000

In essential, convolutional neural networks combine two different operations: convolution and pooling. VGG16 presents thirteen convolution layers and VGG11, eight. Both models have three fully connected layers and a SoftMax final layer. The SoftMax layer has been removed in order to get a feature array as output instead of a classification probability value. Hence, its output is a point in the feature space represented by a 1000-dimensional array $F \in \mathbb{R}^n$ ($n = 1000$). Moreover, the input size used in [303] has been modified to adapt its value to the Re-Id samples dimensions. Therefore, the input of the proposed DCNN is an RGB image of 64x128 pixels. All hidden layers are provided of a Rectified Linear Unit (ReLU), [184], as activation function.

4.2 Siamese Model

Siamese model is a learning model used to train the parameters of a DCNN, which duplicates it in two branches, and compares their outputs. The contrastive essence of the Siamese architecture has led it to be commonly used to learn deep Re-Id neural models since it provides a pair-wise classification approach.

Following sections describe the architecture of the Siamese model, the formulation of a new contrastive loss function, and the implemented learning algorithm.

4.2.1 Siamese Architecture

The Siamese model duplicates a DCNN in two branches, sharing the same parameters. The branches are joined in the final layers, where the similarity is measured, by comparing the obtained features with a connection function, as Fig. 4.2 shows.

Fig. 4.2 Architecture of the Siamese model.

The input of the Siamese model is a pair of images, I^a and I^b , where the indexes a and b refer to the branch receiving each image. The order of the inputs has no effect on the result. If the order is commuted, the result is the same. Moreover, each image is accompanied by an identification number, $ID(I)$, since a supervised training has been conducted.

The labeller function, $y(I^a, I^b)$, is in charge of checking if the input pair is a positive one, when both images render the same person, or a negative one if they belong to different identities. It takes value 1 for positive pairs, and 0, for negative ones, according to Eq. 4.2.

$$y(I^a, I^b) = \begin{cases} 1 & \text{if } ID(I^a) = ID(I^b) \\ 0 & \text{if } ID(I^a) \neq ID(I^b) \end{cases} \quad (4.2)$$

Since both branches share exactly the same weights values, W , only one descriptor is learnt. This descriptor is computed twice (once per image) in the forward propagation of the network.

The descriptors of the input pair of images, $F_W I^a$ y $F_W I^b$, are given by the output of the DCNN branches, as feature arrays.

Once the person features for an input pair of images have been computed, they must be compared by the connection function, $f_c F^a F^b$, in order to get the distance metric, dm . The squared Euclidean distance has been chosen as a connection function in prior experiments, and the squared Mahalanobis distance in further ones (Section 4.9).

The distance between the features measures dissimilarity between the images so the objective is to get smaller distances for positive pairs than for negative ones, achieving a binary classification in the distance space.

Finally, in the last layer, the loss function measures the deviation of the computed distance value with respect to the established objective values for positive ($y=1$) and negative pairs ($y=0$). Therefore, in every iteration, the loss value measures how the classification made by the forward propagation of the network differs from the correct one, given by the label y . The loss value is consequently used by the back-propagation method [283] to force the weights in both branches to get values which make the distance metric, dm , get closer to the objective. For that reason, the loss function plays a crucial role in the learning process.

4.2.2 Normalised Double-Margin-based Contrastive Loss Function

Siamese networks have commonly been trained using the Contrastive Loss function as the loss function. The Contrastive Loss function, f_{CL} , presented in [141] is defined by Eq. 4.3, where m is a constant parameter called margin. B is the batch size, i.e. the number of pairs used to compute the loss function in every iteration. DM is an array, where every element, dm_i , is the distance computed by the connection function for the pair sample $X_i = I^a I^b$, which is computed by Eq.4.4 as the squared Euclidean distance. Analogously, Y is an array, where every element, y_i , is the value given by the labeller function for the pair i .

$$f_{CL} DM Y = \frac{1}{2B} \sum_{i=1}^B y_i dm_i + (1 - y_i) \max(m - dm_i, 0) \quad (4.3)$$

$$dm X_i = \frac{F_W I_i^a - F_W I_i^b}{2}^2 \quad (4.4)$$

The Contrastive Loss function measures the half average of the error computed for every pair, taking into account both cases, when the input images form a positive pair ($y = 1$), or a negative one ($y = 0$). The contributions of a positive and a negative pair to the loss function are described by Eq. 4.5 and 4.6 respectively, and are rendered in Fig.4.3.

$$e_p = dm_i \quad (4.5)$$

$$e_n = \max(m - dm_i, 0) \quad (4.6)$$

Fig. 4.3 Loss contribution of a positive, e_p , and negative, e_n , single pair sample to the contrastive loss function (Eq. 4.3), with $m=1.5$.

According to Eq. 4.5, positive samples cause a certain error or loss even when the distance measured is under the value of the given margin, as is shown in Fig. 4.3. This loss leads the training to learn features which make the distance between images null, causing at the same time that the distance corresponding to quite similar negative samples (inter-class ambiguity) is also lower than the margin, m , also producing an increment of the total loss. Therefore, the total loss value oscillates throughout the training due to the difficulty in leading the distances of positive samples near the zero value.

The selection of discriminative features that properly define a person's appearance is one of the current challenges for Person Re-Identification. To achieve that goal, the inter-class ambiguities have been reduced thanks to the design of the Normalised Double-Margin-based Contrastive Loss (N2MCL) function², f_{N2MCL} .

This new contrastive loss function based on two margins is one of the main contributions of this thesis. Two margins establish the separation between the objective values of the distances (calculated for the connection function) for positive and negative samples. The result of using two margins is an increment in the discriminative capacity of the learnt features, since positive and negative pairs move away from each other in the feature space, as proved in Section 6.2.4.

The formulation of the Normalised Double-Margin-based Contrastive Loss function is described by Eq. 4.7.

$$f_{N2MCL} DM Y = \frac{1}{2B} \sum_{i=1}^B y_i \max(ndm_i - m_1, 0) + (1 - y_i) \max(m_2 - ndm_i, 0) \quad (4.7)$$

²The Normalised Double-Margin-based Contrastive Loss function is implemented in a Caffe python layer, which is publicly available under: <http://github.com/magomez/N2M-Contrastive-Loss-Layer>

$NDM(ndm_1, \dots, ndm_B)$ is an array, where every element, ndm_i , is the normalised distance metric for one of the pairs of the treated batch in one learning iteration. That means that for every sample i of the batch, the metric computed by the connection function, dm , has been previously normalised with the function defined by Eq. 4.8, where e is Euler's number. In the same way, Y is an array, where every element, y_i , is the value given by the labeller function for the pair i .

$$ndm = 2 \left(\frac{1}{1 + e^{-dm}} - 0.5 \right) \quad (4.8)$$

The selection of the margins values is a critical issue which depends on the range of values presented by the distances, dm . However, this range varies along the training process. For that reason, a new intermediate step of normalisation has been added with the goal of obtaining normalised distances, ndm , within a range of values, $[0,1]$.

Subsequently, f_{N2MC} measures the half average of the error computed for every pair, with respect to m_1 and m_2 , which are two constant parameters called margins. The margin parameters have been set with the values $m_1 = 0.3$ and $m_2 = 0.7$. B is the batch size.

Therefore, an effective training process leads the ndm to be lower than m_1 for positive samples and higher than m_2 for negative ones. Consequently, small values of the metric, dm , must represent a high similarity between the images, and vice versa.

The contribution of a positive and a negative pair to the loss function, Eq.4.7, are described by Eq. 4.9 and 4.10, respectively, and rendered by Fig. 4.4.

$$e_p = \max(ndm_i - m_1, 0) \quad (4.9)$$

$$e_n = \max(m_2 - ndm_i, 0) \quad (4.10)$$

Fig. 4.4 Loss contribution of a positive, e_p , and negative, e_n , single pair sample to the N2MCL function (Eq.4.7): a) without normalisation and $m_1 = 1$ and $m_2 = 2$ and b) with normalisation and $m_1 = 0.3$ and $m_2 = 0.7$.

According to Eq. 4.9 and 4.10, no loss is caused by positive samples with a distance value lower than the first margin, m_1 , and negative samples with a distance higher than the second margin, m_2 , as is shown in Fig. 4.4.

The function forces the comparison values obtained for positive pairs to be lower than the first margin, and those obtained with negative pairs to be higher than the second margin.

The null error associated with the properly classified samples decreases the loss value and consequently the magnitude of the increments in the value of the updated parameters. This results in a reduction in the amplitude of the oscillation in the total loss value throughout the training process, as well as in a decrease in the value around which the loss function oscillates. Furthermore, such a value is achieved in a lower number of iterations, becoming the learning process faster, i.e. the model converges in a lower number of iterations, as Fig. 4.5 shows.

The intermediate step of normalisation and the use of two margins instead of only one are the contributions of the N2MCL loss function with respect to the traditional contrastive function, making possible the learning of more discriminative features in a lower number of learning iterations, since the Re-Id scores are almost duplicated by the novel loss formulation, as proved in Section 6.2.4.

Fig. 4.5 Loss function evaluated over a validation set of samples throughout the training process: a) using the traditional contrastive loss function, (Eq. 4.3); and b) using the double-margin contrastive loss function, (Eq.4.7).

4.2.3 Pairs Mini-Batch Learning

The Siamese network is trained on a vast quantity of positive and negative pairs of images. The positive samples render the similarity class, and the negative ones, the dissimilarity class.

The learning algorithm used to minimise the loss function has been Gradient Descent (GD). Batch GD provides more accuracy in the parameters updating than Stochastic GD. Besides of that,

with the vectorised computation performed by the employed deep learning framework (Caffe) the time taken by Batch GD to perform an update has decreased until acceptable values.

However, the huge amount of training samples makes impossible the used of all the data in every iteration, due to the limitations of the computational memory resources. This has led to implementing a Pair-based Mini-Batch Gradient Descent algorithm, where each training input is not an image, but a pair of them. In the performed training processes, the chosen batch size ($B=128$) was that as large as the available memory resources make possible.

Algorithm 2 shows the main procedures of the Pair-based Mini-Batch Gradient Descent learning algorithm.

Algorithm 2 Pair-based Mini-Batch Gradient Descent Learning Algorithm

Require: Batches of pairs, $X^t = \{X_i^t\}$.

Ensure: The network parameters $W^T = \{W_j^T\}$.

```

1:  $W^0 = \{W_j^0\}$ 
2: while  $t < T$  do
3:    $t \leftarrow t + 1$ ;
4:    $\frac{\partial f_{N2MCL}(W^t, X^t)}{\partial W_j^t} = 0$ ;
5:   for all training pair  $X_i^t = (I^a, I^b)$  of the batch set  $X^t$  do
6:     Calculate  $F_{W^t}(I^a)$ , and  $F_{W^t}(I^b)$  by forward propagation;
7:     Calculate  $ndm_i$  by Eqs. 4.4 and 4.8;
8:   end for
9:   Calculate  $f_{N2MCL}(W^t, X^t)$  by Eq. 4.7;
10:  for all training pair  $X_i^t = (I^a, I^b)$  of the batch set  $X^t$  do
11:    Calculate  $\frac{\partial ndm_i}{\partial W_j^t}$ , by Eq. 4.14;
12:    Calculate  $\frac{\partial F_{W^t}(I^a)}{\partial W_j^t}$ , and  $\frac{\partial F_{W^t}(I^b)}{\partial W_j^t}$ , by back propagation;
13:  end for
14:  Calculate  $\frac{\partial f_{N2MCL}(W^t, X^t)}{\partial W_j^t}$  according to Eq. 4.15 and 4.16;
15:  Update parameters according to Eq. 4.17,
16: end while

```

Algorithm 2 computes the features of each pair of images from the training batch by forward propagation, and the distance between them, ndm by Eqs. 4.4 and 4.8. Then, the value of the loss function f_{N2MCL} is obtained with Eq. 4.7.

Subsequently, the back-propagation of the two neural branches is performed to obtain $\frac{\partial F_{W^t}(I^a)}{\partial W_j^t}$, and $\frac{\partial F_{W^t}(I^b)}{\partial W_j^t}$ for every sample of the batch. From these derivatives, the distance derivative, $\frac{\partial ndm}{\partial W_j^t}$, is computed, using Eq. 4.14. This equation is the result of defining $\frac{\partial ndm}{\partial W_j^t}$ as Eq. 4.11, and substituting each term by its formulation, given by Eqs. 4.12 and 4.13 and by the definition of dm , Eq. 4.4.

The term given by $\frac{\partial ndm}{\partial dm}$ has been obviated in the practise since this is a factor bounded between 0 and 0.5. So it has a similar effect as the learning rate, α , whose value is properly adapted by Adagrad method, [93]. In addition, this factor does not affect the gradient descent direction, and its estimation is computationally expensive.

Finally, the partial derivatives of the N2MCL function, with respect to the set of learnt weights, $W = \{W_j\}$, are defined by Eq. 4.15 and 4.16. These partial derivatives are finally used by the weights updating rule, defined by Eq. 4.17.

If α takes a too small value, the GD can be slow, but if α is too large, GD can overshoot the minimum and it may fail to converge, or even diverge. To avoid that, and to make the algorithm converge the value of α has been progressively adapted by Adagrad optimisation, [93]. Adagrad method modifies the general learning rate at each time step t for every parameter W_j based on the past gradients that have been computed for W_j . This is made by performing a matrix-vector product $\odot$, where $G^t \in R^{d \times d}$ is a diagonal matrix that contains the sum of the squares of the past gradients with respect to all parameters W . While $\nabla_W f_{N2MCL}(W^t, X^t) = \left\{ \frac{\partial f_{N2MCL}(W^t, X^t)}{\partial W_j^t} \right\}$ is the gradient vector of the loss function and ϵ is a smoothing term that avoids division by zero ($\epsilon = 1 \times 10^{-8}$).

The model weights W have been initialised using Xavier method [122]. Then, both processes, forward and back propagation, are repeated until achieving the pre-established maximum number of iterations, T .

$$\frac{\partial ndm}{\partial W_j^t} = \frac{\partial ndm}{\partial dm} \cdot \frac{\partial dm}{\partial W_j^t} \quad (4.11)$$

$$\frac{\partial ndm}{\partial dm} = \frac{2e^{-dm}}{(e^{-dm} + 1)^2} = \frac{2e^{-\|F_W(I_i^a) - F_W(I_i^b)\|_2^2}}{(e^{-\|F_W(I_i^a) - F_W(I_i^b)\|_2^2} + 1)^2} \quad (4.12)$$

$$\frac{\partial dm}{\partial W_j^t} = \frac{\partial dm}{\partial F_W(I_i^a)} \cdot \frac{\partial F_W(I_i^a)}{\partial W_j^t} + \frac{\partial dm}{\partial F_W(I_i^b)} \cdot \frac{\partial F_W(I_i^b)}{\partial W_j^t} = 2 \cdot \left(F_W(I_i^a) \cdot \frac{\partial F_W(I_i^a)}{\partial W_j^t} - F_W(I_i^b) \cdot \frac{\partial F_W(I_i^b)}{\partial W_j^t} \right) \quad (4.13)$$

$$\frac{\partial ndm}{\partial W_j^t} = \frac{2e^{-\|F_W(I_i^a) - F_W(I_i^b)\|_2^2}}{(e^{-\|F_W(I_i^a) - F_W(I_i^b)\|_2^2} + 1)^2} \cdot 2 \cdot \left(F_W(I_i^a) \cdot \frac{\partial F_W(I_i^a)}{\partial W_j^t} - F_W(I_i^b) \cdot \frac{\partial F_W(I_i^b)}{\partial W_j^t} \right) \quad (4.14)$$

$$\frac{\partial f_{N2MCL}}{\partial W_j} = \frac{1}{2B} \sum_{i=1}^B h_i \quad (4.15)$$

$$h_1 = \begin{cases} \frac{ndm_i}{W_j} & \text{if } y_i = 1 \\ \frac{ndm_i}{W_j} & \text{if } y_i = 0 \\ 0 & \text{otherwise} \end{cases} \quad (4.16)$$

$$W^{t+1} = W^t - \frac{W^t f_{N2MCL}(W^t X^t)}{G^t} \quad (4.17)$$

4.3 Balancing Re-Identification Data

Solving the Re-Id task by the learning of deep neural networks become a daunting challenge due to the shortage of data in Re-Id datasets, which causes the over-fitting of the models. Besides that, the learning of a distance metric to measure the DoAS between a pair of images is hampered by the unbalanced nature of the Re-Id task.

In the Re-Id task, the number of instances of a query identity is very limited against the vast quantity of different people representations, among which it must be identified. So, the number of available positive pairs is much smaller than the number of negative ones, leading the learning to not consider the contribution of the positive pairs and collapse, i.e. the features always take value zero ($F_W I = 0$).

For those reasons, a dataset generation tool has been designed to exploit the multiple possible combinations of training pair samples³. In addition, this program has been formulated to artificially balance the training set by repeating the positives pairs until getting the same number, or a certain proportion, of positive and negative pairs.

In the Re-Id challenge, the training set is composed of two sets of images, C^a and C^b , corresponding to every camera view. To train the Siamese network, a set of M pairs of images, X_i , has been generated from the training sets, C^a and C^b , according to Eq. 4.18, where $p : n$ factor indicates the proportion of positive pairs with respect negative ones in the training dataset, X . L_a and L_b , are the sizes of the sets C^a and C^b . Fig. 4.6 shows some obtained positive and negative pairs as an example.

$$X_i = \begin{cases} I_i^a \ I_i^b & \begin{matrix} c_j^a \ c_k^b & c_j^a & C^a & c_k^b & C^b & y & c_j^a \ c_k^b & 1 \\ \text{if } i \bmod p = n & p & i & 1 & M & j & 1 & L_a & k & 1 & L_b \end{matrix} \\ I_i^a \ I_i^b & \begin{matrix} c_j^a \ c_k^b & c_j^a & C^a & c_k^b & C^b & y & c_j^a \ c_k^b & 0 \\ \text{if } i \bmod p = n & p & i & 1 & M & j & 1 & L_a & k & 1 & L_b \end{matrix} \end{cases} \quad (4.18)$$

³Pairs Balancing has been implemented as a set of c++ functions, which are publicly available under: http://github.com/magomez/dataset_factory/tree/master/data_factory_from_reid

Fig. 4.6 Pair samples (at every column) from PRID2011 dataset.

The conducted experiments (see Section 6.2.4.c) have revealed that choosing a proportion of 1 : 1, the training set generated differs too much from the target task, where the model has to deal with the unbalanced data. For that reason, a model trained on a partially balanced training set, with a proportion of approximately 1 : 4, one positive pair every four negatives, works better than if it is trained on an absolutely balanced set, 1:1.

4.4 Triplet Model

Triplet model is a learning model used to train the parameters of a DCNN. Instead of duplicating the DCNN in two branches, as the Siamese model does, Triplet model triplicates it. This model provides a relative distance comparison between positive and negative pairs that make it flexible and suitable for the training of deep Re-Id models, as it is explained in Section 4.4.4, which gives a comparative review of the Contrastive and Triplet loss. Previously, Sections 4.4.1, 4.4.2 and 4.4.3 present the triplet loss and architecture, a re-formulated batch-based approach of the triplet model and learning algorithm, and the design of an online triplets selection method. Finally, Section 4.4.5 introduces the problem of model over-fitting.

4.4.1 Triplet Loss and Architecture

In order to train the weights of a DCNN, the Triplet model triplicates it in three branches, which are forced to share the same weights. That means that the learnt weights are identical in the three branches, so a unique feature embedding is learnt. Fig. 4.7 shows the Triplet model structure.

Every i sample of the training dataset, X , is constituted by a triplet of person images, X_i I_i^a I_i^p I_i^n . The first branch of the triplet model receives an anchor sample, I_i^a , the second one takes an image, I_i^p , rendering the same person than the anchor image, and the input of the third branch is a different person's image, I_i^n .

Therefore I_i^a and I_i^p form a positive pair of samples, and they present the same identification number. The identification number of I_i^n is different, so the pair formed by this image and the anchor image, I_i^a , is a negative pair. The triplet model tries to maximise the relative distance between the distance metric values for the positive and the negative pair.

Fig. 4.7 Architecture of the Triplet model.

The feature representation for an image, $F_W I_i$, is given by the output of the DCNN, which maps an input image to the feature space. Such embedding depends on the learnt values for the network weights, W . Hence, a feature descriptor is computed for every input by the forward propagation of the DCNN, and they are contrasted by the Triplet Loss function.

The similarities between the anchor images, I_i^a , and the positive and negative inputs, I_i^p, I_i^n , are measured by a connection function. In the Triplet model, firstly presented in [289], the connection function was the squared Euclidean distance, which is computed between the features arrays of the images, $F_W I_i^a, F_W I_i^p, F_W I_i^n$.

The objective is to learn a transformation from the image to the feature space, such it leads the representations for the same person near, and far away from different people's representations. This constraint is imposed by the Triplet objective formulation, presented in [289], which establishes a relative distance relationship. For a certain triplet of images, the triplet loss requires the squared Euclidean distance for the negative pair, dm^- , to be larger than that for the positive one, dm^+ , by a predefined margin, α . This constraint is shown by Eq.4.19, where dm^+ and dm^- are defined by Eq. 4.20 and 4.21 respectively.

$$dm^+(X_i) + \tau < dm^-(X_i), \forall X_i \in X \quad (4.19)$$

$$dm^+(X_i) = \|F_w(I_i^a) - F_w(I_i^p)\|_2^2 \quad (4.20)$$

$$dm^-(X_i) = \|F_w(I_i^a) - F_w(I_i^n)\|_2^2 \quad (4.21)$$

These equations ensure that the anchor sample is closer to all samples of the same person, in the feature space, than it is to any sample of other people since X is the set of all possible triplets in the training set.

4.4.2 Triplet Mini-Batch Learning

In the Single-Shot Re-Id task, there is only one positive sample for every anchor image. So, the available data is not enough to adopt an individual-meant training approach, which clusters the same person samples close from each other and distant to another person identity cluster.

By contrast, the proposed method treats all the possible positive pairs as a set rendering the condition of similarity. In the same way, negative pairs represent the dissimilarity situation. The discrimination between similarity and dissimilarity is learnt by means of comparing every positive pair with all the possible negative pairs, taking advantage of the triplet model architecture for that. In that way, the network is trained to be able to identify a person between a huge number of negative samples. The training data has been generated by the method formulated in Section 4.5.1.

This global comparison approach calls for the use of a Batch learning algorithm. However, the huge amount of possible triplet combinations composing the training set, and the limitations in processing memory resources have led to implementing a Mini-Batch Triplet Loss.

Therefore, eventually, the loss function to minimise, f_L , is defined by Eq. 4.22 and 4.23, where B ($B=64$) is the number of elements in a batch of triplets, $X^t = X_i$. Eq. 4.23 defines the cost produced by the deviation of the features of a triplet sample from the objective. Eq. 4.22, defines the average loss produced by the costs of an entire batch of triplets. The chosen batch size ($B=64$) was that as large as the available memory resources make possible.

$$f_L(W^t; X^t) = \frac{1}{2B} \sum_{i=1}^B [f_C(W; X_i^t)] \quad (4.22)$$

$$f_C(W; X_i) = \max(\tau + \|F_w(I^a) - F_w(I^p)\|_2^2 - \|F_w(I^a) - F_w(I^n)\|_2^2, 0) \quad (4.23)$$

A Triplet-based Mini-Batch Gradient Descent learning algorithm has been implemented to train a deep Re-Id Triplet model. Their main procedures are shown by Algorithm 3.

The forward propagation of the DCNN of each branch is required to compute the features of each image of a triplet. This process is performed for every sample of a batch to get the value of

the loss function, f_L . Then the partial derivatives of the loss function, given a set of learnt weights, $W = \{W_j\}$, defined by Eq. 4.24 and 4.25, are computed using Eq. 4.26, 4.27 and 4.28.

The back-propagation of the three neural branches is performed to obtain $\frac{\partial F_{W^t}(I^a)}{\partial W_j^t}$, $\frac{\partial F_{W^t}(I^p)}{\partial W_j^t}$ and $\frac{\partial F_{W^t}(I^n)}{\partial W_j^t}$ for every sample of the batch. Both processes, forward and back propagation, are repeated until achieving the pre-established maximum number of iterations, T . These partial derivatives are finally used by the weights updating rule, defined by Eq. 4.29.

This formulation includes the Adagrad method [93] to update the learning rate value, α , as it was explained in Section 4.2.3. In this case, $\nabla_W f_L(W^t, X^t) = \left\{ \frac{\partial f_L(W^t, X^t)}{\partial W_j^t} \right\}$ is the gradient vector of the Mini-Batch Triplet Loss function (Eq. 4.22).

In the prior experiments, the model weights W were initialised using Xavier method [122]. However, in further experiments, in order to alleviate the Re-Id data problem (Section 1.3.2), the Re-Id network weights $W^0 = \{w_j^0\}$, were initialised with values that were pre-trained values on MOT domain (Section 4.7).

Algorithm 3 Triplet-based Mini-Batch Gradient Descent Learning Algorithm

Require: Batches of triplets, $X^t = \{X_i^t\}$.

Ensure: The network parameters $W^T = \{W_j^T\}$.

```

1:  $W^0 = \{W_j^0\}$ 
2: while  $t < T$  do
3:    $t \leftarrow t + 1$ ;
4:    $\frac{\partial f_L(W^t, X^t)}{\partial W_j^t} = 0$ ;
5:   for all training triplet  $X_i^t = (I^a, I^p, I^n)$  of the batch set  $X^t$  do
6:     Calculate  $F_{W^t}(I^a)$ ,  $F_{W^t}(I^p)$  and  $F_{W^t}(I^n)$  by forward propagation;
7:     Calculate  $f_C(W^t; X_i^t)$  by Eq. 4.23;
8:   end for
9:   Calculate  $f_L(W^t; X^t)$  by Eq. 4.22;
10:  for all training triplet  $X_i^t = (I^a, I^p, I^n)$  of the batch set  $X^t$  do
11:    Calculate  $\frac{\partial f_C(W^t; X_i^t)}{\partial W_j^t}$  according to Eq. 4.25;
12:    Calculate  $\frac{\partial f_C(W^t; X_i^t)}{\partial F_{W^t}(I^a)}$ ,  $\frac{\partial f_C(W^t; X_i^t)}{\partial F_{W^t}(I^p)}$  and  $\frac{\partial f_C(W^t; X_i^t)}{\partial F_{W^t}(I^n)}$  by Eqs. 4.26, 4.27 and 4.28;
13:    Calculate  $\frac{\partial F_{W^t}(I^a)}{\partial W_j^t}$ ,  $\frac{\partial F_{W^t}(I^p)}{\partial W_j^t}$  and  $\frac{\partial F_{W^t}(I^n)}{\partial W_j^t}$ , by back propagation;
14:  end for
15:  Calculate  $\frac{\partial f_L(W^t; X^t)}{\partial W_j^t}$  according to Eq. 4.24;
16:  Update parameters according to Eq. 4.29,
17: end while

```

$$\frac{\partial f_L(W^t; X^t)}{\partial W_j^t} = \frac{1}{2B} \sum_{i=1}^B \left[\frac{\partial f_C(W^t; X_i^t)}{\partial W_j^t} \right] \quad (4.24)$$

$$\begin{aligned} \frac{\partial f_C(W; X_i)}{\partial W_j} &= \frac{\partial f_C(W; X_i)}{\partial F_W(I^a)} \cdot \frac{\partial F_W(I^a)}{\partial W_j} \\ &\quad + \frac{\partial f_C(W; X_i)}{\partial F_W(I^p)} \cdot \frac{\partial F_W(I^p)}{\partial W_j} + \frac{\partial f_C(W; X_i)}{\partial F_W(I^n)} \cdot \frac{\partial F_W(I^n)}{\partial W_j} \end{aligned} \quad (4.25)$$

$$\frac{\partial f_C(W; X_i)}{\partial F_W(I^a)} = \begin{cases} 2(F_W(I^n) - F_W(I^p)) & \text{if } dm^- - dm^+ < \tau \\ 0 & \text{otherwise} \end{cases} \quad (4.26)$$

$$\frac{\partial f_C(W; X_i)}{\partial F_W(I^p)} = \begin{cases} 2(F_W(I^p) - F_W(I^a)) & \text{if } dm^- - dm^+ < \tau \\ 0 & \text{otherwise} \end{cases} \quad (4.27)$$

$$\frac{\partial f_C(W; X_i)}{\partial F_W(I^n)} = \begin{cases} 2(F_W(I^a) - F_W(I^n)) & \text{if } dm^- - dm^+ < \tau \\ 0 & \text{otherwise} \end{cases} \quad (4.28)$$

$$W^{t+1} = W^t - \frac{\alpha}{\sqrt{G} + \varepsilon} \odot \nabla_W f_L(W^t, X^t) \quad (4.29)$$

4.4.3 Triplets Selection

With the aim of speeding up the learning process, an online triplet selection stage has been formulated. Faster convergence can be obtained by means of selecting triplets that violate the triplet constraint in Eq. 4.19. Therefore, this selection step acts as a filter which makes the loss function consider only the relevant samples for the training, and obviate those samples easy to classify. In that way, the back-propagation is ruled by the hardest samples, which produce larger increments (or decrements) for the updating of the weights (see Eq. 4.29), accelerating the training process.

Triplet selection was firstly proposed by Schroff et al. [289]. They addressed face recognition by closing the samples of a certain identity in the feature space. They sought an identity clustering and trained their network on multiple instances of every individual. In this frame, triplet selection is performed by the online generation of the triplets: given a certain anchor image, hard-positive, and hard-negative images are selected. That means that for a given anchor, the samples that generate harder triplets are selected.

The intrinsic constraints of the Single-Shot Re-Id challenge do not allow the use of an anchor-meant approach, either in the triplet generation or in the triplet selection. Instead of that, the generation of a wide variety of samples has been sought by an offline combination process (Section

4.5.1). Moreover, the data constraints have led to designing a Mini-Batch Triplet loss function and learning algorithm (Section 4.4.2).

Therefore, a new neural layer has been designed to perform online triplet selection under the constraints of the Re-Id task, to be integrated into the proposed learning algorithm (Algorithm 3), and it has been placed before the loss function layer. At every iteration t , this layer receives features from a batch of B triplets, so the layer input is rendered by $X^t = [F_W I_i^a F_W I_i^p F_W I_i^n]_{i=1}^B$. The layer computation offers an online filter that outputs a smaller batch containing features corresponding to triplets that are helpful for the loss computation. Hence, the output batch of remaining features, $R^t = [I_i^a I_i^p I_i^n]_{i=1}^B$, has a smaller size, which has been set as the half of the input batch size $B = B/2$.

Triplets presenting the lowest values for $dm = X_i$ are considered as the hardest ones. Nevertheless, the objective is to consider those triplets which are difficult to classify but not the hardest ones. In practice, selecting the hardest samples can lead to bad local minima early on the training, and it can result in a collapsed model.

For that reason, the input batch of triplets has been divided into two sorted sequences, M and H , to differ between mid-hard and hard negatives, depending on if $dm = I_i$ is bigger or not than $dm = I_i$, respectively. Eqs. 4.30 and 4.31 defines both sequences. These sequences of triplets are sorted in order of increasing negative distance, dm , that is from harder to easier triplets.

$$M = M_j : M_j = [X_i \quad I_i^a \quad I_i^p \quad I_i^n] \quad X_i \leq dm \quad M_j \quad dm \leq M_{j-1} \quad dm \leq M_j \quad dm \leq M_j \quad i = 1 \dots B \quad (4.30)$$

$$H = H_j : H_j = [X_i \quad I_i^a \quad I_i^p \quad I_i^n] \quad X_i > dm \quad H_j \quad dm \leq H_{j-1} \quad dm \leq H_j \quad dm \leq H_j \quad i = 1 \dots B \quad (4.31)$$

According to Eq. 4.30, M can contain mid and easy triplets (those already well classified). The B 's hardest triplets of this sequence are selected.

If the number of samples in that sequence (even picking the easy ones) is not enough to form the output batch, the triplets from the hard sequence, H , are added to the final batch in decreasing order of the negative distance, that is from easier to harder triplets. The resulting batch, R , is defined by Eq. 4.32 and 4.33, where m is the number of elements in M , and h is the number of elements in H . Therefore, if m is higher or equal to B , the resulting batch, R , only takes triplets from M . Otherwise, it is formed by samples from both sequences, M and H .

$$R = [R_i]_{i=1}^B \quad (4.32)$$

$$R_i = \begin{cases} M_i, M_i \in M & \text{if } i \leq m \\ H_{h+m-i+1}, H_{h+m-i+1} \in H & \text{if } i > m \end{cases} \quad (4.33)$$

4.4.4 Triplet Loss vs. Contrastive Loss

Both loss functions, the Contrastive and the Triplet one, can be used to train a binary pair-wise classifier, like the deep Re-Id model. However, Triplet loss has shown to be more effective for ranking problems, like the Person Re-Identification challenge, where gallery images are ranked in order of increasing similarity with respect to a certain probe image. This fact is demonstrated in Section 6.2.4.d. Fig. 4.8 compares the evolution of the learning of the same DCNN by a Siamese and a Triplet model.

The Contrastive loss function classifies positives and negatives pairs in an independent way, without considering the relative distance between positive and negative instances of a given identity. This consideration is addressed by the Triplet loss function, whose goal is maximising such relative distance. Therefore, the boundary separating similarity and dissimilarity classes is fixed on the Contrastive loss function. In the proposed N2MCL function, these classes are delimited by two fixed boundaries separated by an also fixed margin.

Fig. 4.8 Learning curves for Siamese and Triplet model over PRID2011 and VIPeR datasets.

On the other hand, even though the magnitude of the margin used by the Triplet loss function is constant, the extremes boundaries separating the classes are not. The distance between similarity and dissimilarity classes is relative, where the classes are rendered by the value of the positive, dm^+ , and negative distance, dm^- , respectively.

The relative essence of the comparison made by the triplet loss function makes it flexible and adaptative to deal with the situation of different people with similar appearance, which produces small values of dm^+ , and the occurrence of high dm^- values due to quite different representations of the same individual. In the presence of the mentioned situations, which are quite common in Re-Identification, in contrast to the triplet loss, the contrastive loss value suffers from strong oscillations and slow convergence, as Fig. 4.8 shows.

Contrastive loss function cannot compare positive and negative samples between them. Instead of that, positive and negative samples are independently compared with fixed boundaries, and these constraints are too demanding in the first learning iterations causing big oscillations of the learning curve, as Fig. 4.8 shows.

4.4.5 Model Over-fitting

Solving Person Re-Identification by learning DCNNs is a daunting challenge, due to the coexistence of two circumstances:

- The small size of Re-Id training data, especially in Single-Shot Re-Id, where only two images per person are available.
- The huge number (in the order of millions) of parameters to train, in a highly layered neural network architecture.

These facts cause the over-fitting of the deep Re-Id models, leading to degenerated performance.

There are two main approaches to face model over-fitting, also known as the high-variance problem: simplifying the model, i. e. reducing the number of parameters to learn or their magnitude and increasing the quantity and variety of training data. These are the foundations of some commonly used techniques, like regularization and data augmentation, respectively.

This thesis proposes a set of novel and re-formulated strategies to reduce over-fitting on a Re-Id Triplet model, with independence from the used distance metric and target dataset:

- Firstly, the Triplet Permutation method has been formulated to generate every possible triplet combination from a certain Re-Id dataset and new neural layers have been designed to perform online data augmentation (Section 4.5.1).

- Secondly, a variety of regularization techniques have been employed in the learning of the model (Section 4.6).
- Moreover, the effects of shortening the network architecture have been analysed, over two similar but differently layered well-known architectures (Section 4.1). Besides that, novel Re-Id neural architectures, based on body partition have been designed (Section 4.8).
- In addition, transfer learning from a different domain has been implemented (Section 4.7). This can be considered as a technique halfway between simplifying the model and augmenting the data since it adopts some parameters values, which were learned in a different domain with larger datasets.

4.5 Triplet Feeding

As it has been explained above, the inherent constraints that define the Single-Shot Re-Id challenge results in poor available training data. Indeed, there is only one positive sample for every anchor image, so the number of instances of a query identity is very limited, specifically when compared with the vast quantity of potentially available different people representations.

Therefore, the available data is not enough to adopt an individual-meant training approach. Instead of that, this thesis proposes to treat all the possible positive pairs as a set rendering the condition of similarity, and the negative ones, the dissimilarity situation. For that reason, given a certain Re-Id dataset, its images have been combined to create a vast quantity of training triplets, by coupling every available positive pair with all the possible negative images.

This section presents a series of designed methods to feed the triplet architecture during its training, whose objective is to prevent model over-fitting.

4.5.1 Triplets Permutation

The triplet permutation method has been designed to generate all the possible triplet combinations from a certain Re-Id dataset, and it has been implemented as a triplet generation tool⁴. That allows creating multiple training sets, under different constraints, depending on the outcome that is sought to obtain. Three combining formulations have been defined, providing three different training triplets sets, X_I , X_{II} , X_{III} .

These formulations are presented by Eq. 4.34, 4.35 and 4.36, where $X_i = (I_i^a, I_i^p, I_i^n)$ represents every training triplet. Every image from the Re-Id dataset is denoted as $I_{id,c}$, where id is the identity number, and c is the camera-view set to where it belongs. In Re-Id datasets, two camera-view sets

⁴Triplets Permutation has been implemented as a set of C++ functions, which are publicly available under: http://github.com/magomez/dataset_factory/tree/master/data_factory_from_reid

are given, A and B , so most of the rendered individuals, have two samples representations, $I_{id A}$ and $I_{id B}$. M is the total number of training triplets.

By permuting, the camera set from which every triplet branch takes its corresponding input image, the possible triplet arrangements are augmented.

$$X_I: \quad X_i \quad I_i^a \ I_i^P \ I_i^n : I_i^a : \quad I_{j x} \ I_i^P : \quad I_{j y} \ I_i^n : \quad I_{k y} \\ j \quad k \quad x \quad A \quad y \quad B \quad i \quad M \quad (4.34)$$

$$X_{II}: \quad X_i \quad I_i^a \ I_i^P \ I_i^n : I_i^a : \quad I_{j x} \ I_i^P : \quad I_{j y} \ I_i^n : \quad I_{k y} \\ j \quad k \quad x \quad y \quad i \quad M \quad (4.35)$$

$$X_{III}: \quad X_i \quad I_i^a \ I_i^P \ I_i^n : I_i^a : \quad I_{j x} \ I_i^P : \quad I_{j y} \ I_i^n : \quad I_{k z} \\ j \quad k \quad x \quad y \quad i \quad M \quad (4.36)$$

The first formulation is the simplest one, which takes the anchor samples from one of the views (A) and the positive and negative samples from the other one (B). Then, the second and third formulations increase the number of possible triplet combinations, as demonstrated below.

According to the first formulation, the number of possible positive pairs $I_i^a \ I_i^P$ for each identity, id , is one, since there are only two views and the anchor is always taken from the same view. So, the number of total positive pairs is the number of identities P .

In the second and the third cases, the number of positive pairs, $I_i^a \ I_i^P$ for each identity, id , are two, since the anchor can be taken from any of the two cameras A and B.

Although $I_i^a : \ I_{j A} \ I_i^P : \ I_{j B}$ and $(I_i^a : \ I_{j B} \ I_i^P : \ I_{j A})$ are identical pairs, they are differentially considered. When adding a negative image, this is compared with the anchor images of the triplet. So, depending on which image of the positive pair is taken as an anchor, the triplet objective function will work differently, and for that, the pairs are considered as different ones.

In the general case of having more than two camera views, if an identity has representation in all of the C camera views, the number of pairs formed from it would be $\frac{C!}{C-2!}$. This is the number of variations of two elements $I_{j x} \ I_{j y}$ where each element (x or y) can take C different values but not the same in both elements. So, the total number of positive pairs would be $\frac{PC!}{C-2!}$.

Subsequently, as long as negative samples adding is concerned, in the first and the second formulations, the number of triplets generated from a positive pair is $P - 1$. The reason is that the positive pair generated from an identity id can be coupled with the remaining identities in the camera set from which the positive sample I_i^P was taken. So, the total number of generated triplets

in the first and the second cases are $P(P-1)$ and $2P(P-1)$, respectively. And for the general case of having C different camera views in the second formulation, the number of triplets is $\frac{P!}{C} \frac{P-1}{2!}$.

According to the third formulation, the number of triplets generated from a positive pair is $P-1-C$. That is because the positive pair generated from an identity id can be coupled with the remaining identities in any of the camera sets. Therefore, the total number of triplets formed is $4P(P-1-C)$, and $\frac{P!}{C} \frac{P-1}{2!} C$ for the general case of having C views.

In summary, when having only one pair of camera views $C=2$, which is the case of the Re-Id challenge, the second formulation duplicates and the third formulation, quadruplicates the number of training samples with respect to the first one. Therefore, triplet augmentation is achieved through the proper combination of the training samples. This fact can be easily visualised in Fig. 4.9, which shows some examples of triplets created by using the three proposed formulations.

Fig. 4.9 Training triplet sets generation, according to three formulations (Eq. 4.34, 4.35 and 4.36), from PRID2011 dataset.

The proposed triplet augmentation method not only contributes to alleviating model over-fitting but also affects the features learning process. That is because feeding the triplet network with a particular training set, certain constraints are implicitly imposed in the learning process. These constraints are different for each set configuration, and they modify the characteristics of the solution in which the learning process converges.

Considering every training set formulation, Eq. 4.34, 4.35 and 4.36, together with the triplet objective defined in Eq. 4.19, it can be deducted the following statements, where constraints 1, 2, 3, and 4 are denoted as c_1 , c_2 , c_3 and c_4 and defined by Eq. 4.37, 4.38, 4.39 and 4.40, respectively:

- Training set I, X_I , imposes c_1 .
- Training set II, X_{II} , imposes c_1 and c_2 .
- Training set III, X_{III} , imposes c_1 , c_2 , c_3 and c_4 .

$$j \quad P \quad k \quad P: F_W(I_{jA} - F_W(I_{kB}))^2 - F_W(I_{jA} - F_W(I_{jB}))^2 \quad (4.37)$$

$$j \quad P \quad k \quad P: F_W(I_{jB} - F_W(I_{kA}))^2 - F_W(I_{jB} - F_W(I_{jA}))^2 \quad (4.38)$$

$$j \quad P \quad k \quad P: F_W(I_{jA} - F_W(I_{kA}))^2 - F_W(I_{jA} - F_W(I_{jB}))^2 \quad (4.39)$$

$$j \quad P \quad k \quad P: F_W(I_{jB} - F_W(I_{kB}))^2 - F_W(I_{jB} - F_W(I_{jA}))^2 \quad (4.40)$$

During the training, the loss function leads the network weights to values that produce features able to meet the defined constraints, according to the selected training set. If eventually, these restrictions are complied by all the training samples, four different undesirable situations can be avoided. These situations (a, b, c and d), where the distance between positive pairs is larger than for negative ones (in a measure), are described below, and shown in Fig.4.10.

- a) Sparsity of the positive pairs, with anchors in cam-view set A . The distance from an anchor image from camera A to its positive partner in camera B is not smaller (in a measure) than the distance from the anchor with respect to any of the other samples from camera B . Situation a, s_a , is defined by Eq. 4.41.
- b) Sparsity of the positive pairs, with anchors in cam-view set B . The distance from an anchor image from camera B to its positive partner in camera A is not smaller (in a measure) than the distance from the anchor with respect to any of the other samples from camera A . Situation b, s_b , is defined by Eq. 4.42.
- c) Clustering of different identities from cam-view set A . The distance from an anchor image from camera A to some of the rest of samples from camera A is not larger (in a measure) than the distance to its positive partner in cam B . Situation c, s_c , is defined by Eq. 4.43.

- d) Clustering of different identities from cam-view set B . The distance from an anchor image from camera B to some of the rest of samples from camera B is not larger (in a measure) than the distance to its positive partner in cam A . Situation d, s_d , is defined by Eq. 4.44.

$$p \quad P \quad q \quad P : F_W(I_{p,A}) \quad F_W(I_{q,B})^2 \quad F_W(I_{p,A}) \quad F_W(I_{p,B})^2 \quad (4.41)$$

$$p \quad P \quad q \quad P : F_W(I_{p,B}) \quad F_W(I_{q,A})^2 \quad F_W(I_{p,B}) \quad F_W(I_{p,A})^2 \quad (4.42)$$

$$p \quad P \quad q \quad P : F_W(I_{p,A}) \quad F_W(I_{q,A})^2 \quad F_W(I_{p,A}) \quad F_W(I_{p,B})^2 \quad (4.43)$$

$$p \quad P \quad q \quad P : F_W(I_{p,B}) \quad F_W(I_{q,B})^2 \quad F_W(I_{p,B}) \quad F_W(I_{p,A})^2 \quad (4.44)$$

Fig. 4.10 Undesirable situations (a), (b), (c), and (d), represented in the feature space.

The fact that using different training sets configurations allows to avoid certain undesirable situations is demonstrated below. Previously, as an aside, it is necessary to clarify that the constraints c_1 , c_2 , c_3 and c_4 are imposed over all the training samples, so indexes j and k can take any value between one and the view sets sizes. On the contrary, situations s_a , s_b , s_c and s_d , might arise only for the particular identities rendered by indexes p and q .

Constraint c_1 prevents from situation s_a . Every training triplet $I_{j,x} I_{j,y} I_{k,z}$ is forced to meet the condition defined in Eq. 4.41. If $I_{p,A} I_{p,B} I_{q,B}$ is forced to meet that condition (i.e. j index takes identity p , and k index takes identity q), the resulting proposition is just the opposite to that defining situation s_a , as Eq. 4.45 demonstrates. Hence, no triplet forced to meet c_1 can produce situation s_a . However, the prevention of situations s_b , s_c and s_d is not ensured by constraint c_1 , as Fig. 4.11(1) shows.

$$F_W I_{p,A} - F_W I_{q,B}^2 - F_W I_{p,A} - F_W I_{p,B}^2 \quad s_a \quad (4.45)$$

Constraint c_2 prevents from situation s_b . Every training triplet $I_{j,x} I_{j,y} I_{k,z}$ is forced to meet the condition defined in Eq. 4.42. If $I_{p,B} I_{p,A} I_{q,A}$ is forced to meet that condition, the resulting proposition is just the opposite to that defining situation s_b , as Eq. 4.46 demonstrates. Hence, no triplet forced to meet c_2 can produce situation s_b . However, the prevention of situations s_a , s_c and s_d is not ensured by constraint c_2 , as Fig. 4.11(2) shows.

$$F_W I_{p,B} - F_W I_{q,A}^2 - F_W I_{p,B} - F_W I_{p,A}^2 \quad s_b \quad (4.46)$$

Constraint c_3 , prevents from situation s_c . Every training triplet $I_{j,x} I_{j,y} I_{k,z}$ is forced to meet the condition defined by Eq. 4.43. If $I_{p,A} I_{p,B} I_{q,A}$ is forced to meet that condition, the resulting proposition is just the opposite to that defining situation s_c , as Eq. 4.47 demonstrates. Hence, no triplet forced to meet c_3 can produce situation s_c . However, the prevention of situations s_a , s_b and s_d is not ensured by constraint c_3 , as Fig. 4.11(3) shows.

$$F_W I_{p,A} - F_W I_{q,A}^2 - F_W I_{p,A} - F_W I_{p,B}^2 \quad s_c \quad (4.47)$$

Constraint c_4 , prevents from situation s_d . Every training triplet $I_{j,x} I_{j,y} I_{k,z}$ is forced to meet the condition defined by Eq. 4.44. If $I_{p,B} I_{p,A} I_{q,B}$ is forced to meet that condition, the resulting proposition is just the opposite to the one defining situation s_d , as Eq. 4.48 demonstrates. Hence, no triplet forced to meet c_4 can produce situation s_d . However, the prevention of situations s_a , s_b and s_c is not ensured by constraint c_4 , as Fig. 4.11(4) shows.

$$F_W I_{p,B} - F_W I_{q,B}^2 - F_W I_{p,B} - F_W I_{p,A}^2 \quad s_d \quad (4.48)$$

In conclusion, training set I avoid situation s_a , training set II, situations s_a and s_b , and finally, training set III avoid situations s_a , s_b , s_c and s_d . Therefore, the proposed method to generate triplet combinations, and consequently, triplet augmentation, not only helps to prevent over-fitting but also the convergence of the network in a weights setting that does not let situations s_a , s_b , s_c and s_d arise for the training samples.

Fig. 4.11 Solving of the undesirable situations s_a , s_b , s_c and s_d by imposing constraints c_1 , c_2 , c_3 and c_4 , all rendered in the feature space. In (0) no constraint is imposed. In (1), (2), (3), (4) constraints c_1 , c_2 , c_3 and c_4 are consecutively added.

4.5.2 Data Shuffling

One important issue regarding the Mini-Batch Gradient Descent optimisation is the order in which the training data is presented to the learning algorithm. Inputting the training data in some meaningful order during the model training can affect the gradient and cause poor convergence.

For that reason, after the generation of possible triplet combinations, the list of obtained training triplets has been shuffled to avoid feeding the model in a meaningful order.

4.5.3 Data Augmentation

One of the best strategies to reduce over-fitting is the enlargement of the training data with new samples. However not always is possible, or cheap, to obtain more data. The Single-Shot Re-Id challenge is one of these cases where the quantity of available training data is really poor, and unbalanced, because of the inherent constraints that define the Re-Id task itself.

Data augmentation is a common technique that increases the quantity of training data by applying some transformations over the available samples.

In the experiments of this thesis, mirroring and colour modification have been performed over the input images. Unlike other types of distortions, these augmentation methods do not alter the human shape and proportions of people appearing in the input images, allowing their re-identification. The proposed methods are described below:

I Rectangular cropping with random padding. In the inputs images, a region of fixed size is randomly padded and cropped. Caffe libraries only provide squared cropping, which does not fit the aspect ratio of Re-Id images. For that reason, the design of a new python layer⁵ is proposed to rectangularly crop images, so that, most of the person figure is retain in the cropped image to allow its re-identification.

This layer takes the crop height and width as parameters. Then, the image position from which the rectangle is extracted is randomly set for each training sample, within the possible range. The number of different rectangles (different samples) that is possible to extract relies on such range. This number is given by the multiplication of the difference between the original and the crop height by the difference between the original and the crop width.

In most of the Re-Id datasets, every image presents a centred person with a fixed scale and resolution. Therefore, in almost all the images, most external pixels correspond to the background. Usually, these pixels take similar values in all the images from a cam view, especially in the case of Re-Id datasets that were captured from a fixed pair of cameras, such as PRID2011. By randomly cropping the images, the learning of a fixed background associated with certain pixels, which sometimes causes negative learning, is avoided. In that way, the dependence on the person position in the image, or the proportion of background is alleviated.

Because of the chosen feeding approach, based on mini-batches of multiple combinations of triplets, one image can be taken as input several times throughout the training process. Thanks to random cropping, different regions of that image are taken each time. Therefore, the training set is augmented, although in a redundant way.

II Mirroring. Mirror transformation consists of horizontally flipping the samples. The input data layer randomly applies this transformation to the input images with a probability of 0.5. Due to the triplet model feeding, one image can be taken as input several times throughout the training. Therefore, approximately half of the total times the image is flipped. So two instances of every image are feeding the model training. Hence, the training set is duplicated.

III Random colour modification. A new layer⁶ has been implemented to perform the simulation of multiple changes in illumination conditions over the inputs samples. This computes a pixel-wise transformation of the RGB values in the inputs images. A certain offset value,

⁵Random cropping layer is available under: https://github.com/magomez/data_augmentation_layers

⁶Random colour modification layer is available under: https://github.com/magomez/data_augmentation_layers

p , which can be positive or negative, is added to the values of red, R , green, G , and blue, B , components of every pixel of an image. For every training sample, this offset is randomly set within a certain range, whose value is taken through a layer parameter.

By adding the same offset to every channel RGB, the hue value, H , of the pixels is not modified. According to the formulation presented in [104], H value relies on three new variables, R , G , B . The values of these new variables after the proposed colour modification, R_m , G_m , B_m , are not altered, as Eq. 4.49, 4.50 and 4.51 prove. These equations are based on the formulation of R , G , B , given in [104], where $\max R G B$ is denoted by $\max$, and $\min R G B$ is denoted by $\min$.

$$R_m = \frac{\max p \quad R \quad p}{\max p \quad \min p} R \quad (4.49)$$

$$G_m = \frac{\max p \quad G \quad p}{\max p \quad \min p} G \quad (4.50)$$

$$B_m = \frac{\max p \quad B \quad p}{\max p \quad \min p} B \quad (4.51)$$

Therefore, finally, H is neither modified. In that way, the usual colour tones appearing in natural people images are maintained, allowing the Re-Id task. However, the saturation and lightness values after the colour modification, are altered, as 4.52 and 4.53 prove. These equations are also based on the formulation for saturation, S , and lightness, V , presented in [104].

$$S_m = \frac{\max p \quad \min p}{\max p} \frac{\max \quad \min}{\max p} \quad (4.52)$$

$$V_m = \frac{\max p}{255} V \frac{p}{255} \quad (4.53)$$

Eventually, the denominator of S formulation is modified by p , and an offset of $p/255$ is added to V value. These variations simulate the effects of different illumination or exposition conditions. So, after many iterations, the network receives multiple versions of the same samples, so, although, in a slightly redundant way, the variety of data is augmented.

In order to specifically and independently modify saturation and lightness, a previous colour space transformation stage would be needed. This prohibitively enlarges the computation time of every iteration. For that reason, it has been proposed the direct modification over the RGB channels of the input images.

The proposed data augmentation methods are integrated on the learning as a first stage of the forward propagation step. Therefore, conversely to offline augmentation methods, the newly obtained data is not occupying extra memory space and has no labelling cost.

4.6 Regularization

The number of network weights can be reduced by choosing fewer deep architectures, i.e. with fewer layers. The deeper the network is, the more complex and discriminative features it can model. However, the simpler the model, the less prone to be over-fitted it is. Therefore, a trade-off solution must be found. To avoid the use of too simple architectures, incapable of modelling discriminative features, regularization has been commonly applied over deep neural networks.

Regularization is an extended technique in deep learning to ameliorate the over-fitting. It effectively limits the number of free parameters in a neural model by preventing the network weights, W , to fit so perfectly to over-fit the model. With that purpose, different methods like loss regularization, dropout, early stopping and normalisation have been experimented in this thesis.

4.6.1 Loss Regularization

Mathematically, the regularization technique modifies the loss function, f_L . A term, consequently called regularization term, $\lambda R(W^t)$, is added to the cost function term, $f_C(W; X_s^t)$. Therefore, the loss function, that was presented in Eq. 4.22, takes now the formulation defined by Eq. 4.54.

$$f_L(W^t; X^t) = \frac{1}{2B} \sum_{i=1}^B [f_C(W^t; X_i^t) + \lambda R(W^t)] \quad (4.54)$$

The regularization term penalises large weights, by introducing a zero-mean Gaussian prior over the weights, (L_1 or L_2 are commonly used). It's hard to determine in advance which are the weights that are less likely to be relevant, so, the regularization term penalises all the parameters. In practice, this makes some hidden units have a much smaller effect, so, the network model becomes simpler and less prone to over-fitting. In that way, regularization limits freedom in the model.

Regularization technique also modifies the weights updating rule (Eq. 3.1), since this relies on the gradient of the loss function, which has been regularized. The partial derivatives for the regularized loss function are calculated as Eq. 4.55 shows. The new term coming from regularization causes the weights to decay in proportion to its size.

$$\frac{\partial f_L(W^t; X^t)}{\partial W_j^t} = \frac{1}{2B} \sum_{s=1}^B \left[\frac{\partial f_C(W^t; X_s^t)}{\partial W_j^t} + \lambda \frac{\partial R(W^t)}{\partial W_j^t} \right] \quad (4.55)$$

In this thesis, both, L_2 regularization [72] (also called L_2 norm, or Ridge regularization) and L_1 regularization [259] (also called L_1 norm or Lasso regularization) have been performed and evaluated (Section 6.2.4). Equation 4.56 defines the L_2 regularization term. Considering that W_j^t is a matrix of weights, $R_{L2}(W^t)$ is the matrix norm, also called the Frobenius norm of the matrix. Equation 4.57 presents the formulation for L_1 regularization term.

$$R_{L2} = \sum_{j=1}^K W_j^2 \quad (4.56)$$

$$R_{L1} = \sum_{j=1}^K |W_j| \quad (4.57)$$

The difference between L2 and L1 terms is that L2 is the sum of the square of the weights, while L1 is just the sum of their absolute values. Both L2 and L1 regularization have their own strengths and weakness, because of the properties of their formulations, which are rendered in Fig. 4.12. The solution or hypothesis given by the network output is rendered by h , in Fig.4.12.

Fig. 4.12 L1 (a) and L2 (b) representation for the case of having only two weights to fix (W_1, W_2).

L2 term pushes weights into a hyper-sphere, according to its own formulation, so they're likely to be pretty similar since most of the volume of the hyper-sphere lies in areas where weights are similar. The larger the penalty, λ , the narrower hyper-sphere is, and then, the solution meets in a point closer to zero. In most cases, the solution representation is tangential to the hyper-sphere in a point with components for all the network weights. Therefore, L2 regularization forces the weights to be small but not zero, so the solution is non-sparse.

L2 is not robust to outliers as square terms blow up their error differences and the regularization term tries to fix it by penalising the weights. Moreover, L2 performs better when all the input features influence the output in a similar measure. This is unknown in deep learning, where learning algorithm automatically selects the features, but L2 regularization can determine that some of the pixels, like those corresponding to the background, are no important for the output.

On the other hand, L1 performs shrinkage since the minimum-costed solutions are limited to the corners of the hyper-cube described by L1 formulation. A corner is defined as having one coordinate with value zero. If the loss function hits one of the corners, the weight corresponding to the axis is shrunk to zero. As the number of predictors increase, the hyper-cube has an increasing number of corners, so it is highly probable having some null weights. Hence, L1 leads to sparsity, so it performs shrinkage and effectively subset selection of inputs, producing a simpler model.

In this work, both regularization methods, have been implemented by using the Caffe libraries [169], where regularization is directly added to the weight updating equation through a parameter called weight decay, wd . Eq. 4.58 shows how Caffe libraries implement weight updating for Mini-Batch GD with regularization.

$$W_j^{t+1} = W_j^t - \frac{\alpha}{2B} \left(\frac{\partial f_C(W^t; X_s^t)}{\partial W_j^t} + wd \cdot W_j^t \right) \quad (4.58)$$

According to that, wd , takes different meaning for L2 and L1 regularization, depending on the partial derivatives formulation for L2 and L1. wd is defined by Eq. 4.59 and 4.60, for L2 and L1 regularization, respectively.

$$\frac{\partial R_{L2}(W^t)}{\partial W_j^t} = \frac{\partial \|W^t\|_2^2}{\partial W_j^t} = 2W_j^t \quad (4.59)$$

$$\frac{\partial R_{L1}(W^t)}{\partial W_j^t} = \frac{\partial \|W^t\|_1}{\partial W_j^t} \quad (4.60)$$

The L1 term is not differentiable when weight is zero. One straightforward solution is to consider a subgradient at zero and use Eq. 4.61, where the function $sign(x)$ is defined by Eq. 4.62. This method for weight updating is called “SDG-L1 (Naive)” and it was presented in [321].

$$\frac{\partial R_{L1}(W^t)}{\partial W_j^t} = sign(W_j^t) \quad (4.61)$$

$$sign(x) = \begin{cases} 1 & \text{if } x > 0 \\ -1 & \text{if } x < 0 \\ 0 & \text{if } x = 0 \end{cases} \quad (4.62)$$

Therefore, when L2 regularization is used, wd corresponds to 2λ . So, the step of weights updating (Eq. 4.58), takes the matrix of parameters and subtracts 2λ times this, like multiplying the parameters matrix by $(1 - 2\lambda)$, which is going to be a little bit less than one. So, this is why L2 regularization is also called weight decay.

On the other side, when L1 regularization is used, wd takes value $\frac{\lambda}{|W_j^t|}$, except when W_j^t is zero, in such case wd is also zero.

The wd hyper-parameter determines how dominant the regularization term is in the gradient computation. Different values of wd have been used to train the proposed model (with both L2 and L1 regularization). The evaluation of these learning processes is described in Section 6.2.4 in more detail.

4.6.2 Dropout

Dropout is a regularization technique, where randomly selected neurons are ignored “dropped-out”) during training. The dropout hyper-parameter, p , sets the probability of keeping (not dropping out) a neuron. At each iteration, the pattern of kept and ignored neurons is different. So, many different networks are considered throughout the training process, and all of them are simpler than the original one, where no neuron is dropped out. Since a certain number of neural units have been omitted, much smaller networks are being trained, which regularizes the network. Therefore, dropout can be understood as an adaptive regularization method.

Moreover, if dropout is performed in one layer, the next layer is receiving different inputs at each iteration. Therefore, the training is reluctant to put too much weight on any one input and it is motivated to spread out weights. This will tend to have an effect of shrinking the weights, which regularizes the network to help prevent over-fitting.

Therefore, as an extra measure to reduce over-fitting, dropout has been implemented in all the fully connected layers of the trained architectures, with the exception of the last one, which computes the final feature array.

4.6.3 Early Stopping

The early stopping technique consists of selecting the neural model, i.e. the set of weights values, learnt after a certain number of iterations, without waiting until the final iteration. The network is trained until learning discriminative features, but it is stopped before over-fitting the model.

To perform early stopping the loss value, and even the performance of the network model, are observed over the learning iterations, for the training and the validation set. Therefore, the model is selected by monitoring the learning curves of the training process.

In the first iterations, the parameters of the neural network are close to zero, since they were initialised with small values. As the model is trained, the parameters get larger values. A neural network with smaller parameters is less over-fitted, so early stopping has been used as a regularization technique in the experiments of this thesis.

4.6.4 Normalisation

To facilitate learning, the initial values of the model parameters are typically normalised by initialising them with zero mean and unit variance. Xavier method [122], has been used to initialise the model weights in the experiments conducted in this thesis.

As the training process progresses and the parameters are updated to different magnitudes, this normalisation is faded, which slows down training and amplifies changes as the network becomes

deeper. By making normalisation operations part of the model architecture, the initial normalisation is somehow re-established, and changes are back-propagated through the operation as well. Normalisation additionally acts as a regularizer since it affects the range of weight values.

Different normalisation operations have been integrated not only into the Triplet model but also in the Siamese one.

a) Normalised Double-Margin based Contrastive Loss function.

The use of the novel Normalised Double-Margin based Contrastive Loss function (Section 4.2.2) implicitly performs the normalisation of the learnt distance metric to values from zero to the unit.

The intermediate step of normalisation makes possible the learning of discriminative features in a lower number of learning iterations since the loss function oscillations through the training process is reduced. That is because by means of normalising the distance metric, it takes values of a similar order to the margins values, which defines the objective values for the distance metric for positive and negative pairs. Only in that way, an acceptable measurement of the deviation of the distance with respect to the objective can be measured by the loss function.

b) Local Response Normalization

Local Response Normalization(LRN) layers, [184], have been employed to normalize the output of certain convolutional layers. The LRN layer computes the normalised value, y_i , for every input, x_i , using Eq. 4.63, where n is the size of each local region over which the normalisation is performed, k is a scaling parameter, and α is the normalisation exponent.

$$y_i = \frac{x_i}{1 + \frac{k}{n} \sum_{j=i-\frac{n}{2}}^{i+\frac{n}{2}} x_j^2} \quad (4.63)$$

Concretely, some triplet learning experiments have been conducted, using the architecture presented as the A-LRN version of a set of Very Deep CNNs in [303]. This neural architecture, hereafter called VGG11LRN is an 11-layered network, which only differs from VGG11 (Section 4.1) in the fact that the VGG11LRN network contains a LRN layer.

Table 4.3 lists the layers' specifications for the proposed VGG11LRN-based embedding, where the input size has been modified to take person images of 64x128 pixels.

c) Triplet without normalisation

Through the conducted experiments (Section 6.2.4) has been observed that even though, the normalisation improve the learning and the performance of the Re-Id model when Siamese model is used, it does not seem to provide a significant enhancement when Triplet model is employed.

The relative nature of the triplet loss formulation makes itself flexible and adaptive through the features learning, so the integration of normalisation steps does not affect so strongly as in the Contrastive loss computation.

Table 4.3 Structure of the used VGG11LRN-based model. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, *stride*, or *#outputs* for FC layers.

Layer	Input size	Output size	Kernel
Conv-1-1	128 x 64 x 3	128 x 64 x 64	3 x 3 x 3
LRN	128 x 64 x 64	128 x 64 x 64	3 x 3 x 64
Pool-1	128 x 64 x 64	64 x 32 x 64	2 x 2 x 64, 2
Conv-2-1	64 x 32 x 64	64 x 32 x 128	3 x 3 x 64
Pool-2	64 x 32 x 128	32 x 16 x 128	2 x 2 x 128, 2
Conv-3-1	32 x 16 x 128	32 x 16 x 256	3 x 3 x 128
Conv-3-2	32 x 16 x 256	32 x 16 x 256	3 x 3 x 256
Pool-3	32 x 16 x 256	16 x 8 x 256	2 x 2 x 256, 2
Conv-4-1	16 x 8 x 256	16 x 8 x 512	3 x 3 x 256
Conv-4-2	16 x 8 x 512	16 x 8 x 512	3 x 3 x 512
Pool-4	16 x 8 x 512	8 x 4 x 512	2 x 2 x 512, 2
Conv-5-1	8 x 4 x 512	8 x 4 x 512	3 x 3 x 512
Conv-5-2	8 x 4 x 512	8 x 4 x 512	3 x 3 x 512
Pool-5	8 x 4 x 512	4 x 2 x 512	2 x 2 x 512, 2
FC-6	4 x 2 x 512	1 x 1 x 4096	4096
FC-7	1 x 1 x 4096	1 x 1 x 4096	4096
FC-8	1 x 1 x 4096	1 x 1 x 1000	1000

4.7 Transfer Learning

Transfer learning, also called domain adaptation, [220], is a widely applied method in deep Re-Id model learning.

The objective of the model presented in this chapter is to perform Person Re-Identification, so the Re-Id domain is considered as the target domain. Consequently, the Re-Id performance of the proposed model is measured over some Re-Id datasets, so these are known as target datasets.

However, given the requirement of a large amount of labelled data to learn a non-over-fitted model, able to generalise the solution with unknown samples, and the small size of Single-Shot Re-Id datasets, the transference of learning has been adopted. Therefore, learning previously acquired in a different domain is transferred to initialise the weights of the Re-Id model. That means

that a previous model was previously trained on an auxiliary dataset, also called source dataset so that the learning acquired by the whole model or by some of its layers could be transferred to solve the Re-Id task with improved performance.

This thesis proposes the use of a unique architecture to transfer learning between two different data domains. Therefore, the presented learning model has been used for both, its pre-training on a source dataset, and its fine-tuning on a target dataset.

Fine-tuning, [365], is the most common transfer learning strategy and it has been adopted in this thesis. This is composed of two training processes: firstly, a base network is trained on the source dataset, from a certain domain different from the target task. Secondly, the model is fine-tuned over the target dataset. To do that, the pre-trained weights corresponding to the first l_T layers have been transferred, and the remaining weights have been initialised using Xavier method [122]. Then, the learning algorithm is conducted over the target dataset, so that, only the weights of the last l_U layers are updated through the second training, or fine-tuning.

Therefore, l_T is the number of pre-trained layers transferred to the final model and l_U is the number of layers whose weights are trained or updated by the target dataset. Considering a model of depth L , i.e. L is the total number of layers of the model, it can be deduced that: the weights of the first $L - l_U$ layers are learnt using the source dataset in the first training; the weights of the last $L - l_T$ layers are trained in the second training with the target dataset, and the $l_T + l_U - L$ central layers are pre-trained in the first training process and fine-tuned in the second one. These deductions are represented in Fig. 4.13, where the contribution of the source dataset to the parameters learning is represented in blue, and yellow is used for the target dataset.

Fig. 4.13 Contribution of the source (blue) and target (yellow) datasets on the learning of the weights of the different layers for an example model, and for given values of l_T and l_U .

Six different levels of transfer learning have been implemented and tested in this work, proving that the transference of leaning from a different domain notably increases the Re-Id performance. The values given to l_T and l_U , according to each level, are exposed by Table 4.4.

- Level 0. No layer is pre-trained in the source dataset ($l_T=0$). So, the model is totally and uniquely learnt over the target dataset, where it is also tested. In this level, there is no transferred learning.

- Level 1. Seven of the layers pre-trained on the source dataset ($0 \leq l_T \leq L$) are transferred and fine-tuned on the target dataset. Hence, in the second training, the initial values of the first seven layers come from the first training.
- Level 2. Seven of the layers pre-trained on the source dataset ($0 \leq l_T \leq L$) are transferred to the final model, but not fine-tuned on the target dataset. So, in the final model, the final values of the first seven layers come from the first training.
- Level 3. All the layers pre-trained on the source dataset ($l_T \leq L$) are transferred and fine-tuned on the target dataset. Therefore, in the second training, the initial values of the layers come from the first training.
- Level 4. All the layers pre-trained on the source dataset ($l_T \leq L$) are transferred to the final model, but only nine are fine-tuned on the target dataset. In the final model, the final values for the first seven layers come from the first training. The rest of the layers also takes the initial values from the first training but they are fine-tuned in the second training.
- Level 5. All the layers are trained on the source dataset ($l_T \leq L$) and none of them is fine-tuned ($l_U = 0$). So, the model is totally trained on the source dataset but tested on the target one. In this level, the complete model is transferred from the source domain to the target one, without fine-tuning.

Table 4.4 Set-up values for l_T and l_U , for every level of transfer learning.

Level	l_T	l_U	L	l_U	l_t	l_U	L	L	l_T
0	0	16	0		0				16
1	7	16	0		7				9
2	7	9	7		0				9
3	16	16	0		16				0
4	16	9	7		9				0
5	16	0	16		0				0

The following sections present the developed techniques to apply transfer learning without requiring the modification of the presented neural model, i.e. the target architecture. New source datasets have been generated from data belonging to different domains. The data has been processed to obtain the proper input samples to feed a Re-Id triplet model.

4.7.1 Transfer learning from Multi-Object Tracking domain

In order to alleviate the Re-Id data problem, the transference of learning previously acquired from the MOT domain has been exploited.

This idea has been inspired by the fact that both, people detection and their identification, are available in labelled tracking sequences. Therefore, before training and testing over the target Re-Id dataset, the model has been pre-trained on people detections from MOT sequences.

With this approach, the Re-Id network architecture does not require any modification to transfer learning from one task to the other. Instead of that, the MOT data has been adapted to feed a Re-Id triplet network.

The tracking dataset used as source dataset has been the MOT17 dataset (Section 3.3.2). This dataset includes fourteen variate real-world surveillance sequences, meant to train and test Multi-Person Tracking algorithms. Seven of these sequences provide their MOT ground truth with the bounding boxes of the people detections in every frame and their identification numbers. Taking advantage of this fact, a new source dataset has been created by a data generation tool⁷ that has been designed to create the training and validation sets of triplets, from people detections.

From each frame, the appearing people have been extracted thanks to the bounding boxes defined in the dataset ground truth. Subsequently, triplets have been generated from the extracted people images, taking as the anchor and the positive images pairs of samples from the same individual. These samples have not to be consecutive in time, that means that a certain time step is allowed between the frames from which they come. Then, for each pair, the negative sample is added to form a triplet, taking an image from a different individual, and even from a different sequence of the MOT17 dataset, as Fig. 4.14 shows.

Fig. 4.14 Triplet samples generated from MOT17 dataset.

⁷The data generation tool has been implemented as a set of C++ functions, which are publicly available under: http://github.com/magomez/dataset_factory/tree/master/data_factory_from_mot.

The person images have been resized to the same resolution than Re-Id datasets samples (64x128 has been taken as the standard dimension) to enable the use of the same neural architecture to train with the source and the target datasets. In that way, the advantages of using a different Re-Id dataset as an auxiliary dataset are kept, but with the possibility of getting a larger training dataset.

Furthermore, Single-Shot Re-Id datasets present only two instances of a certain individual against the high number of different people to identify. This unbalanced nature of the data is attenuated by the new source dataset, where many detections of the same person are extracted, making easier the convergence in the model learning process.

In addition, samples from different MOT sequences have been coupled and compared in the training. This setting helps to avoid the dependence on the characteristics of a certain camera view, and consequently, to avoid the negative transfer of learning.

However, in the proposed MOT auxiliary dataset, the samples of the same person are captured from the same camera view. Therefore, although the model is trained to be able to identify people after occlusions, it does not have enough data to learn to identify people across different camera views. For that reason, it is necessary a second step of fine-tuning on the target Re-Id dataset.

In general, the intuition behind this method is that the most representative features of a person are automatically learnt on person images from MOT sequences, so many of the learnt features can be transferred to solve the task of re-identifying people. The learnt features were transferred to the model by initializing its weights, W^0 , with the values of the pre-trained weights.

Therefore, from the set of learnt descriptors, the low-level ones, which are learnt in the earlier layers of the network model, are kept, i.e. low-level features are learnt from the source dataset. Then, the most high-level representations are coded in the further layers. Hence, by fine-tuning the parameters and learning the final layers of the model on the Re-Id target dataset, high-level descriptors are learnt. These descriptors automatically acquire the capacities of discriminating people and recognising an identity in images from different views, through their training on the target dataset. That is because contrary to the source dataset, the Re-Id target dataset contains samples of individuals captured from different camera views, that makes the features robust against view-to-view transitions.

4.7.2 Transfer Learning from Cross-Re-Identification Dataset

By pre-training a Re-Id model on samples from MOT sequences, basic person features are learnt. To get more discriminative features fine-tuning on the target Re-Id dataset is required, as it is mentioned above. However, if a universal model, able to re-identify people between a known pair of cameras, is desired, the fine-tuning on a unique target dataset presents some disadvantages. This is due to the negative transfer of the learning of a specific camera-to-camera transition, or the training on a limited range of background and perspective conditions.

In order to get a Re-Id model robust against multiple camera settings, a cross-Re-Id dataset has been generated. Samples from five different Re-Id datasets (see Section 3.3.1): PRID2011, VIPeR, CUHK-02, GRID and i-LIDS has been used to form a large set of training triplets by means of a especially designed tool⁸.

In addition, this cross-Re-Id dataset has been used to perform an intermediate training step, between the pre-training from MOT samples and the final fine-tuning on the target dataset. The cross-data-set provides a wider quantity and variety of samples, so by introducing this intermediate step and transferring the obtained model to the final fine-tuning stage, model over-fitting is reduced, as the results in Section 6.2.4.1 shows.

Besides, the negative sample in the triplets of the cross-Re-Id dataset can belong to a different dataset from those where the anchor and the positive image came from. In that way, the learning and the negative transfer of a specific setting of a pair of cameras is appalled.

4.8 Human Shape Partition

Apart from the previously described architectures (Section 4.1), three new neural networks have been designed to embed person features for Re-Identification. Both architectures are based on the partitioning of the input images in several body parts.

The human shape partitioning has been motivated by the following reasons:

- Features misalignment is one of the main problems to face in Person Re-Identification. The pose of the individuals, the scale and the perspective can largely variate between different views. Due to that circumstances, there is no a meaningful alignment between the features rendering every region of the input images, so, the comparison of the learnt features to decide whether two representation correspond to the same person or not becomes extremely difficult. By means of body partitioning, and the computation of features for well-defined body parts, the sought alignment is approached, and location awareness is provided to the model. This facilitates the features comparison and avoids the person pose dependence.
- Prior body parts extraction facilitates the learning of person features since the image is divided into several smaller regions. Therefore, every part-dedicated network needs a lower number of layers than that required by a unique neural network to extract features from the whole input image. Automatically finding the human parts or joints in a person image is a useful task and could be implicitly performed by highly-layered neural networks. However, providing such partitioning on a previous stage, apart from the features learning, less neural layers are required and consequently, the over-fitting problem is mitigated.

⁸The data generation tool has been implemented as a set of C++ functions, which are publicly available under: http://github.com/magomez/dataset_factory/tree/master/data_factory_from_reid

- The extraction of well-delimited body parts allows the elimination of most of the background in the input images. Adding a parts extraction stage, before the features learning, the task of identifying and obviating the pixels corresponding to the background is got out from the learning process. It makes the learning process more efficient since it is focused only on the learning of representative features. Illumination and perspective changes, caused by different camera-views, are very notable in the background, so discarding the background reduces the dependence of the final person descriptor on these variations.
- By learning independent features for separated body-parts, the implementation of a Re-Id method robust against occlusions is possible. Re-Identification can be performed from the comparison of the features associated with body parts that are visible in both images. In that way, the visibility of the whole human shape of the individuals is not mandatory to perform their re-identification.

The designed network architectures firstly perform the partition of the person images, and they divide the network flow into so many branches as body parts have been obtained. Hence, a neural branch is associated with each body part to learn the features corresponding to that part.

Next subsections present the three designed neural models, whose differences mainly lie in the method used to divide the human shape, the manner of training the network branches (jointly or independently) and the generation of the final global person descriptor from the learnt parts features.

4.8.1 Three independently learnt part-features

A Re-Id model based on the division of the input images in three parts has been designed, and its architecture is shown by Fig.4.15 and described below.

Fig. 4.15 Re-Identification Method Architecture based on three parts division.

To measure the similarity between two person samples, firstly, each image is divided into three parts roughly corresponding to the head, upper body, and legs. The partitions sizes are constant and have been determined by using human shape proportions.

Secondly, a CNN computes a multi-dimensional feature, ${}^{bp}F_W({}^{bp}I^p) = ({}^{bp}f_1^p, \dots, {}^{bp}f_N^p)$, for each one of the mentioned parts, where the index bp represents one of the labels h , b , and l , to refer to the head, upper body or legs descriptor respectively. The index p takes the values a or b corresponding to each one of the images to compare. Every element of the array descriptor presents the form ${}^{bp}f_j^p$, where the index j represents each one of the elements of the descriptor array. Therefore, j can take values from 1 to N , being N the dimension of the descriptor. The value of N is 100 for ${}^hF_W({}^hI^p)$, and 200 for ${}^bF_W({}^bI^p)$ and ${}^lF_W({}^lI^p)$. Both neural branches are identical, so the same descriptors are computed for both input images.

Subsequently, the distance, ${}^{bp}d$, between the multi-dimensional features obtained for the two images is calculated for every body part. Therefore, three comparisons are made, one for each body part. The connection function is defined by the Euclidean distance, d_E , as Eq.4.64 shows. Then, the distance obtained for each body part comparison is taken as an element of a three-dimensional descriptor $P(p_x, p_y, p_z)$, as it is set in Eq. 4.65, 4.66 and 4.67.

$${}^{bp}d = d_E(F_W(I^a), F_W(I^b)) = \sqrt{\sum_{j=1}^N ({}^{bp}F_W({}^{bp}I^a)_j - ({}^{bp}F_W({}^{bp}I^b)_j)^2} \quad (4.64)$$

$$p_x = {}^h d \quad (4.65)$$

$$p_y = {}^b d \quad (4.66)$$

$$p_z = {}^l d \quad (4.67)$$

The module of this three-dimensional feature vector is then calculated, as Eq. 4.68 shows, and employed as the distance metric, dm , used, in turn, to measure the Degree of Appearance Similarity, DoAS, between the images (see Eq. 4.1). Therefore, $|P|$ and DoAS are complementary values, since similar images comparisons produce small values for the module of P (small features distances), and dissimilar images comparison cause just the opposite effect. Analogously, if P is understood as a three-dimensional point, points corresponding to positive samples must be placed near the origin of the coordinates system, and points representing negative samples must be far.

$$|P| = \sqrt{p_x^2 + p_y^2 + p_z^2} \quad (4.68)$$

a) Convolutional Neural Network Architecture

For each body part image, ^{bp}I , a CNN, is used to learn the corresponding part feature, $^{bp}F_W$. Although the learnt weights and dimensions of the three body-parts-dedicated networks are different, they present an identical structure, which is based on the configuration of the first layers of the *mnistsiamese* example, implemented by the Caffe libraries [169]. The essential layers of this network are two convolutional layers, two max-pooling layers and an inner product layer, which is a fully connected layer whose number of outputs is equal to N , the dimension of the parts feature arrays. A ReLU is used as an activation function.

The convolutional layers outputs have been normalised by LRN layers, in order to regularise the learning process (Section 4.6.4). The main difference between the three CNNs is the dimensions of the corresponding part image input. Table 4.5, 4.6 and 4.7 list the specifications of the layers of the head, body and legs neural networks, respectively.

Table 4.5 Neural network architecture for the fist image division (head). The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters, stride$, or $\#out puts$ for FC layers.

Layer	Input size	Output size	Kernel
Conv-1	28 x 64 x 3	22 x 58 x 64	7 x 7 x 3
LRN-1	22 x 58 x 64	22 x 58 x 64	$n \quad 5 \quad 10^{-4} \quad 0.75$
Pool-1	22 x 58 x 64	11 x 29 x 64	2 x 2 x 64, 2
Conv-2	11 x 29 x 64	7 x 25 x 64	5 x 5 x 64
LRN-2	7 x 25 x 64	7 x 25 x 64	$n \quad 5 \quad 10^{-4} \quad 0.75$
Pool-2	7 x 25 x 64	4 x 13 x 64	2 x 2 x 64, 2
FC-3	4 x 13 x 64	1 x 1 x 1000	100

Table 4.6 Neural network architecture for the fist image division (body). The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters, stride$, or $\#out puts$ for FC layers.

Layer	Input size	Output size	Kernel
Conv-1	32 x 64 x 3	26 x 58 x 64	7 x 7 x 3
LRN-1	26 x 58 x 64	26 x 58 x 64	$n \quad 5 \quad =10^{-4}, \quad 0.75$
Pool-1	26 x 58 x 64	13 x 29 x 64	2 x 2 x 64 2
Conv-2	13 x 29 x 64	9 x 25 x 64	5 x 5 x 64
LRN-2	9 x 25 x 64	9 x 25 x 64	$n \quad 5 \quad =10^{-4}, \quad 0.75$
Pool-2	9 x 25 x 64	5 x 13 x 64	2 x 2 x 64 2
FC-3	5 x 13 x 64	1 x 1 x 1000	200

Table 4.7 Neural network architecture for the fist image division (legs). The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, or $\#outputs$ for FC layers.

Layer	Input size	Output size	Kernel
Conv-1	68 x 64 x 3	62 x 58 x 64	7 x 7 x 3
LRN-1	62 x 58 x 64	62 x 58 x 64	$n = 5, \alpha = 10^{-4}, \beta = 0.75$
Pool-1	62 x 58 x 64	31 x 29 x 64	2 x 2 x 64, 2
Conv-2	31 x 29 x 64	27 x 25 x 64	5 x 5 x 64
LRN-2	27 x 25 x 64	27 x 25 x 64	$n = 5, \alpha = 10^{-4}, \beta = 0.75$
Pool-2	27 x 25 x 64	14 x 13 x 64	2 x 2 x 64, 2
FC-3	14 x 13 x 64	1 x 1 x 1000	200

b) Features Learning

A Siamese model has been implemented to train each one of the three CNNs (Table 4.5, 4.6 and 4.7) in three independent learning process, one per body part feature. The N2MCL function has been used in all the conducted training processes.

c) Euclidean Distance as the Distance Metric

A common approach for the Re-Id task consists of the extraction of a number of features and subsequently the computation of a metric distance to measure the appearance similarity between two person images from their vectors of features.

Following that structure, the vector of features extracted, for each image p , by the proposed method is a 500-dimensional features array, F^p , which is formed by means of concatenating the feature arrays calculated for head, upper body and legs, ${}^hF_W({}^hI^p)$, ${}^bF_W({}^bI^p)$, and ${}^lF_W({}^lI^p)$, respectively, as in Eq. 4.69.

$$F^p = ({}^hF_W({}^hI^p)_1, \dots, {}^hF_W({}^hI^p)_{100}, {}^bF_W({}^bI^p)_1, \dots, {}^bF_W({}^bI^p)_{200}, {}^lF_W({}^lI^p)_1, \dots, {}^lF_W({}^lI^p)_{200}) \quad (4.69)$$

The metric distance used by this model is the Euclidean distance, as can be deduced from the computation of the P module, Eq. 4.68. Taking into account that the elements of P are the distances calculated by the connection function for each one of the body parts, the module of P can be computed as Eq. 4.70 presents. Using Eq. 4.64 to substitutes each one of the distances, the modules computation takes the form shown in Eq. 4.71, which is clearly the formulation for the Euclidean distance between $F_W(I^a)$ and $F_W(I^b)$.

$$|P| = \sqrt{{}^h d^2 + {}^b d^2 + {}^l d^2} \quad (4.70)$$

$$|P| = \sqrt{\begin{aligned} &\sum_{j=1}^{100} ({}^h F_W ({}^h I^a)_j - {}^h F_W ({}^h I^b)_j)^2 + \\ &\sum_{j=1}^{200} ({}^b F_W ({}^b I^a)_j - {}^b F_W ({}^b I^b)_j)^2 + \\ &\sum_{j=1}^{200} ({}^l F_W ({}^l I^a)_j - {}^l F_W ({}^l I^b)_j)^2 \end{aligned}} \quad (4.71)$$

4.8.2 Nine jointly learnt part-features

A Re-Id model based on the extraction of nine body parts has been designed, and its architecture is shown by Fig. 4.16 and described below.

Fig. 4.16 Re-Identification Method Architecture based on the extraction of nine body-parts.

To measure the DoAS between two person images, firstly a feature array, $F_W(I^p)$, is computed for each one of them. The transformation of every image, I^p , to its corresponding representation in the feature space, is performed by a properly weighted combination of CNNs. The feature computation for each image of a pair is rendered in one of the two branches of the Re-Id architecture, which are identical and compute the same features. p takes values a and b to refer each branch.

Then, the features are compared by the connection function which measures the Euclidean distance between them. Normalising this distance in a range of values from zero to one, the connection function offers the probability of that a pair of images are showing different people is obtained. This measurement is complementary to the DoAS, which is defined as the probability of that a pair of images render the same person.

a) Body partitioning

The integration of a body parts extraction layer, which detects well-defined body parts, instead of roughly partitioning the image, like in the previously explained architecture (Section 4.8.1), provides a Re-Id algorithm more robust against different poses, backgrounds, and occlusions.

The body parts extractor layer takes as input a person image, I , and returns nine body parts images, ^{bp}I , corresponding to head and limbs. Therefore, the index bp , which indicates the query body part, can take the following values: h , head; ula , upper left arm; lla , lower left arm; ura , upper right arm; lra , lower right arm; ull , upper left leg; lll , lower left leg; url , upper right left; lrl , lower right leg.

This module has been programmed as a novel Caffe python layer⁹ and it is mainly based on the use of the Convolutional Pose Machine, CPM, presented in [339], which is a pre-trained DCNN composed by a high number of layers. Therefore, the parts extraction layer needs to load the architecture and pre-trained model files for the CPM in order to get its output, which is a set of body joints locations.

The joints set is formed by the following fifteen body joints: crown, neck, right shoulder, right elbow, right wrist, left shoulder, left elbow, left wrist, right hip, right knee, right ankle, left hip, left knee and left ankle. The term right and left refer to the right and left sides of a person, which are identified independently from his/her orientation in the input image. Fig. 4.17 enumerates these body joints (in the same order) over one of the samples of the PRID2011 dataset, except the last joint, which is not used by the body parts extractor layer.

Fig. 4.17 Body parts extracted before being resized.

The extracted body parts are delimited by pairs of the previously found joints, constituting their extremes, as Fig. 4.17 renders. For each body part, an oriented rectangle is extracted from the input image. The orientation angle of the rectangle is the one presented by the line resulting from

⁹The parts extraction layer is publicly available under <http://github.com/magomez/CPMclass>, and the deploy and model file of the CPM presented by [339], which contains the network architecture and learnt weights, respectively, are publicly available under <http://github.com/shienw/convolutional-pose-machine-release>

joining the extreme joints of the query body part, as it is represented by Fig. 4.17 for the case of the lower right leg. The location of the upper joint is chosen as the upper central pixel of the ROI and the location of the lower joint, as its lower central pixel.

Finally, once the corresponding rectangles have been extracted for each one of the nine body parts, they are resized to get certain pre-established fixed dimensions. Subsequently, the body parts images are the inputs for nine CNNs, whose outputs are parts features that will form a person feature array, as it will be explained below. The parts features combination stage requires that the parts features arrays present a certain fixed size. Since these arrays are the outputs of CNNs, their dimensions depend on the dimension of the inputs, which are the parts images. For that reason, the parts images must be resized.

The dimensions of the body part images have been pre-established according to the human shape proportions applied to a human representation with a height of 128 pixels, which has been taken as a standard dimension because it is the height value presented by the samples in most of the Re-Id datasets. Eventually, the established body part sizes are 45x45, for hI , 30x40 for ^{ula}I , ^{lla}I , ^{ura}I , and ^{lra}I , and 30x60 for ^{ull}I , ^{lll}I , ^{url}I , and ^{lrl}I .

b) Convolutional neural network architecture

For each body part image, ^{bp}I , a CNN, is used to learn the corresponding part feature, $^{bp}F_W$ ^{bp}I , which is a multi-dimensional descriptor. Although the learnt weights and dimensions of the nine body-parts-dedicated networks are different, they present an identical structure. Like in the previously explained model, this architecture is based on the configuration of the first layers of the *mnist siamese* example, which has been implemented by the Caffe libraries [169].

The proposed nine body parts networks can be grouped according to three different versions of the network structure, depending on the dimensions of the part image inputs, which can be separated in the head, arm parts, and leg parts. Their layers specifications are listed in Table 4.8, 4.9, and 4.10, respectively.

Table 4.8 Head neural network architecture. The input and output sizes are described in #rows x #cols x #filters; the kernel, in #rows x #cols x #filters, stride, or #outputs for FC layers.

Layer	Input size	Output size	Kernel
Conv-1	45 x 45 x 3	39 x 39 x 64	7 x 7 x 3
LRN-1	39 x 39 x 64	39 x 39 x 64	$n = 5$, $\sigma^2 = 10^{-4}$, $\beta = 0.75$
Pool-1	39 x 39 x 64	20 x 20 x 64	2 x 2 x 64, 2
Conv-2	20 x 20 x 64	16 x 16 x 64	5 x 5 x 64
LRN-2	16 x 16 x 64	16 x 16 x 64	$n = 5$, $\sigma^2 = 10^{-4}$, $\beta = 0.75$
Pool-2	16 x 16 x 64	8 x 8 x 64	2 x 2 x 64, 2

Table 4.9 Arm neural network architecture. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, or $\#outputs$ for FC layers.

Layer	Input size	Output size	Kernel
Conv-1	40 x 30 x 3	34 x 24 x 64	7 x 7 x 3
LRN-1	34 x 24 x 64	34 x 24 x 64	$n \quad 5 \quad 10^{-4}, \quad 0.75$
Pool-1	34 x 24 x 64	17 x 12 x 64	2 x 2 x 64, 2
Conv-2	17 x 12 x 64	13 x 8 x 64	5 x 5 x 64
LRN-2	13 x 8 x 64	13 x 8 x 64	$n \quad 5 \quad 10^{-4}, \quad 0.75$
Pool-2	13 x 8 x 64	7 x 4 x 64	2 x 2 x 64, 2

Table 4.10 Legs neural network architecture. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, or $\#outputs$ for FC layers.

Layer	Input size	Output size	Kernel
Conv-1	60 x 30 x 3	54 x 24 x 64	7 x 7 x 3
LRN-1	54 x 24 x 64	54 x 24 x 64	$n \quad 5 \quad 10^{-4}, \quad 0.75$
Pool-1	54 x 24 x 64	27 x 12 x 64	2 x 2 x 64, 2
Conv-2	27 x 12 x 64	23 x 8 x 64	5 x 5 x 64
LRN-2	23 x 8 x 64	23 x 8 x 64	$n \quad 5 \quad 10^{-4}, \quad 0.75$
Pool-2	23 x 8 x 64	12 x 4 x 64	2 x 2 x 64, 2

Finally, the output of each body-part network is a multi-dimensional feature, ^{bp}F . This can be understood as a matrix whose elements are vectors with a length value of 64, as a result of the numbers of filters used in the convolution layers computation. The matrix dimensions are 8×8 for hF , 7×4 for ^{ula}F , ^{lla}F , ^{ura}F , and ^{lra}F , and 12×4 for ^{ull}F , ^{lll}F , ^{url}F , and ^{lrl}F .

c) Person descriptor

Measuring the appearance similarity in Person Re-Identification is a challenging task which not only requires the selection of discriminative visual descriptors but also their optimal combination.

Once each part feature, $^{bp}F_W$, has been computed, the optimal weighting is learnt by means of an inner product layer. This is a Fully Connected (FC) layer, that weighs and combines all the part features to create the elements of a general person descriptor, $F_W I$, whose size, N ($N=100$), has been experimentally fixed.

However, the inputs of the inner product must be the elements of a single matrix, so a first stage composed of concatenation layers (Concat) is needed to form it from the parts features matrices, resulting in a 46×8 matrix as Table 4.11 exposes. This concatenation stage requires certain

coherence among the dimensions of the body parts matrices to make possible the composition of a single matrix. For that reason, the body parts images are resized in the early stage of body parts extraction to get inputs and outputs with proper dimensions in all the layers of the architecture.

Table 4.11 Weighting network structure. Dimensions are described in $\#rows \times \#cols \times \#filters$.

Layer	Input	Input size	Output	Output size
Concat-left	$ula F$	$7 \times 4 \times 64$	Left-limbs	$38 \times 4 \times 64$
	$lla F$	$7 \times 4 \times 64$		
	$ull F$	$12 \times 4 \times 64$		
	$lll F$	$12 \times 4 \times 64$		
Concat-right	$ura F$	$7 \times 4 \times 64$	Right-limbs	$38 \times 4 \times 64$
	$lra F$	$7 \times 4 \times 64$		
	$url F$	$12 \times 4 \times 64$		
	$lrl F$	$12 \times 4 \times 64$		
Concat-body	Left-limbs	$38 \times 4 \times 64$	Body-matrix	$38 \times 8 \times 64$
	Right-limbs	$38 \times 4 \times 64$		
Concat-head	$^h F$	$8 \times 8 \times 64$	Person-matrix	$46 \times 8 \times 64$
	Body	$38 \times 8 \times 64$		
FC	Person-matrix	$46 \times 8 \times 64$	F	$1 \times 1 \times 100$

d) Features learning

A Siamese model has been used to train the feature embedding. Hence, this architecture presents two identical feature computation branches, which are connected by a distance computation. Each neural branch is composed of a set of nine body-part-dedicated CNNs and their proper weighting to learn the optimal person representation. The extraction of the body parts images, ^{bp}I , is integrated into the learning as a layer, which is, in fact, a nestled CNN itself. Therefore, the whole network can be considered as a DCNN, resulting from summing a large variety of neural layers, compounding each one the stages, which have been described above.

4.8.3 Three jointly learnt part-features

A third Re-Id model based on the combination of two previous architectures has been finally designed to obtain the benefits of both, and its architecture is shown by Fig. 4.18. Three partitions have been performed and the features describing each one are jointly learnt and combine to get a unique embedding to describe each person. In that way, the results are not limited by the performance of the parts extraction stage, as in the previous model (Section 4.8.2). Moreover, the

features are jointly learnt on a unique training process, instead of requiring three different processes, like the model presented in Section 4.8.1.

Fig. 4.18 Re-Identification Method Architecture based on three jointly learnt parts.

The input images division has been performed like it is described in Section 4.8.1, and the connection function and DoAS computation has been calculated as Section 4.8.2 describes.

In contrast to the previous models, where simple networks were used to model each part, this method employs a DCNN. This network, the weighting stage and its learning are described in the following subsections. Moreover, the complete learning architecture is presented in Appendix B.

a) Convolutional Neural Network Architecture

For each body part image, ^{bp}I , a DCNN, is used to learn the corresponding part feature, $^{bp}F_w$. Concretely a new version of VGG networks [303], with only 5 layers, hereinafter called VGG₅ has been re-designed. The main difference between the three neural branches is the dimensions of the corresponding part image input. Tables 4.12, 4.13, and 4.14 list the specifications of the layers of the head, body and legs neural networks, respectively.

Table 4.12 VGG₅ head DCNN architecture. The input and output sizes are described in #rows x #cols x #filters; the kernel, in #rows x #cols x #filters, stride, and #outputs for the FC layer.

Layer		Input size	Output size	Kernel
Conv-1	1	28 x 64 x 3	28 x 64 x 64	3 x 3 x 3
Pool-1		28 x 64 x 64	14 x 32 x 64	2 x 2 x 64 2
Conv-2	1	14 x 32 x 64	14 x 32 x 128	3 x 3 x 64
Pool-2		14 x 32 x 128	7 x 16 x 128	2 x 2 x 128, 2
Conv-3	1	7 x 16 x 128	7 x 16 x 256	3 x 3 x 128
Conv-3	2	7 x 16 x 256	7 x 16 x 256	3 x 3 x 256
Pool-3		7 x 16 x 256	4 x 8 x 256	2 x 2 x 256 2
FC-4		4 x 8 x 256	1 x 1 x 512	512

Table 4.13 VGG5 body DCNN architecture. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, and $\#out\ puts$ for the FC layer.

Layer		Input size	Output size	Kernel
Conv-1	1	32 x 64 x 3	32 x 64 x 64	3 x 3 x 3
Pool-1		32 x 64 x 64	16 x 32 x 64	2 x 2 x 64 2
Conv-2	1	16 x 32 x 64	16 x 32 x 128	3 x 3 x 64
Pool-2		16 x 32 x 128	8 x 16 x 128	2 x 2 x 128, 2
Conv-3	1	8 x 16 x 128	8 x 16 x 256	3 x 3 x 128
Conv-3	2	8 x 16 x 256	8 x 16 x 256	3 x 3 x 256
Pool-3		8 x 16 x 256	4 x 8 x 256	2 x 2 x 256 2
FC-4		4 x 8 x 256	1 x 1 x 512	512

Table 4.14 VGG5 legs DCNN architecture. The input and output sizes are described in $\#rows \times \#cols \times \#filters$; the kernel, in $\#rows \times \#cols \times \#filters$, $stride$, and $\#out\ puts$ for the FC layer.

Layer		Input size	Output size	Kernel
Conv-1	1	68 x 64 x 3	68 x 64 x 64	3 x 3 x 3
Pool-1		68 x 64 x 64	34 x 32 x 64	2 x 2 x 64 2
Conv-2	1	34 x 32 x 64	34 x 32 x 128	3 x 3 x 64
Pool-2		34 x 32 x 128	17 x 16 x 128	2 x 2 x 128 2
Conv-3	1	17 x 16 x 128	17 x 16 x 256	3 x 3 x 128
Conv-3	2	17 x 16 x 256	17 x 16 x 256	3 x 3 x 256
Pool-3		17 x 16 x 256	9 x 8 x 256	2 x 2 x 256 2
FC-4		9 x 8 x 256	1 x 1 x 512	512

b) Person descriptor

Once each part feature, $^{bp}F_W$, has been computed, the optimal weighting is learnt using a concatenation stage, and an inner product layer, defined by Table 4.15. The result is a general person descriptor, $F_W I$.

Table 4.15 Weighting network structure. The sizes are described in $\#rows \times \#cols \times \#filters$.

Layer	Input	Input size	Output	Output size
Concat-left	hF	1 x 1 x 512	Person-array	1 x 1 x 1536
	bF	1 x 1 x 512		
	lF	1 x 1 x 512		
FC	Person-array	46 x 8 x 64	F	1 x 1 x 128

c) Features learning

This architecture presents two identical branches, which are connected by a distance function. Each branch is composed of a set of three body-part-dedicated DCNNs and their proper weighting to learn the optimal person representation. This feature embedding has been trained by its triplication according to a Triplet model. Therefore, a unified learning framework is implemented, composed by DCNNs to simultaneously and automatically learn the most salient features for each one of three body parts and their best weighting to form a person descriptor. This learning architecture is represented in Appendix B.

4.9 Mahalanobis Distance as the Distance Metric

Person Re-Identification requires a distance metric able to compare two images and decide whether they belong, or not, to the same person.

The automation of this task to be applied in Intelligent Surveillance, involves a great challenge, due to the presence of people with a similar appearance. For that reason, discriminative features and a metric to properly combine them are needed. However, the variations of illumination, perspective, background, resolution and scale between two images of the same person, which were captured from different views, make his or her appearance vary, hampering the Re-Identification. This thesis proposes coding the view-to-view transformations in a Mahalanobis matrix, whose estimation is integrated into the discriminative features learning. In that way, the learnt features can render the dissimilarity mainly due to appearance changes instead of the view changes.

Subsequently, the connection function is formulated as the squared Mahalanobis distance, $d_M^2(F_W I^a - F_W I^b)$, between the features corresponding to the pair of images to compare, as Eq. 4.72 defines, where M is the Mahalanobis matrix. The obtained value is taken as the distance metric. M is defined as the inverse matrix of the covariance matrix for the variable formed by the difference of the feature arrays, $F_W I^a - F_W I^b$. Therefore, M allows considering the data structure for that new array, $F_W I^a - F_W I^b$, encoding the relationship of each one of its elements with each other.

$$d_M^2(F_W I^a - F_W I^b) = (F_W I^a - F_W I^b)^T M (F_W I^a - F_W I^b) \quad (4.72)$$

Different methods have been developed to estimate or even learn the Mahalanobis matrix.

4.9.1 Discriminative Mahalanobis Matrix Estimation

A discriminative method has been designed to estimate the Mahalanobis matrix in an adaptive process which takes advantage of the discriminative information given by the dataset labels to analyse

the data structure. This method analyses the probabilistic distribution of the variable formed by the difference between the computed features for a pair of images and discriminates between positive and negative pairs.

This estimation has been implemented as a new neural layer and it has been integrated into the learning process. Therefore, both, the feature neural embedding learning and the Mahalanobis matrix estimation are simultaneously performed in a unique learning process.

Two versions of this layer have been designed and implemented as novel Caffe-python layers¹⁰. The Siamese version takes as inputs a batch of pairs of features and their labels, and the Triplet version, a batch of triplets of features. Both versions allow to save the computed Mahalanobis matrix in a text file, every certain interval of iterations. Fig. 4.19 and Fig. 4.20 show the integration of the Mahalanobis matrix estimation layer in the Siamese and Triplet model, respectively. The distance metric in the Siamese model, dm , is computed according to Eq.4.73 and the positive and negative distances metrics dm^+ , and dm^- , in the triplet model are computed according to Eqs. 4.74 and 4.75.

$$dm = d_M^2(F_W(I^a), F_W(I^b)) \quad (4.73)$$

$$dm^+ = d_M^2(F_W(I^a), F_W(I^p)) \quad (4.74)$$

$$dm^- = d_M^2(F_W(I^a), F_W(I^n)) \quad (4.75)$$

Fig. 4.19 Siamese model to simultaneously train a DCNN and estimate the Mahalanobis Matrix.

¹⁰Data structure analysis layers are publicly available as two Caffe-python modules under: <http://github.com/magomez/MahalanobisMatrixLearning>

Fig. 4.20 Triplet model to simultaneously train a DCNN and estimate the Mahalanobis Matrix.

The designed estimation method performs the analysis of the data structure in an iterative process integrated into the process for learning the analysed features. For that reason, at every iteration, t , the analysed data is not only a pair $F_i^a F_i^b$ or triplet $F_i^a F_i^p F_i^n$ of feature arrays, but a batch of them, since a mini-batch learning algorithm is executed (Sections 4.2.3 and 4.4.2).

The data structure is represented by the probabilistic distribution of a new variable, formed by the difference between the features of the pairs of images. Since the proposed method is discriminative, this distribution is independently determined for two feature subspaces: those rendered by the positive and negative pairs of images. For that reason, at every iteration, two different sets are generated, P^+ and P^- , from the positive and negative pairs that the current batch contains.

When a Siamese model is employed, the sets P^+ and P^- , are defined by Eq. 4.76 and 4.77, respectively, and when a Triplet model is used, they are defined by Eq. 4.78 and 4.79. In all these equations, B refers to the batch size.

$$P^+ = \{F(I_i^a) - F(I_i^b) \mid y(I_i^a) = y(I_i^b) = 1\} \quad i = 1 \dots B \quad (4.76)$$

$$P^- = \{F(I_i^a) - F(I_i^b) \mid y(I_i^a) \neq y(I_i^b)\} \quad i = 1 \dots B \quad (4.77)$$

$$P^+ = \{F(I_i^a) - F(I_i^p) \mid i = 1 \dots B\} \quad (4.78)$$

$$P^- = \{F(I_i^a) - F(I_i^n) \mid i = 1 \dots B\} \quad (4.79)$$

The probabilistic distribution of each feature subspace is rendered by its corresponding covariance matrix, Σ_t and Σ_t^d . However, if the covariance matrices are estimated from the sets P and P^d , only the information given by the data of one batch (one learning iteration) would be considered. This might cause strong oscillations of the matrices values thorough the learning process.

With the aim of obtaining a more representative distribution of the similarity and dissimilarity difference feature spaces, the contribution of the data from previous iterations has been considered to some extent in the computation of Σ_t and Σ_t^d , avoiding the loss of their contributions from a statistical point of view. For that, two different methods, explained below, have been formulated to compute Σ_t and Σ_t^d : one is based on FIFO (First In, First Out) queues and the other one, on the Exponentially Weighted Moving Average (EWMA) algorithm.

Both methods provide similar results (Section 6.2.4.k), but the second one requires less computational memory space since it does not use memory queues to save data from previous iterations.

At every iteration, t , once both covariance matrices have been calculated, the Mahalanobis Matrix, M , is estimated using the formulation presented in [181] and shown by Eq. 4.80, which computes M as the difference between the inverse similarity covariance matrix and the inverse dissimilarity covariance matrix.

$$M = \Sigma_t^{-1} - \Sigma_t^{d-1} \quad (4.80)$$

The computed features are different in every learning iteration, not only due to the different inputs but also to the different computation of the descriptors themselves, since the neural weights are being learned. For that reason, the estimation of the Mahalanobis Matrix, M , must be updated in every iteration, considering the new information given by the new features.

a) Covariance Matrices computation based on FIFO queues.

At every iteration, the elements of the sets P and P^d are respectively added to the queues Q and Q^d , whose size is K . The size, K , of both queues is a layer parameter that takes a value large enough ($K = 1000$) to comprise the contribution of several batches of samples ($B = 128$). Therefore, these queues are $K \times N$ matrices, where N is the dimension of the feature arrays.

When the queues are full, the firstly added elements are deleted to continue adding new ones. Therefore, the type of these queues is First In, First Out (FIFO). In that way, the effects of the most recent training samples are saved and considered in the Mahalanobis Matrix computation, at every learning iteration, t .

Q and Q^d represent subsets of the difference feature space for the situation of similarity (positive pairs) and dissimilarity (negative pairs), so they are updated at every learning iteration, t , and used to compute the similarity covariance matrix, Σ_t , and the dissimilarity covariance matrix, Σ_t^d , as it is described by Eq. 4.81 and Eq. 4.82 respectively.

$_{tj}$, is the expected value for the element j of the difference vector for the similarity subspace, and it is computed as its mean value from all the elements of the similarity queue, Q , using Eq. 4.83. In the same way, the expected value, $_{tj}$, is defined by Eq. 4.84.

$$_{trc} = \frac{\sum_{i=1}^K Q_{rir} \quad _{tr} \quad Q_{tic} \quad _{tc}}{K} \quad (4.81)$$

$$_{trc} = \frac{\sum_{i=1}^K Q_{rir} \quad _{tr} \quad Q_{tic} \quad _{tc}}{K} \quad (4.82)$$

$$_{tj} = \frac{\sum_{i=1}^K Q_{tij}}{K} \quad (4.83)$$

$$_{tj} = \frac{\sum_{i=1}^K Q_{tij}}{K} \quad (4.84)$$

b) Covariance matrices computation based on EWMA method

Two covariance matrices, $_{prc}$ and $_{prc}$, are directly computed from the sets P y P , using the Eq. 4.85 and 4.86, respectively. Therefore, these matrices only render the probabilistic distribution of the features learnt in the current iteration, t . The batch size, B , is fixed but the proportion of positive and negative samples can slightly vary from one iteration to another, so the size of P and P , respectively rendered by L and L also varies.

$_{tj}$ is the expected value for the element j of the difference vector $F I^a - F I^b$, for the similarity feature subspace, and analogously, $_{tj}$, for the dissimilarity feature subspace. These variables, $_{tj}$ and $_{tj}$ provide a general representation of the expected values for the whole subspaces. However, firstly, $_{pj}$ and $_{pj}$, must be calculated. These variables are the expected values calculated from only the elements of P and P , as Eq. 4.87 and Eq. 4.88 define.

Subsequently, $_{tj}$ and $_{tj}$, are obtained at every iteration, t , with the EWMA method, according to Eq. 4.89 and Eq. 4.90. This method computes the variables by considering their values in the previous iteration, $t-1$, and the learnt features in the current iteration, $_{pj}$ and $_{pj}$.

$$_{prc} = \frac{\sum_{i=1}^L P_{tir} \quad _{tr} \quad P_{tic} \quad _{tc}}{L} \quad (4.85)$$

$$_{prc} = \frac{\sum_{i=1}^L P_{tir} \quad _{tr} \quad P_{tic} \quad _{tc}}{L} \quad (4.86)$$

$$_{pj} = \frac{\sum_{i=1}^L P_{tij}}{L} \quad (4.87)$$

$$P_j = \frac{\sum_{i=1}^L P_{t ij}}{L} \quad (4.88)$$

$$t_j = t_{-1 j} + \alpha P_j \quad (4.89)$$

$$t_j = t_{-1 j} + \alpha P_j \quad (4.90)$$

Finally, to consider the contribution of the data from previous iterations, not only in the expected values but also in the covariance matrices, t_{rc} and t_{rc} , the EWMA method has been again applied to estimate these matrices using the Eq. 4.91 and 4.92. According to these equations, the covariance matrices is computed as the weighted average between its value in the previous iteration, $t - 1$, and the covariance matrices computed from the received features in the current iteration.

$$t_{rc} = t_{-1 rc} + \alpha P_{rc} \quad (4.91)$$

$$t_{rc} = t_{-1 rc} + \alpha P_{rc} \quad (4.92)$$

In both, the expected values and the covariance matrices, the parameter α is the weight given to the values obtained in the previous iteration ($t - 1$). These last were likewise calculated by multiplying α by the previously obtained values ($t - 2$). Hence, since α is a positive number lower than the unit, the weights given to the estimations of every iteration exponentially decrease with a factor α , for increasingly early iterations.

In order to determine the value of α , the Eq.4.93 has been used. This equation approximately estimates the average scope, α , i.e. the number of iterations whose treated data is considered by the average.

$$\alpha = \frac{1}{1} \quad (4.93)$$

4.9.2 Mahalanobis Matrix Learning

The previously described method to estimate the Mahalanobis matrix, compute the Mahalanobis distance as the distance metric in the forward propagation step of the network learning, but it does not consider the Mahalanobis distance computation in the backwards propagation stage.

With the objective of improving the features learning, a new Mahalanobis matrix learning algorithm has been developed. In order to back-propagate the effects of the Mahalanobis distance in the features learning, the derivative of the loss function with respect to the features arrays has been calculated taking the Mahalanobis distance as the distance metric in the loss formulation. In addition, in order to use the back-propagation method also to learn the Mahalanobis Matrix, its elements have been taken and updated as an additional set of parameters (weights) of the neural model.

Therefore, the proposed method jointly and simultaneously learns the weights that define the features and the elements of the Mahalanobis matrix. In that way, not only the feature embedding but also the metric distance is automatically learnt to properly weight and combine the elements of the features to highlight the most useful features, with the aim of obtaining the optimal discriminative descriptor. This method has been developed for the Triplet learning model.

The estimation method, previously described (Section 4.9.1) requires the analysis of the data structure through several learning iterations to observe the effects of the Mahalanobis matrix on the learnt features, and, consequently correct the values of the elements of the Mahalanobis matrix. On difference, the new Mahalanobis matrix learning method directly updates the elements of the matrix according to the objective to achieve, which is defined by the loss function.

To perform that, the implemented Triplet-based Mini-Batch Gradient Descent algorithm has been redesigned to learnt both, features and Mahalanobis matrix, at the same time. The main procedures of this optimisation algorithm are presented by Algorithm 4. Moreover, the Triplet Loss function has been reformulated, using the Mahalanobis distance as metric distance, and the needed equations to perform its back propagation have been developed.

The triplet cost function, f_C , has been reformulated as a function of the features, $F_W I^a$, $F_W I^p$ and $F_W I^n$, by means of implicitly computing the distance metrics, dm and dm with the Mahalanobis distance function (Eq. 4.72).

$$f_C = \max \left(F_W I^a - F_W I^p, F_W I^p - F_W I^n, F_W I^n - F_W I^a \right) \quad (4.94)$$

Therefore, the connection computation (distance metric) has been integrated on the triplet loss function computation. In that way, the loss function can be directly derived with respect to the features, $F_W I^a$, $F_W I^p$ and $F_W I^n$, according to Eq. 4.95, 4.96 and 4.97, respectively, where renders the Krockener product between two matrices. I_N is an Identity matrix of dimensions $N \times N$, where N is the number of elements of each feature array, $F_W I$.

$$\frac{f_C}{F_W I^a} = \begin{cases} I_N M F_W I^n - F_W I^p \\ F_W I^n - F_W I^p \end{cases} \quad \text{if } dm < dm \\ 0 \quad \text{otherwise} \quad (4.95)$$

$$\frac{f_C}{F_W I^p} = \begin{cases} I_N M F_W I^p - F_W I^a \\ F_W I^p - F_W I^a \end{cases} \quad \text{if } dm < dm \\ 0 \quad \text{otherwise} \quad (4.96)$$

$$\frac{f_C}{F_W I^n} = \begin{cases} \frac{I_N^T M F_W I^a - F_W I^n}{F_W I^n} & \text{if } dm = dm \\ 0 & \text{otherwise} \end{cases} \quad (4.97)$$

Algorithm 4 Triplet-based Mini-Batch Gradient Descent learning algorithm with Mahalanobis matrix learning

Require: Batches of triplets, $X^t = X_i^t$.

Ensure: The network parameters $W^T = W_j^T$

```

1:  $W^0 = W_j^0$ 
2:  $M = I_k$ 
3: while  $t < T$  do
4:    $t = t + 1$ 
5:    $\frac{f_L}{W} = 0$  and  $\frac{f_L}{M} = 0$ ;
6:   for all training triplet  $X_i$  of the batch set  $X^t$  do
7:     Calculate  $F_W I^a$ ,  $F_W I^p$  and  $F_W I^n$  by forward propagation;
8:     Calculate  $f_C$  by Eq. 4.94;
9:   end for
10:  Calculate  $f_L$  by Eq. 4.22;
11:  for all training triplet  $X_i$  of the batch set  $X^t$  do
12:    Calculate  $\frac{f_C}{F_W I^a}$ ,  $\frac{f_C}{F_W I^p}$  and  $\frac{f_C}{F_W I^n}$  by Eq. 4.95, 4.96 and 4.97;
13:    Calculate  $\frac{F_W I^a}{W_j}$ ,  $\frac{F_W I^p}{W_j}$  and  $\frac{F_W I^n}{W_j}$  by back propagation;
14:    Calculate the gradient  $\frac{f_C}{W}$  according to Eq. 4.25;
15:    Calculate the gradient  $\frac{f_C}{M}$  according to Eq. 4.99;
16:  end for
17:  Calculate the gradient  $\frac{f_L}{W}$  according to Eq. 4.24;
18:  Calculate the gradient  $\frac{f_L}{M}$  according to Eq. 4.98;
19:  Update parameters  $W_j^t = W_j^{t-1} - \frac{f_L}{W_j^{t-1}}$ 
20:  Update parameters  $M_j^t = M_j^{t-1} - \frac{f_L}{M_j^{t-1}}$ 
21: end while

```

The Mahalanobis matrix, M , has been treated as an additional set of parameters to learn. Therefore, the derivative of the loss function with respect to M has been computed by Eq. 4.98 and 4.99.

$$\frac{f_L}{M} = \frac{1}{B} \sum_{i=1}^B \frac{f_C X_i}{M} \quad (4.98)$$

$$\frac{\partial f_C}{\partial M} = \begin{cases} ((F_w(I^n) - F_w(I^p))^T \otimes I_K) \cdot \frac{\partial M}{\partial M} \cdot ((F_w(I^n) - F_w(I^p)) \otimes I_K) & \text{if } dm^- - dm^+ < \tau \\ 0 & \text{otherwise} \end{cases} \quad (4.99)$$

Once $\frac{\partial f_L}{\partial M}$ has been computed, the updating of the elements of the Mahalanobis Matrix can be performed, as it is explained in Algorithm 4.

This optimisation algorithm, Triplet-based Mini-Batch GD learning algorithm with Mahalanobis matrix learning, cannot be fed with any training set configuration, of those generated with the Triplets Permutation method (Section 4.5.1).

The Mahalanobis distance relates each element of the features difference vector array with each other through the Mahalanobis matrix elements. According to the triplet model, two types of vectors of features differences are employed, $F_w(I^a) - F_w(I^p)$ and $F_w(I^a) - F_w(I^n)$, describing the similarity and the dissimilarity subspaces. In order to use the Mahalanobis matrix as an embedding of the view-to-view transformations, the anchor image has to be always taken from the same camera view, and the positive and negative samples from the other one. Therefore, only the first training set configuration (set I in Section 4.5.1) can be employed.

A novel layer¹¹ has been implemented to compute the forward and the backwards propagation of the triplet loss function with Mahalanobis distance. The inputs of this layer are the features arrays, $F_W(I^a)$, $F_W(I^p)$ and $F_W(I^n)$, for a batch of triplets.

4.9.3 Integration of the Mahalanobis distance computation as the distance metric into the feature learning process

The Mahalanobis matrix, M , estimated or learnt with each one of the two presented methods, encodes the relationship of each one of the elements of the feature arrays with each other.

However, a reliable estimation for the Mahalanobis Matrix is not achieved until executing a certain number of learning iterations. For that reason, The connection function, $f_c(F_W(I^a), F_W(I^b))$, takes two different formulations along the learning process, as Eq. 4.100 defines, so the squared Euclidean distance is employed until the number of learning iterations, t , achieves a certain threshold, T_t , and then, the comparison is made by the squared Mahalanobis distance, d_M^2 , instead.

$$dm = f_c(F_W(I^a), F_W(I^b)) = \begin{cases} d_E^2(F_W(I^a), F_W(I^b)) & \text{if } t < T_t \\ d_M^2(F_W(I^a), F_W(I^b)) & \text{if } t \geq T_t \end{cases} \quad (4.100)$$

¹¹The computation of the triplet loss function with Mahalanobis distance learning has been coded in a new Caffe-python layer called TripletMahaLoss, which is publicly available under: <http://github.com/magomez/MahalanobisMatrixLearning>

Both, the estimation and the learning of the Mahalanobis Matrix depend on the person feature weighs, which are learnt at the same time. Because of that, the iteration number that was chosen as the threshold, T_t , to start to use the Mahalanobis distance is large enough to ensure at least the convergence in the learning of the features. Hence, the threshold, T_t , has been established after several experimental observations of the evolution of the loss value during the training process.

The Mahalanobis Matrix Estimation method (Section 4.9.1) computes the connection and the loss function in two independent layers. The connection function formulation has been coded in a layer¹², whose inputs are the features arrays, and it takes T_t as parameter. The layer outputs the measured distance metric.

4.10 Other Applications

This thesis aims the training of a Person Re-Identification model not only to solve that task, but also to develop several versatile learning techniques, algorithms, and tools. For that reason, the Re-Id learning framework, as well as, some of the developed models, layers and functions, presented in this chapter, have been applied and evaluated in other domains as Facial Recognition and Multi-Object Tracking.

4.10.1 Facial Recognition

Facial recognition has gained special attention due to its importance in surveillance systems and forensics analysis. This is a challenging task of computer vision and pattern recognition, due to factors that affect the features of an image, such as changes in illumination, background, facial expression and head pose.

Most automatic face recognition systems compare a given face image (reference image) with images saved in a database in memory, and for that, they use a model trained on a huge number of samples of every individual. In contrast, this thesis proposes the use of the Degree of Appearance Similarity (DoAS) to provide a Single-Shot Face Recognition to identify any unknown person from only two pictures of him or her. This method has powerful applications in the automatization of control accesses, where people are identified by the photograph in their identity's cards.

The presented Re-Id models have been applied to the face recognition domain, by training and testing it on the FEI face dataset¹³. The FEI face database contains a total of 2800 face images, 14 images for each one of 200 individuals, at the Artificial Intelligence Laboratory of FEI in São Bernardo do Campo, São Paulo, Brazil. The individuals are between 19 and 40 years old with a dis-

¹²The connection function module has been coded in a Caffe-python layer called ConnectionFunction, which is publicly available under <http://github.com/magomez/MahalanobisMatrixLearning>

¹³FEI face dataset is publicly available under: <http://fei.edu.br/~cet/facedatabase.html>

tinct appearance, hairstyle, and adorns. The images were captured against a white homogeneous background in an upright frontal position and present a wide range of profile rotation of up to roughly 180 degrees. The original size of each image is 640x480 pixels, and the scale varies 10% approximately. The number of male and female subjects are exactly the same and equal to 100.

The Triplet Permutation method (Section 4.5.1) has been employed to generate a vast training set from a limited number of identity images. 150 identities have been used to create training triplets, 20 for the validation set, and 30 for the test set. A triplet model where each branch is formed by a VGG16 network (Section 4.1) has been trained on the generated training set, producing a model with high performance, as it is demonstrated in Section 6.4.1.

4.10.2 Multi-Object Tracking

This thesis proposes the learning of the Degree of Appearance Similarity (DoAS) for comparing people images, and the conducted experiments present this metric as a potential tool not only in the context of Person Re-Identification but also in Multi-Object Tracking applications.

In people tracking, an identity association process based on visual appearance can be provided by the DoAS measurement. This measurement is the result of comparing two images with modelled deep features, and it can be used as the score of matching a certain detection with previous captures of a certain tracked identity.

Therefore, the presented networks architectures, layers, and learning techniques and algorithms can be employed to train specific models for the MOT task, which is explained in the following Chapter.

In addition, with the aim of extending the tracking to multiple and non-overlapping camera views, the obtained Re-Id models can be used. Therefore, Multi-Target Multi-Camera Tracking can be performed by combining a frame-by-frame association model with a Re-Id module.

Chapter 5

Multi-Object Tracking

Multi-Object Tracking (MOT) problem involves finding the location of multiple objects from their visual measurements and conserving their identities in a video sequence.

This thesis follows the tracking-by-detection paradigm (Section 2.1.1) to address the MOT task. Hence, once a set of reliable detections is collected, the objective of the MOT module is mainly reduced to a data association process. Therefore, the inputs of the proposed tracking algorithm are two sets: one of them is a list of identities to track, called agents, and the other one is a set of detections, i.e. individuals' locations in every new frame, given by a people detector. To sum up, the tracking method aims the matching of every detection with its identity.

To achieve that association objective, this thesis presents a novel approach based on measuring the Degree of Appearance Similarity (DoAS) between two person images, so the agents are visually identified. Unlike systems using the learning of an appearance model for every tracked object, the proposed tracking algorithm is based on a unique model, which is capable of identifying the similarity between the detections belonging to the same person along with different frames.

This method allows online tracking of any target without requiring previous knowledge of it. On the contrary to batch tracking approaches, the proposed association method performs a frame-to-frame assignment where temporary consistency is provided by modelling the agents' appearance with a Long Short-Term Memory (LSTM) network. In that way, the propagation of punctual association mistakes is avoided, without requiring extending the association process through multiple future frames.

The tracking of an individual in a sequence of images from one camera view requires a DoAS model with a series of capabilities and restrictions, which are different from those imposed by the Re-Id challenge. However, most of the learning techniques, neural architectures, and layers presented in Chapter 4 have been employed to learn new DoAS models with tracking purposes.

This chapter presents not only the learning of an appearance model but a whole Multi-Object Tracking system, whose architecture is described in Section 5.1. The multi-agent management

method designed to govern the tracking algorithm is presented in Section 5.2. Since a tracking-by-detection approach is followed, a first-person detection stage is required, and it is described in Section 5.3, and the estimation of the agents' states is presented in Section 5.4.

A novel Cascade Data Association method and Global Hypothesis Generator have been formulated to reduce the number of identities switches in the data association process, which is the core of the tracking system. These methods are presented in Section 5.5. A multimodal metric, combining the individuals' appearance and position, has been used to score the matching between the detections along the sequence. Section 5.6 describes the design of the DoAS model.

Moreover, Section 5.7 explains two designed techniques to reduce the number of false positive and false negatives, which are based on pose attributes. The integration of a Re-Id module into the tracking algorithm to perform Multi-Target Multi-Camera Tracking (MTMCT) is proposed in Section 5.8. Finally, Section 5.9 presents the application of the developed method to different computer vision problems, like rescue and pedestrian tracking from vehicles.¹

5.1 Multi-Object Tracking Algorithm Architecture

As it was mentioned above a complete MOT algorithm has been developed. This section gives an overall vision of its architecture by describing the connections between its main modules. Fig.5.1 provides a simplified scheme of the stages performed by the proposed MOT algorithm in a frame iteration, f , where the identity of every person is represented by the colour of its silhouette.

Since a tracking-by-detection approach has been adopted, a first person detection stage is performed over every new frame, f . A certain people detector is executed to provide the boxes bounding the human figures in the image.

Once people detections have been obtained, the tracking of their identities can be performed. Therefore, in every iteration, the inputs of the tracking algorithm are two sets, the list of agents or identities to track, and the set of detections, found by the people detector in the current frame.

Subsequently, a series of filters are applied over the set of detections to eliminate the false positive detections, which are not corresponding to human representations, or even some redundant detections, which are caused by several bounding boxes grouped over the same individual.

The remaining detections are considered as the set of measurements taken on the current frame f . One measurement is the representation of one person found in the current frame, which is composed of a set of position attributes and appearance features.

The measurements obtained in a frame are used to update the state of the tracked identities, a.k.a. agents. Before such updating, predictions are estimated about the state of the agents in the current frame, and then a data association process is performed.

¹This Chapter includes contents from items 3, 8, 7 and 10 of "Published and Submitted Content" list.

The inputs of the data association process are two sets, measurements and agents' predictions, which are composed of features and attributes to render the current detections and the predicted agents' states. The association process assigns the corresponding identity to every detection, i.e. every agent is associated with its representation in the current frame.

After this association, the state of every agent can be updated with its corresponding measurement. The updated agents are then used to perform the tracking in the next frame iteration.

Eventually, the outputs provided by the tracking algorithm are the locations of every track identity at every frame. The identities assignment is rendered in Fig. 5.1 by the colour of the bounding boxes, so that in the detection stage no colour is given to the boxes, and after a proper tracking, every box takes the colour rendering the identity of the bounded person.

Fig. 5.1 Multi-Object Tracking Algorithm Architecture.

5.2 Multi-Agent Management

In order to make the tracking algorithm able to handle multiple objects, a multi-agent management strategy based on the handling of the agents' states has been designed. The term agent refers to every tracked identity.

A record of all the agents of a sequence is kept during the tracking performance. At every frame, f , the agents' record contains the state of the tracked individuals at that moment. Such a state is composed of the values taken by a series of attributes associated with each agent.

Structures to represent every attribute have been designed. These representations serve to a multi-agent management strategy, which is able to generate newly appearing tracks, update the already existing identities, re-identify the temporal disappeared agents, and delete non-interesting agents from the agent's record.

5.2.1 Structures

A dedicated structure, called *agent* has been designed to render the state of every tracked identity at a certain frame. An agent i at a certain frame f is rendered by a_i^f .

An attributes-oriented representation has been adopted. Therefore, the *agent* structure encompasses a number of attributes containing key cues to track a person, such as his or her visual appearance and position, and even some features measured in previous frames providing short-term memory to the track.

The multi-agent management strategy is based on the use of one array called "Multiagent", which is a record of the state of all the tracked people. Therefore, each element of this array is an instance of the *agent* structure. The *agent* structure is composed of the following attributes:

- An identification number, ID .
- A *person* structure, which is updated by the corresponding detection after the data association process in every iteration. This structure is described below.
- An image used as a visual reference, R , rendering the agent's appearance in the last frame that it was matched. This is a region of that frame, delimited by its corresponding detection's bounding box.
- An array of features, called *memory*, M , which saves the appearance features, F , of the person represented by the agent, for the last T frames where it was matched ($matched\ a_i^k = 1$) (see Section 5.6.3). The content of the *memory* attribute of an agent, a_i , at the frame f , $M\ a_i^f$ is shown by the Eq.5.1, where the suffix t index each element of the memory array, and k refers to previous frames where the agent was matched. Instead of saving a memory

record of the last reference images of the agents, appearance feature arrays are computed and registered, so that the computational time is reduced.

$$M(a_i^f) = \left[M_i(a_i^f) \equiv F(a_i^k) \mid (k < f - t) \wedge \text{matched}(a_i^k) \wedge t \in [1, T] \right] \quad (5.1)$$

- A *tracker* structure to manage a Kalman filter associated with the agent. This structure contains two main variables: its state, x , defined by the location and velocity of the agent's head, and the measurement, z , updated with the head location of its corresponding detection (see Section 5.4).
- An attribute called *age*, which indicates the antiquity of the agent, that is the difference between the number of the current frame and the frame when the agent was created.
- A flag named *matched* that indicates if an agent has been matched or not in the association process.
- A counter of the consecutive frames in which the *matched* flag is down, that has been called *FWM* (Frames Without Matching).
- A flag called *track* that indicates whether an agent must be tracked or not. This flag is down when *FWM* achieves a certain threshold.
- A flag called *output* that indicates whether an agent's state must be given as output of the tracking algorithm or not. There are agents, whose tracking is performed in a hidden manner, without outputting the captured information about them. These agents usually are novel agents (with small *age* value), whose tracking is provisional until achieving a certain level of certainty and latent agents, which are waiting until being re-identified. Moreover, in the frames when an agent is missed ($\text{matched}(a_i^k) = 0$), this is not given as output.

In turn, the *person* structure is composed of location and appearance attributes of the last updated state of the query agent. The person structure is also used to save the information measured for every person detection at every new frame, a.k.a. measurement. A measurement j at a frame f is rendered by m_j^f . The *person* structure is formed by the following attributes:

- A position point, P , indicating the person head position on the last frame where the agent was matched. The position of a certain agent, a_i , is rendered by Eq.5.2. The tracking of the head location has demonstrated to be more reliable than that for other body parts. Even when agents are partially occluded, the head is one of the most visible parts due to the almost zenith setting of most of the monitoring points. In addition, the head movements mostly

follow the person trajectories, unlike limbs with unpredictable movements.

$$P_{a_i} = [p_x^{a_i} \ p_y^{a_i}] \quad (5.2)$$

- An bounding box, B , which is the rectangle enclosing the person representation on the last frame that he/she was matched. For a certain agent, a_i , this rectangle is defined by an initial point, i.e. pixel location of the upper left corner, and its height and width values, as Eq.5.3 defines.

$$B_{a_i} = [b_x^{a_i} \ b_y^{a_i} \ b_{width}^{a_i} \ b_{height}^{a_i}] \quad (5.3)$$

- A feature array, F , which saves the appearance feature of the rendered person. That is the output computed by the appearance neural model taking the person image as input, i.e. the region delimited by the bounding box. This attribute helps to save computational time since saving the person's feature, it is not needed its computation every time that the appearance of the agents and detections are compared.
- A skeleton structure, J , which is a vector of 15 points, so that, every point saves the location of one of the agent's joints in the last frame where it was matched (see Section 5.7.1).

The identification number, ID , of an agent is not editable. Once an identification number is given to an agent (when it is created), this value keeps constant and unalterable under any circumstance, since this is the identity signature of a tracked individual. The rest of attributes of the agent define its state at every tracking iteration and they are updated after the data association process.

5.2.2 Creation and Removal of an Agent

The designed Multi-Agent Management strategy presents two working modes: automatic and semi-automatic. The tracking of the agents is automatically done in both modes. The difference between them resides in the manner in which the tracks are started and finished, that is the way in which agents' instances are created or deleted.

- Automatic mode. Every detected person on a video is tracked until his/her disappearance.
- Semi-automatic mode. This working mode constitutes a “pick and track” software, which allows a user to decide the people whom the system must track. Therefore, the user is able to start and stop a person tracking, clicking over that person in the video sequence.

Several methods have been designed to create and remove agents from the agents' record, according to the occurrence of several conditions. The situations which can trigger the creation or the destruction of an agent, according to the active working mode are listed in Table 5.1.

Table 5.1 Tigger factors for the creation and destruction of an agent in each working mode.

Mode	Agent's Creation	Agent's Destruction
Automatic	A new person's detection	Agent disappearance
Semi-automatic	Click on a person detection	Click on an agent Agent disappearance

The automatic agents' management mode is represented by Fig.5.2

Fig. 5.2 Automatic agent's management mode.

In the automatic mode, every new detection must be added to the list of tracked agents. This is made by creating a new instance of the agent structure and initialising some of its attributes as Eq. 5.4 describes, where a_i is the new agent, and m_j , the detection from which it is created. The identification number given to a new agent is the integer number consecutive to the highest identification number already assigned to one of the existing agents, max_{id} . The agent's reference is the region of the current frame enclosed by the bounding box of the detection. The tracker attribute initialisation is described in Section 5.4, and the values of rest of attributes are obtained in further stages of the learning algorithm.

$$\begin{aligned}
& Id\ a_i : \max_{id} \ 1 \\
& P\ a_i : \ P\ m_j \\
& B\ a_i : \ B\ m_j \\
& R\ a_i : \ frame\ b_x^{m_j} : b_x^{m_j} \ b_{width}^{m_j} \ b_y^{m_j} : b_y^{m_j} \ b_{height}^{m_j} \\
& a_i : \ age\ a_i : \ 0 \\
& \quad \quad \quad matched\ a_i : \ true \\
& \quad \quad \quad FWM\ a_i : \ 0 \\
& \quad \quad \quad tracked\ a_i : \ true
\end{aligned} \tag{5.4}$$

When people appear for the first time on a surveillance sequence, there is no agent on the record yet, and every detected person is turned into new agents. However, in the further frames, association process must be firstly performed in order to decide if the obtained detections correspond to the tracked identities or they are new people appearing on the sequence. In the last case, new agents are created from the new people's detections.

On the other hand, an agent is considered as a disappeared agent, when the number of consecutive frames where the agent has not been matched achieves a certain threshold, T_r . Consequently, such an agent is removed from the agents' record, so it is no longer tracked.

In the semi-automatic mode, the user clicks over the person that must be tracked. If the detection of the selected person is available, a new agent structure is created and added to the agents' record. If the user clicks over one of the existing agents, this is removed from the agents' record. The same happens when an agent disappears in the monitored scene.

When an agent is removed from the record, it can no longer be tracked or re-identified. A different strategy has been designed in order to be able to re-identify agents who were disappeared for a term and reappear on the monitored scene. This strategy is based on the deactivation of the *track* flag to stop the tracking of the agent. However, this agent remains on the record as a latent agent waiting until its re-identification as Fig.5.2 shows. For that reason, the creation of new agents is performed, not only after the association process but also after the re-identification process to discard that the new detections correspond to the tracked and the latent identities. The track flag is deactivated when the number of consecutive frames where the agent has not been matched achieves a certain threshold, T_l $T_l \leq T_r$ (see Appendix A).

5.2.3 Updating Rule

The designed Multi-Agent Management strategy includes a protocol for updating the state of every agent after the association process. As it was mentioned above (Section 5.2.1) the state of an agent is formed by all its attributes, except the identification number.

There are two special attributes. First, the age of the agent, whose value is incremented in one unit at every frame, f , independently of the state of the agent. Secondly, the *matched* flag, from whose value the updating of the rest of attributes depends on. This flag is activated if the data association process has assigned a detection to the query agent and deactivated otherwise. The rest of the attributes can be divided into two types:

- **Attributes describing the agent**, which provides information about its motion and appearance. These attributes are updated from the detection, m_j , assigned to the query agent, a_i , by the association process. These are the *person* structure, the visual reference, R , the feature, F , and the memory, M , whose updating rules are defined by Eq. 5.5, 5.6, 5.7 and 5.8, respectively. If the agent is matched ($matched\ a_i^f = 1$), its *person* attribute is updated with that of its associated detection. Otherwise, it takes its previous value ($f - 1$). The feature, F , attribute is analogously updated. The reference, R , is updated with the region of the frame that is bounded by the bounding box, B , given by the detection (Eq. 5.3). The first element ($t = 0$) of the memory attribute, M , is updated with the feature, F , and the rest of the elements are move one position forward in the memory array. T is the size of the memory array, and M_t is the element t of that array. The *tracker* structure is also updated by the associated detection. This is explained in detail in Section 5.4.

$$person\ a_i^f = \begin{cases} person\ m_j & if\ matched\ a_i^f \\ person\ a_i^{f-1} & if\ not\ matched\ a_i^f \end{cases} \quad (5.5)$$

$$R\ a_i^f = \begin{cases} frame\ b_x^{m_j} : b_x^{m_j} \ b_{width}^{m_j} : b_y^{m_j} \ b_{height}^{m_j} & if\ matched\ a_i^f \\ R\ a_i^{f-1} & if\ not\ matched\ a_i^f \end{cases} \quad (5.6)$$

$$F\ a_i^f = \begin{cases} F\ m_j & if\ matched\ a_i^f \\ F\ a_i^{f-1} & if\ not\ matched\ a_i^f \end{cases} \quad (5.7)$$

$$M_t\ a_i^f = \begin{cases} F\ a_i^f & if\ t = 0 \\ M_{t-1}\ a_i^{f-1} & if\ t = T-1 \\ M_t\ a_i^{f-1} & if\ not\ matched\ a_i^f \end{cases} \quad (5.8)$$

- **Attributes of control**, whose values govern the multi-agent management strategy. These attributes are the number of frames without matching, FWM , and the flags $track$ and $output$, and their updating rules are defined by Eq. 5.9, 5.10, 5.11. FWM is increased when the query agent, a_i , is not matched with any detection, and restarted with zero when it is matched. The flag for tracking, $track$, keeps up while FWM is under T_l . This is the threshold in the value of FWM from which the agent ceases to be tracked and becomes a latent agent. Finally, the tracking algorithm does not show an agent ($output = false$) if it has not been matched or it is a novel agent, or its tracking is stopped. T_p is the age threshold under which an agent is considered as newly created and its tracking is provisional (see Appendix A).

$$FWM\ a_i^f = \begin{cases} 0 & \text{if matched} \\ FWM\ a_i^f + 1 & \text{if not matched} \end{cases} \quad (5.9)$$

$$track\ a_i^f = \begin{cases} true & \text{if } FWM\ a_i^f < T_l \\ false & \text{otherwise} \end{cases} \quad (5.10)$$

$$output\ a_i^f = \begin{cases} false & \text{if } matched\ a_i^f = 0 \text{ or } age\ a_i^f > T_p \\ true & \text{otherwise} \end{cases} \quad (5.11)$$

5.3 Detection

The detection stage is in charge of returning the boxes bounding the people in the processed frame.

Two different MOT datasets have been used in this thesis, CAVIAR and MOT17 (see Section 3.3.2). MOT17 dataset provides the detections on all its sequences. However, this is not the case for CAVIAR dataset. For that reason, a detection stage has had to be implemented in order to conduct some initial experiments over CAVIAR sequences. Different implementations of well-known people detector have been tested:

- The implementation of HOG-SVM (Histogram of Oriented Gradients and Support Vector Machine) people detector [45] provided by the OpenCV2 library.
- A detector based on the upper-body model trained by [144] for the Haar-Cascade classifier from the OpenCV library.
- The fusion of the previous ones, by the union of the detections sets given by both detectors.

These classical detectors provide a simple and initial tracking-by-detection configuration where to try the developed association methods, and proving the effectiveness of some proposed solutions to deal with the errors coming from the detection stage.

On the other hand, MOT17 dataset provides three different sets of detections for each one of its sequences. Each set was obtained with each one of the following people detector algorithms:

- DPM (Deformable Part-based Method) detector [102].
- Faster R-CNN (Region Convolutional Neural Network) detector [274].
- SDP (Scale Dependent Pooling) detector [361].

The found detections constitute the set of measurements provided to the tracking algorithm. The measurements' information is managed with *person* structures. Therefore, after the detection stage, the values for the bounding box, B , of every measurement are obtained.

Moreover, the person's head position, P , can be obtained by two methods: the most computationally cheap method is based on the estimation of the head location inside the bounding box according to human proportions. The second one consists of extracting the head location by the Convolutional Pose Machine presented in [339]. This CPM is also used to obtain the *skeleton* structure of a person when it is required (see Section 5.7.2).

Finally, the appearance feature of a certain detection, F , is computed by a pre-trained neural model, explained in Section 5.6.2.

5.4 State Estimation

The state estimation stage predicts the position of the tracked agents in the current frame, before performing the data association process with the currently taken measurements.

The predicted state of an agent, after the state estimation, only differs from its previous state on the value of the head location attribute. Only head prediction is performed because, even when agents are partially occluded, the head is one of the most visible parts due to the almost zenith setting of most of the monitoring points. The value for the rest of the attributes is not predicted. Therefore, only motion cues are involved in the state estimation stage.

The agent's appearance is not estimated before the association. For that reason, an effective comparative metric of the DoAS has been designed to face not only the appearance differences between consecutive frames but also after long and short-term occlusions and disappearances.

To perform the position prediction the standard implementation of OpenCV [164, 163] of the Linearized Kalman Filter algorithm has been employed. A decentralised configuration is adopted, so the motion of every agent is independently modelled and predicted by a Kalman filter [28] which considers the position, velocity and acceleration of the person's head location.

Therefore, a Kalman filter has been associated with every agent, in order to track its trajectory, and its variables are collected in a structure called *tracker*, which is one of the attributes of the *agent* structure (see Section 5.2.1). The following variables form the *tracker* structure:

- Measurement, z_f . This is the head location of the true observation of the agent at frame f , so this takes the head location of the detection matched to the query agent by the association process at frame f . When the agent is missed, i.e. no detection has been associated with it, z_f cannot be updated with any detection's head location. In that case, two possible procedures can be followed, according to Eq.5.12. If the number of consecutive frames where the agent was missed does not overpass a certain threshold, i.e. the agent has been recently lost, z_f is updated with its own predicted state, $x_{f|f-1}$. However, if the agent was missed many frames ago, z_f is not updated to avoid the tracking of a false or even non-existent trajectory.

$$z_f = \begin{cases} m_J & \text{if matched } a_i \\ x_{f|f-1} & \text{if } \text{matched } a_i \text{ FWM } a_i \leq T_m \\ z_{f-1} & \text{if } \text{matched } a_i \text{ FWM } a_i > T_m \end{cases} \quad (5.12)$$

- A priori estimated state, $x_{f|f-1}$, which involves the agent head location, velocity and acceleration at frame f . This is predicted by Eq.5.13 before matching the agent with its true detection (measurement) at frame f . $x_{f|f-1}$ is not required when the agent was missed many frames ago since no movement is tracked in such a situation, as it was explained above.

$$x_{f|f-1} = A_f x_{f-1|f-1} \quad (5.13)$$

- A priori estimated error covariance matrix, $P_{f|f-1}$. This renders the uncertainty of the previous prediction, and it is predicted, in turn, by Eq.5.14.

$$P_{f|f-1} = A_f P_{f-1|f-1} A_f^T + Q_f \quad (5.14)$$

- Kalman gain, K_f . This is computed by Eq.5.15, and it is used to correct the agent state, and its associated error covariance matrix, at frame f .

$$K_f = P_{f|f-1} H_f^T (R_f + H_f P_{f|f-1} H_f^T)^{-1} \quad (5.15)$$

- A posteriori estimated state, $x_{f|f}$, of the agent head location at frame f . This is corrected by Eq.5.16 in the updating stage of the agents, at the end of the tracking iteration f .

$$x_{f|f} = x_{f|f-1} + K_f (z_f - H_f x_{f|f-1}) \quad (5.16)$$

- A posteriori estimated error covariance matrix, $x_{f,f}$. This is corrected by Eq.5.17 in the updating stage of the agents, at the end of the tracking iteration f .

$$P_{f,f} = I - K_f H_f P_{f,f-1} \quad (5.17)$$

- A set of four matrices: State transition model, A_f , Covariance of the process noise, Q_f , Measurement model, H_f , and Covariance of the measurement model, R_f . These matrices are initialised when the query agent is created, and internally update by the Kalman Filter algorithm at every frame iteration, f . The elements of A_f and Q_f are governed by the physics laws that relate the magnitudes collected by the agent state.

5.5 Data Association

An online MOT method has been developed in this thesis, whose core is a frame-by-frame data association process to perform the assignment of every tracked identity with its corresponding detection. Hence, the input of the data association module (see Fig. 5.1) are two sets:

- Agents $A = a_i$. This set is the record of agents, which saves the state at the current iteration of every tracked identity. This set comes from the previous tracking iteration. Before the data association stage, the position of the agents is predicted in the previous state estimation step. After the association process, the content saved on the agents is updated. Moreover, some agents can be added to or deleted from the record.
- Measurements $M = m_j$. This is a set of people measurements taken in the current tracking iteration. Every measurement renders a person detection found in the current frame, which has been modelled to embed its appearance and location information. The measurements set is completely new at every iteration, since no measurements from previous frames are contained in this set.

In general terms, the data association process is composed of these three stages:

- I. Gating. This is a method to determine possible matching measurements around each predicted agent's location and prune matches that are geometrically unlikely from the start.
- II. Cost computation. The cost of each matching is computed according to several types of contrastive cues, like distance to the matched measurement, appearance differences or a combination of them. To measure the distances between agents and measurements positions, Euclidean distance is used. However, to compare their visual appearances, that is to measure the DoAS, more complex metrics has been learnt by training deep neural models.

- III. **Optimisation.** Once the improbable matches have been pruned, and the cost of the possible matches have been computed, the minimum cost assignment between agents and measurements is found by an optimisation algorithm.

Three different data association methods have been implemented to solve the identities assignment. In the prior experiments, an individual data association process and a global one based on the Hungarian method were proved and compared. Then, a novel Cascade Data Association method has been designed. This method is based on a succession of data association processes which uses a novel Global Hypotheses Generator.

These three association methods present different procedures to perform the stages of gating, cost computation and optimisation. A contrastive vision of their main characteristics is given below, and deeper details of their formulation are described in the following sections.

- **Individual data association.** The search for the minimum cost assignment is independently performed for every agent. An individual gating is also conducted by making a radial search of the nearest detections around the predicted position of every agent. Then, for every agent, the cost of matching it with every candidate measurement is computed and that presenting the minimum value is assigned. The matching cost is calculated by a hand-crafted DoAS metric (Section 5.6.1).
- **Global data association.** Global optimisation is performed by the Hungarian method [246], which finds the global assignment with the minimum cost in a matrix containing the costs of matching every agent to every measurement. The cost is computed by a combination of position distances and a hand-crafted DoAS metric (Section 5.6.1). The cost formulation implicitly performs gating, by given a high-cost value to the improbable matches.
- **Cascade Data Association with Global Hypotheses Generator.** This novel method combines the benefits of the two previous ones since a global optimisation method is used, but it is independently performed for each one of a series of groups of agents. In that way, a dedicated cost formulation has been designed for different types of agents; and for each group, a global minimum cost assignment is searched. This reduces the identities switches since every possible matching (at each level) is considered at once. The optimisation method is based on the generation of all the probable global assignments hypotheses and the selection of that presenting the minimum cost. In contrast to the earliest versions of the Hungarian method, the problem of having not-matching measurements and agents is solved, and the starting and ending of the tracks are also contemplated by the Hypotheses Generator. The matching cost is calculated by combining the distances between agents and measurements positions, their sizes differences, and two DoAS metrics, computed by pre-trained DCNNs. Gating is performed by supplying a mask matrix to the Hypotheses Generator.

5.5.1 Individual Data Association

The design of this association algorithm has a decentralised configuration, where the identification of each one of the tracked agents among the taken measurements is independently performed.

Gating is performed by selecting a set of candidate measurements for every agent. For that, a radial search is performed around the predicted head position of the query agent, which was estimated by its associated Kalman filter, as Fig. 5.3 renders in yellow. All the measurements whose head location are inside a circular region of a certain gating radius, R_g , around the agent's position are selected as candidates. R_g defines the wideness of the search area, so it determines how near a measurement needs to be for being considered as a possible representation of the query agent.

Fig. 5.3 Selection of candidates for a tracked agent. The predicted head location is rendered by a yellow point, and the detections selected as candidates are bounded by red boxes.

Then, for each agent, his/her visual reference is coupled with the candidate measurements and that which presents the lowest value of the matching cost is assigned. The HCSS-DoAS (see Section 5.6.1) has been used to compute the matching cost, f_c , between an agent a_i , and a measurement m_j , according to Eq. 5.18. The matching cost is the complementary value of the DoAS since this metric renders the probability that two representations correspond to the same individual.

$$f_c(a_i, m_j) = 1 - \text{HCSS_DoAS}(a_i, m_j) \quad (5.18)$$

5.5.2 Global Data Association

A global association method considers all the possible matches at the same time, instead of independently searching the best one for each agent. In order to achieve that goal, a matrix, C , has been created to collect the costs of matching every agent, a_i , with every taken measurement, m_j . The problem of finding the global assignment with the minimum total matching cost has been solved by an optimisation algorithm based on the Hungarian Method [185].

Two contrastive functions have been used to measure the matching cost:

- The appearance cost of matching the representations of the agent i , and the measurement j , $f_a(a_i, m_j)$ is defined by Eq.5.19 as the distance between their appearance features, which is the complementary value of the HCSS-DoAS (Section 5.6.1), since this is the probability of that m_j , and a_i form a positive match.

$$f_a(a_i, m_j) = 1 - HCSS_DoAS(a_i, m_j) \quad (5.19)$$

- The distances between the position of the agent i , and the measurement j , $f_d(a_i, m_j)$ is defined by Eq.5.20, where d_E refers to the Euclidean distance.

$$f_d(a_i, m_j) = d_E(P(a_i), P(m_j)) = \sqrt{(p_x^{a_i} - p_x^{m_j})^2 + (p_y^{a_i} - p_y^{m_j})^2} \quad (5.20)$$

Using these functions, the cost matrix, C , combines information about the agents' localisation and their visual appearance. The cost matrix, C , can take two formulations, as Eq.5.21 defines.

$$c_{ij} = \begin{cases} P & \text{if } (f_d(a_i, m_j) > R_g) \\ f_d(a_i, m_j) \cdot f_a(a_i, m_j) & \text{if } (f_d(a_i, m_j) \leq R_g) \end{cases} \quad (5.21)$$

Radial gating is implicitly performed by the matrix cost computation, since those measurements whose heads locations are outside a radial perimeter, of radius R_g , around the expected head location of a query agent, are penalised with high-cost matching value, P . The expected head location of each agent is predicted by the Kalman filter algorithm from the data of the agent's *Tracker* attribute. The matching cost value for the detections that are located inside the perimeter is a combination of the previously describes comparative functions, f_a and f_d .

Once the matrix C is computed, the Hungarian Method found the best assignment, so that only one measurement is matched with each agent and vice-versa. The solution is given through a matrix, M_H , where the elements corresponding to a matching take value of 0.

Only those agents that have been correctly matched, that means its flag *matched* is up, must be updated with its corresponding detection. However, when the measurement corresponding to a certain agent is not available, any other incorrect detection could be assigned to it by the Hungarian method. To avoid the improperly updating of an agent a_i , its *matched* flag, is not activated unless the corresponding cost matching value was under a certain threshold T_c , as well as, the corresponding element, $m_{H,ij}$, of the resulting Hungarian matrix M_H values 0, as Eq. 5.22 defines.

$$matched^{a_i} = \begin{cases} true & \text{if } \exists j \mid (m_{H,ij} = 0) \wedge (c_{ij} < T_c) \\ false & \text{otherwise} \end{cases} \quad (5.22)$$

5.5.3 Cascade Data Association

The Cascade Data Association method is a hierarchical frame-to-frame assignment method, which divides the association process into different and consecutive levels.

The tracked agents are grouped according to different circumstances, such as the intersection among agents' trajectories, or temporal occlusions, disappearances and the birth of new tracks. These circumstances define different types of agents, which require different manners of performing their association. For that reason, a dedicated association process is used to assign the identities of each type of agents with the residual detections from the previous stage, as Fig.5.4 shows.

Fig. 5.4 Architecture of the Cascade Data Association algorithm.

Firstly, the points of concurrency of agents are searched. These points are used to divide both inputs, the set of agents and the set of taken measurements, in different groups. Once the agents have been grouped in four different sets according to their type, each set feeds a data association level. The levels are denoted as association A, B, C, and D, in descending order of the hierarchy. The input of every association level is not only a set of agents but also a set of taken measurements.

The first data association process receives those measurements not intersected by any of the concurrency points, and the rest of the measurements are not associated with any identity. After every association level, the measurements matched with the agents are used to update their state, and those not associated with any identity are used to feed the next association level. Next subsections describe each one of the stages (grey blocks in Fig. 5.4) of the Cascade Association method.

a) Search for concurrency points and classification of measurements

Both circumstances, partial occlusion and crossing of agent's trajectories, can be jointly detected by locating points of concurrency among agents, instead of modelling the intersections among the agents' trajectories or their interactions.

The set of concurrency points, CP , has been generated as Eq. 5.23 defines. This formulation considers that a person representation does not interfere with their neighbours' individuals if there exists a distance larger than half of the person width with respect to them. The head location, P , of those agents that are interfering other people representations are taken as concurrency points, and such agents are considered as intersected by a concurrency point.

$$CP = \left\{ cp_i \equiv P(a_j) \mid \sqrt{(p_x^{a_j} - p_x^{a_k})^2 + (p_y^{a_j} - p_y^{a_k})^2} < \frac{b_{width}^{a_j}}{2} \wedge j \neq k \right\} \quad (5.23)$$

The agents' concurrency results on non-well delimited, merged, split, overlapped and missed detections. It's not advisable to use these types of detections to update the agents' states since this could cause mismatches in further association processes. When two people are rendered inside the same bounding box, it can not be determined which of the rendered identities must be assigned. When the regions delimited by two or more detections' bounding boxes are intersecting each other, it can not be determined which detections are overlapping to which others. Given this uncertainty, every detection near to a concurrency point has not been taken as the input of the association process. Eventually, only those measurements presenting a distance larger than its width, b_{width} , with respect to every concurrency point has been used to perform the data association process.

b) Agents Classification

Four different sets of agents' states are obtained from the record of agents to track, following the scheme presented by Fig. 5.5.

Fig. 5.5 Agents classification.

Firstly, novel agents, those with a value for the *age* attribute lower than the T_n threshold, are established as set IV. From the rest of agents, those with more frames without matching (FWM) than the number established by the T_m threshold are considered as missed agents, and they form the Set III. The remaining agents are divided in matched and not matched ones, according to the value of its *matched* flag. Therefore, the agents which have not been matched to any measurement in the previous frame are considered as recently lost agents, since the previous fork ensures that the number of consecutive frames where they have been missed is less than T_m .

Subsequently, every agent of the matched group is classified as intersected or not intersected by a concurrency point. For that, the concurrency points are calculated as the location of those agents from the matched group that intersect some of the agents of a set formed not only by the rest of the matched agents but also by the recently lost agents, using Eq. 5.23. Therefore, the index j refers to every agent of the matched group and index k to every agent of the joint group formed by the matched and the recently lost agents. The intersected agents and the group of recently lost agents form the Set II.

Finally Set I is composed of the remaining agents, which were matched in the previous frame and are not involved in any intersection. It is worth mentioning that at the first frames containing people, when people are detected for the first time, all the agents are novel. Therefore, in such initial tracking iterations, the agents classified as novel agents are sent to set I instead of the set IV.

c) Data Association Level. Procedure.

The four data association processes which compose the whole Cascade Data Association method (see Fig.5.4), follow a similar procedure. Algorithm 5 defines the general procedure conducted at a certain association level, al , where al can take the notation A , B , C or D to refer the corresponding level, and $al - 1$ refers to the subsequent one in the hierarchy.

Algorithm 5 Data Association Algorithm

-
- Require:** Set of agents' states, $A_f^{al-1} = a_i^{f-1}$ and set of measurements, $M^{al} = m_j$.
- Ensure:** Updated agents' states, $A_f^{al} = a_i^f$, and residual measurements M^{al-1} .
- 1: Calculate the cost matrix, $C^{al} = c_{ij}$ and the binary mask matrix, $B^{al} = b_{ij}$ (see Section 5.5.3 and 5.5.3);
 - 2: Generate a set of global assignment hypotheses $H = h_k$, by the Hypotheses Generator method (see Section 5.5.4);
 - 3: Calculate hypotheses costs H_{cost}^{al} , as Section 5.5.4 describes;
 - 4: Select the minimum cost hypothesis, h^m , as the correct assignment;
 - 5: Perform the identities assignment defined by h^m ;
 - 6: Output the residual measurements, M^{al-1} .
-

Every association process, firstly, computes a cost matrix, C , and a binary mask matrix, B from their inputs. The number of rows of these matrices, for a certain level, is the number of received agents, and the number of columns is the number of measurements arriving at the query association level. The different groups of agents and measurements used by every association process to compute the matrices are not the only differences between them. The formulation employed to compute C and B also differs among the association levels, which is the fact that makes them dedicated association processes for every type of agent.

The Global Hypotheses Generator (presented in Section 5.5.4) generates a series of hypotheses from C and B . Then, the cost of each hypothesis is computed. Finally, the identities assignment is performed according to the hypothesis with the minimum cost, and the agents' state is updated with their matching measurements. An assignment between an agent and a measurement, rendered as $a_i : m_j$ henceforth, is performed by updating the person attribute of the agent with the values of the measurement. Those measurements that were not assigned to any of the agents are the residuals of the current association level and the inputs for the next one, as Eq. 5.24 defines.

When there are several detections rendering the same identity, i.e. slightly displaced boxes around the same person, the association method assigns one of the measurements to that identity, and the others are considered as new agents in the scene. To avoid the creation of redundant agents, a filter to check overlapping is applied. The condition to consider a measurement j as redundant is defined by Eq. 5.25, where m_k renders an already matched measurement, and T_o is the overlapping threshold. The redundant measurements are not assigned to any agent and neither provided as residuals, they are simply deleted.

$$M^{al-1} = m_j^{al} - j \text{ } m_j^f - a_i^f \text{ } matched \text{ } a_i^f \quad (5.24)$$

$$redundant(m_j) = \begin{cases} true & \text{if } \exists k, i, | m_j \subset a_i \wedge matched(a_i) \wedge \\ & \left(\frac{common_area(m_j, m_k)}{area(m_j)} > T_o \right) \wedge \left(\frac{common_area(m_j, m_k)}{area(m_k)} > T_o \right) \\ false & \text{otherwise} \end{cases} \quad (5.25)$$

d) Cost Formulation

A multi-modal formulation to measure the cost of matching a certain identity with a certain detection has been designed, based on motion and visual appearance cues. The classification power of DCNNs has been exploited to measure the DoAS between agents and measurements (Section 5.2.1), and the motion prediction has been implicitly added to the cost function, by the computation of the distance between agents and measurements.

Therefore, the computation of the matching cost relies on these four comparative functions:

- The appearance cost of matching the representations of the agent i , and the measurement j , $f_a(a_i, m_j)$ is defined by Eq.5.26, as the distance between their appearance features, which is the complementary value of the SS-DoAS (Section 5.6.2), since this is the probability of that m_j , and a_i form a positive match.

$$f_a(a_i, m_j) = d_E(F(a_i), F(m_j)) = 1 - SS_DoAS(a_i, m_j) \quad (5.26)$$

- The appearance cost resulting of comparing the memory attribute, M , of the agent i , and the feature attribute, F , of the measurement j , $f_m(a_i, m_j)$ is defined by Eq.5.27, as the complementary value of the MS-DoAS (Section 5.6.3), since this is the probability of that m_j , and a_i form a positive match.

$$f_m(a_i, m_j) = 1 - MS_DoAS(M(a_i), F(m_j)) \quad (5.27)$$

- The distances between the position of the agent i , and the measurement j , $f_d(a_i, m_j)$ is defined by Eq.5.28

$$f_d(a_i, m_j) = d_E(P(a_i), P(m_j)) = \sqrt{(p_x^{a_i} - p_x^{m_j})^2 + (p_y^{a_i} - p_y^{m_j})^2} \quad (5.28)$$

- The size difference between the bounding boxes of the agent i , and the measurement j , $f_s(a_i, m_j)$ is defined by Eq.5.29.

$$f_s(a_i, m_j) = \sqrt{(b_{width}^{a_i} - b_{width}^{m_j})^2 + (b_{height}^{a_i} - b_{height}^{m_j})^2} \quad (5.29)$$

The cost value computation can take different formulations according to certain ambiguities due to the presence of crowds, crossing agents, occlusions, and missed and redundant detections. The formulation of a dedicated cost matrix has been specially designed for each association level.

At data association level A , the cost matrix, C^A , is computed according to Eq.5.30, where c_{ij}^A refers to the element in row i and column j of this matrix. Moreover, this matrix can take two different formulations depending on the circumstance of comparing an ambiguous agent, $amb_1 \ a_i$, or an ambiguous measurement, $amb_2 \ m_j$. An agent is ambiguous if there is more than one probably corresponding measurement, that is near to the agent position, as it is defined by Eq. 5.31. Analogously, a measurement is ambiguous if it presents more than one probably corresponding agent, as Eq.5.32 defines.

At data association levels B , C and D , the corresponding cost matrices, C^B , C^C and C^D , are computed according to Eq. 5.33, 5.34 and 5.35, respectively, where c_{ij}^B , c_{ij}^C and c_{ij}^D refer to the element in row i and column j of each matrix.

In addition, it should be mentioned that when the MS-DoAS computation, $f_m \ a_i \ m_j$, is involved in the cost matrices estimations, their formulations must be differently defined according to the age of the compared agent. If its age is lower than the size of the memory structure $T = 15$, the learnt MS-DoAS cannot be applied, and SS-DoAS has to be used instead.

$$c_{ij}^A = \begin{cases} 100 \ f_m \ a_i \ m_j & \text{if } amb_1 \ a_i \text{ and } amb_2 \ m_j \\ 0.2 \ f_s \ a_i \ m_j & \text{if } f_d \ a_i \ m_j < 2 \ b_{width}^{a_i} \\ 0.3 \ f_d \ a_i \ m_j & \text{if } f_d \ a_i \ m_j \geq 2 \ b_{width}^{a_i} \text{ and } age \ a_i \geq T \\ 100 \ f_a \ a_i \ m_j & \text{if } amb_1 \ a_i \text{ and } amb_2 \ m_j \\ 0.2 \ f_s \ a_i \ m_j & \text{if } f_d \ a_i \ m_j < 2 \ b_{width}^{a_i} \\ 0.3 \ f_d \ a_i \ m_j & \text{if } f_d \ a_i \ m_j \geq 2 \ b_{width}^{a_i} \text{ and } age \ a_i \geq 15 \\ f_d \ a_i \ m_j & \text{otherwise} \end{cases} \quad (5.30)$$

$$amb_1 \ a_i = \begin{cases} true & \text{if } j \neq k \text{ and } f_d \ a_i \ m_j < b_{width}^{a_i} \\ false & \text{otherwise} \end{cases} \quad (5.31)$$

$$amb_2 \ m_j = \begin{cases} true & \text{if } i \neq k \text{ and } f_d \ a_i \ m_j < b_{width}^{m_j} \\ false & \text{otherwise} \end{cases} \quad (5.32)$$

$$c_{ij}^B = \begin{cases} f_m \ a_i \ m_j & \text{if } age \ a_i \geq 15 \\ f_a \ a_i \ m_j & \text{otherwise} \end{cases} \quad (5.33)$$

$$c_{ij}^C = f_a a_i m_j \quad (5.34)$$

$$c_{ij}^D = \begin{cases} f_m a_i m_j & \text{if } \text{age } a_i \leq 15 \\ f_a a_i m_j & \text{otherwise} \end{cases} \quad (5.35)$$

e) Gating

Gating has been performed by creating a binary mask matrix, where its elements take value one when the compared agent i and detection j are considered as a likely matching. Those assignments geometrically or visually improbable to be even considered by the hypotheses generator are marked with the value zero in the corresponding element of the mask matrix.

At association levels A , B , C and D , the corresponding binary mask matrices, B^A , B^B , B^C and B^D , are computed according to Eq. 5.36, 5.37, 5.38 and 5.39, respectively, where b_{ij}^A , b_{ij}^B , b_{ij}^C and b_{ij}^D refer to the element in row i and column j of each matrix. In all the levels, except the first one, the distance threshold depends on the agent's width plus a term which increases with FWM , since the uncertainty about the agent's location increases as the number of frames where he/she is lost does it.

$$b_{ij}^A = \begin{cases} 1 & \text{if } c_{ij}^A \leq 0.8 b_{width}^{a_i} - f_s a_i m_j \leq 0.8 b_{width}^{a_i} \\ 0 & \text{otherwise} \end{cases} \quad (5.36)$$

$$b_{ij}^B = \begin{cases} 1 & \text{if } f_d a_i m_j \leq 1 - 0.1 FWM a_i - b_{width}^{a_i} \\ & f_m a_i m_j \leq 0.3 \text{ age } a_i \leq 15 \\ 1 & \text{if } f_d a_i m_j \leq 1 - 0.1 FWM a_i - b_{width}^{a_i} \\ & f_a a_i m_j \leq 0.3 \text{ age } a_i \leq 15 \\ 0 & \text{otherwise} \end{cases} \quad (5.37)$$

$$b_{ij}^C = \begin{cases} 1 & \text{if } f_d a_i m_j \leq 1 - 0.1 FWM a_i - b_{width}^{a_i} - f_a a_i m_j \leq 0.3 \\ 0 & \text{otherwise} \end{cases} \quad (5.38)$$

$$b_{ij}^D = \begin{cases} 1 & \text{if } f_d a_i m_j \leq 1 - 0.1 FWM a_i - b_{width}^{a_i} \\ & f_m a_i m_j \leq 0.3 \text{ age } a_i \leq 15 \\ 1 & \text{if } f_d a_i m_j \leq 1 - 0.1 FWM a_i - b_{width}^{a_i} \\ & f_a a_i m_j \leq 0.3 \text{ age } a_i \leq 15 \\ 0 & \text{otherwise} \end{cases} \quad (5.39)$$

5.5.4 Global Hypotheses Generator

The Global Hypotheses Generator algorithm has been developed to generate multiple hypotheses, where each hypothesis describes a global assignment between agents and measurements, so each hypothesis describes a complete association solution encompassing all the identities assignments at the same time.

From a mathematical perspective, the Hypotheses Generator provides an array of hypotheses, $H = h_k$. A hypothesis, h_k , in turn, is an array of identification numbers, so that the value of every element of a hypothesis, h_{kj} , is the index to the set of agents, A , that refers the agent associated to the measurement j . Therefore, the identities assignment defined by a certain hypothesis is performed according to Eq.5.40.

$$a_{h_{kj}} : m_j \quad (5.40)$$

The inputs of the Hypotheses Generator algorithm are: the number of measurements M , the number of agents, A , and a binary mask matrix, where the impossible associations are marked with zero value, B , whose dimension is $A \times M$. Before explaining the procedure performed by the Global Hypotheses Generator, some variables must be defined:

- PMM , possible matches for every measurement. It is a vector whose dimension is the number of measurements, M . Each element j of this vector saves the number of possible matches for the corresponding measurement j , as Eq.5.41 describes.

$$PMM_j = \sum_{i=0}^{A-1} b_{ij} \quad (5.41)$$

- PMA , possible matches for every agent. It is a vector whose dimension is the number of agents, A . Each element i of this vector saves the number of possible matches for the corresponding agent i , as Eq.5.42 describes.

$$PMA_i = \sum_{j=0}^{M-1} b_{ij} \quad (5.42)$$

- K is the number of hypotheses that can be generated with A agents, M measurements, and considering the impossible associations given by the mask matrix. K is computed according to Eq.5.43.

$$K = \prod_{j=0}^{M-1} (PMM_j - PMM_j - 0) \quad (5.43)$$

- *nmm*, not-matched measurements. It counts the number of measurements that cannot be associated with any of the agents, and it is defined by Eq 5.44.

$$nmm = \sum_{j=0}^{|M|-1} \prod_{i=0}^{|A|-1} (1 - b_{ij}) \quad (5.44)$$

- *nma*, not-matched agents. It counts the number of agents that cannot be associated with any of the measurements, and it is defined by Eq. 5.45.

$$nma = \sum_{i=0}^{|A|-1} \prod_{j=0}^{|M|-1} (1 - b_{ij}) \quad (5.45)$$

Once, these variables have been computed, the first step of the Global Hypotheses Generator is the creation of a first hypotheses matrix, H^1 , with dimension $K \times |M|$, $H^1 \in R^{K \times |M|}$, where each row h_k defines a hypothesis. Algorithm 6 describes the procedure followed to create this matrix H^1 , which employs Eqs. 5.46, 5.47, 5.48, and 5.49.

Algorithm 6 First Hypotheses matrix, H^1 , generation

Require: $M_{mask,ij}$, $|D|$, PMM .

Ensure: First hypotheses matrix, H^1 .

```

1: for  $n \leftarrow 1$  to  $|M|$  do
2:   if  $PMM_n \neq 0$  then
3:     Calculate the number of times,  $v_{rep}$ , that an identity value is repeated in column  $n$  of
        $H^1$ , according to Eq 5.46;
4:     Initialise  $r_1$ , which is the index of the row where an identity value appears for first
       time in column,  $r_1 = 0$ ;
5:     Generate an array,  $ID_n$ , with the identities values that can appear in column  $n$ , using
       Eq. 5.47;
6:     for  $i \leftarrow 1$  to  $length(ID_n)$  do
7:       Get identity value  $id = ID_{n,i}$ ;
8:       Fill  $H^1$  with  $id$ , according to Eq. 5.48;
9:        $r_1 = r_1 + v_{rep}$ ;
10:    end for
11:   else Fill column  $n$  of  $H^1$  with  $-1$ , according to Eq. 5.49;
12:   end if
13: end for

```

$$v_{rep} = \prod_{i=n+1}^{|D|-1} PMD_i, \forall PMD_i \neq 0 \quad (5.46)$$

$$ID_n = \{i \mid b_{in} = 1\} \quad (5.47)$$

$$h_{kn}^1 = id, \forall k \in \mathbb{Z} \cap [r_1, r_1 + v_{rep}] \neq 0 \quad (5.48)$$

$$h_{kn}^1 = -1, \forall k \in \mathbb{Z} \cap [0, K) \neq 0 \quad (5.49)$$

Instead of using pruning methods to discard the improbable hypotheses from the generated ones, the computation of the hypotheses matrix, H^1 , is implicitly conditioned by a previously calculated mask of impossible associations, B . In that way, only the notably probable hypotheses are generated and proposed, reducing the computational time. If this matrix had been generated without considering the mask matrix, the number of possible hypotheses would have been $K = |A|^{|M|}$. This number exponentially grows with the increasing number of available detections, resulting in impracticable values from a computational point of view for a real-time application. However, with the mask, K value is computed by Eq. 5.43, so under the assumption that in the worst case a measurement could present until 3 possible matches PMM_j (it is very difficult that this happens for every detection), the resulting number of hypotheses is highly reduced ($K \ll 3^{|D|}$).

Once H^1 is obtained, the second step is the application of a filter to remove hypotheses where the same identification number has been assigned more than once since the same identity can not be assigned to two measurements, i.e. a measurement cannot be associated to two agents. Therefore, a second set of hypotheses is obtained, H^2 , where each element of the set is a selected hypothesis vector from H^1 , h_{kj}^1 , as Eq. 5.50 defines.

$$H^2 = h_k^1 \leftrightarrow h_{kj}^1 \neq h_{kj'}^1 \forall j, j' \in \mathbb{Z} \cap [0, |D|) \wedge j \neq j' \quad (5.50)$$

When there exist hypotheses without repeated identities values, $|H^2| > 0$, it is considered that every probable hypothesis is already generated, and H^2 is the final set of hypotheses, H^F . However, if none of the hypotheses passes the filter more computation is needed to get a new set of hypotheses, H^3 , as Eq. 5.51 defines.

$$H^F = \begin{cases} H^2 & \text{if } |H^2| > 0 \\ H^3 & \text{otherwise} \end{cases} \quad (5.51)$$

The possibility of new tracks births is addressed by the Hypotheses Generation method. N is the number of possible new agents considered among the taken measurements. N renders the number of measurements that are not assigned to any of the existing identities and for that reason, they are going to be used to generate new agents to track. Therefore, when H^2 is taken as the final set of Hypotheses, N is given by the value of nmm .

However, if none of the hypotheses pass the filter, $|H^2| = 0$, then the number of new agents must be increased. The total number of new agents in a hypothesis, k , is given by the maximum number of places occupied by the value -1 , i.e. measurements without matched agents, plus the number of repetitions of the identity's values, as Eq. 5.52 defines. This value is measured over every hypothesis of H^1 .

In one hypothesis, several identity values can be repeated, so the sum of the number of repetitions of each one of them is considered. The vector $IR \in \mathbb{R}^K$, saves at every position ir_k the number of identities repetitions, in the row k of H^1 (hypothesis k), according to Eq.5.53 and 5.54.

$$N_k = ir_k + \sum_{j=0}^{|D|-1} \max(H_{kj}^1 \cdot (-1), 0) \quad (5.52)$$

$$ir_k = \sum_{j=0}^{|D|-1} mask_j^R \quad (5.53)$$

$$mask_j^R = \begin{cases} 1 & \text{if } \exists j', h_{kj}^1 = h_{kj'}^1 \wedge j > j' \\ 0 & \text{otherwise} \end{cases} \quad (5.54)$$

A new set of hypotheses, H^3 , is generated with the procedure described by Algorithm 7.

Algorithm 7 Third Hypotheses set, H^3 , generation

Require: H^1 , $|D|$, IR .

Ensure: Third hypotheses set, H^3 .

```

1: Initialisation of a counter of hypothesis in  $H^3$ ,  $c \leftarrow 0$ ;
2: for  $k \leftarrow 0$  to  $K - 1$  do
3:   if  $ir_k = 0$  then
4:      $h_c^3 \leftarrow h_k^1$ ;
5:      $c \leftarrow c + 1$ ;
6:   else
7:     Generation of  $idx$ , according to Algorithm 8;
8:     Generation of  $M$ , according to Algorithm 9;
9:     for  $i \leftarrow 0$  to  $R$  do
10:      Compute  $h_c^3$ , according to Eq. 5.57;
11:       $c \leftarrow c + 1$ ;
12:     end for;
13:   end if;
14: end for;

```

Those hypotheses from H^1 without identity repetitions are maintained and added to H^3 . Each one of the rest of the hypotheses of H^1 is substituted by a list of new possible hypothesis without repetitions of an identity assignment.

To create this list, firstly, a vector of sets, idx , is generated, as Algorithm 8 indicates. At each position, this vector saves a set with the indexes where a certain repeated identity is appearing on the query hypothesis k . Therefore, the length of the saved sets of indexes is variable, and the number of sets is the number of different identity numbers which are repeated.

Algorithm 8 Generation of idx , vector of sets of indexes where a certain repeated identity is appearing on the query hypothesis, k .

Require: h_k^1, D .

Ensure: Vector of sets of indexes idx .

```

1: Declare vector of sets  $idx$ ;
2: for  $d = 0$  to  $D - 1$  do
3:   if  $h_{kd}^1 = 1$  then
4:      $h_{aux} = h_k$ ;
5:     Declare new set of indexes,  $idx\_set$ ;
6:     for  $i = d$  to  $D - 1$  do
7:       if  $h_{aux\ i} = h_{kd}$  then
8:         Add  $i$  to the set  $idx\_set$ ;
9:          $h_{aux\ i} = 1$  ;
10:      end if;
11:    end for;
12:    if  $idx\_set \neq \emptyset$  then
13:      Add  $idx\_set$  to the vector  $idx$ ;
14:    end if;
15:  end if;
16: end for;

```

From idx , a mask matrix, M , is computed for every hypothesis. This mask has so many rows as different possibilities of distribution of the new agents, and so many columns as detections. The matrix presents value 1 in the positions of the query hypothesis, k , where the current identity must be maintained, and value -1 in the positions that are intended for new agents creation.

Eventually, each hypothesis with identities repetitions is substituted in H^3 by the set of hypotheses that results from the pairwise multiplication of the query hypothesis by its corresponding mask, M . The resulting negative values are substituted by -1 , to indicate the positions of detections considered as new agents, as Eq.5.57 defines.

Algorithm 9 Generation of Mask, M , of possible distributions of new agents for a hypothesis k

Require: h_k^1, idx .

Ensure: Mask M .

```

1: Compute  $R$ , the number of rows of  $M$ , according to Eq.5.55, where every element  $idx_i$  is a set
   of indexes;
2: Initialisation of mask matrix  $M^{R \times |D|} = \{m_{xy} = 1\}$ ;
3: for  $i \leftarrow 0$  to  $|idx| - 1$  do
4:   Initialization of the counter of generated rows of  $M$ ,  $r \leftarrow 0$ ;
5:   Calculate the number of repetitions,  $rep$ , of a possible distribution of new agents for the
   repetitions of a certain identity according to Eq. 5.56;
6:   while  $r < R$  do
7:     for  $j \leftarrow 0$  to  $|idx_i| - 1$  do
8:       for  $n \leftarrow 0$  to  $|idx_i| - 1$  do
9:         for  $l \leftarrow 0$  to  $rep - 1$  do
10:          if  $n \neq j$  then
11:             $m_{(r), idx_{in}} = -1$ ;
12:             $r \leftarrow r + 1$ ;
13:          end if;
14:        end for;
15:      end for;
16:    end for;
17:  end while;
18: end for;

```

$$R = \prod_{i=0}^{|idx|-1} |idx_i| \quad (5.55)$$

$$rep = \max \left(\prod_{n=i+1}^{|idx|-1} |idx_n|, 1 \right) \quad (5.56)$$

$$h_c^3 = \max(m_i * [h_k^1 + 1], 0) - 1 \quad (5.57)$$

In conclusion, the proposed Hypotheses generation method is capable of performing the linear assignment without relying on a squared matrix, allowing the number of agents to be different from the number of measurements. Both, the starting and ending of the tracking of an agent is contemplated by this method, where N is the number of tracks births considered.

a) Minimum Cost Hypothesis Selection

Instead of optimising the cost matrix, as the Hungarian method does, the cost of every hypothesis is computed from the cost matrix and then the minimum cost hypothesis is chosen. The cost of a hypothesis corresponds to the sum of the costs of every identity assignment described by it, as Eq. 5.58 and 5.59 define.

When one of the measurements is marked by a certain hypothesis as a new agent $i = 1$, its matching cost is not included in the cost matrix, since its computation is impossible, so there is no previous agent associated to that measurement. In this case, a constant and pre-defined value, P , is taken as the cost of creating a new agent. This value, P , has been set with a value slightly higher than the average cost value for correct matches, with the aim of avoiding the assignment of new identities to already existing agents.

$$h_{cost\ k} = \sum_{j=0}^D v_{cost\ j} \quad (5.58)$$

$$v_{cost\ j} = \begin{cases} m_{cost\ ij} & \text{if } i = 1 \\ P & \text{otherwise} \end{cases} \quad (5.59)$$

Finally, the minimum cost hypothesis, h^m , is found according to Eq. 5.60, and selected as the correct global assignment between agents and measurements.

$$h^m = h_p \quad h_{cost\ p} = h_{cost\ k} \quad k = p \quad (5.60)$$

5.6 Degree of Appearance Similarity, DoAS

The visual appearance differences between a certain agent and a detection have been involved in their matching cost formulation. For that reason, a comparative metric of the Degree of Appearance Similarity has been designed to measure not only the appearance differences between captures from consecutive frames but also after long- and short-term occlusions and disappearances.

The DoAS between two images, is defined as the probability that the images belong to the same person, and it has been modelled as a pair-wise binary classifier to discriminate between the similarity and dissimilarity classes. The similarity class renders pairs of images belonging to the same person, and the dissimilarity class, pair of images corresponding to different people. In that way, the appearance cue for tracking multiple unknown agents is obtained by means of a unique pre-trained model, without requiring previous knowledge about the scene.

This metric has been computed by modelling the appearance of each compared individual in a feature array. Subsequently, a comparison function is computed to contrast the pair of features arrays. The appearance features are saved on the feature attribute F of the *person* structure, for both agents and measurements.

This thesis proposes the design of four different DoAS metrics, which differ from each other in the way of modelling the feature appearance of an individual, and in the formulation of the comparison function, as Table 5.1 depicts.

Table 5.2 DoAS Metrics.

DoAS Metrics	Appearance feature modelling	Comparison function
Hand-Crafted Single-Shot DoAS, HCSS-DoAS	Hand-crafted descriptor	
Deeply learnt Single-Shot DoAS, SS-DoAS	Trained DCNN	Euclidean distance, d_E
Deeply learnt Single-Shot Multi-View DoAS, SS-MV-DoAS		
Deeply learnt Multi-Shot DoAS, MS-DoAS		LSTM neural cell

Firstly, a hand-crafted descriptor has been designed to directly compare the appearance of two person images. Secondly, DCNNs have been trained to model an appearance feature array from a person image. A single-shot comparison is provided by computing the distance between the features of two people representations. Two models have been trained with this configuration, one on mono-camera sequences (SS-DoAS), and the other on multi-view re-identification datasets (SS-MV-DoAS). And finally, a multi-shot comparison is performed by a LSTM neural cell, which considers all the features saved in the *memory* attribute of an agent and compares them with the feature attribute F of a certain measurement.

5.6.1 Hand-Crafted Single-Shot DoAS

A handcrafted descriptor to compare pairs of images has been designed, and a binary classifier to discriminate whether the descriptor values renders positive or negative pairs of images has been trained. The DoAS is obtained from this classification. This approach offers a good discriminative capacity when detections of an agent are available in consecutive frames, but the performance decays when there are missed detections, occlusions or temporal disappearances.

a) Contrastive Descriptor

The designed descriptor compares the appearance of the people appearing in two images. In the data association, this is used to compare an agent with a measurement. The image rendering the person described by a certain agent is saved in its reference attribute, R , and the measurement representation is given by the region of the current frame defined by its bounding box, B .

The similarity appearance descriptor is based on the use of hue data and a variant of Volume Local Binary Patterns (VLBP). Hue value allows the identification of an image region by its colour tone, instead of light level, making the descriptor more robust against illumination changes. Moreover, VLBP can represent the evolution of a person along with several frames. This idea has been adapted to detect the presence of the same person along with two images.

The descriptor calculation consists of these four steps, presented in Fig. 5.6:

- I Common area selection. The bounding boxes of the taken measurements not always present the same size, and the human shape might not be perfectly enclosed or centred in them. Similar parts of the human shape need to be aligned in order to be compared; therefore, an alignment between the input images is performed by means of overlapping the heads locations. Then only the region rendered in both images, i.e. the common area, is selected.
- II Voxels creation. First, a volume structure is created. Most VLBP-based applications create a volume structure extracting the same region in consecutive frames. Instead of that, this VLBP variant forms volumes with different regions of two frames, so that the width and height of the volume are the number of columns, m , and rows, n , of the selected common area and the depth value is two, because the volume is formed by two images. These images can belong to not consecutive frames, so the time step size between them, n , is variable. The step size, n , is the difference between the frame number, f , from which the images were extracted. Subsequently, $3 \times 3 \times 2$ voxels centred in each one of the pixels of the common region are extracted.
- III VLBP calculation. The VLBP value is calculated for every voxel by comparing the hue value of its frontal central pixel with the 4-type neighbour pixels from both depths. If the neighbour pixel has a lower hue value, the comparison returns zero, and one otherwise. The VLBP value is formed by eight binary bits. This is not calculated for the boundary pixels of the image, so the result is an $(m - 2) \times (n - 2)$ image, whose pixels can take values from 0 to $2^8 - 1 = 255$.
- IV Feature array calculation. The histogram of the VLBP image is calculated so that the descriptor is an array of 256 features corresponding to the 256 possible values of VLBP. The histogram values are divided by the total number of pixels (which is variable), to make the descriptor independent from the size of the detections. In that way, each one of the 256 elements of the descriptor array takes values from zero to one.

Fig. 5.6 Computation of the Appearance Similarity Descriptor

b) Classifier

In order to classify the value of the descriptor as the result of a situation of similarity or dissimilarity, the SVM implementation of OpenCV library, based on [45], has been used.

The descriptor is an array of 256 values, which could be rendered as a point in a space of 256 dimensions. The position of this point depends on the fact of belonging to the similarity or dissimilarity class and the SVM defines the boundary which separates the region corresponding to each class. To estimate this boundary, the SVM needs to learn the similarity pattern or model. The absence of that pattern is considered as dissimilarity.

The learning has been performed by an off-line supervised training using the parameters listed in Table 5.3. The SVM has been trained over samples of the descriptor array rendering both the similarity and the dissimilarity class. The training samples have been automatically labelled by means of comparing the identification numbers of the contrasted individuals. If they present the same identification number the label is one (positive pair), and zero (negative pair), otherwise.

Table 5.3 SVM parameters.

Parameter		Value
Kernel type		LINEAR
Termination Criteria	Tolerance	$1e-6$
	Maximum number of iterations	1000

With the aim of producing a large number of samples, some labelled sequences from CAVIAR dataset [107] (Section 3.3.2) have been randomly selected and for each frame, f , every person has been compared with every visible person from the N previous ones, as Fig.5.7 shows. Therefore, the step size, n , previously defined, takes values from 1 to N . this fact is motivated by the necessity of identifying an agent even when its reference was updated for last time several frames before. Several values of N have been used to extract different training sets, and the resulting classifiers have been evaluated (Section 6.3.5). The detections with a too small size and those that partially render a person have been removed from this process by a filter based on human shape proportions.

Fig. 5.7 Extraction of training samples. Positive samples are joint by a green line, and negative samples, by a red line.

c) DoAS Metric

The Hand-Crafted Single-Shot DoAS, HCSS-DoAS, is calculated from the prediction performed by the trained SVM for the similarity descriptor, d , which is in turn, calculated from two images.

Concretely, HCSS-DoAS between two images, I_a , and I_b is calculated from the normalised signed distance from the point represented by the array descriptor, $d(I_a, I_b)$, to the SVM boundary which separates the classes of similarity or dissimilarity. This boundary is a hyperplane defined by the function $f(x) = \beta_0 + \beta^T x$, where β is known as the weight vector and β_0 as the bias.

Eq. 5.61 describes HCSS-DoAS computation, where the term $\frac{|\beta_0 + \beta^T d(I_a, I_b)|}{\|\beta\|}$ is the distance from the point $d(I_a, I_b)$ to the hyperplane $f(x)$. D is a constant with the value of the maximum possible distance between two points in the 256-dimensional features space defined by the used descriptor, where the range of values of each dimension is $\{0, 1\}$. Therefore, D is $16(\sqrt{256})$. In that way, the maximum value, in absolute terms, for the distance is the unit. The sign of the distance is given by y_i , which is the prediction provided by the classifier. y_i takes value 1 if the descriptor represents the similarity class and -1 otherwise. Moreover, the unit has been added, and the result is divided by two, in order to narrow the HCSS-DoAS range of values from 0 to 1, since HCSS-DoAS must measure the probability that the compared images belong to the same person.

$$HCSS_DoAS = \left(\left(y_i \cdot \frac{|\beta_0 + \beta^T d(I_a, I_b)|}{D \cdot \|\beta\|} \right) + 1 \right) \cdot \frac{1}{2} \quad (5.61)$$

5.6.2 Deeply Learnt Single-Shot DoAS

Elementary comparison of images to identify people only works for consecutive and well-aligned detections. In order to deal with partial-term occlusions, after which the representation of a person changes, deep learning has been used to automatically find the most salient features of the individual's appearance.

An appearance feature has been learnt by training a DCNN. Concretely, the VGG11 architecture, described by Table 4.1 in Section 4.1, has been used to model the feature.

This neural network has been trained by the Siamese model, described in Section 4.2, using the Normalised Double-Margin-based Contrastive Loss Function (Eq. 4.7), and the Pair-based Mini-Batch Gradient Descent Learning Algorithm (Algorithm 2). The training data has been generated from the MOT17 set of surveillance sequences (Section 3.3.2). A data generation tool² has been designed to extract people detections from the sequences, and subsequently, the detections are combined to create a huge number of training pairs, by means of using the balancing data method, presented in Section 4.3.

The reason for choosing the Siamese model to train the network, over the triplet model, is that in a tracking algorithm the appearance variations between two compared images are smaller than in Person Re-Identification. Triplet model is more effective than Siamese one when a Re-Id

²The data generation tool has been implemented as a set of c++ functions, which are publicly available under http://github.com/magomez/dataset_factory/tree/master/data_factory_from_mot

model is learnt since triplet loss relies on a relative distance that makes it more flexible against the images' variations. In mono-camera Multi-Object Tracking, the illumination, background, and appearance changes, even after temporary disappearances, are not so wide as in Re-Id domain. Therefore, the Siamese model can perform the discrimination of the pairs of samples in two well-differentiated groups, positive and negative pairs. This discrimination is accentuated by the Normalised Double-Margin-based Contrastive Loss Function.

Once the neural network has been trained, this can be used to compute the appearance feature of a person's image, by means of the feature computation module (see Section 3.5.1). To describe the appearance of a certain measurement, the pre-trained neural network is computed over the frame region delimited by its bounding box, B , and the output of the network is taken as its feature attribute, F . When that measurement is matched to a certain agent, the agent's feature attribute is replaced by the feature attribute of the query measurement.

The deeply-learnt Single-Shot DoAS, SS-DoAS, between two images, I_a , and I_b , is calculated as the complementary value of the Euclidean distance between their appearance features, F , as Eq.5.62 defines.

$$SS_DoAS = 1 - d_E(F(I_a), F(I_b)) \quad (5.62)$$

5.6.3 Deeply learnt Multi-Shot DoAS

Sometimes, in complex scenes, the data association process could produce some identities switches, i.e. the association of incorrect identities to some detections. Therefore, some attributes, like the feature and reference image, of the wrong associated agents is updated with features and person images corresponding to a different identity. For that reason, after an identity switch, in the following tracking iteration, the query agent's appearance is rendered by a different person appearance, and probably it will be matched to that person's detection. So, after an identity switch, a different person's track is associated with an agent in further iterations, making very difficult the correction of such error.

With the aim of avoiding identity switches or dealing with the consequences of a previous identity switch, and in order to avoid the error propagation in further frames, temporal consistency has been given to the appearance comparison function. A contrastive metric called Deeply learnt Multi-Shot Degree of Appearance Similarity, MS-DoAS, has been designed to consider the computed features for a certain agent in several previous frames but allowing a frame-by-frame association, and consequently an online tracking. At the same time, this metric also prevents future identity switches.

Next subsections describe the MS-DoAS computation, its training and the generation of the data for that.

a) MS-DoAS computation

In the Cascade Data Association process (see Section 5.5.3), the MS-DoAS metric is used to obtain the appearance contrastive function f_m , as Eq. 5.27 shows. This contrastive function forms part of the matching cost computation, as Eq. 5.30, 5.33 and 5.35 describe.

The computation of the MS-DoAS between a certain measurement, m_j , and a certain agent, a_i , is rendered by the scheme in Fig. 5.8.

Fig. 5.8 Computation of Multi-Shot Degree of Appearance Similarity, MS-DoAS, between a measurement, m_j , and an agent, a_i .

Once a measurement has been taken, at a certain tracking iteration, f , its appearance is rendered, by a feature array, $F m_j$, computed by a pre-trained DCNN.

Each time a measurement, m_j , is assigned to an agent, the feature attribute of that agent, $F a_i$ is updated with $F m_j$, and its previous value is saved at the first position of its memory structure, displacing the rest of the elements in one position, as Eq.5.8 defines. Therefore, the memory of an agent, $M a_i$ is a record of its features in the previous frames where it was matched. The elements of the memory array are used as inputs of a pre-trained Long-Short-Term-Memory (LSTM) cell, which provides a feature, called memory feature, $F_M a_i$.

$F m_j$ and $F_M a_i$ are concatenated to feed a fully connected (FC) layer, which has been also pre-trained. This FC layer is used as a binary classification function, F_C , which performs the optimal weighting of the elements of the features $F m_j$ and $F_M a_i$ and returns a pair of outputs ($K - 2$) whose values, $Z_0 Z_1$, are representative of the dissimilarity and similarity classes. Finally, a Softmax function, , defined by Eq. 5.63, normalises these values in the range $0 \leq 1$. So the first normalised output, NZ_0 , returns the probability that the agent, a_i , and the measurement, m_j , do not form a correct match, and the second, NZ_1 , the probability that they form a correct match. Therefore, NZ_1 is taken as the MS-DoAS between the agent, a_i , and the measurement, m_j .

$$NZ_n = \frac{e^{Z_n}}{\sum_{k=0}^{K-1} e^{Z_k}} \quad n = 0, 1 \quad (5.63)$$

The used DCNN model is the same that the one used for computing SS-DoAS, (Section 5.6.2), which follows the VGG11 architecture. The LSTM cell and the FC layer weights have been also previously learnt as the next subsection describes.

b) Training algorithm

The training architecture used to learn the parameters of the LSTM cell and the FC layer that allow measuring the MS-DoAS is rendered in Fig. 5.9.

Fig. 5.9 MS-DoAS learning architecture.

Each training sample, $X_i = x_0 \dots x_T$ is formed by an array (with zero-based indexing) of features, called tracklet, whose size is $T + 1$, where T is the size of the memory array of an agent. Therefore, each tracklet element, x_n , corresponds to a feature computed from an image that was taken from a frame whose number is given by $f(x_n)$.

The features have been previously calculated by computing the DCNN described in Section 5.6.2 with the feature computation module (see Section 3.5.1). By computing the features in an off-line process, previous to the learning, the training time is highly reduced. The number of possible training tracklets created from a given set of images is much larger than the size of that set of images. For that reason, computing the features of all the images of the set before forming tracklets combinations is much more efficient, as long as the computational time is concerned.

Because the neural model is learnt by a supervised training process, every feature of a tracklet is accompanied by the identification number of the person that it is rendering, $ID(x_n)$. A tracklet is considered as positive $y = 1$ if its first feature, x_0 , corresponds to the same individual than the rest of features of the tracklet, and it is considered as negative $y = 0$ in the opposite case, as Eq. 5.64 defines. The identity rendered by the T last features of the tracklet is given by the identity represented by the most of its components (the mode, Mo) since some intruders (with different

id) can be added to the tracklet to simulate failed associations.

$$y = \begin{cases} 1 & \text{if } ID(x_0) = Mo(ID(x_n)) \\ 0 & \text{if } ID(x_0) \neq Mo(ID(x_n)) \end{cases} \quad (5.64)$$

A feature tracklet based version of the Mini-Batch Gradient Descent algorithm has been implemented to train the presented neural model, and its main procedures, along with the learning iterations, *it*, are described by Algorithm 10. This algorithm is based on the use of the cross-entropy loss, f_{CE} to compute the loss function, f_L , as Eq. 5.65 and 5.66 define, on its forward propagation and its derivatives, Eq. 5.67, on the backward propagation.

Algorithm 10 Feature Tracklet-based Mini-Batch Gradient Descent Learning Algorithm

Require: Batch of feature tracklets, $X^{it} = \{X_i^{it}\}$.

Ensure: The network parameters $W^{IT} = W_j^{IT}$

```

1:  $W^0 = \{w_j^0\}$ 
2: while  $it < IT$  do
3:    $it \leftarrow it + 1$ 
4:    $\frac{\partial f_L}{\partial W_j} = 0$ ;
5:   for all training tracklet  $X_i$  of the batch set  $X^{it}$  do
6:     Calculate  $Z_i = (Z_{i,0}, Z_{i,1})$  by forward propagation;
7:     Calculate  $\sigma(Z_i)_n$  by Eq. 5.63;
8:     Calculate  $f_{CE}(W^{it}; X_i^{it})$  by Eq. 5.66;
9:   end for
10:  Calculate  $f_L(W^{it}; X^{it})$  by Eq. 5.65;
11:  for all training tracklet  $X_i$  of the batch set  $X^{it}$  do
12:    Calculate  $\frac{\partial f_{CE}(W^{it}; X_i^{it})}{\partial W_j^{it}}$ , by back propagation;
13:  end for
14:  Calculate  $\frac{\partial f_L(W^{it}; X^{it})}{\partial W_j^{it}}$  according to Eq. 5.67;
15:  Update parameters according to Eq. 4.29;
16: end while

```

$$f_L = \frac{1}{b} \sum_{i=1}^B f_{CE}(W^{it}; X_i^{it}) \quad (5.65)$$

$$f_{CE}(W^{it}; X_i^{it}) = -y_{i,0} \cdot \log(\sigma(Z_i)_0) - (1 - y_{i,0}) \cdot \log(1 - \sigma(Z_i)_0) \quad (5.66)$$

$$\frac{\partial f_L(W^t; X^t)}{\partial W_j^t} = \frac{1}{B} \sum_{i=1}^B \left[\frac{\partial f_{CE}(W^t; X_i^t)}{\partial W_j^t} \right] \quad (5.67)$$

c) Training data

As it was explained above, the inputs of the training model are tracklets of previously computed features, in order to reduce the training time. To create a set of training tracklets of features, the data creation module has been employed (see Section 3.4), following the procedure shown by Fig. 5.10, which is a bit different from that shown in Fig.3.7.

Fig. 5.10 Generation of Feature Tracklets Blobs.

Person images have been extracted from the MOT17 dataset (Section 3.3.2) to create tracklets from them. Instead of forming blobs of data from the training samples (images), firstly features are computed from them, and subsequently, the features are used to create blobs. The features are computed by a model previously learnt from training pairs of images (VGG11 architecture).

The data file is in charge of describing all the tracklets combinations to generate, in order to obtain the training, validation and test set of tracklets. The data file is generated by a delivered tool³. Five different formulations have been designed to generate this file, and consequently, five different types of tracklets sets, X_I , X_{II} , X_{III} , X_{IV} , X_V , have been created and used to train the MS-DoAS network, and the resulting models have been evaluated (see Section 6.3.5).

These formulations are defined by the following equations, where M is the training set size, that is its number of tracklets. Every set is formed by the random mixture of two subsets, the one formed by positive, X_+ , and that composed of negative samples, X_- .

The first set, X_I , is the simplest one. Every tracklet is formed by features of a certain person in contiguous frames, as Fig. 5.11 shows. And in the case of the negative tracklet a different person representation is taken as component x_0 to simulate the comparison of an agent with a non-corresponding measurement. The subsets of positive and negative samples for the first set, X_I and X_- , are defined by Eq. 5.68 and 5.69 respectively.

Fig. 5.11 Examples of the images from which tracklets of the set X_I are generated. Positive tracklets are underlined in green, and negatives, in red. f renders the number of the frame from which the first tracklet component was extracted, in the sequences of the MOT17 dataset.

$$X_I : X_i = x_n \quad n \in Z \quad 0 \leq T-1 \quad f \leq x_n \leq f + x_n - 1 \quad 1$$

$$n \in Z \quad 0 \leq T-1 \quad ID \quad x_n \quad k \quad i \quad M \quad (5.68)$$

³The data generation tool has been implemented as a set of C++ functions, which are publicly available under: http://github.com/magomez/dataset_factory/tree/master/data_factory_from_mot

The second set, X_{II} , is similar to the previous one. However, in positive tracklets, the frame from which component x_0 is extracted has not to be contiguous to that for component x_1 , but a maximum time step (number frames difference) of F is allowed between them. In that way, the detection of an identity after a short-term occlusion can be simulated to train the model to re-identify agents. The subsets of positive and negative samples for the second set, X_{II}^+ and X_{II}^- , are defined by Eqs. 5.70 and 5.71 respectively.

$$X_{II} - X_I \quad (5.71)$$

$$X_{III}: \begin{matrix} Xi & x_n & n & Z & 0 & T & 1 & f & x_n & f & x_{n-1} & F & n & j & j & Z & 0 & T \\ j & T & 1 & S & f & x_n & f & x_{n-1} & 1 & n & Z & 0 & T & ID & x_n & k & i & M \end{matrix} \quad (5.72)$$

The fourth set, X_{IV} , is similar to the first one but until N intruders are added in random locations of the positive and negative tracklets. That means, that some components are substituted by features of different people, to simulate incorrect associations in previous frames. The subsets of positive and negative samples for the fourth set, X_{IV}^+ and X_{IV}^- , are defined by 5.74 and 5.75 respectively, where $\odot$ renders the component-wise product operation. In these equations, V_i renders a binary mask vector, of the same length than the tracklets, randomly generated for every tracklet, i . Positions where the mask takes value 1 corresponds to the introduction of an intruder. X_{IV} is a

tracklet formed by randomly picked intruders. V_i and X_i are different for every created tracklet.

$$X_{IV} : \begin{matrix} X_i & V_i & X_i & V_i & V & Z^{T-1} & V_{i,n} & Z & 0 & 1 & \sum_{n=0}^T V_{i,n} & N \\ & & & & & & & & & & ID_{x_{i,n}} & ID_{x_0} & X_i & X_I \end{matrix} \quad (5.74)$$

$$X_{IV} : \begin{matrix} X_i & V_i & X_i & V_i & V_i & Z^{T-1} & V_{i,n} & Z & 0 & 1 & \sum_{n=0}^T V_{i,n} & N \\ & & & & & & & & & & ID_{x_{i,n}} & Mo ID_{x_n} & X_i & X_I \end{matrix} \quad (5.75)$$

The fifth set, X_V , is a combination of the third and the fourth set. It includes time steps and intruders, in order to train the model with a challenging dataset, making it robust to deal with real inputs when it is applied in a tracking algorithm. The subsets of positive and negative samples for the fifth set, X_V and X_V , are defined by Eqs.5.76 and 5.77 respectively.

$$X_V : \begin{matrix} X_i & V_i & X_i & V_i & V_i & Z^{T-1} & V_{i,n} & Z & 0 & 1 & \sum_{n=0}^T V_{i,n} & N \\ & & & & & & & & & & ID_{x_{i,n}} & ID_{x_0} & X_i & X_{III} \end{matrix} \quad (5.76)$$

$$X_V : \begin{matrix} X_i & V_i & X_i & V_i & V_i & Z^{T-1} & V_{i,n} & Z & 0 & 1 & \sum_{n=0}^T V_{i,n} & N \\ & & & & & & & & & & ID_{x_{i,n}} & Mo ID_{x_n} & X_i & X_{III} \end{matrix} \quad (5.77)$$

It should be noted that in the negative tracklets of training sets IV and V, X_{IV} and X_V , the component x_0 could present same *id* as some of the intruders, making the discrimination harder.

In order to generate a wide variety of tracklets, the intruder components and the x_0 component in the negative tracklets has been obtaining not only by taking different person detections from the same sequence but also from different ones. To avoid the overlapping of the numbers of frames and identities numbers among different sequences, firstly a general list of samples has been generated from all the employed sequences. When a person image of a certain frame is added to the list, the frame number, f , and its identification number *ID* are modified in order to not take the already used values, corresponding to images previously taken from other sequences. In that way, the equations defined above can be applied over this general person images list, resulting in larger and cross-sequence tracklets training sets.

5.6.4 Deeply learnt Single-Shot Multi-View DoAS, SS-MV-DoAS

The previously presented neural DoAS models were trained on data extracted from mono-camera sequences. Although several sequences have been used to create pairs and tracklets, there are not representations of a certain person in more than one sequence, i.e. in more than one camera view. In order to re-identify agents among different camera views, a Re-Id model has been trained using samples from multiple Re-Id datasets.

The model used, is the one presented in Section 4.8.3, which has been pre-trained on samples extracted from MOT sequences and fine-tuned on triplets formed by images from five different Re-Id datasets : PRID2011, VIPeR, CUHK-02, GRID and i-LIDS-VID (see Section 3.3.1). In that way, basic person features are learnt from detections of mono-camera video sequences, and more complex and discriminative features are learnt by training on the cross-Re-Id dataset presented in Section 4.7.2, where images from different camera views are compared. Therefore, by the fine-tuning step, the model is trained to deal with view-to-view transitions.

This model has been trained with a Triplet network. Moreover, the training triplets have been formed by combining images from different datasets⁴, to avoid the training of the model on a specific dataset, with a limited range of illumination, perspective, and background variations. By training on the cross-Re-Id dataset a more versatile model is obtained, and suitable to be applied in a Multi-Camera Tracking system, with multiple and different camera-to-camera transitions.

The Deeply-learnt Single-Shot Multi-View DoAS, SS-MV-DoAS, between two images, I_a , and I_b , is calculated by Eq. 5.78, where the features F are computed by the mentioned Re-Id neural model.

$$SS_MV_DoAS = 1 - d_E(F(I_a), F(I_b)) \quad (5.78)$$

5.7 Skeleton Analysis

To deal with the herein errors from the detection stage, which causes missed and false positive agents, two strategies based on the geometrical analysis of human skeletons have been designed:

- **DBT.** The inference of the localisation of missed agents has been performed by a detection-by-tracking approach, where a Convolutional Pose Machine (CPM), [339], is used to search a human shape in the location where each missed agent is expected to be found.

⁴The data generation tool has been implemented as a set of C++ functions, which are publicly available under: http://github.com/magomez/dataset_factory/tree/master/data_factory_from_reid

- **HSV.** A filter to validate the human shapes of the detected objects has been designed. This filter geometrically analysed the structured described by the joints detected by the CPM⁵, to determine whether this corresponds or not to a human skeleton.

These two strategies based on the skeleton analysis have been implemented in two modules, which have been integrated into the tracking procedure. Fig.5.12 represents the relation of these modules with the rest of the stages of the tracking algorithm.

Fig. 5.12 MOT algorithm with Human Shape Validation and Detection-by-Tracking modules.

Once a set of detections is provided, the Human Shape Validation filter removes most of the false detections, in order to maintain only those corresponding to the individuals appearing in the current frame.

⁵Please note that this CPM has been also used to extract body parts in order to model the appearance of a person to identify him/her, as it was described in the previous chapter (Section 4.8.2).

The next stage is the data association process, which performs the assignment of every remained detection to its corresponding agent, whose representation is updated by that detection.

However, sometimes the detector misses an individual, as it is shown in Fig.5.12 (person with a green silhouette). Therefore, there is not always a detection for every agent, so after the association process, for the non-matched agents, its detection is searched by the detection-by-tracking module, where joints are searched around the expected location of the agent. If the detected joints present a human shape, the agent is considered as found and its representation is updated.

The attribute rendering the skeleton of an agent or detection, as well as, the fundamentals of the HSV and DBT modules are presented in the following subsections.

5.7.1 Skeleton attribute

Skeleton structure, J , is one of the attributes of a *person* structure, and this, in turn, is one of the attributes of the *agent* structure, as it was explained in Section 5.2.1. The skeleton structure is a vector, J , which renders the locations of a person's joints in a frame. Each element j_k of the vector is the location $j_{kx} \ j_{ky}$ of the joint k in the image. The length of J is 15, corresponding to 15 human joints saved in the order established by the joints map, JM , defined in Eq.5.79, where the sub-indexes r and l mean right and left, respectively.

$$JM = \text{head neck shoulder}_r \text{ elbow}_r \text{ wrist}_r \text{ shoulder}_l \text{ elbow}_l \\ \text{wrist}_l \text{ hip}_r \text{ knee}_r \text{ ankle}_r \text{ hip}_l \text{ knee}_l \text{ ankle}_l \text{ waist} \quad (5.79)$$

Fig. 5.13 enumerates these body joints (in the same order), except the last joint, which is not used by the body parts extractor layer. For easier visualisation, instead of only representing the joints locations, the limbs between some pairs of joints are rendered.

Fig. 5.13 Skeleton attribute visualisation.

5.7.2 Human Joints Detection Algorithm

An algorithm has been implemented to obtain the locations of the human joints of an individual in a frame. Its input is the region of a frame delimited by the bounding box of a certain agent.

The joints detector has been implemented as a C++ function and it is mainly based on the use of the CPM presented in [339], which is a pre-trained DCNN that provides the human joints locations on a person image. In addition, a C++ class has been coded to load and interpret the architecture and pre-trained model files for the CPM, which are Caffe files. This class is used as a bridge to obtain a set of body joints locations, which is integrated into the MOT code⁶.

The proposed joints detection algorithm has been adapted to be independent of the scale, i.e. independent from the size of the bounding box size of the detections.

Moreover, although the human joints are detected in an image patch, extracted from a frame, the implemented algorithm provides the location of the joints referred with respect to the frame coordinates origin. In that way the global position of the joints is given, allowing the comparison with those for different agents or different instants of a video sequence.

5.7.3 Human Shape Validation (HSV)

The detections found in a frame are saved in *person* structures, with the aim of providing a set of detected measurements, D . The vector of joints, J , of every detection, d_i , saves the locations of its body joints in the current frame. The joints locations of a person detection are obtained by the human joints detection algorithm explained above (Section 5.7.2), giving as input the zone of the current frame that is delimited by the bounding box of the query detection, $B(d_i)$.

Even when $B(d_i)$ is not delimiting any person, the joints detector tries to find its joints. Obviously, in such cases, it provides joints locations which do not follow the physical structure of a human. For that reason, a Human Shape Validation, HSV, filter has been designed, to select the set of human measurements, H , that pass some physical human constraints as Eq. 5.80 defines.

$$\begin{aligned}
 H = \{h_j : h_j := d_i | & \left(j_{1,y}^{d_i} < j_{2,y}^{d_i} \right) \wedge \left(j_{2,y}^{d_i} < j_{3,y}^{d_i} \right) \wedge \left(j_{2,y}^{d_i} < j_{6,y}^{d_i} \right) \wedge \left(j_{9,y}^{d_i} < j_{10,y}^{d_i} \right) \\
 & \wedge \left(j_{10,y}^{d_i} < j_{11,y}^{d_i} \right) \wedge \left(j_{12,y}^{d_i} < j_{13,y}^{d_i} \right) \wedge \left(j_{13,y}^{d_i} < j_{14,y}^{d_i} \right) \\
 & \wedge \left(2 d_E(j_1^{d_i}, j_2^{d_i}) > d_E(j_3^{d_i}, j_4^{d_i}) \right) \wedge \left(2 d_E(j_1^{d_i}, j_2^{d_i}) > d_E(j_4^{d_i}, j_5^{d_i}) \right) \\
 & \wedge \left(2 d_E(j_1^{d_i}, j_2^{d_i}) > d_E(j_6^{d_i}, j_7^{d_i}) \right) \wedge \left(2 d_E(j_1^{d_i}, j_2^{d_i}) > d_E(j_7^{d_i}, j_8^{d_i}) \right) \} \quad (5.80)
 \end{aligned}$$

⁶The Human Joints Detection Function and the bridge C++ Class is publicly available under <http://github.com/magomez/CPMclass>, and the deploy and model file of the CPM presented by [339], which contains the network architecture and learnt weights, respectively, are publicly available under <http://github.com/shienw/convolutional-pose-machine-release>

The filter formulation defines some geometrical constraints to ensure coherence among the locations of the human joints in a walking pose, with the aim of eliminating those detections not corresponding to people. In that way, most of the false positive detections are removed.

5.7.4 Detection-by-tracking (DBT)

For those agents, whose corresponding detection was not found by the detector, a human shape is searched in the frame area where those were supposed to be. This strategy is called Detection-By-Tracking (DBT) since the detection of a missed agent is inferred by the information collected during its previous tracking.

The location where the agent is expected to be found is predicted by its associated Kalman filter [28]. Then the joints detector algorithm explained above (Section 5.7.2) is used to find human joints around that location.

Although with the DBT strategy it is impossible to detect new people who have never been tracked before, this reduces the number of lost tracks since it can find missed agents.

In addition, the HSV filter, (Section 5.7.3), is again used to ensure that the corresponding human detection has been found, avoiding the detection of false positives in this second people detection. In the case of obtaining a skeleton, considered as human, i.e. it passes the HSV filter, it is considered that the detection of the query agent has been found, and the agent can be updated.

5.8 Multi-Target Multi-Camera Tracking

In order to get Multi-Target Multi-Camera Tracking (MTMCT), the connection between tracks from different images must be done by a re-identification module. This module consists of an association process scored by the deeply learnt Single-Shot Multi-View DoAS, SS-MV-DoAS.

The re-identification module performs the association of the detections of the new people appearing on the scene to the latent agents (see Fig. 5.2). Latent agents is a set of disappeared agents, which can come from the sequence where the tracking is being performed, or from sequences captured in different monitoring points. In the first case, mono-camera identification is performed after long temporal disappearances, and in the second case, MTMCT would be performed.

This approach entailed two important challenges:

- The management of the sets of latent agents sent to the neighbour camera sensors.
- The discrimination of appearing individuals, who have not appeared at any sensor sequence before. For these individuals, new agents' structures must be generated to start to be tracked.

A Single-Shot Re-Identification approach has been addressed in order to minimise the volume of the information transmitted between sensors.

5.9 Other Applications

This thesis provides a versatile multi-agent management architecture which can be exploited for multiple applications. Moreover, the developed methods aim not only to perform Multi-Object Tracking from surveillance monitoring points but also from other platforms with different purposes, such as search and rescue from aerial vehicles and tracking pedestrians from ground vehicles.

5.9.1 Appearance-Based Tracking for Aerial Search and Rescue

With the aim of searching victims in disaster environments, aerial videos have been captured from an Unmanned Aerial Vehicle (UAV). The proposed HSV filter has been used to discard false positives among the found detections. This filter is suitable for scenarios where people can be occluded, and body parts detection is essential.

Moreover, the MOT approach proposed in this thesis has been applied to maintain the corresponding identities of the found human beings through a wide sequence. In that way, their rescue is facilitated. In this type of applications, the camera position moves quickly covering wide areas. However, the pose of the hurt people in the scenes is almost invariable. According to these specifications, a data association based on appearance cues, instead of movement, has been designed.

Furthermore, the applied modules have been modified to make them invariant to the scale, translation and rotation of the point of view with respect to the target objects, allowing the tracking from a moving aerial camera. The pose structure, J , of every detected object is rotated around the head location ($k = 0$) according to the Eqs. 5.81 and 5.82, where α is the angle (in radians) needed to obtain a vertical pose, defined by Eq. 5.83. A pose has been considered as vertical when the straight line joining the head location and the average of the feet locations is vertical, as Fig.5.14(a) shows. Then, HSV filter can be applied over the rotated joints, rj_k .

$$rj_{k,u} = j_{0,u} + (j_{k,u} - j_{0,u}) \cos(\alpha) + (j_{v,k} - j_{0,v}) \sin(\alpha) \quad (5.81)$$

$$rj_{k,v} = j_{0,v} - (j_{k,u} - j_{0,u}) \sin(\alpha) + (j_{v,k} - j_{0,v}) \cos(\alpha) \quad (5.82)$$

$$\alpha = \frac{\pi}{2} + \arctan \left(\frac{j_{0,v} - \frac{j_{10,v} + j_{13,v}}{2}}{j_{u,0} - \frac{j_{10,u} + j_{13,u}}{2}} \right) \quad (5.83)$$

Subsequently, the association cost has been computed from the DoAS metric and the skeleton pose. The DoAS allows to visually re-identify people after long term disappearances in the scene. Moreover, a new contrastive function, f_j , has been formulated, which not only relies on the head location but also on the rest of the joints.

The pose dissimilarity, f_j , between a measurement, m_j , and an agent, a_i , is computed as the weighted mean Euclidean distance between the joints location of the rotated pose structure of the agent, $RJ a_i$, and the rotated and translated pose structure of the measurement, $RTJ m_j$, as it is described by Fig. 5.14, and defined by Eq. 5.84.

$$f_j a_i m_j = \frac{\sum_{k=1}^K d_E(rj_k^{a_i}, rtj_k^{m_j}) w_k e_k}{\sum_{k=1}^K w_k e_k} \quad (5.84)$$

d_E renders the Euclidean distance operation between two points. W is a vector, where each element, w_k , is the weight given to the joint indexed by k . E is a vector, where each element, e_k , takes value 1 if the joint k has been detected and 0, otherwise.

Both pose structures are rotated until a vertical orientation, and subsequently the rotated pose structure of the measurement (in red) is translated the displacement, $\vec{x}$, needed to align both head locations. In that way, the pose dissimilarity measure is invariant to the differences in the position and orientation of the objects in consecutive images, which is caused by the UAV movements.

Fig. 5.14 Computation of pose dissimilarity measure $f_j a_i m_j$: a) poses of an agent, $J a_i$, and a taken measurement, $J m_j$; b) rotated poses of the agent, $RJ a_i$, and the measurement, $RJ m_j$; c) rotated pose of the agent, $RJ a_i$, and rotated and translated pose of the measurement, $RTJ m_j$; d) joints distances

The MOT performance of this method in aerial sequences for search and rescue is presented in Section 6.4.2.

5.9.2 Analysis of Pedestrian's Body Language in the Interaction with Autonomous Vehicles

Agent's skeleton attribute has been also used to identify and track people in sequences captured from ground vehicles, with the purpose of analysing pedestrians' body language, as part of an automated tool to analyse the autonomous vehicle-pedestrian interaction.

This tool is detailed described in [241], and the methods proposed in this thesis were used to develop its tracking module, as the proof of its versatility. In the context of analysing the Pedestrian's Body Language in the Interaction with Autonomous Vehicles, the tracking of the pedestrians is essential to categorise their movements for later analysis or their intention of crossing the road.

The estimation of the pedestrians' pose was performed by the Open Pose library, published by CMU-Perceptual-Computing Lab [42] [339], which designed a convolutional, feedback-based neural network that was responsible for locating the human joints in a person image.

Furthermore, the core of pedestrians' tracking is based on the proposed global data association module (Section 5.5.2). In this application, the matching cost has been computed from the joint's locations distances between person images.

Chapter 6

Experimental Results

This section presents the results obtained by applying the proposed appearance similarity learning approach to both surveillance tasks, Person Re-Identification and Multi-Object Tracking.¹

6.1 Orthogonalization methodology

Both, Re-Id and MOT algorithms, are composed by the integration of a wide variety of modules, and functions, which can adopt different formulations. The use or not of certain tools, and processes, and the chosen formulation for each used function lead to a wide variety of possible configurations. Moreover, a huge number of hyper-parameters (see Appendix A) must be set. In order to evaluate the possible options, and the effects of each contribution to the global performance, orthogonalization methodology has been followed to conduct experiments.

The principle of Orthogonalization treats each variable characteristic of the system (Re-Id or MOT system) as a dimension of the space of possible algorithms configurations. Modifying only one of the variables and keeping fixed the rest, the effects of changing each part of the algorithm can be independently analysed. Moreover, not all the possible configurations (all the possible points in the space of possible algorithms) have been evaluated, but exploration in the direction of the advance is performed.

6.2 Person Re-identification Experiments

Different learning techniques, architectures, and methods have been developed in this thesis to obtain a deep Re-Id model. This section evaluates not only the Re-Id performance of the learnt models but also the effectiveness of the conducted learning processes.

¹This Chapter includes contents from items 1, 2, 3, 5, 6, 8, 9, 10 and 11 of "Published and Submitted Content" list.

The next subsections describe the followed protocol to use several Re-Id datasets (Section 6.2.1), and the methodology and metrics employed for both, evaluating the learning processes and the model Re-Id performance (Sections 6.2.2 and 6.2.3). Then, the obtained results for every conducted experiment are exposed (6.2.4), and the final results are summarised, compared with other state-of-the-art methods, and discussed (Sections 6.2.5 and 6.2.6).

6.2.1 Datasets Protocol

The Single Shot Re-Id version of five datasets have been employed to train, validate and test the designed similarity appearance model to perform Person Re-Identification. These datasets, presented in Section 3.3.1, are: PRID2011 [152], VIPeR [138], i-LIDS-VID [385], GRID [223], and CUHK-02 [200, 201]. This assortment of datasets provides a wide variety of scenarios (outdoors and indoors), capturing protocols (from multiple cameras or a fixed pair) or resolutions to examine the performance of the proposed solution in different circumstances.

To conduct the experiments of this thesis, each one of these datasets has been divided into three sets of images: training, validation and test set. The proposed architectures and learning algorithms have been executed over the training set to learn the model parameters. At every learning iteration, a different set of parameters is learnt. From all these parameter settings, one of them is chosen according to its performance over the validation. Finally, the Re-Id capacity of the chosen model is measured over the test set.

The followed procedure to divide the datasets has been pre-establish by benchmark articles and embraced by the Person Re-Identification research community for the evaluation and comparison of the Re-Id algorithms.

- **PRID2011:** set A contains 385 different images, and set B, 749 images. 200 of the captured individuals are rendered in both sets (appearing in both views), and 90 of them were randomly extracted to generate the training set and 10 for the validation set. The test set has been formed by following the procedure described in [152], i.e., the images of set A for the 100 remaining individuals with representation in both sets have been used as the probe set. The gallery set has been formed by 649 images belonging to set B (all images of set B except the 100 corresponding to the training and validation individuals).
- **VIPeR:** this dataset presents 632 pedestrians, each one with representation in both sets. For evaluation, the procedure described in [138] has been followed. The 632 pairs have been randomly grouped into two sets of 316 pairs. One of them has been divided in a proportion of 90% -10% to create the training and validation sets, respectively; and the other set has been used for testing the algorithm. Therefore, the gallery set is formed by 316 images from set A, and the probe set by their matching images from set B.

- **CUHK-02:** The subset P1 of CUHK-02 dataset (CUHK-01) comprises pairs of images of each one of 971 different individuals [201]. The 45% of them (437) were randomly extracted to generate the training set and the 5% (48) for the validation set. The test set has been formed by taken the remaining 486 pairs of images. Therefore, the probe set contains 486 images, and the gallery set their matching images. In addition, the rest of the subsets of CUHK-02 (P2-P5) have been used to pre-train the model. This protocol is defined in [48].
- **GRID:** set A contains 250 different images and set B, 1025 images. 250 of the captured individuals are rendered in both sets (appearing in both views). The 45% of them (112) were randomly extracted to generate the training set and the 5% (13) for the validation set. The test set has been formed by taken the remaining 125 images of set A as probe set, and the gallery set has been formed by their representations on set B and 775 additional images that do not belong to any of the probe images. These extra images should be treated as a fixed portion in the testing set during the test of the methods [214].
- **i-LIDS-VID:** It comprises 300 different individuals, observed across two camera views [335]. To perform the evaluation of the Single-Shot Re-Id method, one image per each person and view has been randomly selected. 135 pairs have been used as the training set, 15 pairs, as validation set, and the remaining 150 pairs as the test set. Therefore, the probe set contains 150 images, and the gallery set their matching images.

For every dataset, those individuals selected as training and validation samples, have been properly combined by the proposed data generation tools (Sections 4.3 and 4.5.1) to generate huge training and validation sets, respectively.

6.2.2 Methodology to Evaluate the Learning Process

The evolution of every training is evaluated, by analysing their learning curves. The learning curve is the representation of the loss function value throughout the learning process, every certain number of learning iterations. This allows checking the model convergence.

Although the proposed models have been trained using only the training set, the learning curve has been rendered for both, the training and the validation set. The model is learnt from the training set samples, for which back-propagation is computed. However, every certain number of learning iterations, forward propagation is also performed for the validation set. In that way, it is possible to observe how good are the predictions given by the model for unknown samples.

Learning curves are a tool to diagnose if a particular learning algorithm may be suffering from high-bias, variance problem or a bit of both.

a) Convergence Checking

The convergence of the Mini-Batch Gradient Descent cannot be guaranteed by an arithmetical method, but experimentally observing the progression of the learning curve of the training process.

The Mini-Batch learning algorithm performs frequent parameters updates with a high variance that cause the objective function to fluctuate heavily, resulting in a learning curve with oscillations. Despite the oscillations, the convergence of the learning algorithms is proved by the decreasing tendency of their learning curves, that eventually are stabilised around a certain value.

If the loss function tends to rise, the learning algorithm is not properly working, and the learning rate, η , must be decreased. For sufficient small η , the loss function should show a decreasing tendency, but if η is too small, the Gradient Descent algorithm can be slow to converge. For that reason, this thesis proposes the use of the Adagrad method [93] to automatically adapt the learning rate value during the learning process. According to that, the learning rate takes a relatively high value in the initial iterations, and then it is progressively decreased to avoid the convergence of the algorithm in a bad local optimum.

Moreover, for neural networks, the loss function is non-convex, so it can theoretically be susceptible to a local minimum. However, in practice learning algorithms, like GD usually achieve a local minimum which is good enough, even if it does not get to the global optimum.

b) Bias-variance diagnosing

The over-fitting of a neural model is also known as high variance problem. On the other hand, if the training suffers from a high bias problem, the model is under-fitted. In order to know what is the problem affecting a certain training process, its learning curve is rendered for both, the training and the validation sets.

If the loss value is high for both sets, the model suffers from under-fitting (high bias). However, if the loss value is low for the training set and high for the validation set, the model is over-fitted (high variance). In that way, the learning curves are an indicator for selecting promising ways to improve the learning algorithm. For example, getting more training data is likely to improve the model performance if the learning algorithm is suffering from high variance, but not if the learning algorithm is suffering from high bias. In such case, a deeper neural network is needed.

In addition, the observation of the learning curves has been used to perform early stopping technique. From each training experiment, a model is taken to evaluate its Re-Id performance. This model is selected according to the early stopping fundamentals. That consists of selecting the model learnt after a certain number of iterations, which is enough to learn discriminative features, but before over-fit the model.

c) Accuracy

In addition, the accuracy of the model has been also estimated during its training. The accuracy is measured as the rate of well-classified pairs.

When the Siamese model is used to train the Re-Id network, the accuracy, $A(X^t)$, measured in a learning iteration, t , for a batch of B pairs, is defined by Eq. 6.1, where $a(X_i^t)$ indicates if the pair i has been correctly classified or not, Eq. 6.2. This equation has been deducted from the N2MCL function, Eq.4.7.

$$A(X^t) = \frac{\sum_{i=1}^B a(X_i^t)}{B} \cdot 100 \% \quad (6.1)$$

$$a(X_i^t) = \begin{cases} 1 & \text{if } |d(m_i, m_1) - y_i| \leq \tau \\ 1 & \text{if } |d(m_i, m_2) - y_i| \leq \tau \\ 0 & \text{otherwise} \end{cases} \quad (6.2)$$

When the Triplet model is employed, two measurements of the prediction accuracy are estimated during the training process. First, hard accuracy metric is the percentage of well-classified triplets over the total, considering as well-classified those triplets where the negative pair distance, $d(m_1, m_2)$, is larger than the positive pair distance, $d(m_1, m_i)$, by a threshold, τ . That means that such triplets do not contribute to the loss function with any cost. The hard accuracy, A_H , calculated at every iteration, t , for a batch of B samples is calculated with Eq. 6.3, where $a_H(X_i^t)$ indicates whether a triplet has been well-classified or not, Eq. 6.4.

$$A_H(X^t) = \frac{\sum_{i=1}^B a_H(X_i^t)}{B} \cdot 100 \% \quad (6.3)$$

$$a_H(X_i^t) = \begin{cases} 1 & \text{if } d(m_1, m_2) > d(m_1, m_i) + \tau \\ 0 & \text{otherwise} \end{cases} \quad (6.4)$$

Second, soft accuracy metric is the percentage of well-classified triplets over the total, considering as well-classified those triplets where the negative pair distance, $d(m_1, m_2)$, is simply larger than the positive pair distance, $d(m_1, m_i)$. The soft accuracy, A_S , calculated at every iteration, t , for a batch of B samples is calculated with Eq. 6.5, where $a_S(X_i^t)$ indicates whether a triplet has been well-classified or not, Eq. 6.6.

$$A_S(X^t) = \frac{\sum_{i=1}^B a_S(X_i^t)}{B} \cdot 100 \% \quad (6.5)$$

$$a_S(X_i^t) = \begin{cases} 1 & \text{if } d(m_1, m_2) > d(m_1, m_i) \\ 0 & \text{otherwise} \end{cases} \quad (6.6)$$

6.2.3 Methodology to evaluate the Re-Id performance

The Re-Id performance of every learnt model has been evaluated over a test set composed by individuals who are different from those belonging to the training and the validation sets.

The test set is formed by two groups of images, the probe and the gallery sets of images. Every probe image renders an individual, who is also rendered by one of the gallery images. Each image of the same person was captured from a different camera view. Moreover, some datasets, such as PRID2011 and GRID (Section 6.2.1), add extra person images to the gallery set. Those are images of individuals without representation on the probe set.

The objective of a certain Re-Id model is to recognise the person rendered by every probe image among all the images of the gallery. For that, every probe image is compared with all the images of the gallery by the evaluated model, which returns the Degree of Appearance Similarity between every pair of images. Then the DoAS values are ranked to evaluate the Re-Id capacity of the model. In that way, the DoAS value is measured for every possible pair of the test set.

The Re-Id performance of the models obtained with the proposed methods has been quantitatively and qualitatively evaluated by the CMC curve, and an error analysis procedure, respectively.

a) Cumulative Matching Characteristic curve

The Cumulative Matching Characteristic (CMC) curve [240] is a standard Re-Id performance measurement that has been calculated to evaluate every conducted experiment.

To obtain the CMC curve, first, every image from the probe set is coupled with all the images from the gallery and the distance metrics, dm , between them are computed. The match presenting the lowest value of dm , i.e. the highest value of DoAS (see Eq. 4.1), is considered as the top match since two images of the same person should be rendered close in the feature space and further from different people representations. The distance metrics, dm , obtained by comparing a probe image with all the gallery set images are ranked. This process is repeated for each one of the probe images. The rank value, i.e. the position of the correct match in the rank, is calculated for each probe image and, subsequently, the percentage in which each rank appears.

Then, the CMC curve renders the expectation of finding the correct match within the top r matches, for different values of r , called ranks. For example, for rank ten, the matching rate measures the expectation of finding the correct match within the top ten matches. The computed percentages are cumulative, so the CMC curve is always increasing since the correct matches found within the top r matches will be also found within the top $r - 1$ matches.

In general, the scores of the CMC curve takes low values. This is due to the intrinsic difficulties imposed by the Re-Id evaluation protocol, where the person rendered in one probe image must be recognised among multiple gallery images. For instance, in PRID dataset, a probe individual must be found among 649 images, and in GRID dataset, among 775 images. All the gallery images

must be ranked in order of decreasing similarity w.r.t. the probe image and the correct match must occupy the first position on the ranking. This is an extremely arduous task, since, even under the human criteria, the probe image can be visually more similar to gallery images from different people than to the corresponding one, because of the inter-class ambiguities and the intra-class variations. For that reason, CMC curves are not comparable to ROC curves 6.3.2, since the first ones renders the ranking capacity of a method instead of its classification capacity.

An appearance Re-Id model can be used as part of a more complex Re-Id mechanism. The appearance model can reduce the search of the image corresponding to a probe image, providing a group of reliable candidates. The rank value provides the conception of how much can be reduced the size of such candidates group.

b) Error Analysis

Error analysis consists of manually examining the examples on which the Re-Id algorithm made errors, with the aim of finding any systematic trend or pattern in what type of examples the model fails. By the process of manually examining the mistakes that the algorithm makes, the most difficult examples to classify for an algorithm can be identified.

This is a method to decide which strategies could improve the method performance, or to define the specifications of the obtained Re-Id model, i.e. the conditions under which it can work.

Two types of error analysis procedures have been implemented. Firstly, to analyse the discrimination capacity of a Re-Id model as a binary classifier, four groups of samples have been visualised:

- True positive samples, TP . Positive pairs that are correctly classified as such.
- True negative samples, TN . Negative pairs that are correctly classified as such.
- False positive samples, FP . Negative pairs that are incorrectly classified as positive ones.
- False negative samples, FN . Positive pairs that are incorrectly classified as negative ones.

FP and FN are to algorithm mistakes, and the error analysis has been conducted over them.

Secondly, to analyse the ranking performance of a Re-Id model, the gallery images are ranked by the model according to their similarity with a certain probe image, and rendered in that order.

6.2.4 Experimental results

This section presents the results obtained of evaluating both, the learning process and the Re-Id performance for each one of the methods developed in this thesis. Each presented learning technique, model, method, layer or architecture has been tested in an experiment, in the order shown by the following list:

- a) Contrastive loss function
- b) Feature embedding
- c) Balancing data
- d) Learning model
- e) Transfer learning
- f) Reduction of neural depth
- g) Triplet Permutation method
- h) Data augmentation
- i) Regularization
- j) Parts-dedicated DCNN
- k) Distance metric
- l) Cross-Re-Id dataset fine-tuning

a) Contrastive loss function

A new Normalised Double-Margin Contrastive loss function, f_{N2MCL} , (Eq. 4.7 and 4.8) has been designed in this thesis (see Section 4.2.2). The same Re-Id model has been learnt using the traditional contrastive loss function, f_{CL} , (Eq. 4.3), and the new one, with and without normalisation, and the obtained results has been compared as follows. Table 6.1 presents the settings of the performed experiments, which only differ in the used loss function.

Table 6.1 Experiments settings to evaluate the effects of different contrastive loss functions.

Experiments	Description	
	Contrastive loss	Other settings
Exp.Contrastive_loss.1	One Margin Contrastive Loss function, f_{CL} , Eq. 4.3	Architecture: three independently learnt part-features (Section 4.8.1). Siamese model. No transfer learning (level 0). Euclidean distance metric. Without data augmentation. L2 regularization, $wd = 0.0005$.
Exp.Contrastive_loss.2	Double-Margin Contrastive Loss function, f_{2MCL} , Eq. 4.7	
Exp.Contrastive_loss.3	Normalised Double-Margin Contrastive Loss function, f_{N2MCL} , Eq.4.7 and 4.8	

Fig. 6.1 shows the learning curves for the training of Exp.Contrastive_loss.1 and Exp.Contrastive_loss.3, using the PRID2011 dataset, to generate the training data.

Fig. 6.1 Loss function evaluated over a validation set of samples throughout the training process: a) using the traditional contrastive loss function, (Eq. 4.3); and b) using the double-margin contrastive loss function, (Eq.4.7).

The Normalised Double-Margin-based Contrastive Loss Function slightly reduces the amplitude of the loss oscillations, and its average value and provides a faster convergence of the learning process, as it was expected due to the reasons given in Section 4.2.2.

In the three listed experiments, the learning of three-dimensional descriptors has been performed, according to the architecture described in Section 4.8.1. The obtained three-dimensional features can be rendered as 3D points in the feature space. Fig. 6.2 represents that points for the test set of images pairs, using the model learnt by both, the traditional Contrastive Loss function and the new one, f_{N2MCL} . In that way, it is possible to visualise the improvement provided by the new loss function on the discriminative capacity of the learnt features.

Fig. 6.2 Three-dimensional representation of learnt descriptors, in green for positive samples, and in red for the negative samples for a test set in the cases of training with: (a) One Margin Contrastive Loss function, (Eq. 4.3), and (b) Double-Margin Contrastive Loss function, (Eq. 4.7).

The point positions for positive samples are nearer the origin than those for the negative ones, proving that the training process has been effectively conducted.

The result of a proper training process is the formation of two separated clusters, those formed by the points representing the positive samples and those rendering the negative ones. The separating boundary between them is a cube, whose dimension is the value of the margin parameter employed in the loss function. Therefore, if the employed loss function is based on only one margin, m , like the traditional contrastive loss function, (Eq. 4.3), the points representing positive samples should be inside a cube of dimension m , and the negatives outside, as Fig. 6.2(a) shows.

If the novel Double-Margin Contrastive Loss function, (Eq.4.7), is employed, the resulting clusters present a bigger separation between them, which means that more discriminative features have been learned. The points representing positive samples should be inside a cube of dimension m_1 , and the negatives outside a larger cube of dimension m_2 , as Fig. 6.2(b) shows.

Moreover, Table 6.2 presents the CMC scores for the three conducted experiments in order to compare the Re-Id performance of the obtained models. The corresponding CMC curves are plotted in Fig. 6.3.

Table 6.2 CMC scores (%) for the models learnt by three different Contrastive Loss functions.

Rank	1	10	20	50	100
Exp.Contrastive_loss.1	1	5	9	19	34
Exp.Contrastive_loss.2	3	15	25	37	56
Exp.Contrastive_loss.3	6	20	26	38	63

Fig. 6.3 CMC curves for the models learnt by three different Contrastive Loss functions.

The use of two margins in the loss function causes remarkable improvement in the performance of the Re-Id method. In addition, the normalisation of the distances considered by that loss function also lightly enhances the obtained results.

The results of the conducted experiments prove how the intermediate step of normalisation and the use of two margins instead of only one allows the learning of more discriminative features in a lower number of learning iterations.

b) Feature embedding

A feature embedding is necessary to get a meaningful representation of a person image, to compare it with others. Table 6.3 exposes the settings of the conducted experiments to evaluate different features embeddings, and Table 6.4 presents the obtained results, over the PRID2011 dataset.

Table 6.3 Experiments settings to evaluate different feature embeddings.

Experiments	Description	
	Feature embedding learning	Other settings
Exp.Feature.3parts	Three independently learnt part-features (Section 4.8.1)	Siamese model. 1 : 1 proportion of positive over negative samples. No transfer learning. Euclidean distance metric. Without data augmentation. Triplet model Permutation of triplets II Transfer learning (level 3) Euclidean distance metric Data augmentation
Exp.Feature.9parts	Nine jointly learnt part-features (Section 4.8.2)	
Exp.Feature.DCNN.1	An unique Deep Convolutional Neural Network (VGG16)	
Exp.Feature.DCNN.2	An unique Deep Convolutional Neural Network (VGG11)	

Table 6.4 CMC scores (%) for different feature embeddings, over PRID2011 dataset.

Rank	1	10	20	50	100
Exp.Feature.3parts	6	20	26	38	63
Exp.Feature.9parts	2	10	18	31	50
Exp.Feature.DCNN.1	1	1	4	14	22
Exp.Feature.DCNN.2	8	39	46	63	79

Firstly, two different training models based on human shape partition have been designed to perform the learning of a feature embedding. The performance of the parts extractor module, used in Exp.Feature.9parts, is poor when the inputs images have a low resolution. That's the case of the Re-Id samples (see Table 3.1). Consequently, the parts extraction stage often badly finds

each human part on the images, so the neural model on Exp.Feature.9parts is wrongly fed. For that reason, the results of this experiment are not so good as it was expected (Section 4.8.2).

On the other hand, Exp.Feature.3parts performs three independent training process to obtain a person feature embedding, so the training time is highly enlarged. Consequently, once the three models have been learnt, three features of every image must be computed to perform Re-Identification, so the computation time is also increased, which is an important disadvantage in a real-time application. To overcome these drawbacks, two new objectives were stabilised:

- Automatically learning salient regions and features in a person's image.
- Jointly learning a unique feature embedding.

The CNNs employed by Exp.Feature.3parts and Exp.Feature.9parts are too simple to achieve these aims. Instead of that, DCNNs are adopted, with a higher number of layers. Therefore, the human partition stage is supplanted by the adding of more neural layers, and a new embedding is modelled by means of deep learning.

A prior experiment, Exp.Feature.DCNN.1, where the learning algorithm and training data was identical to that used in Exp.Feature.3parts and Exp.Feature.9parts, was conducted to train a DCNN. The obtained results were really poor, as Table 6.4 shows. These results are due to the over-fitting problem, caused by the larger number of parameters too train. For that reason, research on new methods, techniques and layers formulations are needed.

Finally, in Exp.Feature.DCNN.2, the developed methods were applied, resulting in a remarkable improvement in the performance. The setting of this experiment has been determined through the analysis of multiple previous experiments which are described in the following sections.

It is necessary to mention that some techniques, as transfer learning from MOT domain, have been also tried to train the nine parts-based model. However, the parts extractor cannot cope with the low resolution of many of the detections in MOT sequences, making unfruitful this strategy.

c) Balancing data

A data generation tool has been designed to create training sets of pairs of images. This tool enables the selection of the proportion of positive against negative pairs. Two identical experiments have been conducted to train a Re-Id model. One of them uses a completely balanced training set (1 : 1 proportion) and the other one, a partially balanced set (1 : 4), as Table 6.5 describes.

Table 6.6 presents the CMC scores obtained from the mentioned experiments, and Fig. 6.4 their corresponding CMC curves, in ease of exposition.

Table 6.5 Experiments settings to evaluate the effects of balancing the training data.

Experiments	Description	
	Balancing setting	Other settings
Exp.Balancing.1:1	1 : 1	VGG16 architecture (Table 4.1). Siamese model. Transfer learning (level 3). Euclidean distance metric. Without data augmentation. L2 regularization, $wd = 0.0005$.
Exp.Balancing.1:4	1 : 4	

Table 6.6 CMC scores (%) of models trained on two balance settings from PRID2011 and VIPeR dataset.

Dataset	PRID2011						VIPeR					
Rank	1	5	10	20	50	100	1	5	10	20	50	100
Exp.Balancing.1:1	0	2	2	10	19	33	5	12	17	24	38	57
Exp.Balancing.1:4	0	4	9	13	19	27	4	13	17	26	42	60

Fig. 6.4 CMC curves for the use of two balancing settings from a)PRID2011 and b)VIPeR dataset.

During the test, the Re-Id network must identify a person among a huge number of negative samples. However, the training of the network, with such a small proportion of positives samples over negatives ones, would be dominated by the negative samples. On the other hand, the relation 1 : 1 (same number of positive and negative pairs), differs too much from the target task, where the model has to deal with the unbalanced data. For that reason, a model trained on a partially balanced training set (1 : 4 proportion) works better than if it is trained on an absolutely balanced set, as the results have proved.

However, when transfer learning is not employed in the experiments, the learning process evolves in a different way. If the training set created with a 1 : 4 proportion from Re-Id datasets (PRID2011 or VIPeR) is directly used to train a network that has not been pre-trained in other domain, the model is collapsed. When the model embedding has been pre-trained, the created partially balanced training set is able to fine-tune the model. However, this is not able to start to learn a Re-Id model from the beginning, since a partially balanced set leads the learning algorithm to obviate the contribution of that type of pair which is fewer in number (the positive samples) to the loss function. Fig. 6.5 shows the learning curve and the accuracy (Section 6.2.2.c) for the training and the validation set during the learning process.

Fig. 6.5 Learning curve and soft accuracy during the training with a proportion of 1 : 4 positive over negative samples.

The collapsed model learns to classify all the training samples as negative samples. Given the training set presents 80% of negative samples, this is the value of the training accuracy since all the negative samples are well-classified. However, for the unknown samples from the validation set, the accuracy only achieves 20%. Moreover, the loss tendency is constant and almost invariably due to the learning is collapse and it does not evolve. The graphics obtained for the learning on PRID2011 and VIPeR dataset are identical.

d) Learning model

Two experiments have been conducted to compare the performance of the Siamese learning model against the Triplet model. The experiments settings are exposed in Table 6.7.

Table 6.7 Experiments settings to evaluate the effects of Siamese and Triplet model.

Experiments	Description			
	Learning model	Feeding	Loss	Other settings
Exp.Siamese	Siamese	1 : 4 balance	N2MCL function, f_{N2MCL} , Eq. 4.7 and 4.8	VGG16 architecture. Transfer learning (level 3). Euclidean distance metric. Without data augmentation. L2 regularization, $wd = 0.0005$.
Exp.Triplet	Triplet	Permutation of triplets I	Triplet loss, f_L , Eq. 4.22	

Table 6.8 presents the CMC scores of the models learnt with the shown experiment settings, and Fig. 6.6 their corresponding CMC curves, in ease of exposition.

Table 6.8 CMC scores (%) for neural networks trained with two learning models on PRID2011 and VIPeR dataset.

Dataset	PRID ₂₀₁₁						VIPeR					
Rank	1	5	10	20	50	100	1	5	10	20	50	100
Exp.Siamese	0	4	9	13	19	27	4	13	17	26	42	60
Exp.Triplet	4	14	20	33	58	77	11	35	54	69	90	96

Fig. 6.6 CMC curves for the use of two learning models over a)PRID2011 and b)VIPeR dataset.

The triplet model offers remarkably better results. In addition, the Triplet loss function presents smaller oscillations through the learning process, causing a faster convergence, as Fig. 6.7 shows.

The relative essence of the comparison made by the triplet loss function makes it more effective for ranking problems, such as Person Re-Identification, as it was discussed in Section 4.4.4.

Fig. 6.7 Learning curves for Siamese and Triplet model over PRID2011 and VIPeR datasets.

e) Transfer learning

Transfer learning from MOT to Re-Id domain has been proposed (see Section 4.7). Six different levels of transfer learning have been conducted over two different Re-Id datasets, PRID2011 and VIPeR dataset. Therefore, twelve different final models have been obtained and evaluated.

The settings of the performed and compared experiments are shown in Table 6.9. The experiments have been enumerated according to the level of learning transference applied in each one. The experiments settings only differ in the transfer level, which is the parameter to evaluate.

Figs. 6.8 and 6.9 show the learning curve for the level 0 and 4 of transfer learning, using as target dataset the PRID2011 and VIPeR dataset, respectively. The curves plot the loss value, f_L , thorough the learning iterations, it . Although the proposed algorithm has been trained only using the training set, the loss value, for both the training and the validation sets, has been represented, in blue and orange respectively.

Table 6.9 Experiments settings to evaluate transfer learning technique.

Experiments	Description	
	Transfer level	Other settings
Exp.Transfer_level.o	o	VGG16 architecture. Triplet model. Permutation of triplets I. Euclidean distance metric. Without data augmentation. L2 regularization, $wd = 0.0005$.
Exp.Transfer_level.1	1	
Exp.Transfer_level.2	2	
Exp.Transfer_level.3	3	
Exp.Transfer_level.4	4	
Exp.Transfer_level.5	5

Fig. 6.8 Learning curves for level 0 and 4 of transfer learning, using PRID2011 as target dataset.

Fig. 6.9 Learning curves for level 0 and 4 of transfer learning, using VIPeR as target dataset.

In Exp.Transfer_level.o, the model has been trained and tested in the target dataset, so no domain adaptation is performed. Because of the small number of samples on the target dataset (especially the number of positive samples), this model suffers from over-fitting. The training loss strongly decreases, so the model is converging, but the validation loss increases since the model do

not generalise with the unknown samples from the validation set. This difference between both loss values indicates that the model is over-fitted.

Conversely, the problem in level 5 is that the model has been trained on an auxiliary dataset that, despite having a huge number of samples, they were not captured from two different views. Consequently, the model is not able to learn a feature robust against the intra-class variations.

On the other hand, in level 3 and 4, all the weights pre-trained in the source dataset have been transferred to the model. Then, in level 3 all the layers have been fine-tuned with the target dataset and, in level 4, whose learning curve is shown in the Figs.6.8 and 6.9, only the final 9 layers. Hence, firstly the model has been trained to extract low-level features from many samples of people from MOT sequences, and secondly, high-level representations have been learnt by fine-tuning with the target dataset. The target dataset allows the model to learn features able to deal with the intra-class variations and inter-class ambiguities, which is inherent to the Re-Id task.

In addition, the model over-fitting is reduced by pre-training in a larger auxiliary dataset, as Figs.6.8 and 6.9 show, which is reflected in the reduction of the validation loss.

Table 6.10 lists the CMC scores for the models learnt over the PRID2011 and VIPeR dataset by applying different transfer learning levels and Fig.6.10 renders them, in ease of exposition.

Table 6.10 CMC scores (%) for six levels of transfer learning, over PRID2011 and VIPeR.

Dataset	PRID2011						VIPeR					
Rank	1	5	10	20	50	100	1	5	10	20	50	100
Exp.Transfer_level.0	2	7	10	20	30	52	6	16	26	39	69	88
Exp.Transfer_level.1	2	8	18	27	46	65	10	32	48	64	80	93
Exp.Transfer_level.2	2	8	11	17	34	59	11	31	48	67	83	95
Exp.Transfer_level.3	4	14	20	33	58	77	11	35	54	69	90	96
Exp.Transfer_level.4	2	12	23	29	47	75	10	33	50	70	90	95
Exp.Transfer_level.5	2	6	7	14	29	42	5	17	25	38	58	75

Fig. 6.10 CMC curves for six levels of transfer learning, over a) PRID2011 and b) VIPeR dataset.

In general, both graphics show that the extreme levels 0 and 5 present the worst results and the intermediate levels 3 and 4, the best scores. Concretely the best performance is achieved when all the network layers are pre-trained in the source dataset and fine-tuned in the target one. This is what level 3 of learning transference performs.

In conclusion, the models that have been obtained by transferring learning clearly outperform the models directly learnt on the Re-Id dataset. This result can be taken as proof of concept to verify that transfer learning can be exploited to solve the Re-Id data problem.

f) Reduction of neural depth

In order to evaluate the effects of reducing the depth of the trained DCNN, two similar architectures, VGG16 and VGG11 which are differently layered, has been tested (see Section 4.1). An experiment has been conducted to train each one of them, as Table 6.11 shows, where the rest of settings are also depicted. The experiments have been named according to the depth of the learnt model.

Table 6.11 Experiments settings to evaluate the effects of reducing the neural depth.

Experiments	Description	
	Architecture	Other settings
Exp.Depth.16	VGG16	Triplet model. Permutation of triplets I. Transfer level 3. Euclidean distance metric. Without data augmentation. L2 regularization, $wd = 0.0005$.
Exp.Depth.11	VGG11	

Figs.6.11 and 6.12 render the learning curve, and accuracy graphics for experiments Exp.Depth.16 and Exp.Depth.11, over PRID2011 and VIPeR dataset, respectively. The reduction of the number of parameters to train decreases the degree of over-fitting. For that reason, the validation loss is lower for VGG11 architecture, which has a lower number of layers, than for VGG16 network. This happens for both PRID2011 and VIPeR datasets. Especially in PRID2011, this over-fitting reduction is accompanied by a notable increase in the validation accuracy.

Fig. 6.11 Comparison of the learning process evolution for two DCNNs architectures (VGG16 and VGG11) over PRID2011 dataset.

Table 6.12 presents the CMC scores obtained from the training of two different neural architectures on PRID2011 and VIPeR datasets, and Figs. 6.13 and 6.14 render their corresponding CMC curves. In both figures, part (a) renders 100 ranks scores, and part (b) the first 25 ranks scores, in detail.

Table 6.12 CMC scores (%) for different DCNN architectures trained on PRID2011 and VIPeR datasets.

Dataset	PRID2011						VIPeR					
Rank	1	5	10	20	50	100	1	5	10	20	50	100
Exp.Depth.16	4	14	20	33	58	77	11	35	54	69	90	96
Exp.Depth.11	4	16	25	32	58	73	13	36	52	73	86	95

Fig. 6.12 Comparison of the learning process evolution for two DCNNs architectures (VGG16 and VGG11) over VIPeR dataset.

Fig. 6.13 CMC curves for different DCNN architectures trained on PRID2011 dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).

Fig. 6.14 CMC curves for different DCNN architectures trained on VIPeR dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).

In the first ranks, which are the more crucial ones, VGG_{II} architecture presents slightly better results. The reduction of the number of parameters helps to prevent over-fitting, producing better Re-Id scores. Although the improvement is not remarkable, the selection of a less-layered network reduces not only the training time but also the computation time.

Moreover, a third experiment, called Exp.Depth.11.LRN, has been conducted over the PRID₂₀₁₁ and VIPeR datasets to evaluate the effects of include a LRN cell, in the VGG_{II} architecture. This experiment is identical to Exp.Depth.11. but using the VGG_{II}LRN neural architecture (Section 4.6.4). Table 6.13 compares the obtained CMC scores and Figs.6.15 and 6.16 render their corresponding CMC curves. In both, part (a) renders 100 ranks scores, and part (b) the first 25.

Table 6.13 CMC scores (%) of VGG_{II} with and without LRN, over PRID₂₀₁₁ and VIPeR dataset.

Dataset	PRID ₂₀₁₁						VIPeR					
Rank	1	5	10	20	50	100	1	5	10	20	50	100
Exp.Depth.11	4	16	25	32	58	73	13	36	52	73	86	95
Exp.Depth.11.LRN	6	17	23	32	50	77	12	35	52	69	89	95

Fig. 6.15 CMC curves for VGG_{II} model with and without LRN cell over PRID₂₀₁₁ dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).

Fig. 6.16 CMC curves for VGG11 model with and without LRN cell over VIPeR dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).

The Re-Id scores resulting from adding LRN to the VGG11 architecture are quite similar to the original ones. Given that the obtained improvement is not remarkable, the use of an extra normalisation layer has been discarded in order to favour a simpler feature embedding.

g) Triplet Permutation method

The Triplet Permutation method has been designed to generate huge training sets of triplet samples. Three sets have been created from the same set of person images but the way in which they are combined to create triplets is different according to three different formulations to perform Triplet Permutation, exposed in Section 4.5.1. In order to evaluate each formulation, an experiment has been conducted using each one of the generated sets to train the Re-Id model. For that reason, the experiments are enumerated according to the used permutation formulation. The experiments settings are listed in Table 6.14.

Table 6.14 Experiments settings to evaluate the Triplet Permutation method.

Experiments	Description	
	Triplet permutation	Other settings
Exp.Permutation.1	Set I (Eq. 4.34)	VGG11 architecture. Triplet model. Transfer level 3. Euclidean distance metric. Without data augmentation. L2 regularization, $wd = 0.0005$.
Exp.Permutation.2	Set II (Eq. 4.35)	
Exp.Permutation.3	Set III (Eq. 4.36)	

Figs. 6.17 and 6.18 present the learning curve, and accuracy graphics for the listed experiments over PRID2011 and VIPeR dataset, respectively. Fig. 6.17 shows how the triplet permutation performed in Exp.Permutation.2 and Exp.Permutation.3 does not seem to produce any improvement,

but just the opposite effect. And in Fig. 6.18, the training set II and III lightly reduce the loss value and increase the accuracy metric, but no remarkable improvement is observed. That is because both sets, training and validation sets, have been created using the same triplet permutation technique at every experiment. In that way, with Triplet Permutation, the network is trained with a larger variety of triplets but also evaluated over a larger variety of situations.

In order to get an objective comparison, the Re-Id performance of these experiments have been evaluated over the same Re-Id test set, proving that the best results are provided by training set II. Table 6.15 presents the results offered by the sets created from PRID2011, and VIPeR dataset. Figs.6.19 and 6.20 render their corresponding CMC curves.

Fig. 6.17 Comparison of the learning process evolution using training sets I, II and III over PRID2011 dataset.

Fig. 6.18 Comparison of the learning process evolution using training sets I, II and III over VIPeR dataset.

Table 6.15 CMC scores (%) for models trained on sets generated by different Triplets Permutation formulations from PRID2011 and VIPeR dataset.

Dataset	PRID2011						VIPeR					
Rank	1	5	10	20	50	100	1	5	10	20	50	100
Exp. Permutation.1	4	16	25	32	58	73	13	36	52	73	86	95
Exp. Permutation.2	8	19	26	33	55	77	14	35	54	71	89	95
Exp. Permutation.3	7	17	24	35	53	75	13	36	52	71	89	94

Fig. 6.19 CMC curves of models trained with different Triplets Permutation formulations from PRID2011 dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).

Fig. 6.20 CMC curves of models trained with different Triplets Permutation formulations from VIPeR dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).

In general, for PRID2011 and VIPeR dataset, in the first ranks, Exp. Permutation.2, corresponding to training set II, presents the highest scores. The reason is that the number of triplets combination created from the same person images is augmented with respect to training set I. This augmentation reduces the over-fitting. However, although the number of triplets obtained in training set III is larger, this does not improve the algorithm performance. The reason is that training set III contains triplets in which negative pairs are formed with images from the same view and this situation never happens in the test set.

In conclusion, the augmentation of training samples increases the model performance, as long as, the training samples conditions are similar to the test conditions. Otherwise, the model would be trained for a task with different specifications.

h) Data augmentation

Four different experiments have been conducted to evaluate the effects of the implemented data augmentation methods (Section 4.5.3). In each one of them, the Re-Id model is learnt by adding

a different data augmentation technique, or none of them, as Table 6.16 describes. This table lists the settings of the compared experiments, which only differ in the data augmentation method. Figs. 6.21 and 6.22 show the learning evolution for the presented experiments, over PRID2011 and VIPeR dataset, respectively.

Table 6.16 Experiments settings to evaluate three data augmentation methods.

Experiments	Description	
	Data augmentation method	Other settings
Exp.Augmentation.0	Without data augmentation	VGG11 architecture. Triplet model. Transfer level 3. Permutation of triplets II. Euclidean distance metric. L2 regularization, $wd = 0.0005$.
Exp.Augmentation.1	Data augmentation I (Cropping)	
Exp.Augmentation.2	Data augmentation I and II (Cropping and mirroring)	
Exp.Augmentation.3	Data augmentation I, II and III (Cropping, mirroring and colour modification)

Fig. 6.21 Comparison of the learning process evolution using data augmentation techniques I, II and III over PRID2011 dataset.

Fig. 6.22 Comparison of the learning process evolution using data augmentation techniques I, II and II over VIPeR dataset.

Fig. 6.21 shows how the over-fitting (the difference between training and validation loss) is reduced by data augmentation. The results are similar for the three data augmentation techniques. However, the accuracy level in the validation set is slightly higher for experiment Exp. Augmentation.1. In this experiment, the cropping method is employed. In contrast to mirroring and colour modification (used in Exp. Augmentation.2 and Exp. Augmentation.3), which notably modifies the background, cropping slightly alters, or shifts, the background of the images. When the background is not homogeneous, mirroring can cause large modifications in the values of some pixel positions, and colour modification directly alters the value of all of them.

Using Re-Id datasets where each images set is captured from a fixed camera, like PRID2011, the network ends up learning that exist a set of pixels positions, with similar values in all the samples belonging to the background that must not be considered in the discrimination task. For that reason, data augmentation techniques that do not modify the background characteristics with respect to the those presented by the test samples produce better results, since a certain alignment and similarity among the background pixels can be established.

In contrast, VIPeR dataset presents more variety of points of view from which the images were captured. This variety is also present in the test dataset and for that reason, a wider variety

of images in the training set reduces the over-fitting of the model without decreasing its Re-Id performance on the test set. Fig. 6.22 shows quite similar graphics for all the data augmentation experiments, so, a better performance comparison is given by the CMC scores of the models.

Table 6.17 presents the CMC scores for the listed experiments, over PRID2011 and VIPeR dataset, and Figs. 6.23 and 6.24 render their corresponding CMC curves.

Table 6.17 CMC scores (%) for models learnt by applying different data augmentation techniques over PRID2011 and VIPeR dataset.

Dataset	PRID2011						VIPeR					
Rank	1	5	10	20	50	100	1	5	10	20	50	100
Exp.Augmentation.0	8	19	26	33	55	77	14	35	54	71	89	95
Exp.Augmentation.1	12	28	39	46	66	79	14	40	54	68	89	95
Exp.Augmentation.2	5	27	38	48	56	71	15	42	58	74	90	97
Exp.Augmentation.3	3	24	30	38	61	78	18	43	57	73	91	97

Fig. 6.23 CMC curves of models learnt by applying different data augmentation techniques on PRID2011 dataset, for the first 100 ranks (a), and detailed for the first 25 ranks (b).

Fig. 6.24 CMC curves of models learnt by applying different data augmentation techniques on VIPeR dataset, for the first 100 ranks (a), and detailed for the first 25 ranks (b).

In general, for both datasets, data augmentation increases the Re-Id performance. However, in PRID2011 dataset, the use of colour modification, which is included in Exp.Augmentation.3, reduces the model performance. There are no large changes in illumination conditions for the sets of images of PRID2011 dataset, so introducing samples remarkably different from the test samples, as the colour modification does, can damage the final model performance.

In contrast, VIPeR dataset presents more variety of camera points of view, from which the images were captured, even in the test images. Hence, Exp.Augmentation.3, which includes the three described data augmentation techniques (cropping, mirroring and colour modification), present the highest CMC scores, especially in the first ranks.

PRID2011 and VIPeR datasets are two representative examples of the cases of having two fixed cameras, or multiple views of data acquisition, respectively. Through the conducted experiments, it is concluded that, although generally, data augmentation decreases the over-fitting, introducing samples remarkably different from the test samples can damage the final model performance.

i) Regularization

With the aim of tuning the weight decay hyper-parameter and evaluating different loss regularization methods, a battery of experiments has been conducted and tested. These experiments settings are listed in Table 6.18. These experiments differ one of each other in the type of used regularization term (L_2 or L_1) and the weight decay, wd , value (Section 4.6.1).

Table 6.18 Experiments settings to evaluate the effects of different regularization methods.

Experiments	Description		
	Regularization term	Weight decay	Other settings
Exp.Regularization.1	L_2	wd 0 0005	VGG11 architecture. Triplet model. Transfer level 3.
Exp.Regularization.2		wd 0 001	
Exp.Regularization.3	L_1	wd 0 0005	Permutation of triplets II. Euclidean distance metric. Data augmentation.*
Exp.Regularization.4		wd 0 000002	

* Data augmentation method I has been used to train and test the Re-Id model over PRID2011 dataset, and data augmentation methods I, II and III have been used to train and test the Re-Id model over VIPeR dataset.

Therefore, in order to choose the regularization type to implement, different regularization experiments have been performed, and their learning curves are presented by Figs. 6.25 and 6.26 for PRID2011 and VIPeR datasets, respectively.

Fig. 6.25 Comparison of the learning process evolution using L2 and L1 regularization with different weight decay values, wd , over PRID2011 dataset.

The weight decay, wd , is a regularization parameter that sets the trade-off between the learning of the weights and their penalisation to prevent from over-fitting. Hence, the weight decay is a hyper-parameter to tune; and to choose its value, the learning curves resulting from using different values must be analysed.

In the first experiment, L2 regularization with $wd = 0.0005$ has been employed. There are no notable changes for different values of wd in L2 regularization because L2 regularization is not able to select features. Even the regularization effect is larger for a bigger value of wd , this is not enough to deal with the huge over-fitting produced in the training of a really deep neural network on a small Re-Id dataset. For that reason, it is necessary to perform features selection to simplify the model by obviating some of its parameters. This is possible with L1 regularization.

Figs. 6.25 and 6.26 shows how L1 regularization decreases the differences between the training and the validation results, which implies an over-fitting reduction. However, the third column shows a remarkable increase in the loss value in the training set and a decrease in its accuracy. That means that the regularization parameter is too big, so its effect, and consequently, the selection of

features is too strong, i.e. most of the parameters are being penalised and forced to take null values, so the resulting model is too simple. This produces a high bias problem, so, wd must be reduced.

In addition, since in most cases, weights are small numbers $W \ll 1$, the L2 norm of the weights is significantly smaller than their L1 norm. Thus, to use L1 regularization, weight decay value has to be tuned to a significantly smaller value. In the fourth column of Figs. 6.25 and 6.26, the correction of the high bias problem can be observed.

Eventually, high accuracy is obtained for the training and the validation set, proving the correct learning of the model and the increase in its capacity to generalise with unknown samples. However, a certain gap between the training accuracy values and those for the validation set is still existing. The accuracy on the training data is an upper limit on the accuracy that is expected to achieve on the validation data since the algorithm has been trained for the training examples specifically.

Fig. 6.26 Comparison of the learning process evolution using L2 and L1 regularization with different weight decay values, wd , over VIPeR dataset.

After tuning the regularization type and parameter by using the presented battery of experiments, the Re-Id performance of Exp.Regularization.1 has been compared with Exp.Regularization.4.

Table 6.19 presents the CMC scores obtained from these experiments from PRID2011 and VIPeR dataset, and Figs.6.27 and 6.28 render their corresponding CMC curves. In both figures, part (a) renders 100 ranks scores, and part (b) the first 25 ranks scores in detail.

The selection of features performed by L_1 regularization helps to prevent from over-fitting, providing the Re-Id performance improvement with respect to the previously employed L_2 regularization, as Figs.6.27 and 6.28 shows.

Table 6.19 CMC scores (%) for models learnt by applying different regularization settings on PRID2011 and VIPeR dataset.

Dataset	PRID2011						VIPeR					
Rank	1	5	10	20	50	100	1	5	10	20	50	100
Exp.Regularization.1	12	28	39	46	66	79	18	43	57	73	91	97
Exp.Regularization.4	11	25	37	51	62	78	19	42	59	75	92	98

Fig. 6.27 CMC curves of models learnt by applying different regularization settings on PRID2011 dataset, for the first 100 ranks (a), and detailed for the first 25 ranks (b).

Fig. 6.28 CMC curves of models learnt by applying different regularization settings on VIPeR dataset, for the first 100 ranks (a), and detailed for the first 25 ranks (b).

j) Parts-dedicated DCNN

Through the experiments described in the last subsections, the Re-Id performance has been improved, in order to achieve the goal of automatically learn a feature embedding by means of Deep Convolutional Neural Networks (DCNNs), proposed in subsection 6.2.4. Once deep learning techniques have been developed, these have been applied over a new embedding. This embedding divides the input into three parts to take advantage of body partitioning (Section 4.8), but jointly learns the parts features to provide a unique embedding. Hence, each part feature is modelled by a DCNN, whose training is optimised by the developed techniques.

To compare the Re-Id performance of this embedding and the VGG11 architecture, previously used, two experiments have been conducted, which are described by Table 6.20. Table 6.21 presents the CMC scores obtained from these experiments over PRID2011 and VIPeR dataset, respectively, and Figs. 6.29 and 6.30 render their corresponding CMC curves. In both figures, part (a) renders 100 ranks scores, and part (b) the first 25 ranks scores in detail.

Table 6.20 Experiments settings to evaluate the effects of partitioning the human shape.

Experiments	Description	
	Embedding	Other settings
Exp.DCNN	An unique deep convolutional neural network (VGG11)	Triplet model. Transfer level 3. Permutation of triplets II. Euclidean distance metric.
Exp.PartsDCNN	Three jointly learnt part-features (Section 4.8.3)	Data augmentation. ¹ Regularization. ²

¹ Data augmentation method I has been used to train and test the Re-Id model over PRID2011 dataset, and data augmentation methods I, II and III have been used to train and test the Re-Id model over VIPeR dataset.

² L2 regularization ($wd = 0.0005$) is used to train and test the Re-Id model over PRID2011 dataset, and L1 regularization ($wd = 0.000002$) has been used to train and test the Re-Id model over VIPeR dataset.

Table 6.21 CMC scores (in [%]) for DCNN models with and without parts partition on PRID2011 and VIPeR dataset.

Dataset	PRID ₂₀₁₁						VIPeR						
Rank	1	5	10	20	50	100	1	5	10	20	50	100	
Exp.DCNN	12	28	39	46	66	79	19	42	59	75	92	98	
Exp.PartsDCNN	10	28	40	49	66	79	20	46	62	78	90	96

Fig. 6.29 CMC curves of DCNN models with and without parts partition on PRID2011 dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).

Fig. 6.30 CMC curves of DCNN models with and without parts partition on VIPeR dataset, for the first 100 ranks in (a), and detailed for the first 25 ranks in (b).

No significant improvement is obtained over PRID2011 dataset. However, the performance over VIPeR dataset is increased by the use of a DCNN embedding based on image partition. This is due to the fact that the range of poses and views presented by VIPeR dataset is wider than those in PRID2011 dataset, where two fixed camera views are used. The three-parts-based embedding makes easier the task of re-identifying people across very different perspectives, with high view variations.

k) Distance metric

With the previously presented methods, remarkable improvements have been obtained in the Re-Id performance over the VIPeR dataset. Some of the developed methods do not cause such beneficial effects over the Person Re-Identification 2011 (PRID2011) dataset. This is due to the different Re-Id scenarios presented by these datasets. VIPeR dataset contains images acquired from

multiple camera views. In contrast, PRID2011 was captured from a fixed camera pair. For that reason, augmenting the variety of training data not always helps in this Re-Id setting.

Mahalanobis matrix has been used to code the view-to-view transitions between two camera views, in order to also get improvements on Re-Id scenarios where the pair of cameras is fixed, as the presented by PRID2011 dataset. PRID2011 is composed by two sets of person images, captured from two fixed camera views with notable differences in camera parameters, illumination, person poses, and background, so this allows to test the capacity of the proposed Mahalanobis matrix learning for embedding the view-to-view variations.

With the aim of comparing the performance of different Mahalanobis matrix estimation methods and the use of the Mahalanobis distance as the Re-Id distance metric with respect to the Euclidean distance, a battery of experiments has been conducted and tested. The setting of these experiments are described in Table 6.22.

Table 6.22 Experiments settings to evaluate different distance metrics and methods to learn them.

Experiments	Description		
	Distance metric	Mahalanobis matrix estimation method	Other settings
Exp.Mahalanobis.1	Mahalanobis	Queues-based method (Section 4.9.1)	VGG11 architecture. Triplet model. Transfer level 3. Permutation of triplets I. Data augmentation I. L2 regularization, wd 0.0005.
Exp.Mahalanobis.2		EWMA-based method (Section 4.9.1)	
Exp.Mahalanobis.3		Mahalanobis matrix learning (Section 4.9.2)	
Exp.Euclidean	Euclidean		

Fig.6.31 shows the learning curve and accuracy graphic for the three experiments that use Mahalanobis distance, over PRID2011 dataset. The evolution of the learning process is analysed by observing Fig. 6.31. In the two first experiments, the Mahalanobis Matrix has been estimated with an adaptive process of data analysis, conducted in every learning iteration, which considers the discriminative information given by the samples labels to create two different features spaces. One of the features spaces represents the similarity class and the other the dissimilarity class, and from both, the covariance matrices have been computed and used to code the view-to-view transformations (see Section 4.9.1).

Exp.Mahalanobis.1 uses queues with a length of $K = 1000$, and Exp.Mahalanobis.2 uses the EWMA formulation with $\alpha = 0.94$. The number of analysed triplets at every iteration is 64 ($B = 64$). The queues save the data processes along approximately 16 iterations ($1000/64 = 16$).

since each one of the sets P and P are formed by B pairs. To make a fair comparison of the methods, γ has been set (0.94) to obtain a scope, γ , of the computed averages of roughly 16 iterations (see Eq. 4.93).

Fig. 6.31 Comparison of the learning process evolution using different Mahalanobis distance learning methods, over PRID2011 dataset.

For the first experiment, a change in the behaviour can be observed in both graphics at iteration 60 000. The reason is that 60 000, is the value of the iteration threshold, T_i , taken by the connection function, defined by Eq. 4.100. From that iteration, the Mahalanobis distance is used as metric distance, dm , to feed the loss function, Eq. 4.100, instead of the Euclidean distance, previously used. Even though the validation loss is increased from this iteration, the Re-Id accuracy is also increased, so a higher number of samples are well-classified by the Mahalanobis distance, although their cost value is higher. In Exp.Mahalanobis.2 the use of the Mahalanobis distance produces larger oscillations in the loss and accuracy value. This is due to the adaptation of the Mahalanobis matrix elements through its estimation process.

The estimation of the covariance matrices by the EWMA method results in better learning of both, the person features and the distance to compare them. This is due to the fact that this method considers the data from previous iterations, but giving more importance to the recent ones, allowing a more efficient updating of the Mahalanobis matrix. In addition, this estimation method requires less computational memory space.

Finally, in Exp.Mahalanobis.3, Mahalanobis matrix is learnt as the set of parameters of a neural layer, by means of the vectorized implementation of its forward and backward propagation. It approach reduces the amplitude of the oscillations and a softer but continuously decreasing trend is observed for the loss value and an increasing trend for the accuracy value. This behaviour indicates that the Mahalanobis distance is being well learnt. Moreover, the gap between both losses (training and validation) is continuously reduced. This means that the algorithm is able to give a more generalised solution for unknown samples. Although the over-fitting is lightly appalled, there is still a gap between the training and validation losses, which should be ideally reduced.

The Mahalanobis learning method applied in Exp.Mahalanobis.3 is a really slow method since more than a million iterations have been conducted until observing a certain stabilisation of the loss value. To speed up this learning a triplets selection layer has been added before the loss function (see Section 4.4.3). This layer does not produce any effect on the Re-Id performance of the model but accelerates its training. This can be observed in Fig. 6.32, where the learning curves obtained with and without the selection layer are shown.

To provide a fair comparison, the selection layer is not applied in the validation. When the selection layer is used to train the model, the validation loss decreases from 0.8 to 0.4 in 25 000 iterations. A million iterations are needed to produce that effect when triplet selection is not used.

Fig. 6.32 Comparison of the learning curves using (a) or not (b) the triplets selection layer.

The Re-Id model cannot be only evaluated from its discriminative accuracy. In addition, its ranking ability must be measured. For that reason, the CMC scores given by the listed experiments are presented in Table 6.23. The best performance is achieved by the Mahalanobis matrix learning method (Exp.Mahalanobis.3), which back-propagates the correction of the elements of the matrix.

In addition, the performance of Exp.Mahalanobis.3 is compared with that for Exp.Euclidean, with the aim of comparing the use of two different distance metrics. The results are given in Table 6.24 and their corresponding curves are rendered in Fig.6.33 for visual comparison.

Table 6.23 CMC scores (in [%]) for models learnt by applying different Mahalanobis estimation methods on PRID2011 dataset.

Rank	1	5	10	20	50	100
Exp.Mahalanobis.1	8	22	33	42	60	77
Exp.Mahalanobis.2	13	23	28	41	54	70
Exp.Mahalanobis.3	13	31	41	47	63	82

Table 6.24 CMC scores (in [%]) for models using Euclidean and Mahalanobis distance metric on PRID2011 dataset.

Rank	1	5	10	20	50	100
Exp.Euclidean	12	28	39	46	66	79
Exp.Mahalanobis.3	13	31	41	47	63	82

Fig. 6.33 CMC curves of models using Euclidean and Mahalanobis distance on PRID2011 dataset.

The scores are generally better for the use of the Mahalanobis distance, especially at the first ranks which are the most critical ones for the Re-Id task. An increase in the performance in the first ranks allows the reduction of the number of candidates provided by a Re-Id system, within which the sought identity must be found. The reason is that the Mahalanobis matrix encompasses the visual camera-to-camera transitions, related to changes in illumination, resolution, and point of view. This reduces the effect of the intra-class variation and making easier the Re-Id task.

1) Cross-Re-Id dataset fine-tuning

In contrast to PRID2011 dataset, which was captured from a fixed pair of cameras, the samples of other datasets have been taken from multiple views. Consequently, the performance of a Re-Id model on multi-view datasets is improved by training such model on a larger variety of samples, to make it capable of dealing with the multiple variations among the different views.

For that reason, a Cross-Re-Id training set has been created (see Section 4.7.2) and an intermediate training step has been performed on it, instead of only fine-tuning on the target dataset.

Moreover, a second objective of the Cross-Re-Id dataset is to train a universal Re-Id model to perform Person Re-Identification between any unknown pair of cameras at any environment, as it was explained in Section 4.7.2. This Re-Id model is meant to be used in the data association process of a Re-Identification module integrated into a tracking system, in order to perform Multi-Target Multi-Camera Tracking (MTMCT), as Section 5.8 describes.

The setting of the experiments conducted with the Cross-Re-Id dataset are described by Table 6.25, and the CMC scores of the obtained models over different Re-Id datasets is presented by Table 6.26.

Table 6.25 Experiments settings to evaluate the effects of training on a Cross-Re-Id dataset.

Experiments	Description		
	Fine-tuning ₁ on Cross-Re-Id dataset	Fine-tuning ₂ on target dataset	Other settings
Exp.Finetuning.o	No	Yes	Three jointly learnt part-features. Triplet model. Transfer level 3. Permutation of triplets II. Data augmentation I, II and III. Euclidean distance metric. L ₁ regularization, $wd = 2 \times 10^{-6}$.
Exp.Finetuning.i	Yes	No	
Exp.Finetuning.2	Yes	Yes	

Table 6.26 CMC scores (in [%]) for models learnt by applying different fine-tuning steps, evaluated over different Re-Id datasets.

Dataset	VIPeR				CUHK-01			
Rank	1	5	10	20	1	5	10	20
Exp.Finetuning.o	19.9	46.2	62.3	78.2	10.7	24.1	35.0	47.3
Exp.Finetuning.i	21.2	46.2	57.3	70.6	12.1	28.6	40.5	54.1
Exp.Finetuning.2	24.68	47.5	60.1	74.4	13.8	30.9	42.0	57.4
Dataset	GRID				i-LIDS-VID			
Rank	1	5	10	20	1	5	10	20
Exp.Finetuning.o	10.4	18.4	24.8	35.2	10.0	26.0	35.3	47.3
Exp.Finetuning.i	5.6	15.2	19.2	27.2	7.3	22.7	35.3	51.3
Exp.Finetuning.2	6.4	14.4	24.0	30.4	7.3	25.3	38.7	54.0

For all the datasets, Exp.Finetuning.2 presents higher scores than Exp.Finetuning.1 on the first ranks since in Exp.Finetuning.2 the model is fine-tuned on the specific target dataset where it is also tested. However, two trends can be observed. The performance on GRID and i-LIDS-VID datasets is not improved by the intermediate step of fine-tuning on the cross-dataset. This is because the Cross-Re-Id dataset introduces a too large variety of samples, with a much bigger range of backgrounds, illumination and perspective changes between compared images than those existing in the target datasets, which were captured in limited indoors environments.

On the other hand, the performance over VIPeR and CUHK-01 datasets is improved by fine-tuning on the cross-dataset since in these target datasets the model has to cope with a larger variety of views, and intra-class variations, so the training on the cross-dataset prepare the model for it.

6.2.5 Final results

Through conducting a wide battery of experiments, exposed in Section 6.2.4, the proposed methods have been evaluated and the optimal neural architecture and learning procedure to obtain a Re-Id model have been found. Two different Re-Id scenarios have been addressed: a unique fixed camera pair or multiple camera views re-identification.

Therefore, eventually, two Re-Id strategies are proposed, one per type of Re-Id environment: Single-Shot Degree of Appearance Similarity for two fixed views, SS_DoAS_2V, and for multiple views, SS_DoAS_MV. These approaches differ in the application of some learning techniques to learn the optimal model in each case. Both strategies have been used to train and test models over several Re-Id datasets, as Table 6.27 shows.

Table 6.28 presents the obtained CMC scores of the proposed methods over every Re-Id dataset. To obtain the results, bench-marked testing protocols have been conducted over PRID2011, VIPeR, GRID and CUHK-01 datasets, for fair comparisons. The performance of the proposed algorithm over these datasets is compared with other state-of-the-art methods in the next section. Conversely, i-LIDS-VID is a Multi-Shot Re-Id dataset, from which a Single-Shot subset has been extracted in this thesis to evaluate the designed re-id model. Nonetheless, i-LIDS-VID is used to compared Multi-Shot Re-Id approaches, and its Single-Shot versions (i-LIDS-MA, i-LIDS-AA, and i-LIDS-119) have been no longer distributed from 2015, so fair comparisons are not available.

Moreover, the ranking power of the obtained models over every dataset has been analysed through the images presented in Figs.6.34, 6.35, 6.36, 6.37, 6.38, 6.39 and 6.40. These figures show the top 20 gallery images taken as most similar for every probe image (first column). The correct match is bounded by a yellow box. Examples of correct matches found at several ranks are given.

Through these images, error analysis can be performed. It can be appreciated in all the images that, although the model sometimes fails to find the correct match in the first rank, it is able to rank the images according to the visual appearance similarity. The model gives the highest DoAS

values to those people images most similar to the query probe sample, in a way akin a human would do. For a certain probe image, people wearing similar clothes, accessories or bags, or in the same colours, are ranked in the top positions, with independence from the pose. This error analysis proves the capacity of the designed model to measure the Degree of Appearance Similarity.

Table 6.27 Final re-identification strategies settings

Model name	Re-id scenario	Re-id strategy setting		Re-id dataset
		Particular characteristics	Common characteristics	
SS_DoAS_2V	Fixed camera pair	Mahalanobis Distance. VGG11 architecture. Data Augmentation I. Regularization L2, $wd = 0.0005$.	Triplet Model. Permutation of triplets II. Transfer level 3*.	PRID2011
SS_DoAS_MV	Multiple camera views	Euclidean Distance. 3 jointly learnt parts. Data Augmentation I, II, III. Regularization L1, $wd = 2 \times 10^{-6}$.		VIPeR CUHK-01 GRID i-LIDS-VID

* Transfer learning from MOT domain has been applied in all the models, and besides of that, an intermediate training step over Cross-Re-Id dataset has been performed for the models tested on VIPeR and CUHK-01 dataset.

Table 6.28 CMC scores (in [%]) for the Re-Id models (each one trained and evaluated over the same datasets).

Dataset	Rank						
	1	5	10	15	20	50	100
PRID2011	13.0	31.0	41.0	43.0	47.0	63.0	82.0
VIPeR	24.7	47.5	60.1	68.4	74.4	91.8	99.1
CUHK-01	13.8	30.9	42.0	51.0	57.4	75.7	87.0
GRID	10.4	18.4	24.8	30.4	35.2	55.2	69.6
i-LIDS-VID	10.0	26.0	35.3	40.0	47.3	68.0	94.7

Fig. 6.34 Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of PRID2011 dataset.

Fig. 6.35 Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of VIPeR dataset, where correct match is found within the top 10 ranks.

Fig. 6.36 Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of VIPeR dataset, where correct match is found between the top 11 and 20 ranks.

Fig. 6.37 Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of CUHK-01 dataset, where correct match is found within the top 10 ranks.

Fig. 6.38 Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of CUHK-01 dataset, where correct match is found between the top 11 and 20 ranks.

Fig. 6.39 Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of GRID dataset.

Fig. 6.40 Top 20 DoAS ranking provided by the proposed Re-Id model over some samples of i-LIDS-VID dataset.

6.2.6 Results Comparison and Discussion

One of the main purposes of this thesis is the learning of the Degree of Appearance Similarity between two images to perform Single-Shot Re-Identification through a neural model. Many strategies and neural layers have been developed to alleviate the Re-Id data problem, the model over-fitting and consequently to make the performance of the deep Re-Id model overcomes state-of-the-art methods based on the design of hand-crafted features and metric distance learning. This achievement is shown by Tables 6.29, 6.30, 6.31, and 6.32, where an extensive list of method's performances are compared with the CMC scores obtained for the model presented in the previous section, evaluated over PRID2011, VIPeR, CUHK-01 and GRID datasets, respectively.

The results can be taken as proof of concept to verify that, despite the data problem, deep learning can be exploited to solve the Single-Shot Re-Id task. Consequently, this also demonstrates that research on new over-fitting reduction techniques, distances and architectures, like those presented in this thesis, is worthy of being developed.

Table 6.29 Comparison of CMC rates (in [%]) of Re-Id methods on PRID2011 dataset, '-' indicates no result was reported.

Dataset	Rank					
	1	5	10	20	50	100
SS_DoAS_2V (proposed method)	13	31	41	47	63	82
Mahalanobis [282]	16	-	41	51	64	76
EIML [154]	16	-	39	51	68	81
KISSME [181]	15	-	39	52	68	80
ITML [81]	12	-	36	47	64	79
LMNN-R [87]	9	-	32	43	60	76
LMNN [341]	10	-	30	42	59	73
PSFI+PRDC [214]	3	9	16	24	39	-
PRDC [387]	3	10	15	23	38	-
PSFI+RankSVM [214]	4	9	13	20	32	-
RankSVM [270]	4	9	13	19	32	-
LDA [108]	4	-	14	21	35	48
GFI [223]	4	-	10	17	32	-
Euclidean [153]	3	-	10	14	28	45
LDML [140]	2	-	6	11	19	32
PSFI [214]	1	2	4	7	14	-

Table 6.30 Comparison of CMC rates (in [%]) of Re-Id methods on VIPeR dataset, ‘-’ indicates no result was reported.

Dataset	Rank					
	1	5	10	20	50	100
SS_DoAS_MV (proposed method)	25	48	60	74	92	99
PS [55]	22	-	57	71	87	-
SDALF [101]	20	38	50	65	85	-
PCCA [235]	19	49	65	80	-	-
DDC [152]	19	-	52	65	80	91
LMNN [341]	17	-	54	69	87	96
ICT [11]	16	-	60	78	-	-
PRDC [387]	16	38	54	70	87	97
PSFI+PRDC [214]	16	38	51	66	-	-
aPRDC [213]	16	38	51	66	-	-
PSFI+RankSVM [214]	16	38	51	66	-	-
RankSVM [270]	15	37	50	65	-	-
ITML [81]	13	-	54	73	91	98
LMNN-R [87]	13	-	50	65	86	95
ELF [138]	12	31	41	58	-	-
PSFI [214]	10	22	31	43	-	-
GFI [223]	9	-	27	34	-	-
LDA [108]	7	-	25	37	61	79
Euclidean [153]	7	-	24	34	55	73
LDML [140]	6	-	24	35	54	72
TFLDA [300]	6	17	26	40	-	-
TCA [256]	5	11	16	25	-	-

Table 6.31 Comparison of CMC rates (in [%]) of Re-Id methods on CUHK-01 dataset, ‘-’ indicates no result was reported.

Dataset	Rank						
	1	5	10	20	25	50	100
SS_DoAS_MV (proposed method)	13 8	30 9	42 0	57 4	61 3	75 7	87 0
ITML [81]	15 98	35 22	45 60	59 81	-	-	-
LMNN [340]	13 45	31 33	42 25	54 11	-	-	-
L1-norm [336]	10 33	20 64	26 34	33 52	-	-	-
L2-norm [158]	9 84	19 84	26 42	33 13	-	-	-
SDALF [101]	9 90	22 57	30 33	41 03	-	-	-

Table 6.32 Comparison of CMC rates (in [%]) of Re-Id methods on GRID dataset, ‘-’ indicates no result was reported.

Dataset	Rank						
	1	5	10	15	20	50	100
SS_DoAS_MV (proposed method)	10	18	25	30	35	55	70
MRank-RankSVM [221]	12	28	36	-	47	-	-
MRank-PRDC [221]	11	26	36	-	47	-	-
ELF6 + XQDA [207]	10	-	39	-	53	-	-
RankSVM [270]	10	25	33	39	44	61	-
PRDC [387]	10	22	33	39	44	64	-
PSFI+RankSVM [214]	10	25	34	-	44	61	-
PSFI+PRDC [214]	9	24	33	-	45	64	-
LDML [140]	8	-	22	-	27	-	-
L2-norm [158]	5	14	20	22	26	-	-
L1-norm [336]	4	12	16	19	25	-	-
PSFI [214]	5	12	20	-	28	41	-
GFI [223]	4	12	16	-	24	36	-

With the aim of studying the advantages of using a deep learning approach to select the proper features, Tables 6.29 and 6.30 show the results given by the algorithm presented in [153], which uses low-level features based on colour and texture. In [153], the Euclidean distance is directly applied to compare hand-crafted person representations. The model SS_DoAS_MV also uses the Euclidean distance, with the difference that the compared descriptors have been learnt by a deep Re-Id neural model. The automatic selection of features provided by the proposed deep learning algorithm results in a considerable improvement of the Re-Id performance compared with the computation of low-level features, which have been traditionally employed.

Tables 6.32 and 6.31 present the performance of other distances formulations, such as L2-norm [158] and L1-norm [336] to learn and compare Shape and Appearance. Moreover, Roth et al. [282] estimate the Mahalanobis matrix with a discriminative study of the features, once these have been previously computed in a separated process. On the other hand, the model SS_DoAS_2V uses a neural layer to learn the Mahalanobis matrix in order to embed the view-to-view transitions and to learn deep features simultaneously.

Other methods, like Implicit Camera Transfer (ICT) [11], model a camera pair transition to deal with intra-class variations. Instead of that, the model SS_DoAS_MV does not depend on the used camera pair and it is generalizable to any dataset.

Some approaches are focused on finding the proper combination of features to represent a person image, like the one presented in [138], based on an Ensemble of Localized Features (Ensemble

of Localized Features (ELF)), and Ranking Support Vector Machines (RankSVM), [270]. The features embedding is automatically found by both models, SS_DoAS_2V and SS_DoAS_MV, which produces a remarkable improvement in the performance.

In addition, other works apply general metric learners to Person Re-Identification, such as Probabilistic Relative Distance Comparison (PRDC), [387], Large Margin Nearest Neighbor (LMNN) [341], Information Theoretic Metric Learning (ITML) [81], Logistic Discriminant Metric Learning (LDML) [140] and Linear Discriminant Analysis (LDA) [108]. aPRDC [213] incorporates attribute-sensitive importance. Some of these methods have been adapted to the Re-Id task, like Large Margin Nearest Neighbor with Rejection (LMNN-R) [87], and others have been explicitly designed for the Re-Id task, like Keep It Simple and Straightforward Metric (KISSME) [181] and Efficient Impostor-based Metric Learning (EIML) [154]. These two last provide some regularisation, producing better results.

The test on the GRID dataset is more challenging than on PRID2011 and VIPeR datasets since each identity of a probe set of 125 identities must be identified among 900 gallery identities. For that reason, high scores are obtained by Manifold Ranking (MRank) [221], which propagates key features along with unlabelled data in an unsupervised way. The combination of this method with other ranking methods, like RankSVM and PRDC, improves their respective performances.

In general, these methods learn a metric distance over a set of previously computed features. Conversely, this paper proposes a jointly learning model to simultaneously find salient features and their optimal combination, providing comparable or even better results.

In [214], a Prototype-Sensitive Feature Importance (PSFI) based method is proposed to adaptively weight features according to different groups of the population. On the contrary, [223] presents a Global Feature Importance (GFI) approach, addressing the learning of a global weighting, i.e. a vector of generic weights and invariant to the population. No population discrimination has been made in the proposed method, and the general weighting of the features to create a global person descriptor have been implicitly and automatically performed by the proposed deep model learning. This proposed approach outperforms the previously cited methods and even the combination of some of them (PSFI+PRDC and PSFI+RankSVM).

Moreover, with the aim of comparing the performance improvement obtained by the proposed transference of learning from MOT domain, the scores for the methods presented in [256] and [300] are listed in Table 6.30. Pan et al. [256] perform domain adaptation via Transfer Component Analysis (TCA), and Si et al. [300] present subspace Transference to Fisher Linear Discriminant Analysis (TFLDA). These works address the alleviation of the gap between source and target domains, instead of adapting the source dataset to the target domain, as this dissertation proposes.

The cross-view comparison of images is also an important task in view-point invariant Person Re-Identification. The work in [207] presents the method Cross-view Quadratic Discriminant Analysis (XQDA), which extend metric learning methods, like KISSME to cross-view metric learning. The proposed SS_DoAS_MV model has been trained to make it robust against cross-view comparisons, but not by means of acting over the used distance metric. Instead of that, a training stage on a Cross-Re-Id dataset has been performed. These methods are compared in Table 6.32, that presents the results of combining XQDA with the implementation of Ensemble of Local Features (ELF), proposed in [387], ELF6.

Some of the techniques with better Re-Id performances are Descriptive and Discriminative classification (Descriptive and Discriminative Classification (DDC)) [152], the exploitation of pedestrians' symmetry through Symmetry-Driven Accumulation of Local Features (SDALF) [101] and the use of Pictorial Structures (PS) [55] to cope with pose and view variations. In contrast, no previous body parts segmentation is performed in the SS_DoAS_2V model, where a unique network models the complete person representation. A body part partition has been conducted by SS_DoAS_MV model to simplify the learning of the appearance model, where the features for each body part have been jointly learnt and automatically combined to provide also a unique model representation.

Recently, the research on Person Re-Identification is changing course. Nowadays, the trend is to use tracklets of the individuals to re-identify them from different cameras, with the aim of solving the Multi-Target Multi-Camera Tracking challenge (MTMCT) [203, 308, 356]. In addition, different datasets are been used to test the MTMCT algorithms, like DukeMTMCT, CUKH03 and Market1501. Therefore, these methods do not treat the Re-Id task under the constraints of Single-Shot Re-Identification challenge, but under a Multi-Shot approach.

Nevertheless, the objective of this thesis is to provide a Single-Shot Re-Identification model. This is motivated by the aim of reducing the quantity of data transmitted between neighbour cameras, with respect to Multi-Shot Re-Id. Therefore, Single-Shot Re-Id speed up communications in a distributed network of cooperative surveillance sensors. Moreover, in Multi-Shot Re-Identification, a tracklet of an agent is provided to re-identify it. These tracklets are formed by consecutive detections, associated with an identity by a tracking algorithm. In that sense, Single-Shot Re-Id prevents from propagating the errors of the tracking in previous associations from one monitoring point to another.

This thesis addresses the aim of designing methods to enable the integration of deep neural networks into the pair-wise binary classification approach of the early metric learning methods. The methods formulated by this dissertation allow the use of deep neural networks to perform Single-Shot Re-Identification, contributing to the development of the Person Re-Identification research.

6.2.7 Computational time

The training of the Re-Id models is an offline process. Once a model is learnt, it is integrated on a surveillance application to perform the appearance comparison between pairs of images. Table 6.33 presents the speed of the training process for different neural networks architectures and training models and the time that is taken by each one of them to perform the comparison of a pair of images. The GPU used in every process is also indicated.

Table 6.33 Computational time of Re-Id models, ‘-’ indicates no result was calculated.

	Hardware	Deep Convolutional Neural Network		
		Vgg16	Vgg11	Three jointly learnt parts
Training speed on Siamese model (B=64) (in seg/iteration)	Nvidia GeForce Titan Xp 12GB GDDR5X	0 045	-	0 0085
Training speed on Triplet model (B=64) (in seg/iteration)		0 627	0 442	0 134
Pair comparison time (in seg/comparison)	Nvidia GeForce GTX Titan X Pascal 12GB GDDR5	0 0085	0 0059	0 0048

Although the triplet model seems to be slower than the Siamese one, it is necessary to consider that the processing of every triplet implies the processing of two pairs simultaneously, so, in fact, triplet model is faster than the Siamese one.

The reduction of the depth of a network consequently reduces its computation time. However, the introduction of more branches by the three jointly learnt parts architecture does not involve a larger waste of time since the branches can be parallelly computed and their depth is smaller.

6.3 Multi-Object Tracking Experiments

This thesis presents the design and formulation of different methods to perform data association, agents’ management, and person modelling in order to develop a MOT algorithm. Moreover, different appearance similarity models have been learnt during this thesis to make the assignment between the detected individuals and their corresponding identities. This section evaluates all the proposed models and methods.

The next subsection describes the protocol to use several MOT sequences (Section 6.3.1). Then, the methodology used to evaluate the employed appearance similarity models is explained (Section 6.3.2). Subsequently, the obtained results are exposed (Section 6.3.4). In the same way, the metrics used to evaluate the effects of the proposed methods on the MOT performance are presented (Section 6.3.3), as well as, the resulting scores of the conducted experiments (Section 6.3.5). Eventually, the results are discussed and compared with other state-of-the-art algorithms (Section 6.3.6).

6.3.1 Datasets Protocols

Two sets of surveillance sequences have been used to train, validate and test the trained models to measure the Degree of Appearance Similarity (DoAS) and to evaluate the performance of the proposed MOT algorithm, where the DoAS models are integrated. These datasets, presented in Section 3.3.2, are CAVIAR [107] and MOT17 [236]. These datasets present significant differences that make them more suitable for determined experiments. Therefore, the protocol followed to use them, and the experiments conducted over each dataset are different.

1. Context Aware Vision using Image-based Active Recognition (CAVIAR) dataset. This dataset provides the ground-truth information about all its sequences. This dataset has been randomly divided into two sets of sequences, a development and an evaluation set, as Fig. 3.1 shows. Person images are extracted from the first set. These images are divided, in turn, into three groups to train, validate and test the DoAS model. The evaluation set of sequences is used to test the performance of the MOT algorithm, once the DoAS model has been integrated into it. The proposed MOT algorithm follows the tracking-by-detection paradigm. However, the localisation of the human detections on the sequences is not provided by CAVIAR dataset. For that reason, some well-known detectors have been implemented as a first stage of the MOT algorithm, and they have been tested on this dataset. Moreover, the developed techniques to avoid the propagation of the errors of the person detector have been also evaluated on this dataset.
2. MOT17 dataset. This dataset provides two groups of sequences, train and test set. The sequences forming the train set are accompanied by its corresponding ground-truth files, and they are taken as development sequences (see Fig.3.1). However, no ground-truth information is given for the sequences of the test set, which are taken as evaluation sequences. The sequences from the development set have been used to extract person images, in order to obtain samples of the identities appearing in those sequences. These identities have been divided, in turn, into three sets, training, validation and test sets, which are formed by the samples of the identities assigned to each one of them. These sets have been used to train, validate and test the DoAS model. On the other hand, the evaluation sequences are used to

measure the performance of the designed MOT algorithm. Since the ground truth of these sequences is not available, the outputs of the MOT algorithm are evaluated by submitting them to the MOT Challenge web², where the results of calculating standard metrics are provided. For all the sequences, MOT17 dataset provides the locations of the people detected by three different algorithms: DPM [102], Faster-R-CNN [274], and SDP [361]. Therefore, this dataset has been employed to evaluate only tracking performance, without requiring the implementation of a previous detection stage.

The tracking difficulty presented by MOT17 sequences is much higher than that for CAVIAR sequences, which can be considered as a semi-constrained scenario. However, MOT dataset presents challenging real-world surveillance sequences, with a wider variety of scenarios, complex situations, and a larger number of people in the scenes. For that reason, the first experiments of this thesis were conducted over the CAVIAR dataset and the final ones, over the MOT17 dataset.

6.3.2 Methodology to Evaluate the Appearance Model

This thesis proposes the measuring of the Degree of Appearance Similarity by means of a pair-wise binary classification model. Several models have been pre-trained over the training sets, formed by samples of person images from MOT sequences. The learnt models have been evaluated as binary classifiers, in order to test their performance to discriminate between positive and negative pairs of samples.

A test set of pairs of images has been generated³, with images of the multiple individuals from the training and validation sets.

The performance of the learnt models to properly classify the pairs samples of the test set has been rendered by a ROC curve [143]. This curve illustrates the diagnostic ability of a binary classifier as its discrimination threshold, th , is varied.

The output of the proposed models is the distance between two person representations in the feature space, which is the complementary value of the DoAS (Eq. 4.1). Therefore, th defines the value until which the classifier output is considered as the prediction of a positive pair, and from which it is considered as a negative pair. In that way, the chosen threshold, th , divides the distance space in two ranges of values corresponding to each class.

The ROC curve plots the True Positive Rate (TPR), also called Sensitivity or Recall, against the False Positive Rate (FPR), also known as the fall-out rate. The TPR and FPR metrics are defined by Eqs. 6.7 and 6.8, respectively, where TP is the number of true positives, TN is the number of true negatives, FP is the number of false positives and FN is the number of false negatives.

²A MOT evaluation server is available in <https://motchallenge.net/>

³The data generation tool has been implemented as a set of C++ functions, which are publicly available under: http://github.com/magomez/dataset_factory/tree/master/data_factory_from_mot.

$$TPR = \frac{TP}{TP + FN} \quad (6.7)$$

$$FPR = \frac{FP}{FP + TN} \quad (6.8)$$

Other metrics widely used to measure the performance of binary classifiers are Positive Predictive Value, *PPV*, also called Precision, *F1* score, and Accuracy, *A*, defined by Eq. 6.9, 6.10 and 6.11, respectively.

$$PPV = \frac{TP}{TP + FP} \quad (6.9)$$

$$F1 = \frac{2 \cdot PPV \cdot TPR}{PPV + TPR} \quad (6.10)$$

$$A = \frac{TP + TN}{TP + FP + TN + FN} \quad (6.11)$$

When the model is desired to predict a positive only if very confident (avoid false positives), high precision is needed. On the other hand, when it is desired to avoid missing many positives (avoid false negatives), high recall is required. *F1* score provides a trade-off between precision and recall, for that reason *F1* has been used to compare methods in the conducted evaluation.

The accuracy value, which is the proportion of well-classified pairs, has been also used as a comparative metric. This is not an appropriate metric for the case of having skewed classes, when the ratio of positive to negative examples is very close to one of two extremes (zero or one). In the case of identifying a person when he/she is compared with many people images, the ratio of positive samples to negative ones is very low. However, in order to provide a fair evaluation through the accuracy metric, the test set has been formed by the same number of positive as negatives pairs, presenting a completely balanced proportion of samples from each class.

6.3.3 Methodology to Evaluate the Multi-Object Tracking Performance

The MOT performance of the proposed algorithm is measured over the evaluation sequences (see Section 6.3.1).

The MOT performance of different matching cost formulations and association methods have been evaluated. Moreover, the effects of adding novel designed modules, like HSV and DBT modules, have been tested through several experiments.

The MOT performance is quantitatively measured by two Classification of Events, Activities and Relationships (CLEAR)-MOT metrics [27].

The Multi-Object Tracking Accuracy (MOTA), combines three error sources: false positives, missed targets and identity switches. This measure is calculated as it is described in Eq. 6.12, where $\overline{FN}$, $\overline{FP}$ and $\overline{IDsw}$ sum the number of false negatives, FN_f , false positives, FP_f , and identification switches, $IDsw_f$, in Eqs. 6.13, 6.14 and 6.15 respectively, at every frame, f , of the dataset. All them are divided by the sum of the number of ground truth objects, g_f , at every frame.

$$MOTA = 1 - \frac{\overline{FN} + \overline{FP} + \overline{IDsw}}{\sum_f g_f} \quad (6.12)$$

$$\overline{FN} = \frac{\sum_f FN_f}{\sum_f g_f} \quad (6.13)$$

$$\overline{FP} = \frac{\sum_f FP_f}{\sum_f g_f} \quad (6.14)$$

$$\overline{IDsw} = \frac{\sum_f IDsw_f}{\sum_f g_f} \quad (6.15)$$

Furthermore, the Multi-Object Tracking Precision (MOTP), defined by Eq. 6.16, measures the misalignment between the annotated and the predicted bounding boxes. This is calculated as the sum of intersection areas of each frame, IA_f , over the union areas UA_f . IA_f is computed as the sum of the intersection area for every identity, this is the common area of its bounding box which is provided by the MOT algorithm and their corresponding ground truth boxes. UA_f is the sum of the unions of the areas of those pairs of bounding boxes.

$$MOTP = \frac{\sum_f IA_f}{\sum_f UA_f} \quad (6.16)$$

Other metrics to measure the MOT performance are:

1. *IDF1* Score [276], which is the ratio of correctly identified detections over the average number of ground-truth and computed detections.
2. *FAF*, the average number of false alarms per frame.
3. *MT*, Mostly tracked targets. This is the ratio of ground-truth trajectories that are covered by a track hypothesis for at least 80% of their respective life span.
4. *ML*, Mostly lost targets. This is the ratio of ground-truth trajectories that are covered by a track hypothesis for at most 20% of their respective life span.
5. *Frag*, the total number of times a trajectory is fragmented (i.e. interrupted during tracking).

Although the proposed MOT algorithm presents a tracking-by-detection approach, implementing and evaluating the detection stage is out of the scope of this thesis. However, the effects of a chosen detector over the tracking performance are significant, as Moussy et al., [244], concluded. For that reason, in the conducted comparisons, the same detector has been used to feed the tracking algorithms to evaluate, in order to provide a fair comparison. In that way, the principle of orthogonalization is complied (see Section 6.1), maintaining the detector choice has a constant coordinate in the experiments space.

6.3.4 Experimental results of evaluating the Appearance models

This section presents the results obtained by evaluating the classification capacity of the three designed DoAS models, which were trained on MOT sequences: Hand-Crafted Single-Shot Degree of Appearance Similarity, HCSS-DoAS, Deeply Learnt Single-Shot Degree of Appearance Similarity, SS-DoAS, and Deeply Learnt Multi-Shot Degree of Appearance Similarity, MS-DoAS.

a) Hand-Crafted Single-Shot Degree of Appearance Similarity, HCSS-DoAS

The HCSS-DoAS model, described in Section 5.6.1, has been trained on four different training sets. Each set has been generated, as it is described in Section 5.6.1, by coupling pairs of images which were extracted from CAVIAR dataset. Each training set has been extracted using one of these values of N : 1 4 7 10. N is the maximum time step between coupled images. One classifier has been trained using each one of these sets. That means that, for example, the first classifier has been trained to identify the similarity between consecutive detections of the same person. And the last one has been trained to identify the same person when the step between the detection is any value from 1 to 10.

Every classifier has been evaluated using precision and recall metrics. Samples have been extracted from the test sequences and they have been grouped in ten different test sets according to the step size, n , between the images forming each test pair. Every test set owns roughly 50 000 samples.

Therefore, the first test set allows evaluating how a classifier identifies the similarity between consecutive detections, the second test, only those with a step size of 2, and so on.

Table 6.34 shows the precision results obtained from evaluating every classifier over every test set. Analogously, Table 6.35 shows the recall results.

Table 6.34 Precision (in [%]) of every classifier trained with $N = 1, 4, 7, 10$ over every test set ($n = 1 : 10$).

	Test set									
	$n=1$	$n=2$	$n=3$	$n=4$	$n=5$	$n=6$	$n=7$	$n=8$	$n=9$	$n=10$
Classifier 1, $N=1$	99	99	99	99	99	99	99	99	98	98
Classifier 2, $N=4$	85	84	84	83	82	81	81	80	79	79
Classifier 3, $N=7$	74	73	72	71	70	69	68	67	67	66
Classifier 4, $N=10$	77	77	76	74	73	72	70	69	69	68

Table 6.35 Recall (in [%]) of every classifier trained with $N = 1, 4, 7, 10$ over every test set ($n = 1 : 10$).

	Test set									
	$n=1$	$n=2$	$n=3$	$n=4$	$n=5$	$n=6$	$n=7$	$n=8$	$n=9$	$n=10$
Classifier 1, $N=1$	99	97	93	88	83	79	75	72	69	66
Classifier 2, $N=4$	97	95	91	86	82	80	77	75	73	71
Classifier 3, $N=7$	96	93	89	85	82	80	77	75	74	72
Classifier 4, $N=10$	96	93	89	83	78	75	72	69	67	65

Each classifier has been trained for identifying the same person in frames separated by step sizes values from 1 to N . The precision decreases with the increment of N . Sometimes the similarity between two different agents is lower than that between the same agent in non-consecutive frames. This fact leads the classifier to increase the number of false positives.

The recall decreases with the increment of the step size, n , since, as time passes between two representations of the same person, the classifier finds more difficult to identify the similarity between them. This results in an increase in the number of false negatives.

The entire MOT algorithm must be able to deal with similar people and identifications after partial-term occlusions, it implies a compromise solution between high precision and high recall. For that reason, the MOT performance of the four classifiers have been evaluated by using them to obtain the HCSS-DoAS value (Eq. 5.61), and compute the cost matching from it, in an MOT algorithm with individual data association, as Section 5.5.1 describes. Fig. 6.41 shows a graphic with the *MOTA* value obtained by using each one of the trained HCSS-DoAS models.

Fig. 6.41 MOTA values for four different HCSS-DoAS models.

The best performance corresponds to the classifier trained with $N = 7$, that was selected as the core of the individual data association module.

b) Deeply Learnt Single-Shot Degree of Appearance Similarity, SS-DoAS

The training of the DCNN used to compute the SS-DoAS is described in Section 5.6.2. Due to the huge quantity and variety of training samples required by deep learning algorithms, this model has been trained on a set of samples generated from the MOT17 dataset, which presents a wide range of different scenarios and identities.

The neural network has been trained using both, a Siamese and a Triplet model, so two experiments have been conducted as Table 6.36 shows. The results obtained with each one of them are presented by Table 6.37 and 6.38. These tables show the scores of several binary classification metrics (see Section 6.3.2) for different values of the classification threshold, th . Moreover, Fig. 6.42 present the ROC curves of the obtained SS-DoAS models.

The results provided by both models are quite similar. Siamese model offers slightly better results, with a larger area under the ROC curve, and higher values of $F1$ score and Accuracy. For that reason, the model trained with the Siamese structures has been the chosen one to compute the SS-DoAS.

The classification test proves the high capacity of the proposed SS-DoAS model to discriminate between positive pairs of images, belonging to the same person, and negative ones, corresponding to different people.

The results show that choosing the value 0.2 for th , the model achieves an accuracy value of 91.7% and with a th value of 0.25, the $F1$ score achieves 91.9%, which are considerably good values for a challenging task as appearance identification in a MOT sequence.

Table 6.36 Experiments settings to evaluate the effects of training with different learning models.

Experiments	Description	
	Learning model	Other settings
Exp.Siamese	Siamese	VGG11 architecture. Euclidean distance metric. Without data augmentation. L2 regularization, $wd = 0.0005$.
Exp.Triplet	Triplet	

Table 6.37 Binary classification metrics for the SS-DoAS network learnt with a Siamese model.

th	TN	FN	FP	TP	TPR [%]	FPR [%]	PPV [%]	$F1$ [%]	A [%]
0.00	20000	20000	0	0	0	0	-	-	50.000
0.05	19777	5758	223	14242	71.21	3.73	98.46	82.646	85.048
0.10	19441	3614	559	16386	81.93	13.40	96.70	88.705	89.568
0.15	18943	2498	1057	17502	87.51	29.73	94.31	90.780	91.113
0.20	18377	1702	1623	18298	91.49	48.81	91.85	91.671	91.688
0.25	17780	1106	2220	18894	94.47	66.75	89.49	91.910	91.685
0.30	17240	667	2760	19333	96.67	80.54	87.51	91.859	91.433
0.35	16771	378	3229	19622	98.11	89.52	85.87	91.583	90.983
0.40	16289	238	3711	19762	98.81	93.97	84.19	90.916	90.128
0.45	15774	149	4226	19851	99.26	96.59	82.45	90.074	89.063
0.50	15262	99	4738	19901	99.51	97.95	80.77	89.164	87.908
0.55	14648	59	5352	19941	99.71	98.91	78.84	88.053	86.473
0.60	13900	32	6100	19968	99.84	99.48	76.60	86.689	84.670
0.65	13150	16	6850	19984	99.92	99.77	74.47	85.340	82.835
0.70	12187	5	7813	19995	99.98	99.94	71.90	83.647	80.455
0.75	11213	0	8787	20000	100.0	100.0	69.48	81.989	78.033
0.80	9868	0	10132	20000	100.0	100.0	66.38	79.789	74.670
0.85	8498	0	11502	20000	100.0	100.0	63.49	77.667	71.250
0.90	7509	0	12491	20000	100.0	100.0	61.56	76.204	68.773
0.95	6047	0	13953	20000	100.0	100.0	58.91	74.139	65.118
1.00	0	0	20000	20000	100.0	100.0	50.00	66.667	50.000

Table 6.38 Binary classification metrics for the SS-DoAS network learnt with a Triplet model.

th	TN	FN	FP	TP	TPR [%]	FPR [%]	PPV [%]	$F1$ [%]	A [%]
0 00	20000	20000	0	0	0	0	-	-	50 000
0 05	19997	14727	3	5273	26 37	0 02	99 94	41 723	63 175
0 10	19990	11599	10	8401	42 01	0 09	99 88	59 139	70 978
0 15	19984	9516	16	10484	52 42	0 17	99 85	68 748	76 170
0 20	19970	7879	30	12121	60 61	0 38	99 75	75 401	80 228
0 25	19936	6542	64	13458	67 29	0 97	99 53	80 294	83 485
0 30	19878	5428	122	14572	72 86	2 20	99 17	84 003	86 125
0 35	19765	4540	235	15460	77 30	4 92	98 50	86 623	88 063
0 40	19600	3849	400	16151	80 76	9 41	97 58	88 375	89 378
0 45	19441	3370	559	16630	83 15	14 23	96 75	89 435	90 178
0 50	19264	2968	736	17032	85 16	19 87	95 86	90 193	90 740
0 55	19030	2646	970	17354	86 77	26 83	94 71	90 565	90 960
0 60	18785	2340	1215	17660	88 30	34 18	93 56	90 855	91 113
0 65	18499	2082	1501	17918	89 59	41 89	92 27	90 911	91 043
0 70	18166	1861	1834	18139	90 70	49 63	90 82	90 756	90 763
0 75	17727	1612	2273	18388	91 94	58 51	89 00	90 445	90 288
0 80	17093	1387	2907	18613	93 07	67 70	86 49	89 658	89 265
0 85	16344	1166	3656	18834	94 17	75 82	83 74	88 6510	87 945
0 90	15356	863	4644	19137	95 69	84 33	80 47	87 422	86 233
0 95	13751	430	6249	19570	97 85	93 56	75 80	85 423	83 303
1 00	0	0	20000	20000	100 0	100 0	50 00	66 667	50 000

Fig. 6.42 ROC curves for SS-DoAS learnt with a Triplet and a Siamese model.

c) Deeply Learnt Multi-Shot Degree of Appearance Similarity, MS-DoAS

Five different formulations have been designed to generate training tracklets with the following characteristics:

- I. It simulates the tracklets of people who have been previously well identified.
- II. It simulates the tracklets of just re-identified people after a temporary disappearance.
- III. It simulates the tracklets of people who have suffered from several disappearances, i.e. their tracks have been interrupted several times.
- IV. It simulates the tracklets of people who have been wrongly identified (mismatched) in some of the previous frames.
- V. It simulates the tracklets of people who have suffered from several disappearances and mismatches.

From each formulation, a training set has been created, which is able to train the model to cope with certain situations, according to the characteristics of its tracklets (see Section 5.6.3).

Five different experiments have been conducted to train the MS-DoAS model with each one of the generated training sets, TR_1 , TR_2 , TR_3 , TR_4 , TR_5 , and consequently to evaluate their effects on the model performance. Table 6.39 presents the settings of the experiments.

Table 6.39 Experiment settings to evaluate the effects of five different training sets of tracklets.

Experiments	Description	
	Training set	Other settings
Exp.MS_DoAS.1	TR_1 , from formulation I, Eqs. 5.68 and 5.69	LSTM learning Pre-trained features with VGG16 architecture. Euclidean distance metric. Without data augmentation. L2 regularization, $wd = 0.0005$.
Exp.MS_DoAS.2	TR_2 , from formulation II, Eqs. 5.70 and 5.71	
Exp.MS_DoAS.3	TR_3 , from formulation III, Eqs. 5.72 and 5.73	
Exp.MS_DoAS.4	TR_4 , from formulation IV, Eqs. 5.74 and 5.75	
Exp.MS_DoAS.5	TR_5 , from formulation V, Eqs. 5.76 and 5.77	

Every obtained model, each one from one of the conducted experiments, has been tested over five different test sets. These test sets have been also generated according to the presented formula-

tions to create tracklets, and they are, called TS₁, TS₂, TS₃, TS₄, TS₅. Therefore 25 different tests have been performed.

Fig. 6.43 presents a comparative graphic for every obtained MS-DoAS model.

Fig. 6.43 ROC curves from the evaluation of every MS-DoAS model on five different test sets (a), and zoomed region (b).

Each graphic of Fig. 6.43 shows the ROC curves resulting from testing the query model over the five test sets.

On the other hand, Fig. 6.44 presents a comparative graphic for every test set. Each graphic shows the ROC curves resulting of testing every obtained MS-DoAS model over the query test

set. Table 6.40 and 6.41 show the highest values of the $F1$ score and the accuracy metric, A , for each one of the 25 conducted tests. These tables also provide the classification threshold, th , with which the maximum values were achieved.

Fig. 6.44 ROC curves from five different evaluations conducted for each one of the MS-DoAS models (a), and zoomed region (b).

Table 6.40 Maximum $F1$ score value (in [%]) for every MS-DoAS model, evaluated over five different test sets, and th value where it is achieved.

	TS ₁	TS ₂	TS ₃	TS ₄	TS ₅
Exp.MS_DoAS.1	99 74	99 63	99 43	85 37	77 57
	($th=0.45$)	($th=0.45$)	($th=0.55$)	($th=0.9$)	($th=0.95$)
Exp.MS_DoAS.2	99 78	99 6	99 54	86 17	78 24
	($th=0.3$)	($th=0.3$)	($th=0.15$)	($th=0.7$)	($th=0.95$)
Exp.MS_DoAS.3	99 86	99 42	99 19	86 01	78 38
	($th=0.4$)	($th=0.25$)	($th=0.55$)	($th=0.85$)	($th=0.95$)
Exp.MS_DoAS.4	99 85	99 49	99 39	98 66	97 49
	($th=0.5$)	($th=0.65$)	($th=0.45$)	($th=0.65$)	($th=0.75$)
Exp.MS_DoAS.5	99 84	99 43	99 39	98 8	96 65
	($th=0.35$)	($th=0.5$)	($th=0.45$)	($th=0.65$)	($th=0.4$)

Table 6.41 Maximum Accuracy, A , value (in [%]) for every MS-DoAS model, evaluated over five different test sets, and th value where it is achieved.

	TS ₁	TS ₂	TS ₃	TS ₄	TS ₅
Exp.MS_DoAS.1	99 74	99 63	99 43	88 56	83 43
	($th=0.45$)	($th=0.45$)	($th=0.55$)	($th=0.8$)	($th=0.95$)
Exp.MS_DoAS.2	99 78	99 60	99 54	88 92	82 83
	($th=0.3$)	($th=0.3$)	($th=0.15$)	($th=0.4$)	($th=0.85$)
Exp.MS_DoAS.3	99 86	99 42	99 19	89 09	83 59
	($th=0.4$)	($th=0.25$)	($th=0.55$)	($th=0.75$)	($th=0.95$)
Exp.MS_DoAS.4	99 85	99 49	99 39	98 97	98 00
	($th=0.5$)	($th=0.65$)	($th=0.45$)	($th=0.65$)	($th=0.75$)
Exp.MS_DoAS.5	99 84	99 43	99 39	98 08	97 35
	($th=0.35$)	($th=0.50$)	($th=0.45$)	($th=0.65$)	($th=0.4$)

The test performed over the test sets from TS₁ to TS₅ are progressively harder since the tracklets on these tests simulate increasingly challenging situations. For that reason, the results are worse from TS₁ to TS₅. The models obtained from Exp.MS_DoAS.4 and 5 provide good results for TS₅, so they are capable to deal with real tracking situations.

The models learnt by means of using the training sets from TR₁ to TR₅ are capable of manage progressively more difficult situations, but in detriment of the performance to deal with the easiest identifications. Therefore, a trade-off solution must be chosen, which is given by the models learn through Exp.MS_DoAS.4 and Exp.MS_DoAS.5.

d) Discussion

HCSS-DoAS presents good results when it is used to identify the similarity between images taken from consecutive frames. The designed descriptor locally compares the pixels of two images, so changes in the pose of a person between two images can make the classifier predict the pair as a negative match. For that reason, the HCSS-DoAS model is not suitable for complex surveillance scenes, where there are partial occlusions and disappearances.

In those situations, a DoAS metric able to identify a person after several frames is required. The SS-DoAS metric has been trained on samples from the MOT17 datasets, using a wide variety of pairs images extracted from multiple sequences filmed at different real scenarios. This metric has been tested over pairs of images with a wide time step between them, and it has achieved a classification accuracy of 92%.

Moreover, the performance of this metric has been overcome by the MS-DoAS, thanks to the incorporation of temporary consistency with a Multi-Shot recognition. This metric has been trained to deal with different challenging situations, and its performance for classifying quite challenging tracklets has been evaluated. The excellent results offered by the MS-DoAS model makes this metric suitable for visually identify a person in a tracking algorithm.

This metric has been included as part of the association process of the proposed MOT algorithm, since it is used to compute the cost of assigning a certain identity to a person detection, from the appearance point of view. When the tracking of a person has recently started, and consequently there is not enough information to provide temporary consistency to the association method, the SS-DoAS metric is used instead of the MS-DoAS.

6.3.5 Experimental results of evaluating the Multi-Object Tracking

Two different MOT algorithms have been developed in this thesis. Each one of them addresses different requirements. The first one has been designed to minimise the tracking errors, mostly inherited from the detection stage. The second one is focused on solving challenging tracking situations at unconstrained scenarios. These algorithms have been respectively called MOT.1 and MOT.2. Both of them present an online data association process based on the Degree of Appearance Similarity between person detections.

- MOT.1. This MOT algorithm has been meant to track multiple people in an established semi-constrained scenario, from a unique fixed camera. This fact allows the use of the HCSS-DoAS, which has been implemented as part of two association methods. One of them is an individual method (Section 5.5.1) and the other is global (Section 5.5.2). This MOT algorithm has been developed and evaluated over CAVIAR dataset, where detections are not given. For that reason, the detection stage has been implemented for this algorithm.

Moreover, the development of this tracking algorithm has been focused on two novel methods to reduce the number of mistakes propagated by the detector algorithm. These methods are Human Shape Validation, HSV, (Section 5.7.3) and Detection-By-Tracking, DBT, (Section 5.7.4).

- MOT.2. This tracking algorithm provides a versatile solution to deal with multiple and variate real-world surveillance scenarios, even from mobile cameras. It is based on a novel Cascade Data Association algorithm (Section 5.5.3), which uses a Global Hypotheses Generator (Section 5.5.4). Moreover, these methods employ the SS-DoAS and MS-DoAS which have been learnt to deal with complex person identification. This MOT algorithm has been, as well as the methods integrated on it, has been developed and evaluated over the MOT17 dataset.

Both MOT algorithms employ the designed multi-agent management strategy to control the creation, updating and destruction of the tracks. They also use a Kalman filter implementation to predict the agents' states. The description of the algorithms is summarised by Table 6.42.

Table 6.42 MOT algorithm settings.

MOT algorithm	Description			
	Developing and evaluation sequences	DoAS model	Implemented modules	Designed methods
MOT.1	CAVIAR	HS_DoAS	Detection. Kalman filter.	Individual data association. Global data association. HSV. DBT. Agents management.
MOT.2	MOT17	SS_DoAS MS_DoAS	Detection. Kalman filter.	Cascade data Association. Global Hypotheses Generator. Agents management.

In this thesis, prior experiments were conducted with the MOT.1 over the CAVIAR dataset. Although the results in that scenario were acceptable, MOT.1 algorithm is not applicable to more complex sequences and more variate and crowded scenes. For that reason, the performance of MOT.1 over MOT17 dataset is poor. This results in bad performance scores, with even negative *MOTA* values. In order to overcome the limits of the proposed DoAS based approach, a second MOT algorithm has been designed, under the same fundamentals. Therefore, finally, MOT.2 have been developed and evaluated over MOT17 sequences.

a) MOT.1

Six sequences belonging to CAVIAR dataset [107] have been used as evaluation sequences to test the methods implied in MOT.1 algorithm. These sequences present some of the most challenging situation for the tracking: crossing people (EnterExistCrossingPaths1 and 2), changing-trajectory individuals (OneLeaveShopReenter1 and 2), and groups and people reappearing in the scene, where until 10 different identities appear (OneShopOneWait1 and 2). For all the experiments, the proposed approach has been forced to track every individual in those sequences, as long as their detections were bigger than 13x26 pixels, and occluded in less than the 50%.

Firstly, MOT.1 algorithm has been fed by these three detectors: an implementation of HOG-SVM [78], one based on the upper-body model trained by [144] for a Haar-Cascade classifier, and the fusion of the two previous ones (introduced in Section 5.3). Fig.6.45 shows the number of false negatives, FN , and false positives, FP , caused by them over the evaluation sequences.

Fig. 6.45 People detectors comparison.

Even though the third detector (FUSION) presents a higher number of false positives, this has been selected to feed the MOT.1 algorithm. This is due to the fact that the designed DBT strategy cannot detect new agents, although it can recover lost ones. For that reason, the third detector has been selected, since it reduces the number of false negatives and its high number of FP can be reduced by the formulated HSV filter.

Furthermore, the performance of two versions of MOT.1 algorithm have been compared by performing two experiments, listed in Table 6.43.

Table 6.43 Experiments settings to evaluate the effects of two different data association methods on the MOT performance

Experiment	Description	
	Data Association method	Other settings
Exp.Individual	Individual (see Section 5.5.1)	Fusion detector HCSS-DoAS HSV module DBT module
Exp.Global	Global (see Section 5.5.2)	

One of the experiments uses an individual data association method (Section 5.5.1) and the other, a global one (Section 5.5.2). The results, provided by Fig. 6.46, prove that the global association method not only reduces the proportion of identities switches, $\overline{IDsw}$, but also the number of false negatives, FN , and false positives, FP , leading to a prominent enhancement of the $MOTA$.

Fig. 6.46 Comparison of data association methods.

Although the improvements on the identity switches seem not to be so remarkable as the reduction of the false positives, they have strong importance. An identity switch is counted only one time in the frame that an identity is badly assigned, but not in the rest of the track, where the new identity is again associated with the agent. So, a unique identity switch badly affects on the real MOT performance.

In addition, to measure the performance improvement caused by the DBT and the HSV modules, four different experiments have been conducted to test different configurations of the MOT.I algorithm, over the evaluation sequences. The experiments settings are described by Table 6.44. In the first version, both modules have been removed, so the tracking task is mainly performed by the global data association module. The second and the third versions include the DBT and HSV modules respectively, and the fourth version corresponds to the complete proposed algorithm. The obtained results are shown in Fig. 6.47.

Table 6.44 Experiments settings to evaluate the effects of DBT and HSV modules on the MOT performance

Experiment	Description		
	DBT module	HSV module	Other settings
Exp.MOT.I.1	No	No	Fusion detector. HCSS-DoAS. Global data association.
Exp.MOT.I.2	Yes	No	
Exp.MOT.I.3	No	Yes	
Exp.MOT.I.4	Yes	Yes

Fig. 6.47 Effect of DBT and HSV modules on the $MOTA$.

The implementation of the DBT strategy notably reduces the FN , which was its purpose, although the FP increases. On the other hand, the implementation of the HSV filter remarkably decreases FP , for what it was meant, but increments FN . However, the combination of both strategies, on Exp.MOT.1.4, highly improves both metrics, resulting in the enhancement of the tracking performance represented by the $MOTA$ value.

One of the main goals of the developing of MOT.1 algorithm is to obtain a MOT approach robust against the failures of the detections given as input, to achieve a versatile MOT, where any people detector was suitable. In order to quantitatively evaluate the improvements provided by the proposed MOT.1 algorithm, this has been fed by the three mentioned detectors. The tracking errors presented by MOT.1 algorithm are mainly caused by the detector, as Table 6.45 shows: in the first case, 80.08% of the FN are caused by the HOG-SVM detector, and in the second case, 94.40% of the FP are inherited from the HAAR-Cascade detector.

Moreover, MOT.1 algorithm is not only able to avoid the increase in the main errors presented by the detectors (which means a 100% performance) but it also reduces such error rates. The reduced error rates are highlighted in bold in Table 6.45. The high rate of FP presented by HOG-SVM detector is decreased, as well as, the FN of the HAAR-Cascade detector and both metrics are improved for the fusion of their detections.

Table 6.45 Detectors and MOT errors rates.

	Detector		Detector+MOT	
	FN	FP	FN	FP
HOG-SVM	10 465	11 577	13 067	610
HAAR-Cascade	8 846	472	6 753	500
FUSION	6 279	10 427	6 207	1 043

b) MOT.2

The algorithm denoted as MOT.2 has been evaluated over the evaluation sequences of the MOT17 dataset (Section 6.3.1).

Table 6.46 and 6.47 show the performance of MOT.2 through the scores obtained for the metrics described in Section 6.3.3. These tables list the results obtained for every sequence as well as the global results (marked in bold). The columns corresponding to metrics for which higher scores mean better performance, present white background, and those for which lower scores mean better performance are shown in shade text.

In addition, the global identification precision P , takes value 69.9% and the global recall, R , 35.2%.

Table 6.46 Multi-Object Tracking performance of algorithm MOT.2 over MOT17 dataset. $MOTA$, $MOTP$, FP , FN and ID_{sw} values.

Sequence	$MOTA$	$MOTP$	FP	FN	ID_{sw}
MOT17-01-DPM	23.2%	71.7%	414	4 465	74
MOT17-03-DPM	41.7%	74.8%	6 280	54 121	595
MOT17-06-DPM	39.1%	73.2%	175	6 891	112
MOT17-07-DPM	30.5%	73.7%	263	11 356	115
MOT17-08-DPM	16.7%	78.6%	592	16 889	116
MOT17-12-DPM	26.7%	76.0%	711	5 576	69
MOT17-14-DPM	17.5%	74.1%	866	14 238	143
MOT17-01-FRCNN	24.9%	76.5%	1 238	3 563	41
MOT17-03-FRCNN	54.9%	78.0%	1 487	45 466	249
MOT17-06-FRCNN	47.1%	79.0%	330	5 808	99
MOT17-07-FRCNN	29.5%	75.8%	770	10 979	153
MOT17-08-FRCNN	18.6%	80.9%	576	16 527	97
MOT17-12-FRCNN	34.2%	78.8%	332	5 344	23
MOT17-14-FRCNN	18.4%	72.7%	1 535	13 321	221
MOT17-01-SDP	36.0%	74.1%	692	3 321	118
MOT17-03-SDP	64.6%	76.4%	2 312	34 207	587
MOT17-06-SDP	49.0%	76.2%	361	5 527	117
MOT17-07-SDP	37.7%	76.0%	475	9 838	217
MOT17-08-SDP	23.2%	79.3%	194	15 880	159
MOT17-12-SDP	35.3%	78.3%	371	5 187	48
MOT17-14-SDP	26.3%	73.4%	1 061	12 293	263
Global	42.3%	76.3%	21 035	300 797	3 616

Table 6.47 Multi-Object Tracking performance of algorithm MOT.2 over MOT17 dataset. IDFI, FAF, MT, ML, and Frag values.

Sequence	IDFI	FAF	MT	ML	Frag
MOT17-01-DPM	33 2%	0 9	8 3%	41 7%	273
MOT17-03-DPM	45 9%	4 2	10 1%	25 0%	3 822
MOT17-06-DPM	43 8%	0 1	5 9%	57 2%	381
MOT17-07-DPM	39 1%	0 5	1 7%	48 3%	861
MOT17-08-DPM	23 2%	0 9	0 0%	59 2%	550
MOT17-12-DPM	42 8%	0 8	2 2%	50 5%	366
MOT17-14-DPM	29 8%	1 2	1 8%	62 8%	575
MOT17-01-FRCNN	41 0%	2 8	20 8%	33 3%	256
MOT17-03-FRCNN	55 4%	1 0	22 3%	18 9%	1 751
MOT17-06-FRCNN	49 6%	0 3	10 4%	38 7%	389
MOT17-07-FRCNN	37 9%	1 5	3 3%	38 3%	690
MOT17-08-FRCNN	24 3%	0 9	2 6%	57 9%	301
MOT17-12-FRCNN	48 5%	0 4	9 9%	57 1%	134
MOT17-14-FRCNN	30 7%	2 0	3 0%	56 1%	654
MOT17-01-SDP	38 6%	1 5	25 0%	29 2%	355
MOT17-03-SDP	59 7%	1 5	31 8%	14 2%	2 621
MOT17-06-SDP	48 5%	0 3	12 6%	40 5%	349
MOT17-07-SDP	44 5%	1 0	6 7%	36 7%	888
MOT17-08-SDP	27 1%	0 3	5 3%	53 9%	399
MOT17-12-SDP	45 3%	0 4	8 8%	53 8%	176
MOT17-14-SDP	36 0%	1 4	1 8%	48 2%	865
Global	46 8%	1 2	9 1%	44 1%	16 656

6.3.6 Results Comparison and Discussion

MOT.1 algorithm has been evaluated over two challenging sequences from the CAVIAR dataset: *EnterExistCrossingPaths* and *OneShopOneWaitsequences*, which present people crossing between them and partial-term occlusions.

The resulting performance has been compared with other tracking-by-detection methods: Decentralized Particle Filters (DPF), [263], Tracker Hierarchy (Hierarchy), [371], and Reversible Jump Markov Chain Monte Carlo - Particle Filter (RJMCMC), [176]. The first method is an example of a decentralised filter, and the other two methods are centralised trackers. A comparative review of these algorithms was given in [244], where they are evaluated over CAVIAR dataset. The obtained results are presented in Table 6.48. The best result for every metric is marked in bold.

All the compared methods have been fed with the detection from the HOG-SVM people detector, and they present high errors rates. The proposed strategies based on human skeletons, such as the HSV and DBT modules, generally decreases the number of false positives and false negatives, resulting in a remarkable improvement of the *MOTA*. Moreover, the main difference with respect to these methods is that they don't use the agents' visual appearance.

Table 6.48 MOT₁ results comparison.

	<i>EnterExistCrossingPaths</i> sequence				<i>OneShopOneWait</i> sequence			
	$\overline{FN}$	$\overline{FP}$	$\overline{IDsw}$	<i>MOTA</i>	$\overline{FN}$	$\overline{FP}$	$\overline{IDsw}$	<i>MOTA</i>
MOT ₁	0 34	0 07	0 02	0 57	0 49	0 09	0 05	0 37
DPF [263]	0 41	0 37	0 00	0 22	0 45	0 45	0 01	0 09
Hierarchy [371]	0 63	0 12	0 02	0 25	0 67	0 04	0 03	0 26
RJMCMC [176]	0 40	0 08	0 01	0 51	0 69	0 15	0 02	0 14

As it has been mentioned, the performance of MOT₁ over MOT₁₇ sequences produces even negative *MOTA* values. This is due to the complexity of such sequences, where the number of appearing individuals is high, there are crowd scenes in outdoors and indoors environments, and they were taken from fixed and mobile cameras from very different perspectives. All these challenging conditions demand the design of a robust MOT algorithm, capable to deal with this variety of real-world surveillance scenarios.

MOT₂. has been evaluated over MOT₁₇ sequences and the results have been submitted to the MOT₁₇ challenge. More than ninety algorithms participate in this challenge with *MOTA* values from 54.7% to -7.3%. Therefore, the proposed MOT₂, whose *MOTA* value is 42.3%, can be considered as a relatively effective and robust algorithm. Moreover, it is necessary to highlight the fact that exactly the same algorithm, with the same hyper-parameters setting, has been evaluated over all the MOT₁₇ sequences, proving that the presented method is versatile under multiple and variate tracking situations.

The global performance of MOT₂ has been compared with the algorithms located on the top of the MOT₁₇ challenge ranking. The results are given by Table 6.49. All the compared methods use the detection set provided by MOT₁₇ dataset. In *MOTA* column, the value in brackets denotes standard deviation across all sequences. In *IDsw* column and Frag column, the values in brackets are the identity switches ratio (the number of identity switches over the recall value) and the track fragmentations ratio (the number of track fragmentations over the recall value), respectively.

The two best MOT algorithms in the MOT₁₇ ranking are offline methods, i.e. they use future frames information to provide the tracking output of a certain frame. Conversely, the proposed method MOT₂ is an online algorithm, i.e. the solution is immediately available with each incoming frame and is not changed at any later time, so that, this approach enables real-time tracking.

Table 6.49 Comparison of Multi-Object Tracking performance of MOT.2 with top 3 benchmarking algorithms over MOT17 dataset.

Sequence	<i>MOTA</i>	<i>FP</i>	<i>FN</i>	<i>ID_{sw}</i>	IDF _i	MT	ML	Frag
LSST ₁₇ [105]	54 7% (12 9)	26 091	228 434	1 243 (20 9)	62 3%	20 4%	40 1%	3 726 (62 6)
DGCT	54 5% (13 1)	10 471	243 143	2 865 (50 3)	51 3%	21 0%	35 4%	4 889 (85 9)
ISDH _HDAv2 [*]	54 5% (14 5)	46 693	207 093	3 010 (47 6)	65 9%	26 4%	32 1%	6 000 (94 8)
MOT.2 [*]	42 3% (12 8)	21 035	300 797	3 616 (77 4)	46 8%	9 1%	44 1%	16 656 (356 7)

^{*} This method is an online (causal) method.

To provide a fair comparison, Table 6.50 presents the performance of the proposed MOT.2 algorithm only with respect to the best online MOT algorithms from the MOT17challenge rank. All of them feed the tracking algorithm with the detections provided by MOT17 sequences.

Table 6.50 Comparison of Multi-Object Tracking performance of MOT.2 with top 3 online benchmarking algorithms over MOT17 dataset.

Sequence	<i>MOTA</i>	<i>FP</i>	<i>FN</i>	<i>ID_{sw}</i>	IDF _i	MT	ML	Frag
ISDH _HDAv2	54 5% (14 5)	46 693	207 093	3 010 (47 6)	65.9	26 4%	32 1%	6 000 (94 8)
Tracktor17 [26]	53 5% (14 5)	12 200	248 047	2 072 (37 0)	52 3	19 5%	36 7%	4 611 (82 3)
MFT	53 1% (16 6)	35 290	225 606	3 681 (61 3)	50 1	20 4%	39 4%	6 271 (104 5)
MOT.2	42 3% (12 8)	21 035	300 797	3 616 (77 4)	46 8	9 1%	44 1%	16 656 (356 7)

From all the compared algorithms, only LSST₁₇ and Tracktor₁₇, described in [105] and [26] respectively, have already been published, because all of them have been recently developed. In [105], it is presented a Multi-Object Tracking method that uses multiple cues and Switcher-Aware classification. Like the approach presented in this thesis, this method employs multiple cues to calculate the matching scores by means of combining position and appearance features.

On the other hand, instead of performing a global data association, as MOT.2 does, LSST₁₇ proposes a Single Object Tracking (SOT) subnet and a Switcher-Aware Classifier (SAC), to make matching decisions, which considers the potential identity-switch causer.

Other important difference is that the work in [105] presents a unified MOT learning framework, instead of integrating previously learnt models on the modules of the MOT architecture, as this dissertation presents. Tracktor17 [26] method neither performs any training or optimisation of its modules on tracking sequences. Tracktor17 exploits the bounding box regression of a people detector to predict the position of an individual, converting a detector into a Tracktor.

In addition, the strategy of integrating a Re-Id model to track individuals after occlusions, proposed in the present research work, is also shared by LSST17 and Tracktor17 methods.

From this comprehensive comparison, it can be concluded that very different systems with almost contradictory approaches can achieve high MOT performance. Therefore, no specific approach can be taken as the totalitarian solution to the MOT problem.

The method proposed in this dissertation share and combine some of the strategies presented by different state-of-the-art algorithms and contributes to the MOT research field with new techniques, and methods, which have been demonstrated to be potential MOT methods by the obtained results.

6.3.7 Computational time

With the aim of implementing an efficient MOT algorithm, a battery of measures has been taken to save computational time at every frame iteration. Some of the prior design characteristics with that purpose are the following ones:

- Agent structure presents an attribute to save the appearance feature, F , of each identity in order to avoid its computation more than once.
- Matrices have been used to save the comparisons scores (Section 5.5.3), between each identity and every new detection. In that way, these scores metrics are computed once and they are available to be used multiple times in the data association process.

The time taken by different stages of the tracking, in a frame iteration, has been measured to identify the most consuming parts. The following measurements have been taken:

- $t_{feature}$, time taken by the computation of the appearance features of the detections.
- t_{matrix} , time taken by the computation of the score matrices, the mask and the cost matrix.
- t_{hypo} , time taken by the global hypotheses generator.
- t_{cost} , time taken by the computation of the hypotheses' cost.
- t_{total} , time taken by a complete frame iteration.

Some of these stages are repeated more than once during a tracking iteration since multiple association processes are conducted by the proposed cascade method. The time taken by each call of each one of these modules in an iteration has been summed. Eventually, the measurements render average values for an iteration, measured over a probe sequence, concretely, MOT_{I7-01-DPM}. The obtained values for the prior design of the algorithm are presented in the first row of Table 6.51. This table also presents the time measurements after diverse phases of code optimization.

After observing the results of the prior design, where the matrices computation is the most consuming part, this time has been reduced under the assumption that the most time-consuming metric is the DoAS. Once the detections' features have been computed, Single Shot DoAS is simply computed by a Euclidean distance, but Multi-Shot DoAS requires the forward computation of a LSTM cell which is a time-consuming process. For that reason, the program flow has been optimised in order to compute the DoAS only the necessary times according to the mask matrix. The results are exposed in the second row of Table 6.51.

The second row of Table 6.51 shows that feature and matrix computation are by far the most time-consuming stages. The reason is that these stages involve the computation of forward propagation of deep neural models. That computation has been accelerated by the use of a more powerful GPU, concretely, Nvidia GeForce Titan Xp 12GB GDDR5X, as the third row shows.

Table 6.51 Computation time measurements (average values per iteration in seconds) for different stages and enhancements of the MOT system design, for MOT_{I7-01-DPM} sequence.

Algorithm design	$t_{feature}$	t_{matrix}	t_{hypo}	t_{cost}	t_{total}
Prior (feature attribute and score matrices)	0 0473	0 2341	$5\ 16 \times 10^{-5}$	$4\ 83 \times 10^{-5}$	0 3036
Optimisation of DoAS computation	0 0422	0 0403	$2\ 20 \times 10^{-5}$	$1\ 35 \times 10^{-5}$	0 1187
Hardware upgrade (Titan Xp GPU)	0 0230	0 0174	$2\ 47 \times 10^{-5}$	$1\ 38 \times 10^{-5}$	0 0743

6.4 Experiments on other applications

The versatility of the presented methods has been proved by evaluating some applications where the learnt model and the proposed methods have been employed.

The Degree of Appearance Similarity is a contrastive measurement with application in other pair-wise verification tasks apart from Single-Shot Re-identification, like facial recognition. Therefore, the developed DoAS model has been used to recognise faces to evaluate its performance and potential application in that domain.

Furthermore, different versions of DoAS models have been integrated into a tracking algorithm to perform different labours, such as data association and identification after occlusions and disappearances. A development framework has been implemented to generate such models. This resource has been leveraged to design an extra version of the DoAS measurement for performing tracking from aerial vehicles. In that way, the field of application of the proposed tracking approach is extended from the Surveillance to the Search and Rescue domain.

6.4.1 Facial Recognition Experiments

A neural model has been trained on FEI dataset to perform facial recognition, as Section 4.10.1 describes. This section presents the prior results obtained on this research field by the proposed DoAS model. Table 6.52 presents the scores of several binary classification metrics (see Section 6.3.2) for different values of the classification threshold, th .

Table 6.52 Binary classification metrics for the face recognition model.

th	TN	FN	FP	TP	TPR	FPR	PPV	$F1$ [%]	A [%]
0	10000	10000	0	0	0 00	0 00	-	-	50 0
0 05	9997	7712	3	2288	0 23	0 00	1 00	37 2	61 4
0 10	9980	6177	20	3823	0 38	0 00	0 99	55 2	69 0
0 15	9947	4964	53	5036	0 50	0 01	0 99	66 8	74 9
0 20	9908	3942	92	6058	0 61	0 02	0 99	75 0	79 8
0 25	9850	3274	150	6726	0 67	0 04	0 98	79 7	82 9
0 30	9782	2740	218	7260	0 73	0 07	0 97	83 1	85 2
0 35	9713	2335	287	7665	0 77	0 11	0 96	85 4	86 9
0 40	9642	2005	358	7995	0 80	0 15	0 96	87 1	88 2
0 45	9553	1649	447	8351	0 84	0 21	0 95	88 8	89 5
0 50	9457	1424	543	8576	0 86	0 28	0 94	89 7	90 2
0 55	9366	1196	634	8804	0 88	0 35	0 93	90 6	90 9
0 60	9246	982	754	9018	0 90	0 43	0 92	91 2	91 3
0 65	9142	782	858	9218	0 92	0 52	0 91	91 8	91 8
0 70	9026	639	974	9361	0 94	0 60	0 91	92 1	91 9
0 75	8889	503	1111	9497	0 95	0 69	0 90	92 2	91 9
0 80	8747	401	1253	9599	0 96	0 76	0 88	92 1	91 7
0 85	8531	291	1469	9709	0 97	0 83	0 87	91 7	91 2
0 90	8274	228	1726	9772	0 98	0 88	0 85	90 9	90 2
0 95	7880	137	2120	9863	0 99	0 94	0 82	89 7	88 7
1 00	0	0	10000	10000	1 00	1 00	0 50	66 7	50 0

An accuracy of 92% has been achieved for a value of th of 0.7.

In addition, some remarks have been extracted from an error analysis. Most of the positive and negative pairs of the test set has been correctly classified, resulting in a high number of true positives, TP , and true negatives, TN . Fig. 6.48 shows some well-classified positive pairs of images, in spite of changes in orientation and illumination. Fig. 6.49 shows some examples of well-classified negative pairs, formed by images corresponding to different identities, despite the high appearance similarity between them.

Fig. 6.48 Examples of true positive pairs of faces images from FEI face dataset.

Fig. 6.49 Examples of true negative pairs of faces images from FEI face dataset.

Moreover, some of the few false positive, FP , and false negatives, FN , provided by the trained model are shown in Fig. 6.50 and 6.51, respectively, allowing an error analysis.

Fig. 6.50 Examples of false positive pairs of faces images from FEI face dataset.

Fig. 6.51 Examples of false negative pairs of faces images from FEI face dataset.

Many of the bad-classified samples (for both, positive and negative pairs, i.e. *FP* and *FN*) are formed by pairs containing profile views of the people, instead of frontal views, and almost black images, where the identification is very difficult. These are avoidable errors in a semi-structured scenario, like the one given in control access, which is properly illuminated. In addition, the pictures on the identity card, used to identify people, are frontal face captures. The training of the model on so hard samples (dark and profile pictures) lead it to learn to solve a harder task than the target one.

Therefore, the conducted error analysis has boosted the performance of a second evaluation, in which the darkest samples and those showing a profile view of the person have not been taken to generate test triplets. Table 6.53 presents the classification performance of the second experiment and Fig. 6.52 shows the obtained ROC curves for both experiments.

Table 6.53 Binary classification metrics for the face recognition model, tested on frontal and well-illuminated images.

<i>th</i>	<i>TN</i>	<i>FN</i>	<i>FP</i>	<i>TP</i>	<i>TPR</i>	<i>FPR</i>	<i>PPV</i>	<i>F1</i>	<i>A</i>
0 00	3480	3480	0	0	0 00	0 00	-	-	50 0
0 05	3480	3132	0	348	0 10	0 00	1 00	18 2	55 0
0 10	3480	1624	0	1856	0 53	0 00	1 00	69 6	76 7
0 15	3480	464	0	3016	0 87	0 00	1 00	92 9	93 3
0 20	3478	348	2	3132	0 90	0 01	1 00	94 7	95 0
0 25	3456	232	24	3248	0 93	0 09	0 99	96 2	96 3
0 30	3410	116	70	3364	0 97	0 38	0 98	97 3	97 3
0 35	3302	0	178	3480	1 00	1 00	0 95	97 5	97 4
0 40	3146	0	334	3480	1 00	1 00	0 91	95 4	95 2
0 45	2906	0	574	3480	1 00	1 00	0 86	92 4	91 8
0 50	2692	0	788	3480	1 00	1 00	0 82	89 8	88 7
0 55	2456	0	1024	3480	1 00	1 00	0 77	87 2	85 3
0 60	2140	0	1340	3480	1 00	1 00	0 72	83 9	80 7
0 65	1814	0	1666	3480	1 00	1 00	0 68	80 7	76 1
0 70	1544	0	1936	3480	1 00	1 00	0 64	78 2	72 2
0 75	1222	0	2258	3480	1 00	1 00	0 61	75 5	67 6
0 80	962	0	2518	3480	1 00	1 00	0 58	73 4	63 8
0 85	732	0	2748	3480	1 00	1 00	0 56	71 7	60 5
0 90	482	0	2998	3480	1 00	1 00	0 54	69 9	56 9
0 95	192	0	3288	3480	1 00	1 00	0 51	67 9	52 8
1 00	0	0	3480	3480	1 00	1 00	0 59	66 7	50 0

Fig. 6.52 ROC curves of the face recognition model over two different test sets.

The model, which was trained also on dark and profile samples, is evaluated over frontal and well-illuminated images in the second experiment (Test 2), resulting in higher performance. In addition, an experiment was conducting by eliminating dark and profile images also from the training set. However, no reliable model was learnt. The elimination of this type of images from the training set implies its reduction, making harder the training of a deep neural model, and producing worse results.

For that reason, although the target samples are easier to classify than the training ones, the learning on challenging images provides a more robust recognition model.

6.4.2 Aerial Search and Rescue Experiments

Section 5.9.1 presents the application of the proposed appearance-based tracking for search and rescue purposes.

This algorithm has been evaluated over a new dataset, called ARMOT⁴ dataset, Aerial Rescue Multi-Object Tracking dataset. Due to the absence of aerial datasets with available ground truth annotations for evaluating tracking, a new dataset has been acquired from an octocopter.

This first version of the ARMOT dataset is composed by four video sequences, listed below in order of increasing difficulty, whose specifications are exposed on Table 6.54:

1. Urban scenario with hovering mode UAV on static human bodies.
2. Urban scenario with hovering mode UAV on dynamic human bodies (walking and jumping), with periods of blurred frames.
3. Open arena with a high-velocity flight and static human bodies.
4. Open arena with high-velocity flight with several disappearances and re-appearances of the people in the field of view.

Table 6.54 ARMOT dataset.

Sequence	Frame Rate (FPS)	Resolution	Length (Frames)	Duration (s)
1	15	960 × 540	221	14
2	30	960 × 540	251	8
3	15	960 × 540	120	8
4	15	960 × 540	645	43

⁴The ARMOT dataset is publicly available under: <https://github.com/magomez/ARMOT-dataset>, where the video sequences and its corresponding tracking annotations can be found

Furthermore, every video is accompanied by its corresponding ground truth. This consists of the bounding box and identification number of every human detection at each frame, as long as they are occluded in less than the 50% and their head are visible. This information has been collected in xml files following the format presented by the ground truth files of CAVIAR dataset.

Table 6.55 presents the MOT metrics results obtained for the proposed MOT algorithm, presented in Section 5.9.1, over the ARMOT dataset.

Table 6.55 presents decreasing values of *MOTA* according to the increase of the difficulties presented by the testing sequences. The decrease of the *MOTA* value is mainly due to the false negatives rates, which are affected by the large variations of the people visual representation in consecutive frames. These differences are caused by both; the tracked people movements, and the increase in the velocity of the scanning performed by the UAV.

In the rescue task, the velocity with which a large area is scanned is a crucial characteristic, and, even though it causes an increase of the false negatives rate, it does not affect on the real tracking performance. The reason for this is that the presented MOT algorithm is perfectly able to track a target even when some of its detections are missed, and even when the time step between detections is large, thanks to the re-identification ability provided by the proposed DoAS comparison. This re-identification success is reflected by the remarkably low rate of identity switches. Moreover, the presented MOT algorithm has been focused on reducing the number of false alarms. Therefore, thanks to the designed Human Shape Validation (HSV) filter, no false positives have been detected or tracked.

Table 6.55 Multi-Object Tracking metrics values for the sequences 1, 2, 3 and 4.

Sequence	<i>FN</i>	<i>FP</i>	<i>ID_{sw}</i>	$\overline{FN}$	$\overline{FP}$	$\overline{ID_{sw}}$	<i>MOTA</i>
1	0	0	0	0 000	0 000	0 000	1 000
2	73	0	0	0 292	0 000	0 000	0 708
3	3	0	1	0 250	0 000	0 083	0 667
4	163	0	1	0 858	0 000	0 005	0 137
Total	236	0	2	0 265	0 000	0 002	0 733

Chapter 7

Conclusions and Future Work

7.1 Conclusions

This PhD dissertation states the learning of a neural model to measure the Degree of Appearance Similarity (DoAS) between people images to perform Multi-Person Tracking and Re-Identification. The research work presented in this document explain, evaluate and discuss this approach.

A collection of learning techniques, architectures and novel layers have been analysed and developed to obtain the DoAS model, which has been integrated into a surveillance system architecture where the tracking of multiple individuals is performed.

A developing framework has been designed and implemented to train, validate and test the DoAS model. This is constituted by a set of tools with different purposes, including datasets generation, interpreting learnt models in different programming languages, training and testing of neural models and evaluation of methods and applications by measuring several metric values. Most of these tools have been publicly delivered.

Through this methodology, the objectives of this thesis, presented in Section 1.5, has been achieved, resulting in multiple contributions to the research fields of Multi-Object Tracking (MOT) and Person Re-Identification (Re-Id), which are exposed in detail in Section 2.3.

Eventually, the evaluation results prove the capacity of the DoAS model to perform the surveillance tasks of Multi-Object Tracking and Single-Shot Person Re-identification, which is the main statement of this dissertation.

In addition, the research and experiments conducted along with this dissertation about the application of deep learning techniques to model the DoAS have demonstrated some hypotheses:

- The results demonstrate the potential application of deep learning to solve the challenging task of Single-Shot Re-Identification, as long as the lack of Re-Id data is faced by a proper strategy.

- The discriminative capacity of the Siamese Re-Id model has been increased through the design of the Normalised Double Margin-based Contrastive Loss function.
- A certain compensation in the sizes of the sets of positive and negative pairs is necessary to avoid that the learning process ends up ignoring the positive pairs' contributions, and collapsing. A model trained on a partially balanced training set presents higher performance than if it is trained on an absolutely balanced set since this last set differs too much from the target task, where the model has to deal with the unbalanced Re-Id data.
- Triplet model is more effective than Siamese one when a Re-Id model is learnt since triplet loss relies on a relative distance that makes it more flexible against the images' variations, caused by their capture from different camera views. However, in mono-camera Multi-Object Tracking, the variations among the images of the same person even after temporary disappearances, are not so wide as in Re-Identification. Therefore, in the MOT domain, the Siamese model can perform the discrimination of the pairs of samples in two well-differentiated groups, positive and negative pairs, better than the triplet model.
- Transference of learning from the Multi-Object Tracking domain to the Re-Identification task and Triplets Permutation reduce the over-fitting of the Re-Id model, using a unique neural architecture. These methods allow the application of DCNNs to automatically extract salient features for Re-Identification. The proposed methods palliate the Re-Id data problem preventing from extra data acquisition and labelling costs.
- The application of some techniques, such as data augmentation and body shape partition not always increase the performance of the Re-Id model. In general, this strategies brings the enhancement of the results, because data augmentation enlarges the variety of training samples and the body shape partition reduces the dependence on the pose and background, so the model is focused on dealing with the variations among different camera views. However, this is not the case when the Re-Id model is meant to re-identify people from two fixed camera views, where the variations between cameras can be modelled by the network. In that case, the subtraction of the background and the introduction of a wide variety of training samples disturb such modelling.
- The training of a model on larger datasets results in an enhancement of its performance, as long as, the training data do not differ in a certain measure from the target test data.
- In the case of re-identifying from two fixed camera views, the use of Mahalanobis distance to compare two images implicitly contributes to deal with the intra-class variations, since the Mahalanobis matrix embeds the camera-to-camera transitions.

- The evaluation results demonstrate that deeply learned features provide larger discriminative power than low-level features based on colour and texture.

Furthermore, some of the highlighted characteristics of the proposed methods are summarised as follows:

- The designed association method and identification models are versatile and robust against multiple situations, and different scenarios, since they have been evaluated over datasets presenting a wide variety and number of people, in outdoors and indoors scenarios, and from fixed and mobile cameras, from different perspectives. For all the sequences the setting of the hyper-parameters of the tracking algorithm was the same, so the versatility of a universal algorithm has been proved.
- The proposed system is modular and scalable. In that way, the developed methods are susceptible of application to different problems like face recognition or tracking with search and rescue purposes, as it has been described in Sections 4.10 and 5.9.
- The tracking method does not depend on future observations, i.e. it is an online tracking algorithm; and temporary consistency is provided by modelling the agents' appearance with a Long Short-Term Memory network.
- A specialised solution is given to several critical tracking situations, like the intersection of agents, their occlusion, disappearances, merged and split observations caused by crossing agents, and the birth of new tracks. This is achieved by means of the hierarchical association provided by the designed cascade method, the adaptive formulation of the multi-modal cost function and the agent management strategy.
- Tracking of multiple people by a unique visual appearance model without previous knowledge about the scene is achieved by integrating the DoAS model into the surveillance system. The use of a previously trained model (offline learning) avoids the requirement of a large number of frames to learn a reliable model for every agent, during the tracking task. Therefore, the proposed data association presents the same performance from the beginning of the tracking.
- The learnt appearance model is capable of dealing with failed associations from previous frames and crossing agents, preventing from further propagation of the identities mismatching, by means of simulating that type of situations and training an LSTM cell on them.
- Identities switches have been reduced through the proposed Global Hypotheses Generator since each agent assignment is conditioned by the rest of the associations in a frame.

- The herein errors from the detection stage, like missed and false-positive agents, are appalled through the geometrical analysis of human skeletons.
- A Single-Shot Re-Identification model is provided to extend the tracking of agents through multiple cameras views with the minimum volume of transmitted information from one sensor to another since the Re-Id model recognises a person among multiple candidates by means of only two images.

7.2 Future Work

This dissertation presents the Degree of Appearance Similarity model as a potential tool with application in a wide variety of computer vision problems. Therefore, many lines of research can emerge from this thesis. In that way, the considered future work encompasses not only the design of strategies to improve the performance of the proposed method, but also to extend its application to the achievement of new surveillance capabilities and modules.

Some of the future works, derived from this dissertation are:

- Implementation of the developed algorithms in embedded systems located at multiple monitoring points of a distributed network of cooperative sensors. The building of a surveillance system of this type is one of the motivations of this thesis, and consequently one of the main future objectives. The architecture and protocols for the communication system must be designed and implemented with that purpose.
- Implementation of the designed Multi-Target Multi-Camera Tracking approach, by the integration of the trained Re-Id model into a module to connect tracks from different camera sequences, and the preparation of the datasets and metrics measurement tools to evaluate such algorithm.
- Designing of action recognition and abnormal behaviour detection methods, from the tracks provided by the presented MOT algorithm, and by means of several of the attributes acquired in the proposed approach, such as the agent's skeletons.
- Implementation of the tracking methods backwards in time, over saved sequences, in a parallel way to the real-time forward Multi-Object Tracking. The adoption of an online approach with a frame-by-frame association enables the application of the algorithm backwards in time easily. The data association method and the appearance models proposed are invariant to causality. This property allows the application of this method in both modes, time forwards and backwards.

- Implementation of a detection stage by integrating one of the bench-marked detectors in the proposed algorithm architecture.
- Designing of a module to identify points of emergence and disappearance of agents in the video sequences to solve the problem of identifying birth and deaths of tracks. In that way, an agent missed by the detector or temporarily occluded can be differentiated from an agent that is moving out of the scene, and a false positive or not well-associated detection can be differentiated from a real new agent appearing in the scene.
- Improving the skeleton extractor module by the use of more modern versions of the Convolutional Pose Machine on which it is based. The aim is to obtain a reliable body parts definition to enable that the tracking and the re-identification rely on only some parts of agents. This approach would provide a good surveillance performance even, when the agents are partially occluded, like in crowd scenes.
- Reduction of the time and memory consumption of the algorithm through some measures like its optimisation and parallel coding.

References

- [1] Adam, A., Rivlin, E., and Shimshoni, I. (2006). Robust fragments-based tracking using the integral histogram. In *2006 IEEE Computer society conference on computer vision and pattern recognition (CVPR '06)*, volume 1, pages 798–805. IEEE.
- [2] Ahmed, E., Jones, M., and Marks, T. K. (2015). An improved deep learning architecture for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3908–3916.
- [3] Al-Kaff, A., Gómez-Silva, M. J., Moreno, F. M., de la Escalera, A., and Armingol, J. M. (2019). An appearance-based tracking algorithm for aerial search and rescue purposes. *Sensors*, 19(3):652.
- [4] Alahi, A., Goel, K., Ramanathan, V., Robicquet, A., Fei-Fei, L., and Savarese, S. (2016). Social lstm: Human trajectory prediction in crowded spaces. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 961–971.
- [5] Alahi, A., Haque, A., and Fei-Fei, L. (2015). Rgb-w: When vision meets wireless. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 3289–3297.
- [6] Ali, S. and Shah, M. (2008). Floor fields for tracking in high density crowd scenes. In *European conference on computer vision*, pages 1–14. Springer.
- [7] Alipanahi, B., Biggs, M., Ghodsi, A., et al. (2008). Distance metric learning vs. fisher discriminant analysis. In *Proceedings of the 23rd national conference on Artificial intelligence*, volume 2, pages 598–603.
- [8] Andriluka, M., Roth, S., and Schiele, B. (2008). People-tracking-by-detection and people-detection-by-tracking. In *Computer Vision and Pattern Recognition, 2008. CVPR 2008. IEEE Conference on*, pages 1–8. IEEE.
- [9] Andriyenko, A., Schindler, K., and Roth, S. (2012). Discrete-continuous optimization for multi-target tracking. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1926–1933. IEEE.
- [10] Ashby, M. P. (2017). The value of cctv surveillance cameras as an investigative tool: An empirical analysis. *European Journal on Criminal Policy and Research*, 23(3):441–459.
- [11] Avraham, T., Gurvich, I., Lindenbaum, M., and Markovitch, S. (2012). Learning implicit transfer for person re-identification. In *European Conference on Computer Vision*, pages 381–390. Springer.

- [12] Ayazoglu, M., Li, B., Dicle, C., Sznaier, M., and Camps, O. I. (2011). Dynamic subspace-based coordinated multicamera tracking. In *2011 International Conference on Computer Vision*, pages 2462–2469. IEEE.
- [13] Aziz, K.-E., Merad, D., and Fertil, B. (2011a). People re-identification across multiple non-overlapping cameras system by appearance classification and silhouette part segmentation. In *Advanced Video and Signal-Based Surveillance (AVSS), 2011 8th IEEE International Conference on*, pages 303–308. IEEE.
- [14] Aziz, K.-E., Merad, D., and Fertil, B. (2011b). Person re-identification using appearance classification. In *International Conference Image Analysis and Recognition*, pages 170–179. Springer.
- [15] Bae, S.-H. and Yoon, K.-J. (2014a). Robust online multi-object tracking based on tracklet confidence and online discriminative appearance learning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1218–1225.
- [16] Bae, S.-H. and Yoon, K.-J. (2014b). Robust online multiobject tracking with data association and track management. *IEEE transactions on image processing*, 23(7):2820–2833.
- [17] Bai, Y.-W., Shen, L.-S., and Li, Z.-H. (2010). Design and implementation of an embedded home surveillance system by use of multiple ultrasonic sensors. *IEEE Transactions on Consumer Electronics*, 56(1):119–124.
- [18] Bai, Y.-W., Xie, Z.-L., and Li, Z.-H. (2011). Design and implementation of a home embedded surveillance system with ultra-low alert power. *IEEE Transactions on Consumer Electronics*, 57(1):153–159.
- [19] Bansal, N., Blum, A., and Chawla, S. (2004). Correlation clustering. *Machine learning*, 56(1-3):89–113.
- [20] Bar-Shalom, Y., Daum, F., and Huang, J. (2009). The probabilistic data association filter. *IEEE Control Systems Magazine*, 29(6):82–100.
- [21] Bayer, J. and Osendorfer, C. (2014). Learning stochastic recurrent networks. *arXiv preprint arXiv:1411.7610*.
- [22] Bazzani, L., Cristani, M., and Murino, V. (2013). Symmetry-driven accumulation of local features for human characterization and re-identification. *Computer Vision and Image Understanding*, 117(2):130–144.
- [23] Bazzani, L., Cristani, M., and Murino, V. (2014). Sdalf: modeling human appearance with symmetry-driven accumulation of local features. In *Person Re-Identification*, pages 43–69. Springer.
- [24] Bazzani, L., Cristani, M., Perina, A., and Murino, V. (2012). Multiple-shot person re-identification by chromatic and epitomic analyses. *Pattern Recognition Letters*, 33(7):898–903.
- [25] Berclaz, J., Fleuret, F., Turetken, E., and Fua, P. (2011). Multiple object tracking using k-shortest paths optimization. *IEEE transactions on pattern analysis and machine intelligence*, 33(9):1806–1819.

- [26] Bergmann, P., Meinhardt, T., and Leal-Taixe, L. (2019). Tracking without bells and whistles. *arXiv preprint arXiv:1903.05625*.
- [27] Bernardin, K. and Stiefelhagen, R. (2008). Evaluating multiple object tracking performance: the clear mot metrics. *EURASIP Journal on Image and Video Processing*, 2008(1):1–10.
- [28] Bishop, G., Welch, G., et al. (2001). An introduction to the kalman filter. *Proc of SIG-GRAPH, Course*, 8(27599-23175):41.
- [29] Blackman, S. and Popoli, R. (1999). Design and analysis of modern tracking systems (artech house radar library). *Artech house*.
- [30] Bottou, L. (2012). Stochastic gradient descent tricks. In *Neural networks: Tricks of the trade*, pages 421–436. Springer.
- [31] Bracken, J. and McGill, J. T. (1973). Mathematical programs with optimization problems in the constraints. *Operations Research*, 21(1):37–44.
- [32] Brederbeck, M., Jiang, X., Körner, M., and Denzler, J. (2012). Data association for multi-object tracking-by-detection in multi-camera networks. In *2012 Sixth International Conference on Distributed Smart Cameras (ICDSC)*, pages 1–6. IEEE.
- [33] Breitenstein, M. D., Reichlin, F., Leibe, B., Koller-Meier, E., and Van Gool, L. (2009). Robust tracking-by-detection using a detector confidence particle filter. In *2009 IEEE 12th International Conference on Computer Vision*, pages 1515–1522. IEEE.
- [34] Breitenstein, M. D., Reichlin, F., Leibe, B., Koller-Meier, E., and Van Gool, L. (2011). Online multiperson tracking-by-detection from a single, uncalibrated camera. *IEEE transactions on pattern analysis and machine intelligence*, 33(9):1820–1833.
- [35] Brendel, W., Amer, M., and Todorovic, S. (2011). Multiobject tracking as maximum weight independent set. In *CVPR 2011*, pages 1273–1280. IEEE.
- [36] Bromley, J., Guyon, I., LeCun, Y., Säckinger, E., and Shah, R. (1994). Signature verification using a "siamese" time delay neural network. In *Advances in neural information processing systems*, pages 737–744.
- [37] Butt, A. A. and Collins, R. T. (2013). Multi-target tracking by lagrangian relaxation to min-cost network flow. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1846–1853.
- [38] Cai, Y. and Medioni, G. (2014). Exploring context information for inter-camera multiple target tracking. In *IEEE Winter Conference on Applications of Computer Vision*, pages 761–768. IEEE.
- [39] Cai, Z., Fan, Q., Feris, R. S., and Vasconcelos, N. (2016). A unified multi-scale deep convolutional neural network for fast object detection. In *European conference on computer vision*, pages 354–370. Springer.
- [40] Calderara, S., Cucchiara, R., and Prati, A. (2008). Bayesian-competitive consistent labeling for people surveillance. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 30(2):354–360.

- [41] Cao, L., Chen, W., Chen, X., Zheng, S., and Huang, K. (2015). An equalised global graphical model-based approach for multi-camera object tracking. *arXiv preprint arXiv:1502.03532*.
- [42] Cao, Z., Simon, T., Wei, S.-E., and Sheikh, Y. (2017). Realtime multi-person 2d pose estimation using part affinity fields. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 7291–7299.
- [43] Castro, J., Delgado, M., Medina, J., and Ruiz-Lozano, M. (2011). Intelligent surveillance system with integration of heterogeneous information for intrusion detection. *Expert Systems with Applications*, 38(9):11182–11192.
- [44] Chan-Lang, S., Pham, Q. C., and Achard, C. (2016). Bidirectional sparse representations for multi-shot person re-identification. In *Advanced Video and Signal Based Surveillance (AVSS), 2016 13th IEEE International Conference on*, pages 263–270. IEEE.
- [45] Chang, C.-C. and Lin, C.-J. (2011). Libsvm: a library for support vector machines. *ACM transactions on intelligent systems and technology (TIST)*, 2(3):27.
- [46] Chari, V., Lacoste-Julien, S., Laptev, I., and Sivic, J. (2015). On pairwise costs for network flow multi-object tracking. In *proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5537–5545.
- [47] Chen, K.-W., Lai, C.-C., Lee, P.-J., Chen, C.-S., and Hung, Y.-P. (2011a). Adaptive learning for target tracking and true linking discovering across multiple non-overlapping cameras. *IEEE Transactions on Multimedia*, 13(4):625–638.
- [48] Chen, S.-Z., Guo, C.-C., and Lai, J.-H. (2016). Deep ranking for person re-identification via joint representation learning. *IEEE Transactions on Image Processing*, 25(5):2353–2367.
- [49] Chen, X., An, L., and Bhanu, B. (2015). Multitarget tracking in nonoverlapping cameras using a reference set. *IEEE Sensors Journal*, 15(5):2692–2704.
- [50] Chen, X., Huang, K., and Tan, T. (2011b). Direction-based stochastic matching for pedestrian recognition in non-overlapping cameras. In *2011 18th IEEE International Conference on Image Processing*, pages 2065–2068. IEEE.
- [51] Chen, Y.-C., Zhu, X., Zheng, W.-S., and Lai, J.-H. (2018). Person re-identification by camera correlation aware feature augmentation. *IEEE transactions on pattern analysis and machine intelligence*, 40(2):392–408.
- [52] Chen, Y.-L., Wu, B.-F., Huang, H.-Y., and Fan, C.-J. (2011c). A real-time vision system for nighttime vehicle detection and traffic surveillance. *IEEE Transactions on Industrial Electronics*, 58(5):2030–2044.
- [53] Cheng, D., Gong, Y., Zhou, S., Wang, J., and Zheng, N. (2016). Person re-identification by multi-channel parts-based cnn with improved triplet loss function. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1335–1344.
- [54] Cheng, D. S. and Cristani, M. (2014). Person re-identification by articulated appearance matching. In *Person Re-Identification*, pages 139–160. Springer.

- [55] Cheng, D. S., Cristani, M., Stoppa, M., Bazzani, L., and Murino, V. (2011). Custom pictorial structures for re-identification. *Bmvc*, 1(2):6.
- [56] Choi, W. (2015). Near-online multi-target tracking with aggregated local flow descriptor. In *Proceedings of the IEEE international conference on computer vision*, pages 3029–3037.
- [57] Choi, W., Pantofaru, C., and Savarese, S. (2013). A general framework for tracking multiple people from a moving camera. *IEEE transactions on pattern analysis and machine intelligence*, 35(7):1577–1591.
- [58] Choi, W. and Savarese, S. (2010). Multiple target tracking in world coordinate with single, minimally calibrated camera. In *European Conference on Computer Vision*, pages 553–567. Springer.
- [59] Choi, W. and Savarese, S. (2012). A unified framework for multi-target tracking and collective activity recognition. In *European Conference on Computer Vision*, pages 215–230. Springer.
- [60] Chung, J., Kastner, K., Dinh, L., Goel, K., Courville, A. C., and Bengio, Y. (2015). A recurrent latent variable model for sequential data. In *Advances in neural information processing systems*, pages 2980–2988.
- [61] Collins, R. T. (2012). Multitarget data association with higher-order motion models. In *2012 IEEE conference on computer vision and pattern recognition*, pages 1744–1751. IEEE.
- [62] Collins, R. T., Lipton, A. J., Fujiyoshi, H., and Kanade, T. (2001). Algorithms for cooperative multisensor surveillance. *Proceedings of the IEEE*, 89(10):1456–1477.
- [63] Collins, R. T., Lipton, A. J., Kanade, T., Fujiyoshi, H., Duggins, D., Tsin, Y., Tolliver, D., Enomoto, N., Hasegawa, O., Burt, P., et al. (2000). A system for video surveillance and monitoring. *VSAM final report*, pages 1–68.
- [64] Colson, B., Marcotte, P., and Savard, G. (2007). An overview of bilevel optimization. *Annals of operations research*, 153(1):235–256.
- [65] Comaniciu, D. and Meer, P. (2002). Mean shift: A robust approach toward feature space analysis. *IEEE Transactions on pattern analysis and machine intelligence*, 24(5):603–619.
- [66] Commission, E. (2003). Research for a secure europe. *Report of the Group of Personalities in the field of Security Research*, page 30.
- [67] Commission, E. (2015). Communication from the commission to the european parliament, the council, the european economic and social committee and the committee of the regions. *The European Agenda on Security*.
- [68] Commission, E. (2017). Special eurobarometer 464b. europeans’ attitudes towards security. *Wave EB87.4*, 1.
- [69] Commission, E. (2018a). Communication from the commission to the european parliament, the european council and the council. *Seventeenth Progress Report towards an effective and genuine Security Union*.
- [70] Commission, E. (2018b). Standard eurobarometer 90 -autumn 2018. public opinion in the european union, first results. *Wave EB90.3*, NA-06-18-369-EN-N.

- [71] Committee, C. S. et al. (2014). Iso international standard iso/iec 14882: 2014, programming language c++. Technical report, Technical report, Geneva, Switzerland: International Organization for
- [72] Cortes, C., Mohri, M., and Rostamizadeh, A. (2009). L₂ regularization for learning kernels. In *Proceedings of the Twenty-Fifth Conference on Uncertainty in Artificial Intelligence*, pages 109–116. AUAI Press.
- [73] Corvee, E., Bremond, F., Thonnat, M., et al. (2010a). Person re-identification using haar-based and dcd-based signature. In *2010 Seventh IEEE International Conference on Advanced Video and Signal Based Surveillance*, pages 1–8. IEEE.
- [74] Corvee, E., Bremond, F., Thonnat, M., et al. (2010b). Person re-identification using spatial covariance regions of human body parts. In *Advanced Video and Signal Based Surveillance (AVSS), 2010 Seventh IEEE International Conference on*, pages 435–440. IEEE.
- [75] Cox, I. J. and Hingorani, S. L. (1996). An efficient implementation of reid’s multiple hypothesis tracking algorithm and its evaluation for the purpose of visual tracking. *IEEE Transactions on pattern analysis and machine intelligence*, 18(2):138–150.
- [76] Cucchiara, R. (2005). Multimedia surveillance systems. In *Proceedings of the third ACM international workshop on Video surveillance & sensor networks*, pages 3–10. ACM.
- [77] Cucchiara, R., Prati, A., and Vezzani, R. (2007). A multi-camera vision system for fall detection and alarm generation. *Expert Systems*, 24(5):334–345.
- [78] Dalal, N. and Triggs, B. (2005). Histograms of oriented gradients for human detection. In *Computer Vision and Pattern Recognition, 2005. CVPR 2005. IEEE Computer Society Conference on*, volume 1, pages 886–893. IEEE.
- [79] Daliyot, S. and Netanyahu, N. S. (2012). A framework for inter-camera association of multi-target trajectories by invariant target models. In *Asian Conference on Computer Vision*, pages 372–386. Springer.
- [80] Das, A., Chakraborty, A., and Roy-Chowdhury, A. K. (2014). Consistent re-identification in a camera network. In *European conference on computer vision*, pages 330–345. Springer.
- [81] Davis, J. V., Kulis, B., Jain, P., Sra, S., and Dhillon, I. S. (2007). Information-theoretic metric learning. In *Proceedings of the 24th international conference on Machine learning*, pages 209–216. ACM.
- [82] Dehghan, A., Modiri Assari, S., and Shah, M. (2015). Gmmcp tracker: Globally optimal generalized maximum multi clique problem for multiple object tracking. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4091–4099.
- [83] Demaine, E. D., Emanuel, D., Fiat, A., and Immorlica, N. (2006). Correlation clustering in general weighted graphs. *Theoretical Computer Science*, 361(2-3):172–187.
- [84] Deng, J., Dong, W., Socher, R., Li, L.-J., Li, K., and Fei-Fei, L. (2009). Imagenet: A large-scale hierarchical image database. In *Computer Vision and Pattern Recognition, 2009. CVPR 2009. IEEE Conference on*, pages 248–255. Ieee.

- [85] detec (Accessed: 21/03/2019). *DETEC - YOUR SECURITY*.
- [86] Dicle, C., Camps, O. I., and Sznaiar, M. (2013). The way they move: Tracking multiple targets with similar appearance. In *Proceedings of the IEEE international conference on computer vision*, pages 2304–2311.
- [87] Dikmen, M., Akbas, E., Huang, T. S., and Ahuja, N. (2010). Pedestrian recognition with a learned metric. In *Asian conference on Computer vision*, pages 501–512. Springer.
- [88] Ding, S., Lin, L., Wang, G., and Chao, H. (2015). Deep feature learning with relative distance comparison for person re-identification. *Pattern Recognition*, 48(10):2993–3003.
- [89] Dollár, P., Appel, R., Belongie, S., and Perona, P. (2014). Fast feature pyramids for object detection. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 36(8):1532–1545.
- [90] Dollár, P., Tu, Z., Tao, H., and Belongie, S. (2007). Feature mining for image classification. In *Computer Vision and Pattern Recognition, 2007. CVPR'07. IEEE Conference on*, pages 1–8. IEEE.
- [91] Dollar, P., Wojek, C., Schiele, B., and Perona, P. (2012). Pedestrian detection: An evaluation of the state of the art. *IEEE transactions on pattern analysis and machine intelligence*, 34(4):743–761.
- [92] Donahue, J., Jia, Y., Vinyals, O., Hoffman, J., Zhang, N., Tzeng, E., and Darrell, T. (2014). Decaf: A deep convolutional activation feature for generic visual recognition. In *International conference on machine learning*, pages 647–655.
- [93] Duchi, J., Hazan, E., and Singer, Y. (2011). Adaptive subgradient methods for online learning and stochastic optimization. *Journal of Machine Learning Research*, 12(Jul):2121–2159.
- [94] Elfes, A. (1989). Using occupancy grids for mobile robot perception and navigation. *Computer*, 22(6):46–57.
- [95] Enzweiler, M. and Gavrila, D. M. (2009). Monocular pedestrian detection: Survey and experiments. *IEEE transactions on pattern analysis and machine intelligence*, 31(12):2179–2195.
- [96] Ess, A., Leibe, B., Schindler, K., and Van Gool, L. (2008). A mobile vision system for robust multi-person tracking. In *2008 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1–8. IEEE.
- [97] Ess, A., Leibe, B., Schindler, K., and Van Gool, L. (2009a). Robust multiperson tracking from a mobile platform. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 31(10):1831–1846.
- [98] Ess, A., Schindler, K., Leibe, B., and Van Gool, L. (2009b). Improved multi-person tracking with active occlusion handling. In *ICRA Workshop on People Detection and Tracking*, volume 2. Citeseer.
- [99] Exner, D., Bruns, E., Kurz, D., Grundhöfer, A., and Bimber, O. (2010). Fast and robust camshift tracking. In *2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition-Workshops*, pages 9–16. IEEE.

- [100] Fan, J., Xu, W., Wu, Y., and Gong, Y. (2010). Human tracking using convolutional neural networks. *IEEE Transactions on Neural Networks*, 21(10):1610–1623.
- [101] Farenzena, M., Bazzani, L., Perina, A., Murino, V., and Cristani, M. (2010). Person re-identification by symmetry-driven accumulation of local features. In *Computer Vision and Pattern Recognition (CVPR), 2010 IEEE Conference on*, pages 2360–2367. IEEE.
- [102] Felzenszwalb, P. F., Girshick, R. B., McAllester, D., and Ramanan, D. (2010). Object detection with discriminatively trained part-based models. *IEEE transactions on pattern analysis and machine intelligence*, 32(9):1627–1645.
- [103] Felzenszwalb, P. F. and Huttenlocher, D. P. (2005). Pictorial structures for object recognition. *International journal of computer vision*, 61(1):55–79.
- [104] Feng, L., Xiaoyu, L., and Yi, C. (2014). An efficient detection method for rare colored capsule based on rgb and hsv color space. In *Granular Computing (GrC), 2014 IEEE International Conference on*, pages 175–178. IEEE.
- [105] Feng, W., Hu, Z., Wu, W., Yan, J., and Ouyang, W. (2019). Multi-object tracking with multiple cues and switcher-aware classification. *arXiv preprint arXiv:1901.06129*.
- [106] Fischer, P., Dosovitskiy, A., Ilg, E., Häusser, P., Hazırbaş, C., Golkov, V., Van der Smagt, P., Cremers, D., and Brox, T. (2015). FlowNet: Learning optical flow with convolutional networks. *arXiv preprint arXiv:1504.06852*.
- [107] Fisher, R., Santos-Victor, J., and Crowley, J. (2005). *CAVIAR: Context aware vision using image-based active recognition*.
- [108] Fisher, R. A. (1936). The use of multiple measurements in taxonomic problems. *Annals of eugenics*, 7(2):179–188.
- [109] Fleuret, F., Berclaz, J., Lengagne, R., and Fua, P. (2008). Multicamera people tracking with a probabilistic occupancy map. *IEEE transactions on pattern analysis and machine intelligence*, 30(2):267–282.
- [110] Fontaine, E., Barr, A. H., and Burdick, J. W. (2007). Model-based tracking of multiple worms and fish. In *ICCV Workshop on Dynamical Vision*.
- [111] Fookes, C., Denman, S., Lakemond, R., Ryan, D., Sridharan, S., and Piccardi, M. (2010). Semi-supervised intelligent surveillance system for secure environments. In *2010 IEEE International Symposium on Industrial Electronics*, pages 2815–2820. IEEE.
- [112] Fukunaga, K. and Flick, T. E. (1984). An optimal global nearest neighbor metric. *IEEE transactions on Pattern analysis and Machine Intelligence*, (3):314–318.
- [113] Ganin, Y. and Lempitsky, V. (2014). Unsupervised domain adaptation by backpropagation. *arXiv preprint arXiv:1409.7495*.
- [114] García, F., García, J., Ponz, A., De La Escalera, A., and Armingol, J. M. (2014). Context aided pedestrian detection for danger estimation based on laser scanner and computer vision. *Expert Systems with Applications*, 41(15):6646–6661.

- [115] Geng, M., Wang, Y., Xiang, T., and Tian, Y. (2016). Deep transfer learning for person re-identification. *arXiv preprint arXiv:1611.05244*.
- [116] Gerónimo Gomez, D., Lerasle, F., and López Peña, A. (2012). State-driven particle filter for multi-person tracking. In *Advanced Concepts for Intelligent Vision Systems*, pages 467–478. Springer.
- [117] Gheissari, N., Sebastian, T. B., and Hartley, R. (2006). Person reidentification using spatiotemporal appearance. In *null*, pages 1528–1535. IEEE.
- [118] Ghodsi, A., Wilkinson, D. F., and Southey, F. (2007). Improving embeddings by flexible exploitation of side information. In *IJCAI*, pages 810–816.
- [119] Gilbert, A. and Bowden, R. (2006). Tracking objects across cameras by incrementally learning inter-camera colour calibration and patterns of activity. In *European conference on computer vision*, pages 125–136. Springer.
- [120] Girshick, R. (2015). Fast r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pages 1440–1448.
- [121] Girshick, R., Donahue, J., Darrell, T., and Malik, J. (2014). Rich feature hierarchies for accurate object detection and semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 580–587.
- [122] Glorot, X. and Bengio, Y. (2010). Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 249–256.
- [123] Goferman, S., Zelnik-Manor, L., and Tal, A. (2012). Context-aware saliency detection. *IEEE transactions on pattern analysis and machine intelligence*, 34(10):1915–1926.
- [124] Golbabaee, M., Alahi, A., and Vandergheynst, P. (2014). Scoop: A real-time sparsity driven people localization algorithm. *Journal of mathematical imaging and vision*, 48(1):160–175.
- [125] Gómez, M. J., García, F., Martín, D., de la Escalera, A., and Armingol, J. M. (2015). Intelligent surveillance of indoor environments based on computer vision and 3d point cloud fusion. *Expert Systems with Applications*, 42(21):8156–8171.
- [126] Gómez-Silva, M., Armingol, J., and de la Escalera, A. (2016). Multi-object tracking with data association by a similarity identification model.
- [127] Gomez-Silva, M., Armingol, J., and de la Escalera, A. (2017). Multi-object tracking errors minimisation by visual similarity and human joints detection.
- [128] Gómez-Silva, M. J., Armingol, J. M., and de la Escalera, A. (2017). Deep part features learning by a normalised double-margin-based contrastive loss function for person re-identification. In *In Proceedings of the 12th International Joint Conference on Computer Vision, Imaging and Computer Graphics Theory and Applications (VISIGRAPP 2017) (6: VISAPP)*, pages 277–285.
- [129] Gómez-Silva, M. J., Armingol, J. M., and de la Escalera, A. (2018). Deep parts similarity learning for person re-identification. In *In Proceedings of the 13th International Joint Conference on Computer Vision, Imaging and Computer Graphics Theory and Applications (VISIGRAPP 2018)*, pages 419–428.

- [130] Gómez Silva, M. J., Armingol, J. M., and de la Escalera, A. (2018). Re-identificación de personas mediante la distancia de mahalanobis. *Actas de las XXXIX Jornadas de Automática, Badajoz, 5-7 de Septiembre de 2018*.
- [131] Gómez-Silva, M. J., Armingol, J. M., and de la Escalera, A. (2019a). Balancing people re-identification data for deep parts similarity learning. *Journal of Imaging Science and Technology*.
- [132] Gómez-Silva, M. J., Izquierdo, E., Escalera, A. d. l., and Armingol, J. M. (2019b). Transferring learning from multi-person tracking to person re-identification. *Integrated Computer-Aided Engineering*, (Preprint):1–16.
- [133] Gong, S., Cristani, M., Loy, C. C., and Hospedales, T. M. (2014). The re-identification challenge. In *Person re-identification*, pages 1–20. Springer.
- [134] Gordon, D., Farhadi, A., and Fox, D. (2017). Re3: real-time recurrent regression networks for object tracking. *arXiv preprint arXiv:1705.06368*, 2.
- [135] Gordon, N. J., Salmond, D. J., and Smith, A. F. (1993). Novel approach to nonlinear/non-gaussian bayesian state estimation. In *IEEE Proceedings F(Radar and Signal Processing)*, volume 140, pages 107–113. IET.
- [136] Grabner, H., Grabner, M., and Bischof, H. (2006). Real-time tracking via on-line boosting. In *Bmvc*, volume 1, page 6.
- [137] Gray, D., Brennan, S., and Tao, H. (2007). Evaluating appearance models for recognition, reacquisition, and tracking. In *Proc. IEEE International Workshop on Performance Evaluation for Tracking and Surveillance (PETS)*, volume 3, pages 1–7. Citeseer.
- [138] Gray, D. and Tao, H. (2008). Viewpoint invariant pedestrian recognition with an ensemble of localized features. In *European conference on computer vision*, pages 262–275. Springer.
- [139] Gregor, K., Danihelka, I., Graves, A., Rezende, D. J., and Wierstra, D. (2015). Draw: A recurrent neural network for image generation. *arXiv preprint arXiv:1502.04623*.
- [140] Guillaumin, M., Verbeek, J., and Schmid, C. (2009). Is that you? metric learning approaches for face identification. In *Computer Vision, 2009 IEEE 12th international conference on*, pages 498–505. IEEE.
- [141] Hadsell, R., Chopra, S., and LeCun, Y. (2006). Dimensionality reduction by learning an invariant mapping. In *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR '06)*, volume 2, pages 1735–1742. IEEE.
- [142] Han, M., Xu, W., Tao, H., and Gong, Y. (2004). An algorithm for multiple object trajectory tracking. In *Proceedings of the 2004 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, 2004. CVPR 2004.*, volume 1, pages I–I. IEEE.
- [143] Hanley, J. A. and McNeil, B. J. (1982). The meaning and use of the area under a receiver operating characteristic (roc) curve. *Radiology*, 143(1):29–36.
- [144] Hannes Kruppa, M. C.-S. and Schiele, B. (2003"). Fast and robust face finding via local context. In *Joint IEEE International Workshop on Visual Surveillance and Performance Evaluation of Tracking and Surveillance*.

- [145] He, K., Zhang, X., Ren, S., and Sun, J. (2015a). Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pages 1026–1034.
- [146] He, K., Zhang, X., Ren, S., and Sun, J. (2015b). Spatial pyramid pooling in deep convolutional networks for visual recognition. *IEEE transactions on pattern analysis and machine intelligence*, 37(9):1904–1916.
- [147] He, K., Zhang, X., Ren, S., and Sun, J. (2016). Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778.
- [148] Helbing, D. and Molnar, P. (1995). Social force model for pedestrian dynamics. *Physical review E*, 51(5):4282.
- [149] Held, D., Thrun, S., and Savarese, S. (2016). Learning to track at 100 fps with deep regression networks. In *European Conference on Computer Vision*, pages 749–765. Springer.
- [150] Hermans, A., Beyer, L., and Leibe, B. (2017). In defense of the triplet loss for person re-identification. *arXiv preprint arXiv:1703.07737*.
- [151] Hinton, G. E. and Salakhutdinov, R. R. (2006). Reducing the dimensionality of data with neural networks. *science*, 313(5786):504–507.
- [152] Hirzer, M., Beleznaï, C., Roth, P. M., and Bischof, H. (2011). Person re-identification by descriptive and discriminative classification. In *Scandinavian conference on Image analysis*, pages 91–102. Springer.
- [153] Hirzer, M., Roth, P., Köstinger, M., and Bischof, H. (2012a). Relaxed pairwise learned metric for person re-identification. *Computer Vision–ECCV 2012*, pages 780–793.
- [154] Hirzer, M., Roth, P. M., and Bischof, H. (2012b). Person re-identification by efficient impostor-based metric learning. In *Advanced Video and Signal-Based Surveillance (AVSS), 2012 IEEE Ninth International Conference on*, pages 203–208. IEEE.
- [155] Hochreiter, S. and Schmidhuber, J. (1997). Long short-term memory. *Neural computation*, 9(8):1735–1780.
- [156] Hong, S. and Han, B. (2014). Visual tracking by sampling tree-structured graphical models. In *European Conference on Computer Vision*, pages 1–16. Springer.
- [157] Hu, M., Ali, S., and Shah, M. (2008). Detecting global motion patterns in complex videos. In *2008 19th International Conference on Pattern Recognition*, pages 1–5. Ieee.
- [158] Hu, W., Hu, M., Zhou, X., Tan, T., Lou, J., and Maybank, S. (2006). Principal axis-based correspondence between multiple cameras for people tracking. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 28(4):663–671.
- [159] Huang, C., Change Loy, C., and Tang, X. (2016). Unsupervised learning of discriminative attributes and visual representations. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5175–5184.

- [160] Huang, C., Li, Y., and Nevatia, R. (2013). Multiple target tracking by learning-based hierarchical association of detection responses. *IEEE transactions on pattern analysis and machine intelligence*, 35(4):898–910.
- [161] Huang, C., Wu, B., and Nevatia, R. (2008). Robust object tracking by hierarchical association of detection responses. In *European Conference on Computer Vision*, pages 788–801. Springer.
- [162] Ibrahim, S. (2016). A comprehensive review on intelligent surveillance systems. *Communications in Science and Technology*, 1.
- [163] Itseez (2014). *The OpenCV Reference Manual*. Itseez, 2.4.9.0 edition.
- [164] Itseez (2015). Open source computer vision library. <https://github.com/itseez/opencv>.
- [165] Izadinia, H., Ramakrishna, V., Kitani, K. M., and Huber, D. (2013). Multi-pose multi-target tracking for activity understanding. In *2013 IEEE Workshop on Applications of Computer Vision (WACV)*, pages 385–390. IEEE.
- [166] Izadinia, H., Saleemi, I., Li, W., and Shah, M. (2012). 2 t: multiple people multiple parts tracker. In *European Conference on Computer Vision*, pages 100–114. Springer.
- [167] Javed, O., Shafique, K., Rasheed, Z., and Shah, M. (2008). Modeling inter-camera space-time and appearance relationships for tracking across non-overlapping views. *Computer Vision and Image Understanding*, 109(2):146–162.
- [168] Jeong, K. and Jaynes, C. (2008). Object matching in disjoint cameras using a color transfer approach. *Machine Vision and Applications*, 19(5-6):443–455.
- [169] Jia, Y., Shelhamer, E., Donahue, J., Karayev, S., Long, J., Girshick, R., Guadarrama, S., and Darrell, T. (2014). Caffe: Convolutional architecture for fast feature embedding. In *Proceedings of the 22nd ACM international conference on Multimedia*, pages 675–678. ACM.
- [170] Junior, J. C. S. J., Musse, S. R., and Jung, C. R. (2010). Crowd analysis using computer vision techniques. *IEEE Signal Processing Magazine*, 27(5):66–77.
- [171] Kalchbrenner, N., Danihelka, I., and Graves, A. (2015). Grid long short-term memory. *arXiv preprint arXiv:1507.01526*.
- [172] Kalman, R. E. (1960). A new approach to linear filtering and prediction problems. *Journal of basic Engineering*, 82(1):35–45.
- [173] Kamal, A. T., Farrell, J. A., and Roy-Chowdhury, A. K. (2013). Information consensus for distributed multi-target tracking. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2403–2410.
- [174] Kang, K., Ouyang, W., Li, H., and Wang, X. (2016). Object detection from video tubelets with convolutional neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 817–825.
- [175] Khan, F. M. and Brémond, F. (2016). Unsupervised data association for metric learning in the context of multi-shot person re-identification. In *Advanced Video and Signal Based Surveillance (AVSS), 2016 13th IEEE International Conference on*, pages 256–262. IEEE.

- [176] Khan, Z., Balch, T., and Dellaert, F. (2005). Mcmc-based particle filtering for tracking a variable number of interacting targets. *IEEE transactions on pattern analysis and machine intelligence*, 27(11):1805–1819.
- [177] Khanloo, B. Y. S., Stefanus, F., Ranjbar, M., Li, Z.-N., Saunier, N., Sayed, T., and Mori, G. (2012). A large margin framework for single camera offline tracking with hybrid cues. *Computer Vision and Image Understanding*, 116(6):676–689.
- [178] Kim, C., Li, F., Ciptadi, A., and Rehg, J. M. (2015). Multiple hypothesis tracking revisited. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 4696–4704.
- [179] Kim, M.-G., Moon, H.-M., Chung, Y., and Pan, S. B. (2012a). A survey and proposed framework on the soft biometrics technique for human identification in intelligent video surveillance system. *BioMed Research International*, 2012.
- [180] Kim, S., Kwak, S., Feyereisl, J., and Han, B. (2012b). Online multi-target tracking by large margin structured learning. In *Asian Conference on Computer Vision*, pages 98–111. Springer.
- [181] Kostinger, M., Hirzer, M., Wohlhart, P., Roth, P. M., and Bischof, H. (2012). Large scale metric learning from equivalence constraints. In *Computer Vision and Pattern Recognition (CVPR), 2012 IEEE Conference on*, pages 2288–2295. IEEE.
- [182] Kratz, L. and Nishino, K. (2012). Tracking pedestrians using local spatio-temporal motion patterns in extremely crowded scenes. *IEEE transactions on pattern analysis and machine intelligence*, 34(5):987–1002.
- [183] Kreutz-Delgado, K., Murray, J. F., Rao, B. D., Engan, K., Lee, T.-W., and Sejnowski, T. J. (2003). Dictionary learning algorithms for sparse representation. *Neural computation*, 15(2):349–396.
- [184] Krizhevsky, A., Sutskever, I., and Hinton, G. E. (2012). Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pages 1097–1105.
- [185] Kuhn, H. W. (1955). The hungarian method for the assignment problem. *Naval research logistics quarterly*, 2(1-2):83–97.
- [186] Kumar, R., Charpiat, G., and Thonnat, M. (2014). Multiple object tracking by efficient graph partitioning. In *Asian Conference on Computer Vision*, pages 445–460. Springer.
- [187] Kuo, C.-H., Huang, C., and Nevatia, R. (2010a). Inter-camera association of multi-target tracks by on-line learned appearance affinity models. In *European Conference on Computer Vision*, pages 383–396. Springer.
- [188] Kuo, C.-H., Huang, C., and Nevatia, R. (2010b). Multi-target tracking by on-line learned discriminative appearance models. In *2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, pages 685–692. IEEE.
- [189] Kuo, C.-H. and Nevatia, R. (2011). How does person identity recognition help multi-person tracking? In *CVPR 2011*, pages 1217–1224. IEEE.

- [190] Layne, R., Hospedales, T. M., and Gong, S. (2013). Domain transfer for person re-identification. In *Proceedings of the 4th ACM/IEEE international workshop on Analysis and retrieval of tracked events and motion in imagery stream*, pages 25–32. ACM.
- [191] Layne, R., Hospedales, T. M., and Gong, S. (2014). Attributes-based re-identification. In *Person Re-Identification*, pages 93–117. Springer.
- [192] Le, N., Heili, A., and Odobez, J.-M. (2016). Long-term time-sensitive costs for crf-based tracking by detection. In *European Conference on Computer Vision*, pages 43–51. Springer.
- [193] Leal-Taixé, L., Canton-Ferrer, C., and Schindler, K. (2016). Learning by tracking: Siamese cnn for robust target association. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pages 33–40.
- [194] Leal-Taixé, L., Milan, A., Reid, I., Roth, S., and Schindler, K. (2015). Motchallenge 2015: Towards a benchmark for multi-target tracking. *arXiv preprint arXiv:1504.01942*.
- [195] Leal-Taixé, L., Pons-Moll, G., and Rosenhahn, B. (2011). Everybody needs somebody: Modeling social and grouping behavior on a linear programming multiple people tracker. In *2011 IEEE international conference on computer vision workshops (ICCV workshops)*, pages 120–127. IEEE.
- [196] LeCun, Y., Bengio, Y., and Hinton, G. (2015). Deep learning review. weekly journal of science in nature international. *Nature*, 521.
- [197] Leininger, B., Edwards, J., Antoniadis, J., Chester, D., Haas, D., Liu, E., Stevens, M., Gershfield, C., Braun, M., Targove, J. D., et al. (2008). Autonomous real-time ground ubiquitous surveillance-imaging system (argus-is). In *Defense Transformation and Net-Centric Systems 2008*, volume 6981, page 69810H. International Society for Optics and Photonics.
- [198] Li, K., Miller, E. D., Chen, M., Kanade, T., Weiss, L. E., and Campbell, P. G. (2008). Cell population tracking and lineage construction with spatiotemporal context. *Medical image analysis*, 12(5):546–566.
- [199] Li, W. and Wang, X. (2013). Locally aligned feature transforms across views. In *Computer Vision and Pattern Recognition (CVPR), 2013 IEEE Conference on*, pages 3594–3601. IEEE.
- [200] Li, W., Wu, Y., Mukunoki, M., and Minoh, M. (2012a). Common-near-neighbor analysis for person re-identification. In *2012 19th IEEE International Conference on Image Processing*, pages 1621–1624. IEEE.
- [201] Li, W., Zhao, R., and Wang, X. (2012b). Human reidentification with transferred metric learning. In *Asian Conference on Computer Vision*, pages 31–44. Springer.
- [202] Li, W., Zhao, R., Xiao, T., and Wang, X. (2014). Deepreid: Deep filter pairing neural network for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 152–159.
- [203] Li, W., Zhu, X., and Gong, S. (2018). Harmonious attention network for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2285–2294.

- [204] Li, Y., Huang, C., and Nevatia, R. (2009). Learning to associate: Hybridboosted multi-target tracker for crowded scene. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 2953–2960. IEEE.
- [205] Li, Z., Chang, S., Liang, F., Huang, T. S., Cao, L., and Smith, J. R. (2013). Learning locally-adaptive decision functions for person verification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3610–3617.
- [206] Lian, G., Lai, J.-H., Suen, C. Y., and Chen, P. (2012). Matching of tracked pedestrians across disjoint camera views using ci-dlbp. *IEEE Transactions on Circuits and Systems for Video Technology*, 22(7):1087–1099.
- [207] Liao, S., Hu, Y., Zhu, X., and Li, S. Z. (2015). Person re-identification by local maximal occurrence representation and metric learning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2197–2206.
- [208] Liao, S. and Li, S. Z. (2015). Efficient psd constrained asymmetric metric learning for person re-identification. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 3685–3693.
- [209] Lin, L., Liu, X., and Zhu, S.-C. (2010). Layered graph matching with composite cluster sampling. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 32(8):1426–1442.
- [210] Lin, L., Wang, X., Yang, W., and Lai, J. (2015). Discriminatively trained and-or graph models for object shape detection. *IEEE Transactions on Pattern Analysis & Machine Intelligence*, (1):1–1.
- [211] Lisanti, G., Masi, I., Bagdanov, A. D., and Del Bimbo, A. (2015). Person re-identification by iterative re-weighted sparse ranking. *IEEE transactions on pattern analysis and machine intelligence*, 37(8):1629–1642.
- [212] Liu, C., Change Loy, C., Gong, S., and Wang, G. (2013a). Pop: Person re-identification post-rank optimisation. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 441–448.
- [213] Liu, C., Gong, S., Loy, C. C., and Lin, X. (2012). Person re-identification: What features are important? In *European Conference on Computer Vision*, pages 391–401. Springer.
- [214] Liu, C., Gong, S., Loy, C. C., and Lin, X. (2014a). Evaluating feature importance for re-identification. In *Person Re-Identification*, pages 203–228. Springer.
- [215] Liu, H., Feng, J., Qi, M., Jiang, J., and Yan, S. (2017). End-to-end comparative attention networks for person re-identification. *IEEE Transactions on Image Processing*, 26(7):3492–3506.
- [216] Liu, H., Ma, B., Qin, L., Pang, J., Zhang, C., and Huang, Q. (2015). Set-label modeling and deep metric learning on person re-identification. *Neurocomputing*, 151:1283–1292.
- [217] Liu, J., Carr, P., Collins, R. T., and Liu, Y. (2013b). Tracking sports players with context-conditioned motion models. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1830–1837.

- [218] Liu, W., Anguelov, D., Erhan, D., Szegedy, C., Reed, S., Fu, C.-Y., and Berg, A. C. (2016). Ssd: Single shot multibox detector. In *European conference on computer vision*, pages 21–37. Springer.
- [219] Liu, X., Song, M., Tao, D., Zhou, X., Chen, C., and Bu, J. (2014b). Semi-supervised coupled dictionary learning for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3550–3557.
- [220] Long, M., Zhu, H., Wang, J., and Jordan, M. I. (2016). Deep transfer learning with joint adaptation networks. *arXiv preprint arXiv:1605.06636*.
- [221] Loy, C. C., Liu, C., and Gong, S. (2013). Person re-identification by manifold ranking. In *2013 IEEE International Conference on Image Processing*, pages 3567–3571. IEEE.
- [222] Loy, C. C., Xiang, T., and Gong, S. (2009). Multi-camera activity correlation analysis. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1988–1995. IEEE.
- [223] Loy, C. C., Xiang, T., and Gong, S. (2010). Time-delayed correlation analysis for multi-camera activity understanding. *International Journal of Computer Vision*, 90(1):106–129.
- [224] Luo, W., Kim, T.-K., Stenger, B., Zhao, X., and Cipolla, R. (2014). Bi-label propagation for generic multiple object tracking. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1290–1297.
- [225] Ma, B., Su, Y., and Jurie, F. (2012). Bicov: a novel image representation for person re-identification and face verification. In *British Machine Vision Conference*, pages 11–pages.
- [226] Ma, B., Su, Y., and Jurie, F. (2014a). Discriminative image descriptors for person re-identification. In *Person Re-Identification*, pages 23–42. Springer.
- [227] Ma, L., Yang, X., and Tao, D. (2014b). Person re-identification over camera networks using multi-task distance metric learning. *IEEE Trans. Image Processing*, 23(8):3656–3670.
- [228] Makris, D., Ellis, T., and Black, J. (2004). Bridging the gaps between cameras. In *Proceedings of the 2004 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, 2004. CVPR 2004.*, volume 2, pages II–II. IEEE.
- [229] Markets and Markets (2017). Perimeter security market. *Market Research Report, TC 2196*.
- [230] Martí, E., Martín, D., García, J., De La Escalera, A., Molina, J., and Armingol, J. (2012). Context-aided sensor fusion for enhanced urban navigation. *Sensors*, 12(12):16802–16837.
- [231] matlab (Accessed: 20/03/2019). *Deep Learning Seminar*.
- [232] Matsukawa, T., Okabe, T., Suzuki, E., and Sato, Y. (2016). Hierarchical gaussian descriptor for person re-identification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1363–1372.
- [233] McLaughlin, N., Del Rincon, J. M., and Miller, P. (2015). Enhancing linear programming with motion modeling for multi-target tracking. In *Applications of Computer Vision (WACV), 2015 IEEE Winter Conference on*, pages 71–77. IEEE.

- [234] Meijering, E., Dzyubachyk, O., Smal, I., and van Cappellen, W. A. (2009). Tracking in cell and developmental biology. In *Seminars in cell & developmental biology*, volume 20, pages 894–902. Elsevier.
- [235] Mignon, A. and Jurie, F. (2012). Pcca: A new approach for distance learning from sparse pairwise constraints. In *Computer Vision and Pattern Recognition (CVPR), 2012 IEEE Conference on*, pages 2666–2672. IEEE.
- [236] Milan, A., Leal-Taixé, L., Reid, I., Roth, S., and Schindler, K. (2016). Mot16: A benchmark for multi-object tracking. *arXiv preprint arXiv:1603.00831*.
- [237] Milan, A., Rezatofighi, S. H., Dick, A., Reid, I., and Schindler, K. (2017). Online multi-target tracking using recurrent neural networks. In *Thirty-First AAAI Conference on Artificial Intelligence*.
- [238] Milan, A., Roth, S., and Schindler, K. (2014). Continuous energy minimization for multi-target tracking. *IEEE transactions on pattern analysis and machine intelligence*, 36(1):58–72.
- [239] Molina-Cabello, M. A., Luque-Baena, R. M., López-Rubio, E., and Thurnhofer-Hemsi, K. (2018). Vehicle type detection by ensembles of convolutional neural networks operating on super resolved images. *Integrated Computer-Aided Engineering*, (Preprint):1–13.
- [240] Moon, H. and Phillips, P. J. (2001). Computational and performance aspects of pca-based face-recognition algorithms. *Perception*, 30(3):303–321.
- [241] Morales-Álvarez, W., Gómez-Silva, M. J., Fernández-López, G., García-Fernández, F., and Olaverri-Monreal, C. (2018). Automatic analysis of pedestrian’s body language in the interaction with autonomous vehicles. In *2018 IEEE Intelligent Vehicles Symposium (IV)*, pages 1–6. IEEE.
- [242] Mordohai, P. and Medioni, G. (2010). Dimensionality estimation, manifold learning and function approximation using tensor voting. *Journal of Machine Learning Research*, 11(Jan):411–450.
- [243] Morellas, V., Pavlidis, I., and DETER, P. T. (2003). Detection of events for threat evaluation and recognition machine vision and applications, 15 (1): 29-46.
- [244] Moussy, E., Mekonnen, A. A., Marion, G., and Lerasle, F. (2015). A comparative view on exemplar ‘tracking-by-detection’ approaches. In *Advanced Video and Signal Based Surveillance (AVSS), 2015 12th IEEE International Conference on*, pages 1–6. IEEE.
- [245] Munaro, M., Fossati, A., Basso, A., Menegatti, E., and Van Gool, L. (2014). One-shot person re-identification with a consumer depth camera. In *Person Re-Identification*, pages 161–181. Springer.
- [246] Munkres, J. (1957). Algorithms for the assignment and transportation problems. *Journal of the society for industrial and applied mathematics*, 5(1):32–38.
- [247] Nam, H. and Han, B. (2016). Learning multi-domain convolutional neural networks for visual tracking. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4293–4302.

- [248] Narayan, N., Sankaran, N., Arpit, D., Dantu, K., Setlur, S., and Govindaraju, V. (2017). Person re-identification for improved multi-person multi-camera tracking by continuous entity association. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pages 64–70.
- [249] Ng, A. (Accessed: 20/03/2019). *Nuts and Bolts of Applying Deep Learning (Andrew Ng)*.
- [250] Nillius, P., Sullivan, J., and Carlsson, S. (2006). Multi-target tracking-linking identities using bayesian network inference. In *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'06)*, volume 2, pages 2187–2194. IEEE.
- [251] Oh, S., Russell, S., and Sastry, S. (2009). Markov chain monte carlo data association for multi-target tracking. *IEEE Transactions on Automatic Control*, 54(3):481–497.
- [252] Okuma, K., Taleghani, A., De Freitas, N., Little, J. J., and Lowe, D. G. (2004). A boosted particle filter: Multitarget detection and tracking. In *European conference on computer vision*, pages 28–39. Springer.
- [253] Oreifej, O., Mehran, R., and Shah, M. (2010). Human identity recognition in aerial images. In *Computer Vision and Pattern Recognition (CVPR), 2010 IEEE Conference on*, pages 709–716. IEEE.
- [254] Oron, S., Bar-Hillel, A., and Avidan, S. (2014). Extended lucas-kanade tracking. In *European Conference on Computer Vision*, pages 142–156. Springer.
- [255] Oron, S., Bar-Hillel, A., and Avidan, S. (2015). Real-time tracking-with-detection for coping with viewpoint change. *Machine Vision and Applications*, 26(4):507–518.
- [256] Pan, S. J., Tsang, I. W., Kwok, J. T., and Yang, Q. (2011). Domain adaptation via transfer component analysis. *IEEE Transactions on Neural Networks*, 22(2):199–210.
- [257] Pan, S. J., Yang, Q., et al. (2010). A survey on transfer learning. *IEEE Transactions on knowledge and data engineering*, 22(10):1345–1359.
- [258] Papageorgiou, D. J. and Salpukas, M. R. (2009). The maximum weight independent set problem for data association in multiple hypothesis tracking. In *Optimization and Cooperative Control Strategies*, pages 235–255. Springer.
- [259] Park, M. Y. and Hastie, T. (2007). L1-regularization path algorithm for generalized linear models. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 69(4):659–677.
- [260] Pellegrini, S., Ess, A., Schindler, K., and Van Gool, L. (2009). You'll never walk alone: Modeling social behavior for multi-target tracking. In *Computer Vision, 2009 IEEE 12th International Conference on*, pages 261–268. IEEE.
- [261] Pellegrini, S., Ess, A., and Van Gool, L. (2010). Improving data association by joint modeling of pedestrian trajectories and groupings. In *European conference on computer vision*, pages 452–465. Springer.
- [262] Peng, P., Xiang, T., Wang, Y., Pontil, M., Gong, S., Huang, T., and Tian, Y. (2016). Unsupervised cross-dataset transfer learning for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1306–1315.

- [263] Perez, P., Vermaak, J., and Blake, A. (2004). Data fusion for visual tracking with particles. *Proceedings of the IEEE*, 92(3):495–513.
- [264] Petrovskaya, A. and Thrun, S. (2009). Model based vehicle detection and tracking for autonomous urban driving. *Autonomous Robots*, 26(2-3):123–139.
- [265] Pirsiavash, H., Ramanan, D., and Fowlkes, C. C. (2011). Globally-optimal greedy algorithms for tracking a variable number of objects. In *CVPR 2011*, pages 1201–1208. IEEE.
- [266] Pnevmatikakis, A. and Polymenakos, L. (2006). 2d person tracking using kalman filtering and adaptive background learning in a feedback loop. In *International Evaluation Workshop on Classification of Events, Activities and Relationships*, pages 151–160. Springer.
- [267] Porikli, F. (2003). Inter-camera color calibration by correlation model function. In *Image Processing, 2003. ICIP 2003. Proceedings. 2003 International Conference on*, volume 2, pages II–133. IEEE.
- [268] Porikli, F., Ivanov, Y., and Haga, T. (2008). Robust abandoned object detection using dual foregrounds. *EURASIP Journal on Advances in Signal Processing*, 2008:30.
- [269] Possegger, H., Mauthner, T., Roth, P. M., and Bischof, H. (2014). Occlusion geodesics for online multi-object tracking. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1306–1313.
- [270] Prosser, B., Zheng, W.-S., Gong, S., Xiang, T., and Mary, Q. (2010). Person re-identification by support vector ranking. In *BMVC*, volume 2, page 6.
- [271] Qian, H., Wu, X., and Xu, Y. (2011). *Intelligent surveillance systems*, volume 51. Springer Science & Business Media.
- [272] Qian, N. (1999). On the momentum term in gradient descent learning algorithms. *Neural networks*, 12(1):145–151.
- [273] Reid, D. (1979). An algorithm for tracking multiple targets. *IEEE transactions on Automatic Control*, 24(6):843–854.
- [274] Ren, S., He, K., Girshick, R., and Sun, J. (2015). Faster r-cnn: Towards real-time object detection with region proposal networks. In *Advances in neural information processing systems*, pages 91–99.
- [275] Research, G. V. (2019). Perimeter security market size, share trends analysis report by system (alarms notification, video surveillance), by service, by end use (government, transportation), and segment forecasts, 2019 - 2025. *Market Research Report, Report ID: GVR-2-68038-042-2*, page 243.
- [276] Ristani, E., Solera, F., Zou, R., Cucchiara, R., and Tomasi, C. (2016). Performance measures and a data set for multi-target, multi-camera tracking. In *European Conference on Computer Vision*, pages 17–35. Springer.
- [277] Ristani, E. and Tomasi, C. (2014). Tracking multiple people online and in real time. In *Asian Conference on Computer Vision*, pages 444–459. Springer.

- [278] Ristani, E. and Tomasi, C. (2018). Features for multi-target multi-camera tracking and re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 6036–6046.
- [279] Robicquet, A., Sadeghian, A., Alahi, A., and Savarese, S. (2016). Learning social etiquette: Human trajectory understanding in crowded scenes. In *European conference on computer vision*, pages 549–565. Springer.
- [280] Rodriguez, M., Ali, S., and Kanade, T. (2009). Tracking in unstructured crowded scenes. In *2009 IEEE 12th International Conference on Computer Vision*, pages 1389–1396. IEEE.
- [281] Rossum, G. v. (1995). Python tutorial, technical report cs-r9526. *Centrum voor Wiskunde en Informatica (CWI), Amsterdam*.
- [282] Roth, P. M., Hirzer, M., Köstinger, M., Beleznaï, C., and Bischof, H. (2014). Mahalanobis distance learning for person re-identification. In *Person Re-Identification*, pages 247–267. Springer.
- [283] Rumelhart, D. E., Hinton, G. E., and Williams, R. J. (1988). Learning representations by back-propagating errors. *Cognitive modeling*, 5(3):1.
- [284] Sadeghian, A., Alahi, A., and Savarese, S. (2017). Tracking the untrackable: Learning to track multiple cues with long-term dependencies. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 300–311.
- [285] Sánchez, J., Perronnin, F., Mensink, T., and Verbeek, J. (2013). Image classification with the fisher vector: Theory and practice. *International journal of computer vision*, 105(3):222–245.
- [286] Sanchez-Matilla, R., Poiesi, F., and Cavallaro, A. (2016). Online multi-target tracking with strong and weak detections. In *European Conference on Computer Vision*, pages 84–99. Springer.
- [287] Satta, R., Fumera, G., and Roli, F. (2011a). Exploiting dissimilarity representations for person re-identification. In *International Workshop on Similarity-Based Pattern Recognition*, pages 275–289. Springer.
- [288] Satta, R., Fumera, G., Roli, F., Cristani, M., and Murino, V. (2011b). A multiple component matching framework for person re-identification. In *International Conference on Image Analysis and Processing*, pages 140–149. Springer.
- [289] Schroff, F., Kalenichenko, D., and Philbin, J. (2015). Facenet: A unified embedding for face recognition and clustering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 815–823.
- [290] Schuster, S., Vernaza, P., Choi, W., and Chandraker, M. (2017). Deep network flow for multi-object tracking. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 6951–6960.
- [291] Schwartz, W. R. and Davis, L. S. (2009). Learning discriminative appearance-based models using partial least squares. In *Computer Graphics and Image Processing (SIBGRAPI), 2009 XXII Brazilian Symposium on*, pages 322–329. IEEE.

- [292] Scovanner, P. and Tappen, M. F. (2009). Learning pedestrian dynamics from the real world. In *2009 IEEE 12th International Conference on Computer Vision*, pages 381–388. IEEE.
- [293] Segal, A. V. and Reid, I. (2013). Latent data association: Bayesian model selection for multi-target tracking. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2904–2911.
- [294] Shafique, K., Lee, M. W., and Haering, N. (2008). A rank constrained continuous formulation of multi-frame multi-target tracking problem. In *2008 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1–8. IEEE.
- [295] Shafique, K. and Shah, M. (2005). A noniterative greedy algorithm for multiframe point correspondence. *IEEE transactions on pattern analysis and machine intelligence*, 27(1):51–65.
- [296] Shitrit, H. B., Berclaz, J., Fleuret, F., and Fua, P. (2011). Tracking multiple people under global appearance constraints. In *2011 International Conference on Computer Vision*, pages 137–144. IEEE.
- [297] Shitrit, H. B., Berclaz, J., Fleuret, F., and Fua, P. (2014). Multi-commodity network flow for tracking multiple people. *IEEE transactions on pattern analysis and machine intelligence*, 36(8):1614–1627.
- [298] Shu, G., Dehghan, A., Oreifej, O., Hand, E., and Shah, M. (2012). Part-based multiple-person tracking with partial occlusion handling. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1815–1821. IEEE.
- [299] Si, J., Zhang, H., and Li, C.-G. (2015). Regularization in metric learning for person re-identification. In *Image Processing (ICIP), 2015 IEEE International Conference on*, pages 2309–2313. IEEE.
- [300] Si, S., Tao, D., and Geng, B. (2010). Bregman divergence-based regularization for transfer subspace learning. *IEEE Transactions on Knowledge and Data Engineering*, 22(7):929.
- [301] Sidhu, R. S. and Sharad, M. (2016). Smart surveillance system for detecting interpersonal crime. In *2016 International Conference on Communication and Signal Processing (ICCSP)*, pages 2003–2007. IEEE.
- [302] Siebel, N. T. and Maybank, S. (2004). The advisor visual surveillance system. In *ECCV 2004 workshop applications of computer vision (ACV)*, volume 1.
- [303] Simonyan, K. and Zisserman, A. (2014). Very deep convolutional networks for large-scale image recognition.
- [304] Smail, H., David, H., and Larry, S. D. (2000). W4: Real-time surveillance of people and their activities. *IEEE transactions on pattern analysis and machine intelligence*, 22(8).
- [305] Smeulders, A. W., Chu, D. M., Cucchiara, R., Calderara, S., Dehghan, A., and Shah, M. (2014). Visual tracking: An experimental survey. *IEEE transactions on pattern analysis and machine intelligence*, 36(7):1442–1468.
- [306] Solera, F., Calderara, S., and Cucchiara, R. (2015). Learning to divide and conquer for online multi-target tracking. In *proceedings of the IEEE International Conference on Computer Vision*, pages 4373–4381.

- [307] Solera, F., Calderara, S., Ristani, E., Tomasi, C., and Cucchiara, R. (2017). Tracking social groups within and across cameras. *IEEE Transactions on Circuits and Systems for Video Technology*, 27(3):441–453.
- [308] Song, C., Huang, Y., Ouyang, W., and Wang, L. (2018). Mask-guided contrastive attention model for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1179–1188.
- [309] Song, X., Cui, J., Zha, H., and Zhao, H. (2008). Vision-based multiple interacting targets tracking via on-line supervised learning. In *European Conference on Computer Vision*, pages 642–655. Springer.
- [310] Spampinato, C., Chen-Burger, Y.-H., Nadarajan, G., and Fisher, R. B. (2008). Detecting, tracking and counting fish in low quality unconstrained underwater videos. *VISAPP (2)*, 2008(514-519):1.
- [311] Spampinato, C., Palazzo, S., Giordano, D., Kavasidis, I., Lin, F.-P., and Lin, Y.-T. (2012). Covariance based fish tracking in real-life underwater environment. In *VISAPP (2)*, pages 409–414.
- [312] Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I., and Salakhutdinov, R. (2014). Dropout: a simple way to prevent neural networks from overfitting. *The Journal of Machine Learning Research*, 15(1):1929–1958.
- [313] Sulman, N., Sanocki, T., Goldgof, D., and Kasturi, R. (2008). How effective is human video surveillance performance? In *2008 19th International Conference on Pattern Recognition*, pages 1–3. IEEE.
- [314] Sun, B. and Velastin, S. (2003). Fusing visual and audio information in a distributed intelligent surveillance system for public transport systems. *Acta Autom. Sin.*, 20(3):393–407.
- [315] Taigman, Y., Yang, M., Ranzato, M., and Wolf, L. (2014). Deepface: Closing the gap to human-level performance in face verification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1701–1708.
- [316] Tang, S., Andres, B., Andriluka, M., and Schiele, B. (2015). Subgraph decomposition for multi-target tracking. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5033–5041.
- [317] Tang, S., Andres, B., Andriluka, M., and Schiele, B. (2016). Multi-person tracking by multicut and deep matching. In *European Conference on Computer Vision*, pages 100–111. Springer.
- [318] Tang, S., Andriluka, M., Andres, B., and Schiele, B. (2017). Multiple people tracking by lifted multicut and person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3539–3548.
- [319] Transport, U. A. P. and Communications, A. (2018). International trends in video surveillance public transport gets smarter. *Statistics Brief*.
- [320] Tsochantaridis, I., Joachims, T., Hofmann, T., and Altun, Y. (2005). Large margin methods for structured and interdependent output variables. *Journal of machine learning research*, 6(Sep):1453–1484.

- [321] Tsuruoka, Y., Tsujii, J., and Ananiadou, S. (2009). Stochastic gradient descent training for l_1 -regularized log-linear models with cumulative penalty. In *Proceedings of the Joint Conference of the 47th Annual Meeting of the ACL and the 4th International Joint Conference on Natural Language Processing of the AFNLP: Volume 1-Volume 1*, pages 477–485. Association for Computational Linguistics.
- [322] Uijlings, J. R., Van De Sande, K. E., Gevers, T., and Smeulders, A. W. (2013). Selective search for object recognition. *International journal of computer vision*, 104(2):154–171.
- [323] Ustinova, E., Ganin, Y., and Lempitsky, V. (2017). Multi-region bilinear convolutional neural networks for person re-identification. In *Advanced Video and Signal Based Surveillance (AVSS), 2017 14th IEEE International Conference on*, pages 1–6. IEEE.
- [324] Valera, M. and Velastin, S. A. (2005). Intelligent distributed surveillance systems: a review. *IEE Proceedings-Vision, Image and Signal Processing*, 152(2):192–204.
- [325] Varior, R. R., Haloi, M., and Wang, G. (2016). Gated siamese convolutional neural network architecture for human re-identification. In *European Conference on Computer Vision*, pages 791–808. Springer.
- [326] Velastin, S., Khoudour, L., Lo, B., Sun, J., and Vicencio-Silva, M. (2004). Prismatic: a multi-sensor surveillance system for public transport networks.
- [327] Vezzani, R., Baltieri, D., and Cucchiara, R. (2013). People reidentification in surveillance and forensics: A survey. *ACM Computing Surveys (CSUR)*, 46(2):29.
- [328] Wager, S., Wang, S., and Liang, P. S. (2013). Dropout training as adaptive regularization. In *Advances in neural information processing systems*, pages 351–359.
- [329] Wan, J. and Li, L. (2013). Distributed optimization for global data association in non-overlapping camera networks. In *2013 Seventh International Conference on Distributed Smart Cameras (ICDSC)*, pages 1–7. IEEE.
- [330] Wang, B., Wang, G., Luk Chan, K., and Wang, L. (2014a). Tracklet association with online target-specific metric learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1234–1241.
- [331] Wang, H., Gong, S., and Xiang, T. (2014b). Unsupervised learning of generative topic saliency for person re-identification.
- [332] Wang, J., Song, Y., Leung, T., Rosenberg, C., Wang, J., Philbin, J., Chen, B., and Wu, Y. (2014c). Learning fine-grained image similarity with deep ranking. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1386–1393.
- [333] Wang, P. and Bai, X. (2018). Regional parallel structure based cnn for thermal infrared face identification. *Integrated Computer-Aided Engineering*, (Preprint):1–14.
- [334] Wang, S. and Fowlkes, C. C. (2015). Learning optimal parameters for multi-target tracking. In *BMVC*, volume 1, page 6.
- [335] Wang, T., Gong, S., Zhu, X., and Wang, S. (2016a). Person re-identification by discriminative selection in video ranking. *IEEE transactions on pattern analysis and machine intelligence*, 38(12):2501–2514.

- [336] Wang, X., Doretto, G., Sebastian, T., Rittscher, J., and Tu, P. (2007). Shape and appearance context modeling. In *Computer Vision, 2007. ICCV 2007. IEEE 11th International Conference on*, pages 1–8. IEEE.
- [337] Wang, X., Zheng, W.-S., Li, X., and Zhang, J. (2016b). Cross-scenario transfer person reidentification. *IEEE Trans. Circuits Syst. Video Techn.*, 26(8):1447–1460.
- [338] Webb, B. and Laycock, G. (1992). Reducing crime on the london underground. *Crime prevention unit paper*, 30.
- [339] Wei, S.-E., Ramakrishna, V., Kanade, T., and Sheikh, Y. (2016). Convolutional pose machines. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 4724–4732.
- [340] Weinberger, K. Q., Blitzer, J., and Saul, L. K. (2006). Distance metric learning for large margin nearest neighbor classification. In *Advances in neural information processing systems*, pages 1473–1480.
- [341] Weinberger, K. Q. and Saul, L. K. (2008). Fast solvers and efficient implementations for distance metric learning. In *Proceedings of the 25th international conference on Machine learning*, pages 1160–1167. ACM.
- [342] Weinberger, K. Q. and Saul, L. K. (2009). Distance metric learning for large margin nearest neighbor classification. *Journal of Machine Learning Research*, 10(Feb):207–244.
- [343] Wen, L., Lei, Z., Lyu, S., Li, S. Z., and Yang, M.-H. (2016). Exploiting hierarchical dense structures on hypergraphs for multi-object tracking. *IEEE transactions on pattern analysis and machine intelligence*, 38(10):1983–1996.
- [344] Wen, L., Li, W., Yan, J., Lei, Z., Yi, D., and Li, S. Z. (2014). Multiple target tracking based on undirected hierarchical relation hypergraph. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1282–1289.
- [345] Weng, S.-K., Kuo, C.-M., and Tu, S.-K. (2006). Video object tracking using adaptive kalman filter. *Journal of Visual Communication and Image Representation*, 17(6):1190–1208.
- [346] Wu, B. and Nevatia, R. (2007). Detection and tracking of multiple, partially occluded humans by bayesian combination of edgelet based part detectors. *International Journal of Computer Vision*, 75(2):247–266.
- [347] Wu, T., Bîlbîe, F.-D., Păun, A., Pan, L., and Neri, F. (2018). Simplified and yet turing universal spiking neural p systems with communication on request. *International journal of neural systems*, 28(08):1850013.
- [348] Wu, Z., Thangali, A., Sclaroff, S., and Betke, M. (2012). Coupling detection and data association for multiple object tracking. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1948–1955. IEEE.
- [349] Xiang, S., Nie, F., and Zhang, C. (2008). Learning a mahalanobis distance metric for data clustering and classification. *Pattern Recognition*, 41(12):3600–3612.

- [350] Xiang, Y., Alahi, A., and Savarese, S. (2015). Learning to track: Online multi-object tracking by decision making. In *Proceedings of the IEEE international conference on computer vision*, pages 4705–4713.
- [351] Xiao, T., Li, H., Ouyang, W., and Wang, X. (2016). Learning deep feature representations with domain guided dropout for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1249–1258.
- [352] Xing, E. P., Jordan, M. I., Russell, S. J., and Ng, A. Y. (2003). Distance metric learning with application to clustering with side-information. In *Advances in neural information processing systems*, pages 521–528.
- [353] Xing, J., Ai, H., and Lao, S. (2009). Multi-object tracking through occlusions by local tracklets filtering and global tracklets association with detection responses. In *Computer Vision and Pattern Recognition, 2009. CVPR 2009. IEEE Conference on*, pages 1200–1207. IEEE.
- [354] Xing, J., Ai, H., Liu, L., and Lao, S. (2011). Multiple player tracking in sports video: A dual-mode two-way bayesian inference approach with progressive observation modeling. *IEEE Transactions on Image Processing*, 20(6):1652–1667.
- [355] Xiong, F., Gou, M., Camps, O., and Sznai, M. (2014). Person re-identification using kernel-based metric learning methods. In *European conference on computer vision*, pages 1–16. Springer.
- [356] Xu, J., Zhao, R., Zhu, F., Wang, H., and Ouyang, W. (2018). Attention-aware compositional network for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2119–2128.
- [357] Xu, Y., Lin, L., Zheng, W.-S., and Liu, X. (2013). Human re-identification by matching compositional template with cluster sampling. In *proceedings of the IEEE International Conference on Computer Vision*, pages 3152–3159.
- [358] Yamaguchi, K., Berg, A. C., Ortiz, L. E., and Berg, T. L. (2011). Who are you with and where are you going? In *CVPR 2011*, pages 1345–1352. IEEE.
- [359] Yang, B. and Nevatia, R. (2012a). Multi-target tracking by online learning of non-linear motion patterns and robust appearance models. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1918–1925. IEEE.
- [360] Yang, B. and Nevatia, R. (2012b). An online learned crf model for multi-target tracking. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pages 2034–2041. IEEE.
- [361] Yang, F., Choi, W., and Lin, Y. (2016). Exploit all the layers: Fast and accurate cnn object detector with scale dependent pooling and cascaded rejection classifiers. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2129–2137.
- [362] Yang, M. and Jia, Y. (2016). Temporal dynamic appearance modeling for online multi-person tracking. *Computer Vision and Image Understanding*, 153:16–28.
- [363] Yang, Y., Yang, J., Yan, J., Liao, S., Yi, D., and Li, S. Z. (2014). Salient color names for person re-identification. In *European conference on computer vision*, pages 536–551. Springer.

- [364] Yi, D., Lei, Z., Liao, S., and Li, S. Z. (2014). Deep metric learning for person re-identification. In *Pattern Recognition (ICPR), 2014 22nd International Conference on*, pages 34–39. IEEE.
- [365] Yosinski, J., Clune, J., Bengio, Y., and Lipson, H. (2014). How transferable are features in deep neural networks? In *Advances in neural information processing systems*, pages 3320–3328.
- [366] Yu, Q., Medioni, G., and Cohen, I. (2007). Multiple target tracking using spatio-temporal markov chain monte carlo data association. In *2007 IEEE Conference on Computer Vision and Pattern Recognition*, pages 1–8. IEEE.
- [367] Zamir, A. R., Dehghan, A., and Shah, M. (2012). Gmcp-tracker: Global multi-object tracking using generalized minimum clique graphs. In *Computer Vision–ECCV 2012*, pages 343–356. Springer.
- [368] Zhai, M., Chen, L., Mori, G., and Roshtkhari, M. J. (2018). Deep learning of appearance models for online object tracking. In *European Conference on Computer Vision*, pages 681–686. Springer.
- [369] Zhan, B., Monekosso, D. N., Remagnino, P., Velastin, S. A., and Xu, L.-Q. (2008). Crowd analysis: a survey. *Machine Vision and Applications*, 19(5-6):345–357.
- [370] Zhang, G., Kato, J., Wang, Y., and Mase, K. (2013). Adaptive metric learning in local distance comparison for people re-identification. In *Pattern Recognition (ACPR), 2013 2nd IAPR Asian Conference on*, pages 196–200. IEEE.
- [371] Zhang, J., Presti, L. L., and Sclaroff, S. (2012). Online multi-person tracking by tracker hierarchy. In *Advanced Video and Signal-Based Surveillance (AVSS), 2012 IEEE Ninth International Conference on*, pages 379–385. IEEE.
- [372] Zhang, L., Li, Y., and Nevatia, R. (2008). Global data association for multi-object tracking using network flows. In *Computer Vision and Pattern Recognition, 2008. CVPR 2008. IEEE Conference on*, pages 1–8. IEEE.
- [373] Zhang, S., Staudt, E., Faltemier, T., and Roy-Chowdhury, A. K. (2015a). A camera network tracking (camnet) dataset and performance baseline. In *2015 IEEE Winter Conference on Applications of Computer Vision*, pages 365–372. IEEE.
- [374] Zhang, S., Zhu, Y., and Roy-Chowdhury, A. (2015b). Tracking multiple interacting targets in a camera network. *Computer Vision and Image Understanding*, 134:64–73.
- [375] Zhang, X., Yu, F. X., Chang, S.-F., and Wang, S. (2015c). Deep transfer network: Unsupervised domain adaptation. *arXiv preprint arXiv:1503.00591*.
- [376] Zhang, Y., Li, B., Lu, H., Irie, A., and Ruan, X. (2016). Sample-specific svm learning for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1278–1287.
- [377] Zhang, Y. and Li, S. (2011). Gabor-lbp based region covariance descriptor for person re-identification. In *Image and Graphics (ICIG), 2011 Sixth International Conference on*, pages 368–371. IEEE.

- [378] Zhao, R., Ouyang, W., and Wang, X. (2013a). Person re-identification by salience matching. In *Computer Vision (ICCV), 2013 IEEE International Conference on*, pages 2528–2535. IEEE.
- [379] Zhao, R., Ouyang, W., and Wang, X. (2013b). Unsupervised salience learning for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3586–3593.
- [380] Zhao, R., Ouyang, W., and Wang, X. (2014). Learning mid-level filters for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 144–151.
- [381] Zhao, X., Gong, D., and Medioni, G. (2012). Tracking using motion patterns for very crowded scenes. In *Computer Vision–ECCV 2012*, pages 315–328. Springer.
- [382] Zheng, L., Bie, Z., Sun, Y., Wang, J., Su, C., Wang, S., and Tian, Q. (2016a). Mars: A video benchmark for large-scale person re-identification. In *European Conference on Computer Vision*, pages 868–884. Springer.
- [383] Zheng, L., Shen, L., Tian, L., Wang, S., Wang, J., and Tian, Q. (2015). Scalable person re-identification: A benchmark. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 1116–1124.
- [384] Zheng, L., Yang, Y., and Hauptmann, A. G. (2016b). Person re-identification: Past, present and future. *arXiv preprint arXiv:1610.02984*.
- [385] Zheng, W.-S., Gong, S., and Xiang, T. (2009). Associating groups of people. In *BMVC*, volume 2.
- [386] Zheng, W.-S., Gong, S., and Xiang, T. (2011). Person re-identification by probabilistic relative distance comparison. In *Computer vision and pattern recognition (CVPR), 2011 IEEE conference on*, pages 649–656. IEEE.
- [387] Zheng, W.-S., Gong, S., and Xiang, T. (2013). Reidentification by relative distance comparison. *IEEE transactions on pattern analysis and machine intelligence*, 35(3):653–668.
- [388] Zhuang, B., Lin, G., Shen, C., and Reid, I. (2016). Fast training of triplet-based deep binary embedding networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 5955–5964.

Appendix A

Notation

A.1 Deep Learning notation

Several discrete magnitudes are considered in a learning process, which are indexed with lower-case letters, and whose maximum values are constants rendered in capital letters, as follows:

- t , iteration number,
- T , maximum number of iterations,
- i , sample number,
- M , number of samples of the training set,
- B , number of samples of a batch,
- n , feature element position,
- N , length of the feature vector,
- j , parameter position,
- W , set of all the parameters of a neural network, a.k.a, neural weights.

The weights values, W , define the network model. These parameters are different from those defining the learning process characteristics, which are called hyper-parameters. Some hyper-parameters are:

- η , learning rate, factor in the weights updating,
- λ , regularization factor, factor multiplying the regularization term in the loss function,

- wd , weight decay, factor multiplying the regularization component in the loss derivative value, so, this also affects in the weights updating,
- γ , dropout factor,
- m , margin of the Contrastive loss function,
- m_1 m_2 , margins of the Normalised Double Margin-based Contrastive Loss function,
- γ , margin of the Triplet loss function.

A.2 Multi-Agent Tracking algorithm notation

The indexes that the Multi-Agent Tracking algorithm uses are rendered by lower case letters, and the constant values, defining the dimension of the structures are rendered by capital letters:

- f , frame number, which is equivalent to the tracking iteration number,
- i , index referring to a position in the agents record,
- j , index referring to a position in the set of taken measurements,
- t , index referring to a position of the memory attribute of an agent,
- T , size of the memory attribute of the agents.

Several thresholds are used by the proposed tracking algorithm. They are defined as follows, and their values are compared by Eq. A.1 and A.2.

- T_o , overlapping threshold, upper which two bounding boxes are overlapped, where overlapping is the ratio between the common region of two bounding boxes and the area of one of them.
- T_p , threshold in the age of an agent, $age\ a_i$, under which an agent is considered as newly created and its tracking is provisional.
- T_n , threshold in the age of an agent, $age\ a_i$, under which an agent is considered as novel.
- T_m , threshold in the number of frames without matching an agent, $FWM\ a_i$, from which the agent is considered as missed, but it is still tracked.
- T_l , threshold in the number of frames without matching an agent, $FWM\ a_i$, from which the agent ceases to be tracked and becomes a latent agent.

- T_r , threshold in the number of frames without matching an agent, $FWM\ a_i$, from which the agent is destroyed.

$$T_p \quad T_n \quad (A.1)$$

$$T_m \quad T_l \quad T_r \quad (A.2)$$

Appendix B

Architecture of the three jointly learnt parts-features model.

The three jointly learnt parts-features model is described in Section 4.8.3. This embedding models a person feature through the weighting of the outputs of three Deep Convolutional Neural Networks, one per body partition. To train this embedding this has been triplicate, in turn, in three branches, following the triplet model architecture. Eventually, nine neural branches compose the learning architecture, and each branch contains a DCNN, concretely the VGG5 network (see Tables 4.12, 4.13 and 4.14), which is a less-layered version of the VGG networks presented in [303].

Consequently, the final model is a complicated architecture with a high number of layers. Fig. B.1 shows this architecture, where red boxes renders convolution layers, yellow boxes, polling layers, purple boxes, fully connected layers, green boxes, activation functions, and blue boxes, python layers. The grey octagons render the inputs and outputs of the layers. This figure gives an overall vision of the network architecture. However, due to the magnitude of the network, the layer details are unreadable in Fig. B.1, which has a limited resolution¹.

¹The Architecture of the three jointly learnt parts-features model is rendered with higher resolution in a publicly available file, under https://github.com/magomez/deep_neural_architecture

Appendix C

MOT algorithm Architecture

The Multi-Object tracking algorithm proposed in this thesis is based on an cascade association method with a Global Hypotheses Generator. Moreover, a multi-agent management strategy has been developed to control the flow of the agents' information. Many other modules has been designed, and presented on this thesis, such as, Human Shape Validation, Detection-by-Tracking, Re-Identification, or Feature computation. The integration, and connection of all these developed methods requires of a complex architecture, which has been implemented by means of C++ classes¹.

Following figures give an overall view of the MOT algorithm architecture. Fig. C.1 presents the modules called by the main algorithm. And respectively, Fig. C.2 and C.3, describes the classes relationships for two of the main modules: agent management (see Section 5.2) and association module (see Section 5.5.3).

¹The description of the MOT algorithm architecture, and each one of its components is publicly available under: https://github.com/magomez/CGHA_MOT

Fig. C.2 Architecture of Agent Management module.

Fig. C.3 Architecture of Association module.