Advanced AAA System for interoperable distributed architectures

By

Fidel Paniagua Diez

A dissertation submitted by in partial fulfilment of the requirements for
the degree of Doctor of Philosophy in

Telematic Engineering

Universidad Carlos III de Madrid

Advisors:

José María Sierra Cámara

Diego Suárez Touceda

Tutor:

José María Sierra Cámara

May 2020

This thesis is distributed under license “Creative Commons **Attribution – Non Commercial – Non Derivatives**”.

Acknowledgements

In deference to my family, I would like to write these lines in my mother tongue, Spanish.

A mi morena, que apareció cuando este proyecto ya estaba iniciado y que ha sabido tener la paciencia suficiente para aguantar esos momentos de soledad, apoyándome en todo momento.

A mis padres, que me han apoyado siempre y sin los que hoy no estaría aquí. Su esfuerzo y sacrificio han supuesto siempre una motivación muy fuerte para seguir adelante e intentar compensarles una pequeña parte de todo lo que me han estado aportando estos años.

A mi hermano, por saber que una gran parte de su trabajo era dedicada a que yo fuese avanzando etapas educativas y, que en lugar de habérmelo podido reprochar en algún momento, siempre me ha apoyado.

A mis tíos, Santi y Matilde, y a mi prima Patricia, por aceptar que durante muchos años les invadiese la casa y por su ayuda incondicional. Sin duda, si hoy estoy completando este nuevo hito es en buena parte gracias a vosotros.

Al resto de mi familia que, aunque por ser tan extensa no los puedo nombrar a todos, siempre que les he necesitado me han ayudado y apoyado.

A mi familia política que, aunque en algún momento hayan podido tener la impresión de que esta tesis era más importante que cualquier otra cosa, han sabido tener la paciencia suficiente para entender los sacrificios que un trabajo de este estilo requiere.

A mis amigos, que han sabido comprender de la mejor forma posible que a veces no podía estar presente, mientras que otras veces necesitaba ese momento de salir y despejarme. Gracias por ese apoyo tan necesario para conseguir llevar a buen puerto un proyecto tan a largo plazo como es una tesis.

A las personas con las que a lo largo de este tiempo he coincidido en Evalues, de ellas he aprendido muchas cosas que sin duda me han servido para desarrollar este trabajo.

A todos los alumnos de TFG con los que he colaborado a lo largo de este tiempo: Isaac, Nacho, Sergio, Javi y Alberto, sin duda una parte de vuestro esfuerzo se ve reflejado en esta tesis.

A Juanjo y todo el personal de UNIR que ha confiado en mí y han tenido la paciencia suficiente para esperar a que llegará este momento.

A todas las personas con las que tuve la oportunidad de coincidir durante mi estancia en la Universidad de Passau y, especialmente, a Joachim Possega por su apoyo.

A todo el personal de CloverTechnologies con los que he coincidido a lo largo de estos años, por haberme ayudado a resolver muchas de las dudas que me han ido surgiendo, y por haber entendido que a veces priorizase avanzar con mi tesis. Aunque han sido muchos y no me sería posible nombrarlos a todos, pero si quiero hacer una mención especial a Miguel, ya que desde la etapa en el laboratorio Evalues ha estado ahí, ayudándome y aconsejándome siempre que lo he necesitado.

A todo el personal y compañeros del proyecto de investigación SAVIER de Airbus Defense and Space. No solamente ha significado la financiación de este trabajo, sino que me ha permitido disponer, por un lado, de un entorno de validación único para mis investigaciones y, por otro lado, estar rodeado de grandes profesionales de los que sin duda he aprendido mucho y que espero haber podido reflejar parte de esas enseñanzas en esta tesis. Tampoco quiero olvidarme de agradecer la ayuda y apoyo recibido en estos años de trabajo de esos once compañeros que han estado trabajando en sus tesis dentro de este proyecto.

A mis directores de Tesis, Diego y José María, sin vosotros nunca hubiese llegado a culminar este proyecto. Espero poder devolveros de alguna forma todo el esfuerzo que habéis dedicado a mi tesis.

Por último, en un trabajo de esta duración y envergadura, es imposible citar en una hoja a todas las personas a las que les pertenece una parte de esta tesis, pero no tengo duda que no me he olvidado de las personas que han estado cerca. En muchos casos ya es una realidad que, aunque nuestra relación empezó como un vínculo profesional, os habéis convertido en verdaderos amigos.

This documentation is based on a template created by Patrik FUHRER and Pedro DE ALMEIDA (Software Engineering Group, University of Fribourg, Switzerland). The template is open source and freely available from: <https://www3.unifr.ch/inf/softeng/en/resources/thesis-templates.html>

Published and Submitted Content

The work contained in this dissertation has resulted in 3 journal papers already accepted for publication. Also, it has resulted in a conference publication. Below, all publications are listed along with their details:

- **Toward self-authenticable wearable devices,**
Contribution type: JCR Journal paper,
PhD candidate role: first author,
Published in: IEEE Wireless Communications (Volume: 22, Issue: 1, February 2015),
Impact Factor: 4.148 (Q1),
URL: <https://ieeexplore.ieee.org/abstract/document/7054717>,
DOI: 10.1109/MWC.2015.7054717,
Note: wholly included in the thesis in Chapter 2.
Statement: The material from this source included in this thesis is not singled out with typographic means and references.
- **Advance Information Access Control System for Mobile Devices,**
Contribution type: Conference presentation,
PhD candidate role: first author,
Published in: WSO2 Conference,
Date: 07/06/2016 – 09/06/2016
URL: <https://wso2.com/videos/advance-information-access-control-system-for-mobile-devices>,
Note: partially included in the thesis in Chapter 4.
Statement: The material from this source included in this thesis is not singled out with typographic means and references.

- **Modeling XACML Security Policies Using Graph Databases,**
Contribution type: JCR Journal paper,
PhD candidate role: first author,
Published in: IT Professional (Volume: 19, Issue: 6, November/December 2017),
Impact Factor: 1.618 (Q2),
URL: <https://ieeexplore.ieee.org/document/8123470>,
DOI: 10.1109/MITP.2017.4241465,
Note: wholly included in the thesis in Chapter 5,
Statement: The material from this source included in this thesis is not singled out with typographic means and references.

- **Lightweight Access Control System for Wearable Devices,**
Contribution type: JCR Journal paper,
PhD candidate role: first author,
Published in: IT Professional (Volume: 21, Issue: 1, Jan.-Feb. 2019),
Impact Factor: 2019 not published yet. It was 2.424 (Q2) in 2018,
URL: <https://ieeexplore.ieee.org/document/8657469>,
DOI: 10.1109/MITP.2018.2876985,
Note: wholly included in the thesis in Chapter 3,
Statement: The material from this source included in this thesis is not singled out with typographic means and references.

Other Research Merits

Other contributions made during this PhD include:

- **CertiBlock: Emisión y validación de títulos universitarios con Blockchain,**
Contribution type: Conference Poster,
PhD candidate role: second author,
Published in: Congreso Internacional de Educación Superior de Calidad en el Espacio Latinoamericano (ESCEL),
Date: 08/03/2018-09/03/2018
URL:
https://www.researchgate.net/publication/323966578_CertiBlock_Emision_y_validacion_de_titulos_universitarios_con_Blockchain,
- **A blockchain-based platform for the secure coordination of a robotic swarm,**
Contribution type: Conference presentation,
PhD candidate role: first author,
Published in: Digital Enterprise Show (Madrid),
Date: 22/05/2019
URL: <https://www.des-madrid.com/agenda-2020/a-blockchain-based-platform-for-the-secure-coordination-of-a-robotic-swarm-20190522/>,
Note: This project won the first European Defence Agency Innovation Prize in 2018.
- **Development of a Methodology to Securitize Smart Toys in Household Environments,**
Contribution type: Conference paper,
PhD candidate role: second author,
Published in: Congreso Iberoamericano de Seguridad Informática (CIBSI),
Date: 22/01/2020-23/01/2020
Note: Conference Proceedings have not been published yet. Congress agenda can be accessed from <https://www.urosario.edu.co/CIBSI/inicio/>.

- **Blockchain, mitos y realidades,**
Contribution type: Keynote,
Published in: Congreso Iberoamericano de Seguridad Informática (CIBSI),
Date: 22/01/2020-23/01/2020

- **Blockchain-based system for issuing and validating certificates,**
Contribution type: Patent,
PhD candidate role: first author,
Published in: European Patent Office (EPO),
Patent: 19382933.0-1219 (European),
Date: It was accepted at 28/10/2019 but it will be open published around April 2021,
Note: https://www.researchgate.net/publication/338886939_Blockchain-based_system_for_issuing_and_validating_certificates.

Abstract

This thesis addresses the design of Authentication, Authorization and Accounting (AAA) security systems for current and future heterogeneous environments. In particular, we started focusing on authentication and authorization of portable devices that, due to their limited computational capacities, cannot employ traditional access control protocols to protect the information they manage. Within this area of research, we have proposed an authentication protocol, an authorization protocol and a complete XACML access control architecture for decentralized and heterogeneous environments. Then, we directed our research to improving the performance limitations of XACML protocol implementations identified during the aforementioned access control system deployment. To this matter, we have proposed two Graph database-based solutions which highly improve the performance of XACML access control when the number of access control policies increase. One based on a pure Graph database model and the other based on a hybrid approach for scenarios when making the needed changes to the pre-existing architecture, it may represent a substantial effort or investing a considerable amount of resources. After that, we moved on to accounting and presented a proposal to cover the gap for registering logs in a distributed environment in a flexible and secure way using Blockchain. All these proposals have been prototyped as well as either integrated in a Ground Control Station (GCS) demonstrator (authentication, authorization and complete access control) or simulated their integration (graph-based databases and blockchain logging network).

Keywords: AAA, Authentication, Authorization, Accounting, XACML, Security Policy, Ground Control Station

Resumen

Esta tesis aborda el diseño de sistemas seguros de Autenticación, Autorización y Registro (Authentication, Authorization y Accounting (AAA) en inglés) para los actuales y futuros entornos heterogéneos. En particular, hemos empezado centrándonos en la autenticación y la autorización de dispositivos portables que, debido a sus limitadas capacidades computacionales, no pueden usar protocolos de control de acceso tradicionales para proteger la información que gestionan. Dentro de esta área de investigación, hemos propuesto un protocolo de autenticación, un protocolo de autorización y una arquitectura de control de acceso completa usando XACML para entornos heterogéneos y distribuidos. Posteriormente, hemos enfocado nuestra investigación a mejorar las limitaciones de rendimiento de las implementaciones existentes del protocolo XACML, que fueron identificadas durante el despliegue del anteriormente apuntado sistema de control de acceso. A este respecto, hemos propuesto dos soluciones que se basan en el uso de bases de datos gráficas las cuales mejoran el rendimiento del control de acceso con XACML cuando el número de políticas de control de acceso crece. Uno de ellos se basa en un modelo puro de bases de datos gráficas y el otro se basa en una aproximación híbrida para escenarios donde los cambios necesarios en la arquitectura de la primera solución puedan tener problemas de implantación debidos a la arquitectura preexistentes. Tras esto nos movimos a la parte de registro y presentamos una propuesta para cubrir la brecha existente para registrar logs en entornos distribuidos de una forma flexible y segura utilizando Blockchain. Todas estas propuestas han sido prototipadas e integradas en el demostrador de la estación de control de tierra o Ground Control Station (GCS) en inglés (la autenticación, la autorización y el sistema de control de acceso) o simulada esa integración (bases de datos gráficas y la red de logs basada en Blockchain).

Palabras clave: AAA, Autenticación, Autorización, Registro, XACML, Política de Seguridad, Estación de Control de Tierra

Table of Contents

1	Introduction	1
1.1	Motivation.....	1
1.1.1	Authentication	3
1.1.2	Authorization.....	4
1.1.3	Accounting	5
1.1.4	Use Case: Ground Control Station	5
1.2	Objectives	9
1.3	Contributions	9
1.4	Organization	11
2	Towards Self-Authenticable Wearable Devices	12
2.1	Introduction.....	12
2.2	Related Work and Technologies.....	15
2.2.1	Wearable Devices.....	15
2.2.2	Near Field Communication (NFC).....	16
2.2.3	Smart Cards	16
2.2.4	Point-to-Point Protocol (PPP)	16
2.2.5	Extensible Authentication Protocol (EAP)	17
2.2.6	Imprinting.....	17
2.3	Proposed Authentication Protocol	17
2.3.1	Wearable Device Requirements and Proposed Design Justification	18
2.3.2	Application Scenarios	19
2.3.3	Architecture	20
2.3.4	Authentication Methods	22
2.4	Security Evaluation.....	26
2.5	Conclusion	27
3	Lightweight Access Control System for Wearable Devices	29
3.1	Introduction.....	29
3.2	Proposed Access Control System	32
3.2.1	Wearable Device Requirements and Proposed Design Justification	33
3.2.2	System Architecture	34
3.2.3	Security Policy	35
3.2.4	Access Control System.....	36

3.3	Security Evaluation.....	37
3.4	Prototype.....	38
3.4.1	Server	39
3.4.2	Wearable Device	39
3.4.3	Secure SD Card	39
3.4.4	Functional Testing.....	39
3.5	Conclusion	40
4	Access Control System for interoperable distributed architectures	41
4.1	Introduction.....	41
4.2	Related Work and Technologies.....	44
4.2.1	Android.....	44
4.2.2	SAML.....	44
4.2.3	XACML	44
4.3	Access Control System Design.....	45
4.3.1	System Architecture	46
4.3.2	System Capacities	47
4.4	Prototype.....	52
4.4.1	Monitoring System Prototype	53
4.4.2	Command and Control System Prototype.....	59
4.5	Conclusion	64
5	Modelling XACML Security Policies Using Graph Databases	66
5.1	Introduction.....	66
5.2	Related Work and Technologies.....	68
5.2.1	Access Control	68
5.2.2	XACML	68
5.2.3	Graph Databases.....	69
5.3	Proposed Access Control System	69
5.3.1	Meta Model	70
5.3.2	XAML Graph Model.....	70
5.4	Evaluation	72
5.5	Conclusion	73
6	Hybrid XACML-Graph Database Policy Decision Point	74
6.1	Introduction.....	74
6.2	Related Work and Technologies.....	75
6.2.1	WSO2 Balana	75
6.2.2	NEO4J	75
6.3	Architecture	75

6.4	Prototype.....	77
6.4.1	Example.....	79
6.5	Evaluation.....	80
6.5.1	Conformance Evaluation.....	81
6.5.2	Performance Evaluation.....	81
6.6	Conclusion.....	82
7	Secure Blockchain-based Logging System for Distributed Environments	84
7.1	Introduction.....	84
7.2	Related Work and Technologies.....	87
7.2.1	Blockchain.....	87
7.3	Logging System.....	88
7.3.1	Requirements and Proposed Design Justification.....	88
7.3.2	Architecture.....	89
7.3.3	Smart Contracts (SC).....	90
7.3.4	System capabilities.....	92
7.4	Security evaluation.....	96
7.5	Prototype.....	97
7.5.1	7nodes network.....	97
7.5.2	Node services.....	97
7.5.3	Functional Testing.....	98
7.6	Conclusion.....	100
8	Conclusions and Future Research Lines	101
8.1	Conclusions.....	101
8.1.1	Towards Self-Authenticable Wearable Devices.....	103
8.1.2	Lightweight Access Control System for Wearable Devices.....	103
8.1.3	Access Control System for interoperable distributed architectures.....	103
8.1.4	Modelling XACML Security Policies Using Graph Databases.....	104
8.1.5	Hybrid XACML-Graph Database Policy Decision Point.....	104
8.1.6	Secure Blockchain-based Logging System for Distributed Environments....	105
8.2	Future Research Lines.....	105
	References	107

List of Figures

Figure 1: <i>Isolated GCS Architecture</i>	6
Figure 2: <i>Predator MQ-1 Ground Control Station</i>	7
Figure 3: <i>Distributed GCS Architecture</i>	8
Figure 4: <i>Wearable devices</i>	15
Figure 5: <i>System elements</i>	20
Figure 6: <i>Proposed Authentication Architecture</i>	21
Figure 7: <i>Pairing process</i>	23
Figure 8: <i>WD-SCard – Mobile Device authentication flow</i>	24
Figure 9: <i>WD-SCard – Authentication Server authentication flow</i>	26
Figure 10: <i>Proposed System Architecture</i>	34
Figure 11: <i>Access Control Flow of Communication</i>	36
Figure 12: <i>Prototype</i>	40
Figure 13: <i>Access Control System Phases</i>	42
Figure 14: <i>Access Control System Functionalities</i>	43
Figure 15: <i>System entities</i>	47
Figure 16: <i>Users Enrolment</i>	49
Figure 17: <i>Content Download</i>	51
Figure 18: <i>Content Visualisation</i>	52
Figure 19: <i>Monitoring System Prototype Architecture</i>	53
Figure 20: <i>Monitoring Application prototype content protection and download</i>	56
Figure 21: <i>Monitoring Application prototype state diagram</i>	56
Figure 22: <i>C&C System Prototype Architecture</i>	60
Figure 23: <i>XACML request flow diagram</i>	67
Figure 24: <i>Meta Model</i>	70
Figure 25: <i>Policy Elements</i>	71
Figure 26: <i>Graph Model Example</i>	72
Figure 27: <i>Hybrid XACML – Graph Database Architecture</i>	76
Figure 28: <i>Graph Database Schema</i>	77
Figure 29: <i>Authorization Request Flow</i>	78

Figure 30: <i>XACML Policy example</i>	79
Figure 31: <i>Graph database representation of the XACML Security Policy</i>	80
Figure 32: <i>XACML Request example</i>	80
Figure 33: <i>Performance Comparison</i>	82
Figure 34: <i>Difference in request processing times</i>	82
Figure 35: <i>Log Management Process</i>	85
Figure 36: <i>Blockchain-based Logging System Architecture</i>	90
Figure 37: <i>Create Log Bucket</i>	93
Figure 38: <i>Register public and private logs</i>	94
Figure 39: <i>Access logs</i>	96
Figure 40: <i>Security Services of our Logging System proposal</i>	96
Figure 41: <i>Functional Testing Use Cases</i>	99
Figure 42: <i>Distributed GCS Architecture</i>	102

List of Tables

Table 1: <i>Security level – Authentication control</i>	20
Table 2: <i>Figure 6 Abbreviations</i>	21
Table 3: <i>Monitoring System expected test results</i>	59
Table 4: <i>Performance Test Results</i>	81

1

Introduction

1.1 Motivation	1
1.1.1 Authentication.....	3
1.1.2 Authorization	4
1.1.3 Accounting.....	5
1.1.4 Use Case: Ground Control Station	5
1.2 Objectives	9
1.3 Contributions	9
1.4 Organization	11

1.1 Motivation

Technology is continuously evolving with new devices, systems and how they communicate. In the last years, this evolution has brought new tendencies such as Bring Your Own Devices (BYOD) [1], Cloud Computing [2] or Internet of Things (IoT) [3]. Integrating these tendencies both in personal and corporate environments offers new opportunities at the cost of increasing the attack surface. Unfortunately, traditional security measures are not enough to protect the information in these new scenarios, which cannot rely neither on centralization (information is being used and stored in multiple heterogenous devices), nor in physical isolation (devices tend to be outside of the information owner's security limits -its intranet-) , nor in computationally demanding solutions (devices may have very low computational resources available).

Good examples of these problems are data leaks that continuously appear in the news during the last years. Cases such as the personal attack to the actresses Jennifer Lawrence [4] (unauthorized access and leakage of private pictures), business aimed attacks to several companies, such as Google [5] or Allen & Hoshall [6], (insider attacks stealing company's

knowhow to use it in competitors), or military aimed attacks such as the famous case of Edward Snowden [7] (releasing to the general public NSA's sensitive information).

As we evolve from isolated systems to a network of heterogeneous devices sharing information, the attack surface moves out from the companies' internal network to a new distributed environment with no barriers. Traditionally, information was managed within a company's internal network using securely configured devices. However, nowadays, most of the information is no longer stored and used within this internal environment (e.g. Cloud computing). Also, external devices can both share the information they collect and receive information from other devices or information services which makes difficult validating the devices using the information and ensuring access control (e.g. BYOD or IoT). And even worst, the limited capacities of most of these devices make impractical the implementation of state of the art security measures to them (e.g. wearable devices [8]).

Several examples can be provided to illustrate this evolution in different environments and how the new scenarios demand new security solutions:

- Personal Environment: In their private environments, people evolved from having one single desktop computer with all their information to use several heterogenous devices (laptops, tablets, mobile phones, wearables, ...), some of them with very low computational capacities, that not only store but generate new data (about the users' behavior, preferences, etc.) and share them in the Cloud.
- Corporate Environment: Corporate networks were once systems with well limited boundaries. However, today with the emergence of remote working, outsourcing services, Cloud Computing, Bring Your Own Devices (BYOD) or Corporate Owned Personally Enabled (COPE) [9] this delimitation is no longer clear.
- Health Environment: These environments have followed the same path for decentralization, heterogenization and information sharing through their digitalization. However, due to the sensitivity of the information handled (such as medical records or pacemaker's configurations), their protection is crucial, but, at the same time, difficult to achieve when devices with low computational resources, such as wearable devices, are involved in the process.
- Military Environment: In general, these environments have always been the most restricted ones (e.g. isolating classified systems and networks as a general rule).

However, to remain competitive, they are also evolving. Examples of this evolution are, among others, the use of wearable devices to monitor and aid soldiers in the battlefield, using Unmanned Aerial Vehicles (UAV) [10] to complete or support missions, or the decentralization of previously centralized and physically protected Command and Control Systems that can now be set ad-hoc for a mission.

These examples, especially the last two (i.e. medical and military) for being more security demanding, were the beginning of several discussions about the capacity of existing solutions to provide to those environment three essential security services: Authentication, Authorization and Accounting; also known as AAA [11].

1.1.1 Authentication

Authentication is a security service that ensures a user¹ is who it says it is after its identification with an ID or similar value. The user first answers the question “Who are you?” (identification) and then has to provide a proof of it. Authentication can be provided using one or a combination of the following elements: something you know (e.g. a password), something you are (e.g. a biometric characteristic such as a fingerprint) or something you have (e.g. an authentication token such as a smart card).

Several well-known protocols exist that provide end-to-end authentication (among other security services) such as Transport Layer Security (TLS) [12] or EAP-TLS for smartcards [13]. Unfortunately, they are not a viable option for the presented environments due to the lack of the necessary resources to both implement a TCP/IP stack and manage their overhead of some the devices involved (e.g. wearable devices). A few solutions exist that address the problem of a secure authentication service for wearable devices [14] [15], but they are more concerned about authenticating the user holding the wearable device than the device itself and are limited to scenarios where direct communication between the authenticating parties is possible. It is, therefore, necessary for securing the described environments to go a step beyond and have an autonomous and independent wearable device that can authenticate end-to-end with a remote entity by itself. This matter is addressed in Chapter 2.

---

¹ With *user* we refer to any entity accessing a system, without restricting the term to a human being. A user may, among other, refer to a person, a device, a robot or an application. With this in mind, and to avoid any confusion, the impersonal pronoun *it* (or any of its variants) will be used when referring to a *user*.

1.1.2 Authorization

Authorization answers the question “What can you do?”. Once a user has been successfully authenticated, decisions can be made about what actions the user is allowed to perform and which ones it is not according to a security policy.

As for the authentication case, several well-known solutions for authorization in distributed systems exist including the more restricted ones, such as the proposed in [16] [17] for health environments or in [18] for military environments. However, none of these solutions are available for the specific characteristics (portability, small size, low computational resources and capacity, limited range of connectivity, etc.) associated with current wearable devices. Conversely, current wearable device-oriented solutions are mostly focused on protecting (by the use of encryption) information access from unauthorized third parties and do not cover the access control over the information when this is handled by the device itself [19] [20]. An authentication mechanism is necessary to protect access to the information stored in the wearable device that not only controls who can access the information but also what can be done with it. This matter is addressed in Chapters 3 and 4.

1.1.2.1 Authorization Performance

The eXtensible Access Control Markup Language (XACML) [21] is a widely used, XML-based language for defining access control policies in attribute-based access control (ABAC) [22]. It was developed to standardize access control by providing common terminology and interoperability among multiple ABAC implementations and defines an access control model in which a set of policies is used to make an access decision based on subject attributes, resource attributes, and current environmental conditions. Despite its wide use, most of its implementations, such as [23] [24], suffer a serious performance problem when the number and complexity of policies increases, while others, such as [25] [26] have improved performance at the cost of reducing functionality. A solution to reduce the computational complexity of evaluating XACML policies while still maintaining all functionalities is needed. This matter is addressed in chapters 5 and 6.

1.1.3 Accounting

Accounting is a security service that answer the question “What did you do?” by keeping track of the user activities (generally, using data logs). In order to provide a reliable accounting service ensuring logging data integrity is key [59]. Several solutions exist to store and manage the logs generated by systems, but most of them, such as [27] [28] [29], depend on central servers to store the data logs and trusted third parties to manage their integrity. This dependency on a centralized architecture makes these solutions unsuitable for the heterogenous distributed environments under discussion. With these limitations in mind, a strong current of research on blockchain as the solution to solve this problem has emerged, such as [30] [31] [32] [33] [34] [35]. These proposals offer immutability of the logs in heterogenous and decentralized environments, but do not provide a fine-grained access control to the data logs (data is public to all the network’s members) as centralized logging solutions do. It is, therefore, desirable to find a solution suitable for the discussed environments while maintaining all the relevant functionalities of the traditional logging systems. This matter is addressed in Chapter 7.

1.1.4 Use Case: Ground Control Station

During the initial discussions that led to this thesis we found a big partner with similar concerns about the security of one of these previously discussed changing environments. In particular, Airbus Defence and Space was seeking for novel security solutions that allowed the decentralization and heterogenization of future Ground Control Station (GCS) [36] in a secure way. From this collaboration arises, not only the funding of this thesis, but also the possibility of applying its results in a real environment.

A Ground Control Station is an element that provides the necessary systems for human control of Unmanned Aerial Vehicles (UAV) [10]. GCS systems are locally interconnected, but they do not have connection with any external systems, but the UAV (using a secure link) that is being controlled during a mission. The most important systems in a GCS, Figure 1, are:

- The Command and Control System defines and monitors a mission plan. Pilots have full control of the mission when they have access to this system.
- The Monitoring System receives information from the UAV about the mission and this information is stored within the GCS in order to make it accessible to the GCS operators.

- Mission Planning system is used to generate mission plans based on the environments conditions defined by the operator. Missions plans are later loaded by the Command and Control System to execute them.
- Logging system receives the logs generated by every system within the GCS. Besides, it offers an interface to visualize the information received.
- Storage Database represents the data storage systems a GCS has. Multiple databases are used to save information such as mission plans, images, terrain data, etc.
- Data Distribution Service (DDS) [37] allows exchanging data in distributed real-time systems using a public-subscriber communication. DDS nodes can be publishers by sending information to the network or subscribers by accessing to data of their interest. In the context of the GCS, this protocol is used to forward the information to every GCS system.
- UAV executes the mission and records data such as photos, videos, audio, etc. during it.

Figure 1: *Isolated GCS Architecture*

Most of the security of this kind of GCS relies on its physical isolation. Once granted access to the room where the GCS systems are located, the security controls applied are residual. Figure 2 shows an example of this kind of GCS for the UAV Predator MQ-1 [38] with two pilots using replicated GCS architectures to control the UAV in an isolated room.

Figure 2: *Predator MQ-1 Ground Control Station*²

However, GCSs are evolving from isolated systems that are only connected to the UAV using a private link to a network of heterogeneous devices using public links. Besides, this evolution includes the communication of different and remotely located GCS to allow, among others, missions to be operated by a collaboration of several pilots in remote locations or log mission data to be shared in real time. Unfortunately, the transition to this new environment and the integration of portable devices within GCSs have been done without properly evaluating the opened threats and providing protection to GCS systems against them, as described in [39].

The evolution of the GCS architecture is presented in Figure 3 as well as labels pointing out where our previous general discussion for AAA and the presented solutions for them described in the following chapters of this thesis have been applied to selected parts of a future GCS architecture.

---

² By United States Air Force photo by Master Sergeant Steve Horton -
<http://www.af.mil/News/Photos.aspx?igphoto=2000461305>.
<https://commons.wikimedia.org/w/index.php?curid=2553107>
Public Domain,

Figure 3: *Distributed GCS Architecture*

The elements of this distributed GCS architecture are:

- A Control Center with the classical GCS systems deployed plus:
  - A new Access Control System to manage the access control decisions within the GCS (including those from remote portable devices).
  - A Blockchain Logging system for logging data sharing with other GCS through the Blockchain Logging network.
  - Provision of authentication and access control service in the Command and Control and Monitoring systems.
  - Connectivity with the UAV.
- A remote portable device with some of the GCS systems deployed:
  - Command and Control (provisioned with an authentication and access control service).

- Monitoring system (provisioned with an authentication and access control service).
  - Blockchain Logging forwarder system.
  - Connectivity with the UAV for piloting the mission.
- All the collaborative GCS are no longer isolated but connected using the Blockchain Logging network.

1.2 Objectives

Based on the limitations that we have found in the Authentication, Authorization and Accounting solutions for the discussed environments, this thesis has the following objectives:

- **Objective 1**: Providing secure mutual end-to-end authentication between any device within the environment independently of its resource limitation and regardless whether other intermediate devices are trusted or not.
- **Objective 2**: Providing a fine-grained access control system that, besides of protecting the information from unauthorized access, allows defining and enforcing a set of restrictions about how the information should be handled by the pair user-device.
- **Objective 3**: Designing a complete access control architecture and integrating it in the Command and Control system and in the Monitoring system of an Airbus GCS demonstrator.
- **Objective 4**: Reducing the performance bottleneck of attribute-based access control systems when the number and complexity of policies increases.
- **Objective 5**: Designing a logging system flexible enough to be integrated in distributed and heterogenous systems while, at the same time, protecting the “need to know” of the logging data.

1.3 Contributions

These contributions of this thesis can be summarized as:

- **Contribution 1 matching Objective 1**: Design and implementation of an authentication protocol that enables secure mutual end-to-end authentication between a

wearable device and any other entity such as another wearable device, a personal device (mobile phone), a remote server, or a user's application. It uses a point-to-point authentication protocol (end-to-end authentication) regardless whether other intermediate devices are trusted or not. The proposal focusses on wearable devices, but the designed protocol can be extended to any device facing the same limitations. Chapter 2 explains this contribution in detail.

- **Contribution 2 matching Objective 2:** Design and implementation of an attribute access control system that, besides of protecting the information from unauthorized access, allows defining (using a security policy) and enforcing (using a hardware and software solution) a set of restrictions about how the information should be handled into a portable devices with limited computational capacity, memory, etc. The proposal focusses on wearable devices, but the designed access control system can be extended to any device facing the same limitations. Chapter 3 explains this contribution in detail.
- **Contribution 3 matching Objective 3:** Definition and integration in an Airbus GCS demonstrator of a access control architecture for heterogenous and distributed environments. The proposal uses XACML to define the access control rules at the corporate level. Chapter 4 explains this solution in detail.
- **Contribution 4 matching Objective 4:** Design and implementation of an access control model based on graph databases that drastically improves performance in comparison to existing XACML classic solutions while maintaining all XACML functionalities. Chapter 5 explains this contribution in detail.
- **Contribution 5 matching Objective 4:** Design and implementation of a hybrid access control model for scenarios where changing the architecture needed for a pure graph database model may not be an option. This model is compatible with classical XACML implementations and minimizes the architecture modifications while still improving the system performance using a graph database. Chapter 6 explains this contribution in detail.
- **Contribution 6 matching Objective 5:** Design and implementation of a blockchain-based logging solution suitable for heterogenous and distributed environments, with participants that do not need to trust each other. This solution allows introducing logs

that will be readable only by specific set of nodes within the network and adding an access control layer to limit how users can manage these logs. Chapter 7 explains this contribution in detail.

1.4 Organization

The remainder of this document is structured in the following way:

- Chapter 2, *Towards Self-Authenticable Wearable Devices*, defines an end to end authentication solution for wearable devices.
- Chapter 3, *Lightweight Access Control System for Wearable Devices*, defines an attribute-based access control system for devices with limited capacities.
- Chapter 4, *Access Control System for interoperable distributed architectures*, provides a complete access control architecture supplementing the attribute-based access control system defined in the previous chapter.
- Chapter 5, *Modelling XACML Security Policies Using Graph Databases*, defines a XACML graph database schema that drastically reduces the performance bottleneck of attribute-based access control systems when the number and complexity of policies increases.
- Chapter 6, *Hybrid XACML-Graph Database Policy Decision Point*, defines an access control system that combines graph databases with classical XACML evaluation engines for scenarios where changing the architecture needed for a pure graph database model may not be an option.
- Chapter 7, *Blockchain-based Logging solution*, defines a logging solution using a Blockchain network for future interoperable distributed architectures.
- Chapter 8, *Conclusions and Future research lines*, describes the results obtained during this thesis and provides ideas of future research lines that can arise from it.

2

Towards Self-Authenticable Wearable Devices

2.1 Introduction	12
2.2 Related Work and Technologies	15
2.2.1 Wearable Devices	15
2.2.2 Near Field Communication (NFC)	16
2.2.3 Smart Cards	16
2.2.4 Point-to-Point Protocol (PPP).....	16
2.2.5 Extensible Authentication Protocol (EAP)	17
2.2.6 Imprinting	17
2.3 Proposed Authentication Protocol	17
2.3.1 Wearable Device Requirements and Proposed Design Justification	18
2.3.2 Application Scenarios	19
2.3.3 Architecture	20
2.3.4 Authentication Methods.....	22
2.4 Security Evaluation	26
2.5 Conclusion	27

2.1 Introduction

According to various studies the number of wearable devices is expected to continue to grow in the near future. For example, ABI research [40] estimates the global market for wearable devices in health and fitness could reach 170 million devices by 2017. These wearable devices can hold a lot of useful information about their users. Such information includes blood pressure, heart rate, activity tracker, tastes that can be used for several purposes including health, fitness, recommendations, etc. However, this information is of little use if wearable devices lack the ability to exchange it with other devices or services. Due the wearable devices' limited range

of connectivity, the use of other personal devices as intermediaries to share this information over longer distances must be possible.

Similarly, because of the sensitive information (such as medical records or pacemaker's configurations) wearable devices may handle, it is essential that such information be protected from unauthorized access or modification. For example, consider a pacemaker updating the actual conditions of its holder in an online medical system of a hospital. Before sending the updated patient's information, the pacemaker has to make sure that it is really communicating with the hospital (hospital's authentication) to prevent information leaks. In the same way, before updating the patient's information the medical system has to make sure that the information is really coming from the patient's pacemaker (pacemaker's authentication) to ensure that the patient's medical information is also correctly updated. Furthermore, if, after receiving the updated patient's information, the medical service would like to change the patient's pacemaker's configuration, again, mutual authentication is necessary to protect the patient's health. The medical service would have to check the identity of the pacemaker to know that it is updating the configuration of the right device. The pacemaker would also need to check the identity of the medical service to verify that the new configuration is coming from a trusted source. It is, therefore, necessary that a secure authentication service be associated with any wearable device holding sensitive information.

At present, a few solutions exist that address the problem of a secure authentication service for wearable devices, but they are more concerned about authenticating the user holding the wearable device than the device itself and are limited to scenarios where direct communication between the authenticating parties is possible. Some of them, such as [14], are only oriented to the authentication among wearable devices in the same BAN (Body Area Network), while others, such as [15], consider a bigger scenario where a wearable device needs to communicate also with a remote entity. However, in the latter case, end-to-end authentication between the wearable device and the remote entity is not provided. First, the wearable device authenticates itself with an intermediate device (such as a mobile phone) in its BAN that collects the wearable's information and, afterwards, the intermediate device authenticates itself with the remote entity to send the information collected from the wearable. From our point of view, this approach is not robust enough: wearable devices are not really authenticating against a remote entity, but only to an intermediate device; and the whole process of communication could be compromised in the case of an unreliable intermediate device. We want to go a step beyond and

have an autonomous and independent wearable device that can authenticate end-to-end with a remote entity by itself.

To this concern, another well-known protocols that provide end-to-end authentication (among other security services), such as TLS, are not an option due to the wearable' lack of the necessary resources to both implement a TCP/IP stack and manage their overhead. Neither are other TLS-based alternatives, such as EAP-TLS for smartcards [13], since they are based on the assumption that the smartcard performs the authentication in conjunction with a Smartcard Interface Entity that does have the necessary resources.

With the aforementioned limitations of current solutions, in this paper, we propose an authentication protocol that can perform a secure mutual end-to-end authentication between a wearable device and any other system such as another wearable device, an external personal device, an authentication server, or a user's application it needs to communicate with. Our design is based on a point-to-point protocol where the wearable device is authenticated directly against the other final entity regardless of whether the communication is direct or through other some intermediate (trusted or not) devices (such as the user mobile phone) used for forwarding purposes because of the wearable devices' lack of long range connectivity. Furthermore, although our protocol is initially focused on authentication, it could be easily extended to also include the exchange of a session key that allows the establishment of a secure channel to protect the data in transit.

One of the main objectives of this work is to design a solution that is as independent as possible while leveraging standard and secure technologies; also taking into consideration the device size to make our solution viable for wearable devices: wristband, rings, pacemakers, etc. With this in mind, we propose the use of a smart card (based on the Java Card Technology [41]) within the wearable device in order to make it self-authenticable and provide it with Near Field Communication (NFC) [42] connectivity.

The rest of the chapter is organized as follows. In section II we briefly present an overview of the technologies used. Section III describes our proposed authentication protocol including its architecture and the authentication methods used. The security of our proposal is analyzed in section IV. Finally, Section V concludes the work presented in this chapter.

2.2 Related Work and Technologies

In this section we describe the most important technologies used in our proposed authentication protocol.

2.2.1 Wearable Devices

The idea behind wearable devices is to add technology in everyday life, helping to improve human's day-to-day activities. A few examples of areas where wearable devices are increasingly being deployed and have demonstrated satisfactory results include health, sports, entertainment and the textile industry.

The early wearable devices were limited in storage capacity and were generally standalone devices. Over the years, they have matured into advanced and useful interoperable wearable devices that support short-range connectivity using standardized protocols such as Bluetooth and NFC. An overview of different wearable devices and their applications are illustrated in Figure 4.

Figure 4: *Wearable devices*³

Recent research efforts have focused on improving the connectivity range of wearable devices using more powerful personal devices (such as mobile phones or tablets) as intermediate devices. However, this new communication method also opens up new security challenges that should be addressed which involve protecting the wearable devices from both malicious

³ Figure created using images from several sources:

Sport industry image: Nike FuelBand by Peter Parkes licensed under CC BY.

Entertainment industry image: Detail of Google Glass by Antonio Zugaldia, reduced from the original, licensed under CC BY.

Health Industry: Cardioverter defibrillator by Gregory Marcus licensed under CC BY.

Security Industry: The HMDS for the F-35 Lightning II by the United States Marine Corps of public domain.

intermediate devices and unauthorized access attempts from other entities residing on the Internet.

2.2.2 Near Field Communication (NFC)

Near Field Communication [42] is a technology that is currently integrated in many mobile devices that try to simplify life's common tasks such as making transactions, exchanging digital content or connecting electronic devices. The NFC market penetration is expanding each year and it is expected that, by 2015, half a billion people worldwide will use it in conjunction with their mobile devices as travel tickets on metros, subways and buses [43].

NFC operates in the radio frequency of 13.56 MHz with data transmission rates ranging from 106 Kbits/s to 424 Kbits/s.

2.2.3 Smart Cards

Smart cards are hardware devices used to protect sensitive operations such as electronic payments, access control, etc. They can store sensitive information securely and have cryptographic capabilities.

Smart cards' characteristics, ranging from its physical characteristics to commands to interact with the cards are described in the ISO/IEC 7816 standard series. Security and commands for information interchange are defined in the ISO/IEC 7816-4 standard [44].

Traditionally, the use of smart cards has been strictly attached to a terminal. Both the terminal and the smart card were involved in the authentication process, working together as a split-suppliant [13]. However, more recent works [45] have proposed using a smart card in an autonomous way (stand-alone suppliant) where the card is able to take part in the authentication process by itself. This new functionality is based on the Java Card technology that allows to run Java based applications on smart cards, and its autonomy can only be achieved if the smartcard has connectivity.

2.2.4 Point-to-Point Protocol (PPP)

Point-to-Point Protocol [46] is a data link protocol used to establish a direct connection between two nodes. It provides a variety of services (such as encapsulating multi-protocol datagrams) once connectivity is achieved.

PPP allows Extensible Authentication Protocol (EAP) packets to be transported over the ISO 7816 protocol by mapping the PPP header to commands proposed in the ISO/IEC 7816-4 standard.

2.2.5 Extensible Authentication Protocol (EAP)

The Extensible Authentication Protocol [47] is an authentication framework, and it is not a specific authentication mechanism. It provides some common functions and negotiation options of authentication methods called EAP methods. Some of these methods are based on the use of regular passwords (EAP-MD5), the use of one-time passwords (EAP-OTP) or the use of certificates (EAP-Transport Layer Security (TLS)). Besides, EAP can be extended with new authentication mechanisms.

2.2.6 Imprinting

The imprinting mechanism was defined in [48]. This mechanism attempts to solve the problem of establishing trust between two devices. It is based on the duckling imprinting phase, i.e., the process by which a new-born duck establishes a pattern of recognition for its parents. Imprinting consists of a secure association established when devices are going to be deployed. During this phase both devices share something that allow the identification between these devices in the future.

2.3 Proposed Authentication Protocol

As we mentioned previously, the new connectivity capabilities for wearable devices using short range communication protocols, such as NFC, and the need to increase their communication range to allow Internet connectivity using other personal devices as intermediate devices opens up new security challenges. These intermediate devices may be malicious and try to intercept or modify the information in transit during wearable devices' communications. Once connected to the Internet, the wearable device could become a target for attacks attempting to access or modify the data it holds.

To address the aforementioned challenges, we have proposed a new authentication protocol for wearable devices. The main functionalities of this protocol include:

- A secure protocol for the mutual authentication of wearable devices and any other network element such as another wearable device, a user's application, a remote server, etc. This protocol can work directly over a short-range connection or using other intermediate devices (trusted or untrusted) for Internet access.
- A secure imprinting mechanism that allows the wearable device to differentiate between trusted and untrusted Intermediate devices.
- Storage of different authentication credentials (password, certificates, etc.) within the wearable device. This also opens the opportunity of using the holder's biometric data obtained by the wearable device itself as a source of authentication.
- Inclusion of cryptographic and logical capabilities within the wearable device allowing it to take decisions according to the sensitivity of information handled by the wearable device.

In the rest of this section we first analyze the functional and non-functional requirements and justify the design of the wearable device used. Then, we present several application scenarios of our proposed authentication protocol according to the sensitivity level of the information being handled by the wearable device. Finally, the proposed system architecture is presented followed by a description of the authentication methods available in our proposed protocol.

2.3.1 Wearable Device Requirements and Proposed Design

Justification

Several requirements arise for wearable devices in order to solve the challenges raised from the ability to securely exchange information with other devices or services:

1. The first requirement is the limited size of a wearable device. The proposed solution should fit inside a wearable device of any kind using existing technologies.
2. The second requirement arises from the necessity of providing the wearable device with strong authentication capabilities. In order to do so, the wearable device should have the capability to perform cryptographic and logic operations.
3. The third requirement has to do with credentials used to perform the authentication as we describe further below. The wearable device should have storage capabilities.

4. Finally, the fourth requirement is Internet connectivity. Since a direct connection with Internet is not possible due the limited capabilities of a wearable device, we need to use a short range communication technology that allow the wearable device to use other devices in its communication range as intermediate devices to enable Internet access.

The objective of our solution is to design a protocol as device independent as possible while exploiting already proven standards that enable its security and interoperability. With this in mind, we propose to include a Java Card based on the smart card technology within the wearable device to satisfy requirements 2 (cryptographic and logic capabilities) and 3 (storage capability); also requirement 1 (size limit) due to the small size of smart cards. To satisfy requirement 4 (connectivity) and considering the size limit requirement, we have included NFC capabilities within the wearable device. One of the motivations for using NFC compared to other alternatives such as RFID [49], is its resilience against man-in-the-middle attacks.

During the rest of this chapter we call this device WD-NFC-JCard: wearable device with NFC and Java Card capabilities.

2.3.2 Application Scenarios

Before describing our proposed protocol, we present three different application scenarios according to the sensitivity of information handled by the wearable device. These scenarios are based on Figure 5 where a WD-NFC-JCard wants to authenticate itself to a remote server using a personal device with Internet connectivity (such as a mobile phone) as an intermediate.

We describe below different modes of operation that our proposed architecture provides:

1. Low security level: The information that the WD-NFC-JCard holds is unclassified. In this scenario, we can use an untrusted intermediate (no authentication between the wearable device and the mobile phone is required) and we only perform mutual authentication with the remote server. It is worth noting that even if the intermediate device is not trusted, the end-to-end authentication can still be performed in a secure way.
2. Intermediate security level: The information that WD-NFC-JCard holds has a moderate security level. In this scenario we limit the use of intermediate devices to only trusted ones in order to provide an additional level of protection to the information. Therefore,

prior to performing the mutual authentication with the remote server, it is necessary to perform a secure pairing (mutual authentication) with the intermediate device.

3. High security level: The information that the WD-NFC-JCard holds has a high classification security level. In this case, before applying the mechanisms (secure pairing and mutual authentication) described in the previous scenario, a PIN input from the holder of the wearable device is required. Due to the fact that some wearable devices do not have a keyboard, a biometric token is also acceptable.

	Remote Authentication	Intermediate Authentication	Holder Authentication
Low	X		
Intermediate	X	X	
High	X	X	X

Table 1: *Security level – Authentication control*

2.3.3 Architecture

As mentioned before, when a wearable device needs to communicate with a remote server over the Internet, it uses an intermediate device that is within its communication range. To do so, a communication channel should be established between the wearable device and the intermediate device using the NFC protocol. Once this channel has been established, the intermediate device will be responsible for opening the communication channel between itself and the remote server; forwarding the packets in both directions between the wearable device and the remote server as shown in Figure 5.

Figure 5: *System elements*

This communication method is based on the stand-alone supplicant where the WD-NFC-JCard uses the intermediate device only for communication but not to authenticate the remote server. When this communication channel is set up between the WD-NFC-JCard and the remote server, the authentication process starts.

Our proposed authentication protocol is based on the EAP authentication protocol. Since EAP is an authentication framework that does not assume the use of any particular authentication

method, we define the specific methods used in our proposed authentication protocol. In addition, the fact that EAP will be running within the WD-NFC-JCard implies that the mobile device does not need to understand the authentication messages (except when its own authentication is also required), but only need to forward the messages received in both directions.

As shown Figure 6, in the WD-NFC-JCard the EAP messages are encapsulated in PPP frames as explained in [45]. The mapping of the PPP headers with the ISO/IEC 7816-4 commands has been done based on [50]. Finally, the commands are transmitted over the air over 13.56 MHz radio waves between the WD-NFC-JCard and the intermediate device according to the ISO-14443-4 standard [51].

The intermediate device receives and un-encapsulates the packets from the WD-NFC-JCARD until the EAP level, and then re-encapsulates and sends them over Internet. If a packet comes from the remote server the encapsulation/un-encapsulation process is the exact opposite. The AAA protocol is used to exchange the authentication messages between the intermediate device and the remote server.

Finally, the remote server un-encapsulate the different protocols until it can retrieve the authentication information encapsulated by the EAP protocol.

Figure 6: Proposed Authentication Architecture

AAA: Authentication, Authorization and Accounting.
EAP: Extensible Authentication Protocol.
IP: Internet Protocol.
ISO: International Organization for Standardization.
L1/L2: Open System Interconnection (OSI) layers 1 and 2.
PPP: Point-to-Point Protocol.
UDP: User Datagram Protocol.

Table 2: Figure 6 Abbreviations

2.3.4 Authentication Methods

We used two different authentication methods in our proposed authentication protocol. First, a method to authenticate the intermediate device and the WD-NFC-JCard is defined. Then, a method to authenticate the WD-NFC-JCard and the remote server is defined. In both cases, it should be taken into account that:

- The certificates used in our system are based on the standard X509v3 [52]. Since our authentication methods are algorithm independent, the size of the certificates would depend, mainly, on the specific algorithm and key length chosen.
- We describe the cryptographic operations (encrypt, decrypt, sign, verify) that should be performed in each case, but we do not specify the particular algorithm to be used. Any algorithm supported by the smartcard can be chosen depending on the application needs.

2.3.4.1 Intermediate Device - WD-NFC-JCard Authentication

In this case, the holder of the wearable device is responsible for registering the trusted intermediate device with the WD-NFC-JCard. To do so, pairing the intermediate device with the WD-NFC-JCard is performed using the imprinting mechanism described in [48]. The necessary steps to establish this link between the intermediate device and the WD-NFC-JCard are shown in Figure 7:

1. NFC communication between the WD-NFC-JCard and the Intermediate Device is established.
2. If the WD-NFC-JCard has not been paired with any Intermediate Device before, a pairing process is automatically started by the WD-NFC-JCard by sending a pairing request.
3. The Intermediate Device sends to the WD-NFC-JCard some unique identifiable information (such as its International Mobile Equipment Identity (IMEI), Media Access Control (MAC) and processor model in a smartphone).
4. The WD-NFC-JCard stores the data received from the Intermediate Device and creates a pair of private and public keys.
5. A Public Key Certificate (PKC) and a digital signature of the received data are sent from WD-NFC-JCard to the Intermediate Device.

6. Finally, the Intermediate Device verifies the digital signature received and if everything is correct, the certificate is stored and a confirmation message is sent to the WD-NFC-JCard.

Figure 7: Pairing process

If the holder of the wearable device wants to link another device in the future, the holder should remove the data stored in WD-NFC-JCard associated with the old Intermediate Device, and then start the pairing process with the new Intermediate Device.

In future communications, if WD-NFC-JCard wants to authenticate the Intermediate Device as a trusted one it can use the EAP Method described in Figure 8. The steps to be followed during this authentication method which we have called Wearable Device Intermediate Device (WBID) are:

1. A communication channel is established between the WD-NFC-JCard and the Intermediate Device through NFC using PPP configuration messages.
2. The WD-NFC-JCard sends to the Intermediate Device an EAP Authentication message informing that it wants to start an authentication process with it.
3. The Intermediate Device sends an EAP Request message to the WD-NFC-JCard to start the authentication procedure. Within the request, the Intermediate Device includes a random number encrypted with the public key of the WD-NFC-JCard.
4. The WD-NFC-JCard decrypts the received message and sends an EAP Response to the Intermediate Device with the number received.
5. If the received number is correct, the Intermediate Device confirms this to the WD-NFC-JCard. The WD-NFC-JCard has been authenticated.

6. Next, WD-NFC-JCard sends an EAP Request message to the Intermediate Device in order to start the authentication procedure in the other direction.
7. The Intermediate Device sends an EAP Response message to the WD-NFC-JCard with its unique identifiable information (IMEI, MAC and processor model for a smartphone) encrypted with the WD-NFC-JCard's Public key.
8. Finally, the WD-NFC-JCard decrypts the received message and verifies that the data corresponds to that of the Intermediate Device paired in the imprinting process. If it is correct the WD-NFC-JCard confirms this to the Intermediate Device. As a result, both devices have been mutually authenticated.

Figure 8: *WD-SCard – Mobile Device authentication flow*

2.3.4.2 WD-NFC-JCard – Remote Server Authentication

In this case, the objective is to enable mutual authentication between the WD-NFC-JCard and the remote server. This authentication is achieved through the use of public key certificates. These two assumptions are made:

- The Public Key of the WD-NFC-JCard is known by the authentication server and is trusted.
- The Public Key of the Authentication Server is known by the WD-NFC-JCard and is trusted.

The WD-NFC-JCard and the authentication server hold a PKC which shall be used during this phase of mutual authentication. The EAP name chosen for this authentication method is

Wearable Device Remote Server (WDRS). It is based on a double challenge-response in four rounds. The general steps (as shown in Figure 9) to perform this authentication are as follows:

1. A communication channel is established between the WD-NFC-JCard and the Intermediate Device through NFC using PPP configuration messages.
2. The WD-NFC-JCard sends to the Intermediate Device an EAP Authentication message informing that it wants to start an authentication process with a remote server.
3. The Intermediate Device sends an EAP Request message to the WD-NFC-JCard allowing it to start the authentication process.
4. The WD-NFC-JCard sends an EAP Response message, including its certificate ID, to the Remote Server via the Intermediate Device.
5. The Intermediate Device encapsulates this message and sends it to the Remote Server.
6. The Remote server generates a random number, rS , and initiates the wearable device authentication process by sending a response, including rS , to the WD-NFC-JCard via the Intermediate Device.
7. The Intermediate Device unencapsulates the EAP packet received from the Remote Server and forwards it to the WD-NFC-JCard.
8. The WD-NFC-JCard generates a random number rC , encrypts rS with its private key. Finally, it encapsulates rC and sign (rS) in an EAP Response and sends it to the Remote Server via the Intermediate Device.
9. The Intermediate Device encapsulates this message and forwards it to the Remote Server.
10. The Remote Server checks the correctness of the digital signature received. If it is correct, the WD-NFC-JCard is authenticated. Next, it encrypts rC with its private key and encapsulates this digital signature in an EAP Request packet which is sent to the WD-NFC-JCard through the Intermediate Device.
11. The Intermediate Device un-encapsulates the EAP packet received from the Remote Server and sends it to the WD-NFC-JCard.
12. The WD-NFC-JCard checks to see if the digital signature over rC is correct. If it is, the Remote Server has also been authenticated. Finally, the WD-NFC-JCard sends an EAP

SUCCESS to the Remote Server via the Intermediate Device to inform to the Remote Server that the mutual authentication has been successful.

13. The Intermediate Device encapsulates this message and forwards it to the Remote Server.

Figure 9: WD-SCard – Authentication Server authentication flow

2.4 Security Evaluation

In this section we evaluate our proposed authentication protocol which supports three main functionalities.

The first functionality is related to the imprinting of the WD-NFC-JCard and the Intermediate Device. Since the WD-NFC-JCard and the Intermediate Server do not previously know each other, the owner of WD-NFC-JCard is the responsible for starting this phase with the appropriate devices. This process is protected against eavesdropping attacks due to the short range distance and the physical properties of NFC communications.

Once the impairing process has been executed, the devices will share unique identifiable data between them, which will allow them to mutually authenticate in the future using the second WBID functionality. In this process the Intermediate Device identity is protected by previously exchanged identifiable data (IMEI, MAC and processor model for a smartphone) while the identity of WD-NFC-JCard is protected by the proof of possession of the private key related to its digital certificate. Both mechanisms together prevent the possibility of spoofing attacks. Also, as in the impairing process, the integrity of the communication is protected by the physical properties of NFC communications.

The third functionality of our protocol is WDAS which is related to the mutual authentication of the WD-NFC-JCard and the Remote Server. In this case, both identities are protected by the proof of possession of the private keys related to their digital certificates. Authentication and integrity are, therefore, provided by digitally signing the exchanged messages. However, the possibility of using an untrusted Intermediate Device should be clarified. Two possible scenarios arise:

- Although being untrustworthy, the Intermediate Device forwards the packets between the WD-NFC-JCard and the Remote Server. In this scenario the authentication protocol can carry out the mutual authentication of the involved parties in a secure way.
- A different scenario occurs when the untrustworthy Intermediate Device denies to forward the packets between the WD-NFC-JCard and the Remote Server. In this case, the Intermediate Device cannot break the security of our authentication protocol (it is not possible to successfully authenticate a party without the necessary credentials), but it can, however, prevent the communication between the involved parties. In this case, WD-NFC-JCard should find another Intermediate Device willing to forward the communication.

In relation to the operation and storage of credentials, the use of a smart card increases their security in comparison with a non hardware based solution. However, smart cards are not unbreakable and their resilience against some attacks, such as the side channel attack [53], should be taken into account to choose the specific one to be used.

Finally, although our protocol is initially focused on authentication, it could be easily extended to include the exchange of a session key that allows the establishment of a secure channel to protect the data in transit.

2.5 Conclusion

Secure authentication has not had much attention in the area of wearable devices. However, from our point of view and because of the sensitivity of the information handled by wearable devices, authentication should be an essential service that any wearable device should provide.

With this in mind, in this paper we have presented an authentication protocol for wearable devices that allows performing a secure mutual authentication between a wearable device and any other entity. Our proposed protocol is based on a digital signature scheme with a challenge-

response mechanism used to authenticate the different entities present in the system. Our proposed authentication protocol is not only secure, but flexible enough to provide different levels of protection based on the sensitivity of the information handled.

3

Lightweight Access Control System for Wearable Devices

3.1 Introduction	29
3.2 Proposed Access Control System	32
3.2.1 Wearable Device Requirements and Proposed Design Justification	33
3.2.2 System Architecture.....	34
3.2.3 Security Policy	35
3.2.4 Access Control System	36
3.3 Security Evaluation	37
3.4 Prototype	38
3.4.1 Server.....	39
3.4.2 Wearable Device.....	39
3.4.3 Secure SD Card.....	39
3.4.4 Functional Testing	39
3.5 Conclusion	40

3.1 Introduction

Originally, wearable devices were intended to monitor vital signs (such as heart rate, body temperature, body motion, etc.) locally. However, current wearable devices have become more sophisticated and now they can both share the information they collect and receive information from other devices or information services.

The increase in the functionalities provided by wearable devices has prompted their deployment in different areas and market segments [54], including:

- Sports and fitness wearables.
- Multimedia and entertainment wearables.

- Lifestyle wearables: smart clothing and jewelry.
- Smart watches.
- Smart glasses.
- Enterprise wearables.
- Healthcare wearables.
- Military wearables.
- Wearables are part of IoT - which are divided into PIoT (personal) and IIoT (industrial).

Thus, different areas where wearable devices can be used, show that they can manage diverse kinds of information with different sensitivity levels: from user's activity information with low sensitivity that could be made public (such as his/her sport activity) to user's personal information with high sensitivity that is private (such as health information) or, over and above that, private third-party information (such as classified military information).

In this paper, we focus on protecting the latter scenarios (high sensitivity information), i.e. how the wearable device protects the information received from external sources. In these cases, apart from the information it collects with its sensors, a wearable device receives information from other entities, e.g. another wearable device, or a remote entity such as a command and control center. For example, the report by Raytheon's Aviation Warrior and D. Tam [55] presents a military environment where a wearable device accesses the sensitive information of an aircraft central unit. Other interesting scenarios are wearable devices which store both personal and business information. Personal and business applications must not access each other's information. In the same way, and due to their sensitivity, other widely used wearable devices, such as the implantable medical devices must be highly protected to avoid their information disclosure, as pointed out in the report by Daniel Halperin and colleagues [56]. For such cases, an access control mechanism is necessary to protect access to the information stored in the wearable device that not only controls who can access the information but also what can be done with it. Additionally, this mechanism must be able to handle different levels of information for military and health scenarios where information is classified according to its sensitivity (from non-classified to top-secret in military and from low to high in health).

Unfortunately, although several access control proposals exist for these environments in general, including enforcing the security policy of health information in a distributed

environment [16] [17], or protecting access to different classification levels of information in a military environment [18], there is no access control solution available for the specific characteristics (such as portability, small size, low computational resources and capacity, limited range of connectivity, and so on) associated with current wearable devices. In the same way, current desktop right management solutions such as Microsoft IRM [57], or Adobe DRM [58], that allow restricting the permissions (e.g. read, write, copy or print) over the information once it has been accessed are not a viable option: 1. They have not been ported yet to wearable devices, 2. They are constrained to the most popular file formats (e.g. PDFs and Microsoft Office documents), and 3. They are very limited in functionality. These solutions can neither restrict the device in which the information will be visualized nor can they work offline due to their dependency on servers provided by their manufacturing companies. This dependency on an Internet connection or on a server to check the security policy may not be a problem in some non-restricted scenarios, but it definitively is in others. Imagine, for example, a soldier in the battlefield without Internet connection or a restricted environment where communication with a third-party provided server is not an option due to security reasons. Finally, current wearable device-oriented solutions for information protection focus primarily on protecting the confidentiality of the information when it is transmitted from the wearable device to other devices or information services [19] [20], but do not restrict how wearable devices work with the information they receive. In the same way, current access control solutions related to wearable devices such as the Nymi wrist-band [59] focus more on using the wearable device as a physical access control token itself rather than controlling the access to the information stored in the wearable device.

In order to address the aforementioned limitations of current access control solutions for wearable devices, in this paper we present a novel access control system for wearable devices. Our proposed model provides multilevel and multilateral security which is lightweight enough to run within a wearable device's computational constraints. Our proposed solution is extensible, platform-independent and provides a secure storage and secure execution environment by using a combination of hardware and software mechanisms.

The rest of the chapter is organized as follows. In section II we describe our access control system. We analyze the security of our system in section III. Section IV describes the prototype used to validate our solution. Finally, Section V concludes the work presented in this chapter.

3.2 Proposed Access Control System

As we mentioned previously, there are scenarios where it is necessary that wearable devices be able to protect the information they receive by enforcing a security policy defined by the owner of the information. This protection must not only protect access by unauthorized users but must also provide protection against authorized users who perform actions on the information not allowed by the policy. To address this challenge, we propose a lightweight access control system for wearable devices. The main functionalities of this access control system include:

- Protection of the information according to a security policy that defines the requirements the wearable device should fulfil to access the information and the operations permitted on it. On the one hand, Multi-Level Security⁴ (MLS) by preventing vertical access control attacks. Our access control system is flexible enough to allow an appropriate MLS model to be used depending on the characteristics of the project in which it will be deployed. For instance, Bell LaPadula model [60] for confidentiality or Biba model [61] for integrity. A specific policy can be defined for each operation according to the needs of the model used (e.g. read-down and write-up for Bell LaPadula or read-up and write-down for Biba). On the other hand, Multilateral Security by preventing horizontal access control attacks. Wearable devices and users will have assigned a set of labels (e.g. company, department, mission, etc.) that must match the information labels in order to be granted access.
- Use of an extensible access control model to formally represent and interpret the security policy.
- Combination of hardware and software solutions to enforce the security policy.
- Secure storage of credentials (password, certificates, and others) and secure cryptographic and logical capabilities within the wearable device.
- Independence from the communication technology used for data exchange.

---

⁴ Multilevel security represents a hierarchical structure of data classified according to different levels (from low to high, non-classified to top-secret, and so on) and where the access is provided only to the entities that have the same or higher level than the object that is being accessed. In contrast, Multilateral security partitions information within the same security level according to different labels (company, department, and so on). In this case, access to the information is allowed only to the entities which have the required compartment labels.

3.2.1 Wearable Device Requirements and Proposed Design

Justification

Several requirements arise for a wearable device in order to solve the challenges identified from the ability to securely protect the information according to a security policy:

1. Limited size of a wearable device: the proposed access control solution should fit inside a wearable device using existing technologies.
2. The need to protect the information from unauthorized access while it is stored in the wearable device: the wearable device should have the capacity to perform cryptographic operations.
3. The need to prevent users with access to the information from carrying out unauthorized actions (such as disclosing it to a third party): the wearable device must be able to restrict available actions to a user accessing the information.
4. Operations performed on both the information (encryption/decryption) and its associated security policy (authenticity, integrity and compliance checking) must be performed in a secure environment.
5. The keys used to perform the operations described above must not be accessible to the wearable device's user. The wearable device must have secure storage capabilities.

Based on the above requirements, we could propose a lightweight cryptographic method for wear-able devices. However, this solution satisfies requirements 1 to 3, but not 4 (secure environment) and 5 (secure storage capabilities). In addition, the existing lightweight cryptography algorithms such as PRESENT block cipher algorithm (proposed in its standard ISO/IEC 29192) have several vulnerabilities [62]. Thus, we propose the inclusion of a Java Card [41], into the wearable device, as we have already done for authentication purposes in a previous report [63], to achieve a secure implementation of the access control system. This solution satisfies requirement 1 (size limit) due to the small size of smart card, requirement 2 (cryptographic capabilities), requirement 4 (secure operation environment) and requirement 5 (secure storage). In addition, requirement 3 (restricted actions) is fulfilled along with the use of a secure application (whose integrity can be checked by the smartcard) to display the information stored in the wearable device.

3.2.2 System Architecture

The architecture of our system (see Figure 10) consists of two different entities: the server where the information is initially stored and their associated security policies, and the wearable device that is going to be used to remotely access that information. Within the wearable device, we also differentiate between the smartcard, the rest of the wearable components (such as the Storage Module (SM)) and the Secure Application (SA) used to access the information.

Figure 10 also shows the necessary parameters (explained in more detail later) that each participant must have for our proposed access control system: the asymmetric keys shared between the Server and the Java Card, the symmetric keys used to cipher the information, the security policies of the information, the Java Card holder credentials and the information encrypted and signed. It is important to note that the symmetric keys and the security policies are encrypted in the wearable device to avoid their unauthorized disclosure or modification. Finally, communication must exist between the remote server and the wearable device in order to send the information and their associated security policies to the wearable device. This communication can be offline by having all the information preloaded into the wearable device before its use; online when a real-time communication channel exists while the wearable device is being used, or both. Our system is independent of the communication protocol used. It is also worth pointing out that this communication is only needed once to transfer the information to the wearable device and not every time the information is accessed as is the case with other previously proposed solutions [57] [58].

Figure 10: Proposed System Architecture

3.2.3 Security Policy

A security policy protects the information by defining the necessary requirements to access it and the operations permitted. The owner of the information creates the security policy that is directly tied to the information it protects. In our proposed system, we have defined a security policy that uses the following attributes:

- Information reference: verifies if the information matches with the security policy and vice versa. A SHA2 hash [64]of the information is used to create a unique link.
- Application authentication: the owner of the information can force the Java Card to restrict the applications allowed to access the information by setting this flag. The applications need to present a valid digital signature in order to access the information.
- Security clearance: establishes the security level of the information and, therefore, the security clearance needed to access it.
- Company and department labels: filters the access based on the company or/and department membership.
- Operations: defines the operations allowed on the information.
- Position: restricts access to a specific area defined by a GPS location and distance from it.
- Time: restricts the access to a determined date and time.

Our proposed access control model requires only 55 bytes to represent the security policy associated with any information. This small size makes our model particularly suitable for Java Cards (satisfying their computational and storage constraints), while allowing the definition of a robust access control policy.

In addition, our security policy can be extended and more parameters can be added when needed. To do so:

- A new parameter is defined and added to the security policy and to the holder's credentials (if needed).
- The procedure to analyze this parameter must be included in the access control applet.

- The updated applet must be deployed in the Java Card. This deployment is only necessary in the specific Java Card that will need to evaluate this new parameter.

3.2.4 Access Control System

Figure 11 shows the communication steps during the exchange of security information for our proposed system. The files containing the information, the key to decrypt them and their security policies stored are encrypted and signed in the wearable memory, whereas the keys needed to access them and check their integrity are stored in wearable device's Java Card. In this case, when one of the wearable device's applications requests access to some information, the Java Card performs all the necessary checks to ensure that it has the necessary rights to do so, i.e., it is a trusted application and satisfies the information security policy. Finally, if the requirements are satisfied, the application accesses the information and makes it available to the wearable device of the user in a restricted environment that only allows performing the operations permitted by the security policy.

Figure 11: Access Control Flow of Communication

- The application sends to the Java Card the information associated with the security policy.
- The Java Card checks the integrity and authenticity of the security policy (using the remote server's public key), then decrypts the policy (using its private key) and checks internally if the wearable satisfies the requirements of the policy it stores (company,

department and security clearance). Finally, it requests application the missing information from the wearable to satisfy the policy.

- The application returns the requested credentials back to the Java Card.
- The Java Card checks the received data against the security policy and returns a result code to proceed with the loading of the symmetric key.
- The application sends the encrypted symmetric key to the Java Card.
- The Java Card checks the integrity and authenticity of the symmetric key (using the remote server's public key) and decrypts it (using its private key) and returns a result code to proceed with the loading of the information.
- The application sends the encrypted information to the Java Card.
- The Java Card checks the integrity and the authenticity of the file (using the remote server's public key) as well as if the security policy actually references this information. Finally, the Java Card decrypts the file (using the symmetric key) and sends the information along with the operations allowed for the application.

If any of the previous operations fail, then access is denied.

3.3 Security Evaluation

Our proposed system uses asymmetric cryptography to protect the integrity and authenticity of the data (information, associated security policy and symmetric encryption key). Besides, data confidentiality is also protected: a symmetric encryption key is used to protect the information and its associated security policy, while the symmetric key itself is protected using the wearable device's Java Card's public key (this satisfies the requirement defined in section II part A point 1). Using a different symmetric encryption key (protected by the wearable device's Java Card's public key) for each wearable device prevents any other device from accessing information if it is not authorized to do so. The information is encrypted with a symmetric key rather than with the wearable device's Java Card's public key for better performance.

All the necessary cryptographic operations are performed in the secure environment the Java Card provides (this satisfies the requirement defined in section II part A points 2 and 4), thereby ensuring that the symmetric encryption key is never available in clear text within the wearable device's memory (this satisfies the requirement defined in section II part A point 5). Using the

Java Card for the operation along with the storage of credentials increases the security compared to a non-hardware-based solution. However, we are aware that smart cards are not unbreakable and their resilience against some attacks, such as the side channel attacks [53], should be taken into account when choosing a specific smart card for the wearable device.

In order to access the information, a wearable device's application has to communicate with the Java Card which will allow this access only if the security policy is satisfied. The remote server signature protects the security policy's integrity and authenticity, while the Java Card's secure environment ensures its enforcement. Moreover, the link between the information and its associated security policy is secured by using the SHA2 hash of the information within the security policy. This prevents any attempt to swap the security policy associated with the information with another more relaxed security policy and ensures the integrity and authenticity of all the parameters used to satisfy the security policy's requirements, which are securely stored in the Java Card (this satisfies the requirement defined in section II part A point 3). However, further research must be done in order to ensure the integrity and authenticity of the ones (i.e., GPS location and date) provided by the wearable device.

If information access had been granted, the Wearable Device's user operations that can be performed on it are restricted by a secure application whose integrity is provided by a digital signature that the Java Card checks before providing it with the decrypted information. Unfortunately, this mechanism is not unbreakable. We are aware that if this signature is extracted by using reverse engineering over the application, an attacker could use it to perform unauthorized operations over the information after having satisfied the security policy. This is one the aspects we must improve in future works by including, for example, not only application startup verification, but also application runtime check-ups.

3.4 Prototype

To validate the functionalities of our system we have designed a prototype (see Figure 12). In this prototype, for a wearable device we have used a smartwatch with a Secure SD Card, supporting Java Card technology (this satisfies the requirement defined in section II part A point 1), while the server has been deployed as a WEB service.

3.4.1 Server

A web application (AC Web Server.war) has been developed with J2EE [65]. This application has two functionalities: 1) allowing the owner of the information to upload it to the server and define the security policy for it, and 2) allowing users who use the AC App.apk to connect to this service and download this information to the smartwatch for later use.

The web application has been deployed on a WSO2 Application Server running over a Linux operating system.

3.4.2 Wearable Device

The smartwatch model used in this prototype is K18 [66]. It has, among other capabilities, a Micro SD card slot, Wi-Fi connection and Android OS. In it, we have deployed an Android application (AC App.apk) which allows users to download the information and to visualize it.

3.4.3 Secure SD Card

A Secure SD card, Go Trust MicroSD [67], has been added to the smartwatch to provide it with Java Card support (Java Card Classic 3.0.1 Execution Environment). In it, the application used to validate security policies (AC Applet.cap) has been deployed.

3.4.4 Functional Testing

Functional testing has been performed over this prototype that allowed us to check if our proposal is technically possible and that it provides all the intended functionalities. We performed the following tests:

- On the Server: User Registration, File Upload and Policy Definition, File Encryption.
- On the WD: File Download and Information Visualization
- Secure SD Card: User Authentication and Access Control, File Decryption.

All these tests have been successful. Besides, the execution time to validate the security policy of all these tests has been in the order of milliseconds.

Figure 12: *Prototype*⁵

3.5 Conclusion

Access control has not received much attention in the area of wearable devices. This is mainly because, in early wearable devices, the information they managed was not sensitive or important. However, today, because of the sensitivity of the information handled by current and future wearable devices, access control should be an essential service that any wearable device should provide. With this in mind, in this paper we have proposed a lightweight access control system for wearable devices that protects the information from unauthorized access and allows defining a set of restrictions about how the information can be handled in a wearable device. Our proposal is based on the use of a security policy enforced through a combination of software (secure application) and hardware (Java Card) solutions.

As a future work, we find interesting the possibility of extending our MLS system to provide a role-based access control (RBAC) on top of it.

⁵ The source of the Smartwatch and Micro SD card icons is <https://thenounproject.com> and they are licensed under CC BY

4

Access Control System for interoperable distributed architectures

---

4.1 Introduction	41
4.2 Related Work and Technologies	44
4.2.1 Android	44
4.2.2 SAML	44
4.2.3 XACML	44
4.3 Access Control System Design	45
4.3.1 System Architecture.....	46
4.3.2 System Capacities	47
4.4 Prototype	52
4.4.1 Monitoring System Prototype.....	53
4.4.2 Command and Control System Prototype	59
4.5 Conclusion	64

4.1 Introduction

As already discussed in the introduction of this thesis, the decentralization and heterogenization of the operational environment has raised doubts about the capacity of existing solutions to provide to those new environments essential security services such as authentication and authorization. In Chapter 2 we have already proposed a solution for the authentication problem for portable devices with restricted capacities while in Chapter 3 we presented an authorization solution to control how the information is consumed in these devices once the user has been authenticated. In this chapter, we will combine both to provide a complete access control system for portable devices. Figure 13 presents the four phases our access control system will provide.

Figure 13: Access Control System Phases

The Enrolment phase covers the user registration within the access control system. During this phase, the system operator should configure a JC according to the user profile and (optionally) executing the pairing process of the user's trusted device and its JC.

The Protection phase covers the upload of resources to the access control system. During this phase, the access control system receives new resources, their access and download security policies are generated and the resource themselves and their access security policies are protected.

The Download phase covers the download of resources from the access control system to a PD. During this phase, user and (optionally) its trusted device are authenticated against IdP and user's JC respectively. Then, if authorized to do so (by the download security policy), downloads the desired resource and its associated access policy.

Last phase, Access, covers the access to the downloaded protected resource on the PD. During this phase, user and (optionally) its trusted device are authenticated against user's JC. Then, if authorized to do so (by the access security policy), the protected resource is deciphered and displayed to the user.

Figure 14 summarizes the functionalities provided by our access control system pointing out the ones that have been already described in Chapters 2 and 3 and the remaining ones that will be covered within this chapter:

- JCs configuration according to the users' profiles.
- Definition of the protected resources access and download security policies.
- Ciphering and signing protected resources and their access policies.
- Verification of download security policy and key protection.
- Secure resource download.

Figure 14: Access Control System Functionalities

Once presented our complete access control system, we will apply it to a specific scenario: a Ground Control Station. Thanks to a collaboration with Airbus Corporation we had the opportunity of integrating two prototypes of our solution in a Ground Control Station to prove its correct operation.

4.2 Related Work and Technologies

In this section, we describe the most significant related works and technologies that have been added in this chapter.

4.2.1 Android

The Android Operating System [68] is an open source solution for mobile, wearable and IOT devices that it is based on the Linux kernel (> 2.6 version). The system architecture is organised in layers that provide functionality to the next layer in the stack. Besides, Android has an adapted virtual machine to work in systems with limited resources and can establish communication with the hardware device using libraries added to the system. One of these libraries allows developers to use the NFC chip. Finally, another interesting feature of Android for our project is that since 4.3 version it includes SELinux [69]. SELinux allows Operating Systems to provide an access control model in which access is controlled based on comparing objects' security labels with security clearances applicable to the subject.

4.2.2 SAML

Security Assertion Markup Language [70] is a framework that allows exchange information in a secure way between devices that has established a trust relationship. SAML defines three roles:

- User device: Requests access to the information or services offered by the Service Provider.
- Service Provider (SP): Contains the information or services that are being protected.
- Identity Provider (IdP): Contains the user authentication data and it is in responsible for evaluating the access control requests.

4.2.3 XACML

eXtensible Access Control Markup Language (XACML) [21] is an access control protocol to define security policies following the Attribute Based Access Control [22] idea. ABAC is a model that defines permissions based on the properties of both the object and the subject as well as the current environment conditions.

XACML defines an authorization framework composed of subsystems, also called actors, to define and to evaluate the policies. These actors are the following:

- Policy Administration Point (PAP): Repository that creates and stores policies. Its main function is providing policies to the Policy Decision Point.
- Policy Enforcement Point (PEP): Interface within the environment responsible for receiving requests for access authorization. Prepares a response to allow or deny the access to the resource with the help of the Policy Decision Point
- Policy Decision Point (PDP): Responsible of the access control decision. This actor collects all the information from the other actors and, after evaluating the different policies of access that exist, determines if the request should be approved or not.
- Policy Information Point (PIP): System entity that acts as a source of external attribute values, such as (in our case) security clearance, mission, country, etc.

4.3 Access Control System Design

As we mentioned previously, the Chapter 2 offers an end to end authentication protocol for PDs and Chapter 3 offers a lightweight access control protocol specifically designed to be used with PD. However, they offer these security services to PDs in an isolated way. With this in mind, in this section we define a complete access control system that includes the authentication functionality presented in chapter 2 and the authorization functionality described in chapter 3 and provides the following functionalities:

- User and device enrolment.
- Resource download and access policy definition.
- Download access control.
- Resource access control.

In the rest of this section we introduce the proposed system architecture followed by a description of the access control system capabilities.

4.3.1 System Architecture

To provide the functionalities described above we propose using standardized solutions that link the authentication and authorization protocols already described in chapter 2 and 3 and provide the remaining services. SAML has been chosen to split authentication (IdP) from service provision (SP) while XACML has been the solution chosen for the security policies definition and validation. IdP also offers to the system operator the capacity of registering users and PDs.

Figure 15 presents the four different entities included in our system and their relation with the authentication and authorization protocols described in chapter 2 and 3:

- Service Provider (SP): Stores resources downloaded by users (Encrypted Data), together with the access security policies (Encrypted Access Security Policies). Also, it manages the information encryption keys (Symmetric keys) and its own public/private keys (SP Public/Private Key). Besides, it has a copy of the public key of the Idp (IdP Public Key).
- Identity Provider (IdP): Authenticates users (using JCs Public Keys) when requested by SP (SP Public Key) (using the authentication protocol described in section 2.3.4.2) and authorizes resource download requests when a user (Users Data) fulfils the requirements of the download security policy (Download Security Policies). Besides, it manages its own public/private keys (IdP Public/Private Key).
- Java Card 3.0 (JC): Contains a cryptographic chip that allows performing cryptographic operation within a secure environment, including: user authentication (holder's credentials), mutual authentication with the previously described servers (SP Public Key and IdP Public Key), access security policy validation (signature of trusted applications) and ciphering/deciphering information. Also, it provides a secure container to store the ciphering/deciphering keys preventing that a portable device theft would compromise them. Besides, it manages its own public/private keys (JC Public/Private Key).
- Portable device (PD): Users will access to protected resources using these devices (using the access protocol described in section 3.2.4). PDs use JCs to access the protected resources by providing them the ciphered information (Encrypted Data), the ciphered symmetric key (Encrypted Symmetric Key) and the access security policy (Encrypted Access security policies).

Figure 15: System entities⁶

4.3.2 System Capacities

Once the entities of our access control system have been presented, below we describe the main capabilities not yet described in the previously mentioned chapters: users enrolment, security policy generation, content download and content visualization.

4.3.2.1 Users Enrolment

Before being able to access the system, users must be enrolled. After this process, performed offline, users are provided with a JC including:

- User security data: Security clearance, Company, Department and PIN.
- Signature of the trusted applications where the information can be displayed.

⁶ Cryptographic Chip icon licensed under CC BY. <http://www.clerk.com/clipart-smart-card-chip-only-.html>

- Pair of Public and Private Key (generated within the JC). The Public Key will be shared with the IdP while the private key will be only stored safely inside the JC.
- Public Key of both servers, SP and IdP, to ensure security (confidentiality, authentication and integrity) of future communications with them.
- Optionally, impairing with user's trusted device.

The communication flow of this process, Figure 16, is as follows:

1. System Operator starts the user enrolment process.
2. IdP requests JC Identifier.
3. The identifier is returned by the JC.
4. IdP requests JC public key.
5. JC internally generates a pair of Public and Private Keys.
6. JC sends the Public Key to the IdP.
7. System Operator enters the user's security data, selects the trusted applications and sends them to the IdP.
8. The IdP sends this security data and the trusted applications' signature to JC.
9. JC sends a verification code acknowledging the correct reception.
10. IdP sends to JC its public key and the SP public key.
11. JC sends a verification code acknowledging the correct reception and finishing the process.

Figure 16: *Users Enrolment*

Optionally, a user's trusted device can be registered in the JC to fulfil the authentication requirements of scenarios classified as intermediate or high (described in section 2.3.2). This registration follows the impairing process presented in section 2.3.4 where in this more general case the WD-NFC-JC represents the JC itself and the intermediate device represents user's trusted device that will be also used to access to the information.

At the end of this process JC will have all the needed information to allow a user to authenticate against the system and to evaluate the access security policies.

4.3.2.2 Security policies generation

Prior to make any resource available within the system (stores in the SP), its owner has to define its access and download security policies. Both policies can include the following parameters:

- A SHA2 hash of the resource protected by this security policy.

- The security level of the information protected by the security policy, such UNCLASSIFIED, RESTRICTED, CONFIDENTIAL or any other value we want to define.
- List of the operations allowed on the information, such as READ, WRITE, SHARE or any other operation we want to define.
- Area (defined by a GPS position plus a radius) in which the information could be accessed or downloaded depending on the policy.
- Date and time in which the information can be accessed or downloaded depending on the policy.
- Security labels allowed to access or download the information, such as Company, Department, Country or any other label we want to define.
- Allowed applications (only included in the access security policies) to access the information.

Access policies are generated according to the structure defined in section 3.2.3 Security Policy to minimize the computational resources used by the JC to evaluate them. Download policies, however, are evaluated in a server without computational restrictions, the IdP, and can be defined according to the XACML standard. After their generation, the download policy is registered in the IdP while the access policy and its referenced resource are uploaded to the SP. Then, SP encrypts both the resource and its access policy with a (different for each resource) symmetric key and signs them with its public key. This symmetric key prevents an unauthorized access to the protected resource.

4.3.2.3 Content download

Prior to request access to a resource, a user has download it. When SP receives a download request from a user (1) it forwards the request to the IdP (SAML protocol) (2) that will require user authentication (3). For scenarios classified as intermediate or high (described in section 2.3.2) this authentication process starts with the portable device authentication against the user's JC following the process described in section 2.3.4.1 (4) and it is followed (for all the scenarios) by a mutual authentication between the user's JC and the IdP as described in section 2.3.4.2 (5). Once the user has been successfully authenticated, IdP verifies the download security policy (6) and, if its requirements are fulfilled, the user gets an authorization token

(including the user's JC public key) from the IdP to download the requested resource (7). Then, user sends the authentication token to SP (8). SP verifies the received token (9) and returns to the user a message including the symmetric key used to cipher the requested resource (during the security policy generation) encrypted with user's JC public key and the resource and its access security policy ciphered with the symmetric key (10). Ciphering the symmetric key used to encrypt the resource with the user's JC public key ensures that the downloaded information can only be read with the user's JC. Figure 17 graphically describes this process.

Figure 17: Content Download

4.3.2.4 Content Visualization

For scenarios classified as intermediate or high (described in section 2.3.2) the content visualization process starts with the portable device authentication against the user's JC following the process described in section 2.3.4.1. After that, (for all the scenarios) the resource can be visualized in the user's portable device following the access control process described in section 3.2.4 that verifies that the user's fulfils the requirements to access the resource. Figure 18 graphically describes this process.

Figure 18: *Content Visualisation*

4.4 Prototype

To test our access control system we have decided to apply it to a specific scenario and deployed two prototypes for a Ground Control System demonstrator (as described in Section 1.1.4) in collaboration with Airbus:

1. The first prototype focuses on the GCS monitoring system to allow a user downloading and visualizing missions' contents securely in a Remote Portable Device. The proposed access control system will verify that the user fulfils all the requirements before allowing the access.
2. The second prototype focus in the Command and Control System to allow a pilot to operate a mission (control over an UAV included) securely from its Remote Portable Device. The proposed access control system will verify that the user fulfils all the requirements before allowing access to the mission data and pilot the UAV.

4.4.1 Monitoring System Prototype

4.4.1.1 Architecture

The deployment of this prototype has been done according to the architecture described in Figure 19. In it, they are represented all the elements of a GCS included in the prototype and how they match the GCS global architecture described in Section 1.1.4.

Figure 19: Monitoring System Prototype Architecture⁷

Starting with the architecture of a traditional GCS we have added the Access Control System. Both elements of this system, IdP and SP, have been prototyped using the WSO2 [71] open source solutions. We extended its IdP to include our authentication proposal defined in Chapter 2 and configured its Application Server to provide, using a web application, access to the information received from the Monitoring system.

Unfortunately, we were not allowed to directly integrate the access control system within the traditional GCS due to its functional and security restrictions. This system had to be deployed in an external system using a connector to communicate with the GCS and receive the mission resources. This connector, deployed using a SFTP [72] shared folder, defines a process to transfer the resources and their metadata (that represent the attributes to be included in the

⁷ Cryptographic Chip icon licensed under CC BY. <http://www.clker.com/clipart-smart-card-chip-only-.html>

security policies to be created by the SP) from the Monitoring system to the Access Control System.

The metadata schema used as source for the access and download security policies is based on XML[73] including the following fields:

- Metadata_File_Name: Complete filename, including extension and timestamp, of the Metadata file. It is a mandatory field.
- Data_File_Name: Complete filename, including extension and time stamp, of the resource data file referenced by this Metadata File. It is a mandatory field.
- Classification_Level: Classification level of the information stored in the resource data file. It is a mandatory field and can take the following values: UNCLASSIFIED, CONFIDENTIAL, SECRET, RESTRICTED and TOP-SECRET (based on the North Atlantic Treaty Organization (NATO) classification levels [74]).
- Company: Company of the owner of the information. It is a mandatory field.
- Department: Department of the owner of the information. It is a mandatory field.
- User authentication: Boolean value indicating whether the user must authenticate before download the information or not. It is a mandatory field.
- Applications: List of the digital signature of the applications allowed to access the information. It is a mandatory field.
- Download requirements: Set of optional requirements that must be fulfilled to download the referenced data file from the SP. It may include the following requirements:
  - Initial_Download_Datetime: Date and time, from which the download or access to the information is permitted. It has to be specified according to ISO 8601[75] using the following form "YYYY-MM-DDThh:mm:ss" where:
    - YYYY indicates the year.
    - MM indicates the month.
    - DD indicates the day.
    - T indicates the start of the required time section.
    - hh indicates the hour.

- mm indicates the minute.
- ss indicates the second.
- Final_Download_Datetime: Date and time, using the same format than the previous field, when the right to download or access to the information expires.
- Access_Requirements: Set of optional requirements that must be fulfilled to have access to referenced data file in the Portable Device. It is optional and follows the same structure as “Download requirements”.

Finally, Monitoring Application is a prototype used to access to the Monitoring System information from user’s portable device. This application requests access to the resource to the user’s JC that checks if the user fulfils all the access requirements

4.4.1.2 Functional Test

This test covers the life cycle of a resource from its integration in the Access Control System to its download (both described in Figure 20) and its visualization in the portable device (described in Figure 21). An operator of the Monitoring System (acting as owner of the information) selects the resource (1) to be shared and defines its download and access requirements in a XML metadata file (2) and exports both files to the shared SFTP folder (3). SP, who is monitoring the shared SFTP folder, downloads both files (4) and checks their integrity (5). Then, SP generates an XACML (language used by IdP) download security policy (6) and an access security policy according to the structure defined in section 3.2.3 Security Policy (language used by JC) (7) using the content of the metadata file. After that, the download security policy is sent by SP to IdP using its Entitlement Policy Admin Service[76] (8). Then, SP generates a symmetric key (9), ciphers the resource and the access security policy with it (10) and publish both files encrypted in the SP web application (11). Then, the user downloads the published files and the symmetric key used to cipher them encrypted with its JC public key following the process defined in section 4.3.2.3 (12) that checks that the user has the necessary permissions to do so. Finally, user visualizes the mission information in the portable device following the process defined in section 4.3.2.4 (that checks that the user has the necessary permissions to do so) and represented for the prototype in Figure 21 (13).

Figure 20: Monitoring Application prototype content protection and download

Figure 21: Monitoring Application prototype state diagram

To test the deployed prototype, a set of users were created and a set of images were uploaded and visualized.

The defined users were:

- User A
  - Security Clearance: Confidential
  - Company: Spanish Army
  - Department: Tanks
  - PIN: No
- User B
  - Security Clearance: Top Secret
  - Company: Spanish Army
  - Department: Submarines
  - PIN: Yes
- User C
  - Security Clearance: Secret
  - Company: France Army
  - Department: Tanks
  - PIN: No

The used resources had the following security policies:

- File 1:
  - Classification level: Confidential
  - Company: Spanish Army
  - Department: Tanks
  - User authentication: NO
  - Applications: Monitoring Application digital signature
  - Download Requirements: NO

- Access Requirements: NO
- File 2:
  - Classification level: Confidential
  - Company: Spanish Army
  - User authentication: NO
  - Applications: Monitoring Application digital signature
  - Download Requirements: NO
  - Access Requirements: NO
- File 3:
  - Classification level: Secret
  - Company: Spanish Army
  - Department: Tanks
  - User authentication: YES
  - Applications: Monitoring Application digital signature
  - Download Requirements: NO
  - Access Requirements: NO
- File 4:
  - Classification level: Confidential
  - Company: France Army
  - Department: Tanks
  - User authentication: NO
  - Applications: Monitoring Application digital signature
  - Download Requirements:
    - Initial Download Datetime: 2019-12-16T15:00:00
    - Final Download Datetime: 2019-12-16T16:00:00
  - Access Requirements:

- Initial Access Datetime: 2019-12-17T15:00:00
- Final Access Datetime: 2019-12-17T16:00:00

The expected results are summarized in Table 3:

	User A	User B	User C
File 1	X		
File 2	X	X	
File 3		X	
File 4			X (only if access and download time requirements are fulfilled)

Table 3: Monitoring System expected test results

Results of the test matched with Table 3 meaning that the prototype worked as expected.

4.4.2 Command and Control System Prototype

4.4.2.1 Architecture

The deployment of this prototype has been done according to the architecture described in Figure 22. In it, they are represented all the elements of a GCS included in the prototype and how they match the GCS global architecture described in section 1.1.4.

Figure 22: C&C System Prototype Architecture⁸

A few new elements have been added to this architecture in comparison with the previous prototype: A DDS Publisher in the traditional GCS and DDS Subscriber in the Portable Device have been added while the Web Application deployed in the SP and the Application used in the Portable device change according to the new tested functionality. Finally, an UAV has been also included, being the final objective of this prototype to prove that a mission can be piloted in a UAV remotely with a portable device in a secure way using our proposed model.

In this scenario the concept of access and download policies will be slightly different from the general case described in our model (and the use given to them in the previously presented prototype). The download policies will be the policies analysed before allowing a pilot to download a mission data (same functionality as in the general case), but the access policies will not only be the policies evaluated before opening the mission in the C&C Application but also before executing any command to pilot the UAV. For that purpose, several files will be created:

- A Mission Data File including all the data about the mission.
- A download and an access policy related to the mission data file that indicate the restrictions to download the file and then to open it using the C&C Application.

⁸ Cryptographic Chip icon licensed under CC BY. <http://www.clker.com/clipart-smart-card-chip-only-.html>

- A Mission ID file including only the ID number of the mission. The objective of this file is to reduce computational cost when checking in JC if an operation over the UAV is permitted. During phase of our access control protocol described in section 3.2.4 JC checks the integrity and the authenticity of the file as well as if the security policy actually references this information and, finally, decrypts it. Since in this case we do not want access to any information but to check if an operation is permitted or not we use an smaller file than the mission data file to reduce the cost of decrypting it. This file includes the mission ID to prevent a malicious user from bypassing the access control passing a policy related to another mission.
- A download policy associated to the mission ID file.
- Several access control policies, one for each possible operation in the UAV, all of them linked to the mission ID file.

4.4.2.2 Functional Test

This test covers the life cycle of a mission from its integration in the Access Control System to piloting it using a UAV.

The first phases of the process from the mission creation to its publication in the SP (phases 1 to 10) are identical to the described in the previous prototype changing only the number of files involved (two files, 2 download policies and $1 + \text{number of operations}$ access policies in this case). After that, things change. When it is time to start a mission, GCS broadcasts the mission ID signed with its Private Key using DDS (that is the way in a traditional GCS to indicate the mission kick off). C&C Application in the portable device receives the signed mission ID and checks that its signature is valid. Then, starts the download process of all the mission's associated files and the symmetric key used to cipher them encrypted with its JC public key following the process defined in section 4.3.2.3 that controls that the pilot using the application has the necessary permissions to do so. After that, C&C application opens the mission after checking that the pilot has the necessary permissions (following the process described in section 4.3.2.4) to join it. Once within the mission, any operation the pilot wants to perform over the UAV will be checked first against its specific policy before being performed according to the process described in section 3.2.4.

To test this prototype a single pilot and a single mission were defined (as the correct operation of the Download policies was already tested in the previous prototype):

- Pilot A
  - Security Clearance: Confidential
  - Company: Spanish Army
  - Department: UAV
  - PIN: No
- Mission 1:
  - Classification level: Confidential
  - Company: Spanish Army
  - Department: UAV
  - User authentication: YES
  - Applications: C&C Application digital signature
  - Download Requirements: NO
  - Access Requirements: NO

Also, to control the operations for piloting the UAV in this mission several security policies were defined:

- Take Off:
  - Classification level: Confidential
  - Company: Spanish Army
  - Department: UAV
  - User authentication: NO
  - Applications: C&C Application digital signature
  - Download Requirements: NO
  - Access Requirements: NO
- Landing:
  - Classification level: Confidential
  - Company: Spanish Army

- Department: UAV
- User authentication: NO
- Applications: C&C Application digital signature
- Download Requirements: NO
- Access Requirements: NO
- Flight Direction:
  - Classification level: Confidential
  - Company: Spanish Army
  - Department: UAV
  - User authentication: NO
  - Applications: C&C Application digital signature
  - Download Requirements: NO
  - Access Requirements: NO
- Photo:
  - Classification level: Confidential
  - Company: Spanish Army
  - Department: UAV
  - User authentication: NO
  - Applications: C&C Application digital signature
  - Download Requirements: NO
  - Access Requirements: NO
- Fire:
  - Classification level: Secret
  - Company: Spanish Army
  - Department: Bombers
  - User authentication: NO

- Applications: C&C Application digital signature
- Download Requirements: NO
- Access Requirements: NO

Results of the test matched the expected results. Pilot A was able to take off and land the UAV. He was also able to take photos from the UAV, but not to fire to any target.

4.5 Conclusion

This chapter merges the authentication (Chapter 2) and authorization (Chapter 3) proposals to provide a complete access control system for portable devices. To do so, it defines a global architecture that covers the whole life cycle of the resources since their inclusion in the system until their (user's) consumption. The proposed system covers several gaps between the previously defined protocols such as users enrolment, security policy definition or download access control; providing several benefits:

- Improving the access control to resources on portable devices that not only prevents against unauthorized access but also limits the actions that an authorized user can perform once he has accessed to it.
- Improving businesses security measures against information leaks using encryption and security policies to ensure that information is only available, for example, within the owner facilities and by certain people based on their security level or department.
- Preventing information leaks for BYOD. Each resource displayed on a employee's device will never be stored in clear text within its memory. Encryption, JC and security policies will ensure the appropriate use of information.
- Safe terminal sharing. Sensitive resources stored in shared devices remain safe as possession of the associated JC, knowing its PIN and meeting the access requirements specified in their security policy are necessary to access them.
- Secure key storage using a JC.
- Active protection of information during access. JC is responsible of safely decrypting resources while the reliable application ensures that the access security policy restrictions are not bypassed.

- Definition of different security levels according to the sensitivity of the information processed.
- Multifactor authentication and authorization: Java Card, PIN, reliable portable device and other factors that can defined in the security policy (such as time or user's department) can be used as source of authentication and authorization.

Finally, the proposed access control system was successfully tested using two prototypes for an Airbus GCS demonstrator: the Monitoring System and the Command and Control System.

5

Modelling XACML Security Policies Using Graph Databases

5.1 Introduction	66
5.2 Related Work and Technologies	68
5.2.1 Access Control.....	68
5.2.2 XACML.....	68
5.2.3 Graph Databases	69
5.3 Proposed Access Control System	69
5.3.1 Meta Model.....	70
5.3.2 XAML Graph Model	70
5.4 Evaluation	72
5.5 Conclusion	73

5.1 Introduction

The eXtensible Access Control Markup Language (XACML) [21] is a widely used, XML-based language for defining access control policies in attribute-based access control (ABAC) [22]. Approved by OASIS, it was developed to standardize access control by providing common terminology and interoperability among multiple ABAC implementations. XACML defines an access control model in which a set of policies is used to make an access decision based on subject attributes, resource attributes, and current environmental conditions.

Figure 23 shows an XACML request flow diagram. When a subject wants to perform an action on a resource, (1) the subject submits an access request to the policy decision point (PDP). This user request (2) is translated into XACML by the policy enforcement point (PEP) and is sent to the PDP, which checks the request against its stored policies to make an access decision. If the PDP needs to recover the attributes of an external entity such as a user database, (3) it uses the

policy information point (PIP) (4) to get them. Finally, (5) the PDP sends the access decision to the PEP, which (6) provides access to the resource or not based on this answer, (7) reporting the result to the user.

Figure 23: XACML request flow diagram

As the number of rules in the policy increases, the PDP becomes a performance bottleneck for the system. To be able to process numerous requests simultaneously, an efficient implementation of the evaluation engine is necessary.

The existing classical implementations of the policy evaluation engine (see bit.ly/2xNIXdT and bit.ly/2fY0S76) perform policy matching using brute force, which is a costly operation in terms of performance when the number of users and resources is large. In [77], a performance analysis of classical PDP implementations was done that showed that performance is poor when the number of targets and conditions increases. With these limitations in mind, other approaches [25] [26] have emerged that improve PDP performance by adapting security policies to decision trees. Unfortunately, these performance improvements come with an associated cost: a limitation on the number of functions that such approaches could implement.

Here, we propose a solution to reduce the computational complexity of evaluating XACML policies by modeling them using a graph database while maintaining all functionalities. By implementing the policies in a graph data structure, we can optimize the evaluation engine's performance and obtain a performance gain of several orders of magnitude compared to traditional XACML implementations (graph databases store data as relationships between records, which enables recovering them directly without analyzing all system policies [78]).

Graph databases also scale well with increases in the number of access control policies, and their performance stays constant with growth in data. Moreover, due to the power of the engines and connectors that graph databases offer, we can ensure that the solution offers all the functions XACML defines.

5.2 Related Work and Technologies

In this section, we describe the most significant related works and technologies used in our solution.

5.2.1 Access Control

Access control [79] is a process by which selective restrictions are placed on access to a resource based on a security policy that can be categorized as discretionary or mandatory. Discretionary access control (DAC) [80] is a model in which access to objects (resources) is restricted based on the identity of the subject (human user or a process that wants access to the resource) or groups to which this subject belongs. A subject that has access to a resource can enable another entity to access the same resource. Alternatively, mandatory access control (MAC) [81] is an access control model in which access is controlled based on comparing objects' security labels with security clearances applicable to the subject. In this model, a subject that has access to a resource cannot enable another subject to access that resource.

These models can be enforced in different ways, the most common being role-based access control (RBAC) and ABAC. In RBAC [82], access to a resource is regulated by comparing the roles that users have in an organization with rules that describe what access is allowed to users in that role. ABAC defines permissions based on both object and subject properties as well as current environmental conditions.

5.2.2 XACML

XACML defines an authorization framework composed of subsystems, also called actors, to define and evaluate policies. The policy administration point (PAP) is a repository that creates and stores policies. Its main function is to provide policies to the PDP. The PEP is an interface within the environment that receives requests for access authorization. With the help of the PDP, it prepares a response to allow or deny access to a resource. The PDP is responsible for the decision. It collects all the information from the other actors and, after evaluating the

different access policies that exist, determines whether the request should be approved. Sometimes, to establish a correct decision about the request, it is necessary to find information from other sources. The PIP lets the PDP get information from other entities.

The following elements are used in policy storage:

- Policy: a set of rules that is associated with a service. The PDP establishes an algorithm to combine the rules.
- Policy set: a set of policies associated with a service. The PDP decides which policies can be applied and therefore which rules should be analyzed. It must also establish a policy mix algorithm.
- Rule: a minimum unit with a unique identifier in which the attributes required are established to provide access or not to the service.
- Target: a set of attributes used to specify the rule objective. Within a target, subject represents the subject making the request for access; resource is the service that the user requests; action determines the action that the subject wants to execute on approval; and environment is an attribute that adds more data to the request.

5.2.3 Graph Databases

Graph databases [83] are a type of NoSQL database. They are based on graph theory and use nodes, properties, and edges to represent stored data. They are useful for storing information in models with several relationships, such as networks and social connections, because they allow quick retrieval of hierarchical data.

There are many implementations of graph databases on the market. However, according to a survey in New Trends in Database and Information Systems II [84], Neo4j is the database that offers the best performance [85]. Therefore, it is the database we selected for our prototype.

5.3 Proposed Access Control System

We aim to provide a way to model XACML policies within a graph database. This model will allow us to achieve a several-orders-of-magnitude improvement in the evaluation engine's performance while maintaining all XACML functionalities. Unlike with traditional approaches, modeling the policies within a graph database allows the evaluation engine to navigate through

the nodes and reach the access decision at a constant rate. This compares favourably to traditional approaches that use brute force or many SQL joins in a relational database.

We created this model from scratch with the intention of defining security policies using the graph model. However, translating it from existing XACML policies is also possible. This process can be easily automatized using a tool we discuss later, in the evaluation section.

During the rest of this section, we describe the models needed to define an XACML policy in a graph database.

5.3.1 Meta Model

This model includes the graph database elements as nodes. The relationships among nodes describe the behavior between them. We use the meta model to represent XACML as a graph model, which will be the base for defining the XACML policies in a graph database. Figure 24 represents the elements necessary to define the XACML model. The meta model ensures that every relation defined in our database will have an origin and a destination node. It also ensures that a node is related to another node through a relation node. Finally, it allows that a node and a relation could have properties.

Figure 24: Meta Model

5.3.2 XAML Graph Model

XACML policies are grouped in sets. If there is more than one policy that fulfills a request, a combining algorithm is applied to all the policies that have been selected. Each policy applies to a specific target that is defined via the aforementioned subject, resource, action, and environment parameters, where each parameter could have more than one value. For instance, the policy could apply to two targets. In the same way, it is not necessary to define all the parameters—for example, the policy could apply to every action executed over a target. The

policy effect is based on the evaluation of a set of rules; as we've described, if there is more than one rule that fulfills a request, a combining algorithm is applied to all the rules.

When the evaluation process ends, we get an effect: if the request satisfies all the requirements, access is permitted; otherwise, access is denied. Figure 25 represents this XACML logic as a graph database model that enables modeling XACML policies in graph databases.

Figure 25: Policy Elements

The nodes and their relationships in the figure follow XACML logic. Starting from the top-left corner, a PolicySet contains (1) a set of policies. In the same way, a policy is (2) associated with a specific target. This target definition is (3) defined by the subject, the resource, the action, and the environment. These attributes allow the policy engine to determine if a policy is applicable for a specific request.

To evaluate applicable requests, a policy also (4) defines rules whose (5) effect is to permit or deny a specific request. Rules are (6) based on conditions that at the same time (7) have attributes that are (8) analyzed with functions according to specific values.

Finally, policies and rules (9) specify the particular combining algorithm to be applied when more than one policy or rule applies to a request at the same time. Combining algorithms define

how to prioritize the results when different results are obtained after evaluating all the conditions associated with a rule or policy.

The global result obtained from a policy is based on the combination algorithm used on it.

5.4 Evaluation

To validate our solution, we modeled an XACML policy and created a prototype to manage it. Using the relationship between the policy elements defined in Figure 25, the XACML schema described next was modeled to obtain a graph (Figure 26). Numbered labels have been added to the figure for better understanding.

Figure 26: Graph Model Example

The XACML (1) policy is associated with (2) the target defined by (3) resource File 1 and (4) the action Read. It defines (5) a rule (Rule 1) that (6) permits the specified action based on (7) two conditions: (8) a security level (9) greater than or equal to (10) 3 and (11) the membership to the (12) finance (13) department. Also, (14) a fall-through rule (Rule 2) is defined to (15) deny access when Rule 1 is not satisfied. Finally, the policy uses (16) a deny-overrides combination algorithm. Each time a user requests access to the resource (File 1), the request is evaluated using the graph in Figure 26, and an access decision is obtained.

The prototype of the proposed system was modeled using a Neo4j database and an evaluation module. The database includes both the graph described in Figure 4 and an additional graph that has been modeled to store the list of users and their attributes. Neo4j Cypher queries were used to evaluate requests formatted as (user, resource, action). A first cipher query is used to obtain user attributes from the user's graph. Then, a second cipher query is used to get the rules that are applicable for the target (resource and action) of the request.

The evaluation module has been developed in Java using the Neo4j Java Driver. It has the capacity to evaluate the rules. To do so, it first extracts the functions from the rules retrieved from the second query (stored as strings) and translates them into executable code (comparison operators). Then, it applies the comparison operator to the results of the two queries to obtain the access decision, taking into account the combining algorithms when necessary.

5.5 Conclusion

Our XACML access control model based on graph databases drastically improves performance in comparison to existing classic solutions while maintaining all XACML functionalities; something that, as far as we know, has not been done before. It allows us to use the capabilities offered by this type of database in our field of research, specifically using the performance this database provides to offer an access control solution that could be implemented in real-time environments.

The next step of this project is extending the prototype to offer a full PDP. After that, a detailed performance analysis over every policy operation (create, edit, publish, and evaluate) will be performed to validate the result obtained with the prototype.

6

Hybrid XACML-Graph Database Policy Decision Point

6.1 Introduction	74
6.2 Related Work and Technologies	75
6.2.1 WSO2 Balana	75
6.2.2 NEO4J.....	75
6.3 Architecture	75
6.4 Prototype	77
6.4.1 Example	79
6.5 Evaluation	80
6.5.1 Conformance Evaluation	81
6.5.2 Performance Evaluation.....	81
6.6 Conclusion	82

6.1 Introduction

Previous chapter uses a graph database-based solution to model and validate XACML security policies. The presented solution improves performance while maintaining all XACML functionalities. However, its architecture is not compatible with classical XACML implementations. In some scenarios, e.g. production environments where many services using a classical XACML implementation are already running, changing the architecture needed for the previously proposed solution may not be an option. For such scenarios, in this chapter we define a hybrid approach compatible with classical XACML implementations that minimizes the architecture modifications while still improving the system performance using a graph database.

This new approach extends the PDP module within the XACML architecture by including a graph database that improves performance by filtering security policies prior to the request evaluation while keeping unchanged the request flow from a user point of view.

6.2 Related Work and Technologies

In this section, we describe the most significant related works and technologies that have been added to this hybrid proposal. This description is an extension of the technologies presented in the previous chapter that are also related to this solution.

6.2.1 WSO2 Balana

The WSO2 Balana library [86] is an open source implementation of the XACML protocol built on Sun's XACML Implementation[87]. It supports all the XACML versions: 1.0, 1.1, 2.0 and 3.0 and has been developed with Java.

6.2.2 NEO4J

NEO4J [88] is a graph database that stores the information in a related way, creating a direct graph between the nodes and the relations among them. The nodes can be labelled, and these labels can be used to narrow queries. It allows to change elements relations once the system has been created. Based on those properties, graph databases are ideal to respond to complex and valuable questions in real time.

6.3 Architecture

The proposed hybrid solution extends the PDP module adding a graph database that is used to filter security policies prior to its evaluation. In this way, the graph database is used to identify policies relevant to the incoming Authorization Requests and only these policies will be evaluated by the PDP. Figure 27 shows the elements of this hybrid system:

- Policy Enforcement Point (PEP): Is an interface within the environment that is responsible for receiving requests for access authorization. With the help of the Policy Decision Point, it prepares a response to allow or deny the access to the Resources.

- Policy Decision Point (PDP): Is the point responsible of the decision. This actor collects all the information from the other actors and after evaluation of the different policies of access that exist, determines if the request should be approved or not.
- Policy Information Point (PIP): Sometimes, to establish a correct decision of the request, it is necessary to find information in other sources. This actor allows getting the information from other entities.
- Graph Module: It translates the authorization request in a graph database query. Based on the results of the query, it activates the selected security policies in the PDP.

XACML Request Flow Diagram is also represented in Figure 27. When a subject wants to perform an action on a resource, (1) the subject submits an access request. This user request (2) is translated into XACML by the policy enforcement point (PEP) and is sent to the PDP. PDP forwards (3) the XACML requests to the Graph Module that is used to connect to the Graph database. This module breaks down these requests into their primitive entities (subject, resource, action, environment) and identifies policies relevant to these entities. The matched policies are then activated (4) in the PDP for evaluation. This allows us to limit the number of policies that need to be loaded and evaluated for each Access Request. Then, the PDP checks the request against these policies to make an access decision. If the PDP needs to recover the attributes of an external entity such as a user database, (5) it uses the policy information point (PIP) (6) to get them. Finally, (7) the PDP sends the access decision to the PEP, which (8) provides access to the resource or not based on this answer, (9) reporting the result to the user.

Figure 27: Hybrid XACML – Graph Database Architecture

As a previous step to work with the system, it is necessary to populate the graph database with the current security policies. This process reads all the existing security policies in the Policy Store and create a mirror in the Graph database. Later, when a new security policy is added to the system using the Policy Administration Point (PAP), it should be created both in the Policy Store and in the Graph database.

The graph database schema used by our solution is shown in Figure 28. Each policy is broken down into its primitive components: Subject, Resource, Action, and Environment and these components are stored as graph nodes in the database. The attributes of the components are reflected as node attributes. An additional node is created to store the policy Policy Id. The policy components are connected to their policy node through a relationship. In this Hybrid Implementation, we do not require to store the effect of the policy (Permit or Deny) or the Rule Combining Algorithm associated with the policy (as we did in the previous chapter), because it will be evaluated later by the PDP module with the selected policies.

Figure 28: *Graph Database Schema*

6.4 Prototype

To test the performance improvements of our solution we have deployed a prototype. This prototype focuses in the modified part of the architecture: PDP module with a graph database. The selected PDP implementation has been WSO2 Balana and NEO4J graph database.

In this prototype WSO2 Balana core has been modified to include a graph module that filters security policies, based on the Authorization Request data, using the Graph Database prior to its evaluation. Figure 29 illustrates this process:

1. User sends an authorization request to WSO2 Balana that contains the subject identification, the resource to be accessed, the action to be performed and the environment.
2. WSO2 Balana core sends the Authorization Request parameters to the Graph module.
3. Graph module sends a query to the NEO4J looking for the policy IDs of the applicable security policies.
4. NEO4J returns the policy IDs of every applicable security policy according to the parameters received within the query.
5. Graph module activates all the applicable security policies in the WSO2 Balana core.
6. WSO2 Balana core evaluates the security policies that are activated and, after that, deactivated them for the next request.
7. WSO2 Balana core sends to the user the result of the Authorization Request.

Figure 29: Authorization Request Flow

6.4.1 Example

For a better illustration of this process an example of the prototype application is provided below. Figure 30 represents a policy (taken from [89]) containing a rule that allows the user Ann Hunt (subject) to read or modify (actions) Ina Bruce's medical records (resource).

```
<Policy olicyId="policy1" RuleCombiningAlgId="deny-overrides">
  <Rule RuleId="rule1" Effect="Permit">
    <Description>
      Ann Hunt can read or write Ina Bruce's medical record.
    </Description>
    <Target>

      <Subjects>
        <Subject>
          <SubjectMatch MatchId="string-equal">
            <AttributeValue DataType="string">Ann Hunt</AttributeValue>
            <SubjectAttributeDesignator AttributeId="subject-id"/>
          </SubjectMatch>
        </Subject>
      </Subjects>

      <Resources>
        <Resource>
          <ResourceMatch MatchId="anyURI-equal">
            <AttributeValue DataType="anyURI">http://medico.com/InaBruce</AttributeValue>
            <ResourceAttributeDesignator AttributeId="resource-id"/>
          </ResourceMatch>
        </Resource>
      </Resources>

      <Actions>
        <Action>
          <ActionMatch MatchId="string-equal">
            <AttributeValue DataType="string">read</AttributeValue>
            <ActionAttributeDesignator AttributeId="action-id"/>
          </ActionMatch>
        </Action>
        <Action>
          <ActionMatch MatchId="string-equal">
            <AttributeValue DataType="string">write</AttributeValue>
            <ActionAttributeDesignator AttributeId="action-id"/>
          </ActionMatch>
        </Action>
      </Actions>
    </Target>
  </Rule>
</Policy>
```

Figure 30: XACML Policy example

The graph database will break down this policy into five nodes as shown in Figure 31.

Figure 31: Graph database representation of the XACML Security Policy

Figure 32: XACML Request example

When an access request (as the one shown in Figure 32) is submitted by ‘Ann Hunt’ to access the medical records of ‘Ina Bruce’, the following simple cypher query is used to identify policies relevant to the subject ‘Ann Hunt’:

```

1 MATCH (policy)-[:ASSOCIATED_WITH]->(target)-[:DEFINED_BY]->(subject)
2 WHERE subject.AttributeValue= 'Ann Hunt'
3 RETURN DISTINCT policy.filename

```

Finally, the results returned by the query are forwarded to WSO2 Balana Core for its evaluation.

6.5 Evaluation

To test the feasibility of this hybrid graph database model, a series of XACML conformance and performance tests were executed. The testbed used for evaluation was an Ubuntu laptop with the following hardware configurations: 2.5GHz Intel Core i7 processor, 16 GB RAM, 256MB SSD. Only the essential system services running during the execution of these tests.

6.5.1 Conformance Evaluation

In order to reinforce the applicability of our proposal we use the standard XACML conformance test provided by OASIS [89]. This suite consists of 230 different policies, the same number of different requests and verification responses. PDP was tested to accept the requests and policies as input and produce the given validation responses as output.

The graph model was successfully able to evaluate all the policies in the conformance test suite and arrive at the correct access result.

6.5.2 Performance Evaluation

A performance evaluation of the graph database model was also carried out to compare its performance with the ordinary WSO2 Balana XACML file-based model.

To gather a close proximity to the real-world performance of this model, the performance evaluation was carried out with five different test suites, which include an increasing number of policies. The policy set was also a combination of different types of policies, that were all a part of the OASIS Conformance Tests. One access requests was sent per policy of the suite to the PDP in sequence and response time in each batch was measured. Table 4 shows the results of the performance evaluation of traditional XACML file-based implementation versus the Hybrid Graph model.

	N° of policies	Time (seconds)		Performance Gain
		WSO2 Balana PDP	Hybrid Graph Model	
Test Suite 1	329	15.11	4.59	~70%
Test Suite 2	444	17.48	5.50	~70%
Test Suite 3	644	23.38	6.58	~70%
Test Suite 4	811	30.68	7.55	~75%
Test Suite 5	973	41.74	8.25	~80%

Table 4: Performance Test Results

For the Hybrid graph database model, the request processing time includes the time taken by the graph database to locate matching policies and the time taken by the PDP to evaluate these

policies. In the case of the WSO2 Balana PDP implementation, the request processing time is equal to the time required to load each policy into the memory and evaluate those policies.

In all test suites, a significant gain in performance was observed while using the Hybrid graph database model as shown in Table 4.

Figure 33: Performance Comparison

The performance comparison graph shown in Figure 33, shows that as the number of security policies increases, the graph database approach is significantly more efficient than Balana PDP. In the same way, Figure 34 represents that the difference in performance between WSO2 Balana PDP and the Hybrid Graph database approach increases exponentially with the linear increase in the number of security policies.

Figure 34: Difference in request processing times

6.6 Conclusion

This chapter presents our attempt to improve the performance of XACML implementations with minimal architectural changes (in comparison with the solution presented in the previous chapter) while also being able to offer a fully OASIS compliant implementation for all the functions provided by XACML. The results of the experiments conducted show the substantial

increase in performance achieved by the Hybrid Graph database approach over a traditional XACML PDP implementation such as WSO2 Balana, when the system requires a significant number of policies or simultaneous Access Requests.

7

Secure Blockchain-based Logging System for Distributed Environments

7.1 Introduction	84
7.2 Related Work and Technologies	87
7.2.1 Blockchain	87
7.3 Logging System	88
7.3.1 Requirements and Proposed Design Justification.....	88
7.3.2 Architecture	89
7.3.3 Smart Contracts (SC).....	90
7.3.4 System capabilities	92
7.4 Security evaluation	96
7.5 Prototype	97
7.5.1 7nodes network.....	97
7.5.2 Node services.....	97
7.5.3 Functional Testing	98
7.6 Conclusion	100

7.1 Introduction

Logging systems work with events received from many sources such as operating systems, applications, libraries, etc. These events are analysed, and the obtained results are displayed to the log operators with accounting purposes.

Log management process can be divided in five phases [90]: generating, transmitting, storing, analysing and disposing. Figure 35 describes the general process followed to complete every phase: an agent that is deployed (1) in every data source system is in charge of collecting (2) the logs and forwarding (3) them to a management server which stores (4) and analyses (5) the

received data from all the agents and shows (6) the results, such as new alerts, to the logging system operators. Finally, central management server disposes (7) the logs when they stop being needed.

Figure 35: Log Management Process

There are many logging solutions which follow this general architecture, such as Splunk [27], ELK [28], Graylog [29], etc., that can be integrated in a company system in two different ways:

- **On premises:** The management server is deployed and managed by the company in their own facilities. Its main advantage is always keeping the log data under control of the company. However, it requires a significant effort from the company to deploy the log management server architecture and to operate and maintain it.
- **Cloud:** The management server architecture is deployed and managed by the log service provider. The client has a web application to access them, but log data sets are being stored outside of the company facilities. In this case, company is losing the full control over its log data but reduces its deployment and operations effort.

Usually, in both options, the management server is not a single server to store, analyse and show the information, but it is a cluster of distributed nodes collaborating among them. The cluster contains multiple databases in which logs are replicated. Access control to this infrastructure is enforced using an extra layer which verifies the permissions of log operators before executing a request. However, system administrators can skip this control and have access to every data stored within the logging system. This is something generally acceptable when a single company is running its own logging system but, (1) what happens when several companies collaborating in a project want to create a common logging space? (2) Will they accept that system administrators have unlimited access to their data even if some of them are employees of other companies? (3) Are existing solutions flexible enough for distributed environments with very dynamic collaborating groups? The true is that traditional solutions for these distributed and collaborating scenarios have been always linked to third party deployments (1) that must be trusted by all participants (2) and where changes must be previously agreed among them, lacking the necessary flexibility for very dynamic scenarios (3).

With this problem in mind, Blockchain emerges as a possible solution for distributed logging systems because of its ability of defining immutable records of data generated and managed in a distributed environment without third trusted parties' involvement. Some previous researches in this line already exist, such as [30] [31] that propose storing a cryptographic digest of the security logs in the Bitcoin[91] network, [32] that defines a log storage model to be offered as a service, including functionalities to store and validate the logs, or [33] that presents a prototype of this system using the Ethereum[92] network. [34] also provides a blockchain based solution to assure the integrity of the logs, but using Hyperledger[93]. And [35] defines a custom blockchain to assure the immutability of the secure logs using the Practical Byzantine Fault Tolerance consensus [94]. All these proposed solutions define different options to record audit logs using Blockchain, but, unfortunately, none of them put attention to two of the key services that, according to NIST [90], a secure logging system must provide: access control and confidentiality. In all these blockchain based systems all the members of the network have access to all the logging information. Also, [30] [31] [33] would have to cope with the expenses of using Bitcoin and Ethereum, and their low throughput and high confirmation time (e.g. Bitcoin has a maximum throughput of 3–7 transactions per second). [34], on the other hand, only can manage a data source and a type of assets, being very restrictive in scenarios that could have multiple data sources and assets, while [35] has a high message complexity because of the consensus protocol selected, a high storage overhead because logs are replicated in every peer

and a weak link with the application which means that if the application itself is compromised, the system will not be able to detect it.

With the limitations of the existing solutions in mind, in this chapter we propose a Blockchain based logging system without third party dependencies that provides log immutability, confidentiality and access control. Our solution is based on Quorum [95] that has an acceptable transaction rate [96] and does not have any transaction fees associated.

7.2 Related Work and Technologies

In this section, we describe the most significant related works and technologies that have been added in this chapter.

7.2.1 Blockchain

Blockchain [97] can be defined as series of immutable data records that are distributed in a P2P network without central authorities. To achieve this, blockchain network use consensus algorithms which are mechanisms to get an agreement between all the network nodes using cryptography operations. Every node in the Blockchain network has access to the information registered in the network and its immutability is ensured by cryptography. The evolution of Blockchain allows to share not only data but also programs, known as smart contracts, that are stored in the Blockchain and executed by any of the nodes belonging to it, ensuring that their execution cannot be modified and preventing denial of service attacks. The access level to the different Blockchain networks allows to classify them in:

- Public: Participants do not need to request permission to anybody in order to participate in the network and every participant can vote. Blockchain transactions are public. Examples of this types of networks are Bitcoin [91] and Ethereum [92].
- Permissioned: Participants have to be identified and validated before they can participate in the network. Blockchain transactions are only opened to the nodes that are members of the network. Examples of this type of network are Hyperledger [93], Corda [98] or Quorum [95].
- Private: Similar to permissioned blockchain, but they allow only known nodes to participate in the network. They are also built with Hyperledger, Corda or Quorum.

7.2.1.1 Quorum

Quorum [95] is a permissioned Blockchain network based on Ethereum, a public-permissionless Blockchain. Its main difference with other Blockchain networks is that nodes can send private transactions. A private transaction is only sent to a group of nodes specified in the own transaction. In the first version of the network this was done using the Constellation [99] technology, but it was recently updated to Tessera[100]. Other important characteristic of Quorum is its performance. [96] shows a detailed analysis of the quorum performance that reaches a throughput of 600-900 private transactions per second thanks to the consensus algorithms used: Raft [101], based in Paxos [102], or Istanbul BFT [103].

7.3 Logging System

In this section we present a Quorum-based immutable logging system that suits to distributed environments without central authorities while still being able to provide other essential security services apart from immutability, confidentiality and access control, that other existing blockchain based logging systems cannot offer. The main functionalities of this system include:

- Log Immutability: Using blockchain as a registry of logs.
- Log Confidentiality and Node Access Control: Capacity of creating (encrypted) private transactions that only can be accessed by a subset of the network nodes. Logs can be marked as either public and private in the network. Logs registered as public are open to every node in the network, but logs inserted as private are encrypted and only accessible to a set of predefined nodes.
- Log User Access Control: Incorporates an access control layer enforced by the network itself to evaluate users' log access requests.

In the rest of this section we first analyse the functional and non-functional requirements and justify the design of the logging system and then, the proposed system architecture is presented followed by a description of the logging system capabilities.

7.3.1 Requirements and Proposed Design Justification

Several requirements arise for a logging system wanting to offer a secure distributed logging management platform without trusted third parties' dependencies:

1. Immutability of logs is a must.
2. A full distributed environment requires using a platform with no dependencies in any trusted third parties that offer a good performance and not have transaction fees associated.
3. Log information may be sensitive and require security mechanisms that allow sharing logs confidentially between a subset of the nodes.
4. In the same way, an access control system must be provided that allows defining the accesses to a set of data that are allowed and the ones that are not.

With this in mind, to satisfy requirement 1 and 2 we propose to use Quorum as a Blockchain platform which allow defining public and private transactions without trusted third parties dependencies, has an acceptable transaction rate and does not have any transaction fees associated. To satisfy requirement 3, we define logs structures (public and private) that will be deployed within the network. The private ones are encrypted and will define the list of nodes that will be able to decrypt them. Finally, requirement 4 is partially satisfied by the previously defined log structures that provide node access control. Also, we provide the system with a user access control to both public and private structures by defining a list of attributes (following the security policy attributes representation presented in chapter 3) that must be satisfied by any user request in order to be granted access.

7.3.2 Architecture

From a general point of view, the proposed system is a Quorum-based blockchain network that registers logs using public and private transactions and their access control attributes. Nodes have to be identified and validated before they can participate in the network and must deploy three different modules (Figure 36) to participate in the logging system:

- Administration module: Creates new log buckets (smart contract related structure described below that store a set of related logs), sets the security requirements to access them (using the security policy attributes representation described in chapter 3, section 3.2.3) and deploys them within the quorum network.
- Forwarder service: Records security logs inside a log bucket using private or public transactions in the network.

- Display module: Lists log buckets that can be accessed from the node and request access to them.

Figure 36: Blockchain-based Logging System Architecture

7.3.3 Smart Contracts (SC)

They represent the data structures and operations that are needed to register logs in the blockchain network. When a subset of nodes wants to create a private logging container they need to deploy their own log bucket contract. SC are also the responsible for enforcing the access control security policy defined for each log bucket.

Two different smart contracts are used in the system: a registry bucket and log buckets.

7.3.3.1 Registry Bucket

The registry bucket is a unique public smart contract that has a list of every log bucket registered in the network, including its address and bucket ID. It is used by nodes' display module to obtain a list of log buckets registered in the network.

The data structure of this smart contract is:

- Log References: Array of references to the log buckets registered in the network. Each reference has the following structure:
  - Address: Address of the log bucket.
  - Bucket ID: Bucket ID of the log bucket.

Also, this smart contract offers the following operations:

- Bucket Registration: Receives a log bucket ID and its address and adds them to the Log References array.
- Get Buckets: Returns a list with all the log buckets registered in the Log References array.

7.3.3.2 Log Bucket

A log bucket represents a container of logs associated with a specific subset of nodes. A log bucket is represented in the network with one smart contract that can be public or private. Public log buckets are accessible by all the members of the network while the private ones will be encrypted and only accessible by the subset of authorized nodes defined in the SC deployment.

The data structure of this kind of smart contract, either public or private, is:

- Bucket ID: Represents the unique ID of the bucket.
- Log Records: Array of logging records stored using the following structure:
  - Source: Identity of the system that has generated the logging record.
  - Timestamp: Date and time when the logging record was generated.
  - Logging Data: Logging message.

- Access control requirements: Access control attributes that must be fulfilled to access the log records included in the bucket. Its definition follows the structure described in chapter 3, section 3.2.3.

Also, these smart contracts, either public or private, offer the following operations:

- Constructor: Creates a new smart contract from a bucket ID and, optionally, its access control requirements.
- Registering log: Receives a bucket ID, a log data and the user attributes and, if source node and user fulfil the access control requirements of the bucket ID, records the log data in it.
- Access Log: Receives a bucket ID and the user attributes and, if source node and user fulfil the access control requirements of the bucket ID, provides access to the log data.
- Update AC: Permits to the owner of a Log Bucket changing its user access control requirements.

7.3.4 System capabilities

Once our access control architecture has been described, below we present its main capabilities: create log bucket, register log and access log.

7.3.4.1 Create Log Bucket

Process, Figure 37, starts with the definition of the bucket properties using the administration module interface. These properties include the bucket ID, type of smart contract (public or private), (for private SCs) the nodes that will have access to the smart contract and (optionally) its access control requirements (1). With this information, two operations start: the deployment of the SC (either public or private) in the network (2) that once completed returns the log bucket address (3) and its registration in the registry bucket (4).

Figure 37: Create Log Bucket

7.3.4.2 Register Log

Logs can be registered in both public and private buckets. All the nodes of the network can register logs in public buckets, while registering logs in private ones is restricted to the authorized nodes defined during the bucket creation. Also, if defined, user performing the operation must fulfil the bucket access control requirements for the operation to succeed.

The communication flow, Figure 38, performed for this operation is as follows:

1. A user of the system (application in this case) selects the addresses of the Bucket where it wants to register a log and sends a register message to the forwarder service including, apart from the bucket address, its attributes and the log content.

For a Public Log Bucket

2. Forwarder service receives the request and sends to the quorum node a register request to store the log data in a public bucket. Quorum node, on the other hand, forwards this request to the public bucket.
3. If defined, Bucket SC verifies that the application attributes fulfil the user access control policy of the bucket.
4. Bucket SC acknowledges the operation to the quorum node that passes the answer to the forwarder service.

For a Private Log Bucket

2. Forwarder service receives the request and sends to the quorum node a register request to store the log data in a private bucket.
3. Quorum network verifies that the node is an authorized member of the private bucket and, if so, forwards the request to the private bucket.
4. If defined, Bucket SC verifies that the application attributes fulfil the user access control policy of the bucket.
5. Bucket SC acknowledges the operation to the quorum node that passes the answer to the forwarder service.

Figure 38: Register public and private logs

7.3.4.3 Access Log

To access a log, a log operator selects the bucket where the log it wants to access is stored and then consults the registry bucket to get its address. Once in possession of the bucket address, it requests access to the bucket to the network. If the bucket is public, all the nodes of the network will have access to it, while if it is private the access will be restricted to the authorized nodes defined during the bucket creation. Also, if defined, user performing the operation must fulfil the bucket access control requirements for the operation to succeed.

The communication flow, Figure 39, performed for this operation is as follows:

1. Log operator requests the bucket list to the display module in the quorum node that forwards the request to the register bucket SC.
2. Register bucket SC returns a list with the reference of all the log buckets of the network.
3. Log operator requests to the display module access to the address of the select bucket including, within the request, its attributes.

For a Public Log Bucket

4. Display module receives the request and sends to the quorum node an access request to a public bucket. Quorum node, on the other hand, forwards this request to the public bucket.
5. If defined, Bucket SC verifies that the log operator attributes fulfil the user access control policy of the bucket.
6. Bucket SC returns the bucket logs to the quorum node that passes the answer to the display module.

For a Private Log Bucket

4. Display module receives the request and sends to the quorum node an access request to a private bucket.
5. Quorum network verifies that the node is an authorized member of the private bucket and, if so, forwards the request to the private bucket.
6. If defined, Bucket SC verifies that the log operator attributes fulfil the user access control policy of the bucket.
7. Bucket SC returns the bucket logs to the quorum node that passes the answer to the display module.

Figure 39: Access logs

7.4 Security evaluation

In this section we provide an evaluation of the security services (summarized in Figure 40) provided by our proposed logging system.

Figure 40: Security Services of our Logging System proposal

At the lower level, using a blockchain based network for storing the logs, provides them with immutability, i.e. data logs cannot be altered without the alteration being detected (integrity) neither can be modified the order in which they were registered in the network.

A medium layer of security is provided by Quorum. Quorum private transactions specify the group of destination nodes of a transaction encrypting all the log data for them (confidentiality). In this way, only the authorized nodes that belong to the group can access the log data (node access control).

Finally, at the top layer, an access control system is provided by the defined smart contracts to limit how users of the system can access to the logs (user access control). This access control system uses the security policy attribute representation presented in chapter 3 of this thesis.

7.5 Prototype

A prototype has been developed to validate that the proposed logging system is technically possible and that it provides all the intended functionalities. In this prototype, the quorum network was deployed using a 7nodes network [104] and the node services (display module, administration module and forwarder service) have been deployed as WEB services on a WSO2 Application Server.

7.5.1 7nodes network

7nodes network deploys a quorum network with seven nodes. This testing network allowed as to create public and private transactions among the nodes of the network. Some of the nodes of the network emulate collaborating companies sharing logs between them while other emulate companies of the network but that are not part of the collaborating group that shares logs.

7.5.2 Node services

In our prototype, node services have been emulated as WEB services deployed on a WSO2 Application Server. They connect with the quorum node using the Web3 JavaScript library [105]

7.5.2.1 Administration module

Web application (AdministrationServer.war) developed with Java 2 Platform, Enterprise Edition (J2EE) [65]. This application allows administrator users to create new log buckets and to define the access rules associated with them using the Create Log bucket operation (described in section 7.3.4.1).

7.5.2.2 Display module

Web application (DisplayServer.war) developed with J2EE. This application allows user to access log contents using the Access Log operation (described in section 7.3.4.3).

7.5.2.3 Forwarder Service

Web application (TestingApp.war) developed with J2EE. This application allows user to register log using the Register Log operation (described in section 7.3.4.2).

7.5.3 Functional Testing

During this functional testing (Figure 41) we intend to test the main functionalities of the proposed logging system using the deployed prototype. The tested functionalities have been:

1. Correct deployment of public and private buckets.
2. Correct registration of logs in public buckets.
3. Only authorized nodes can register logs in private buckets.
4. Any node can access public buckets.
5. Only authorized nodes can access logs in private buckets.
6. Only authorized users can access to the logs in a bucket and also, for private buckets, they must be operating from an authorized node.

For this test three different users were defined:

- Application 1: Holds a confidential security clearance and generate logs.
- Operator 1: Holds a confidential security clearance and accesses logs.
- Operator 2: Holds no security clearance and accesses logs.

And five of the nodes of the network were involved: Nodes 1, 2, 3, 4 and 5.

To test functionality 1, Node 1 uses the administration module to create two log buckets, one public (Bucket Pub) and the other private (Bucket Priv) with the following attributes:

- Only nodes 2 and 4 can access to the bucket.
- Only users with a security clearance of Confidential or higher can access to the bucket.

As a result of this test, two new buckets were created in the network, their addresses sent to Node 1 and their references registered in the Registry Bucket.

Figure 41: Functional Testing Use Cases

To test functionalities 2 and 3, the same application (Application 1 with confidential security clearance) was running in Nodes 2 and 3 using their forwarder service to register logs. Application 1 was able to register logs from both nodes in the public bucket Pub, but it was only able to register logs in the private bucket Priv from Node 2, because Node 3 is not authorized to access this bucket.

To test functionalities 4, 5 and 6, operators 1 and 2 tried to access to log information from different nodes of the network:

- From Node 4 operator 1 was able to access to the logs stored both in the public bucket Pub and the private bucket Priv because both the node and the user satisfied the defined access control requirements.

- From Node 5 operator 1 was able to access to the logs stored in the public bucket Pub but not to the ones stored in the private bucket Priv because Node 5 is not authorized to access this bucket.
- From Node 4 operator 2 was able to access to the logs stored in the public bucket Pub but not to the ones stored in the private bucket Priv because the user's security clearance did not satisfy the bucket access control requirements.

The actual results of these tests matched with the expected results, validating that the prototype functionalities were working correctly.

7.6 Conclusion

Secure logging for distributed environments is an active area of research because traditional logging solutions are not flexible enough to operate securely in these environments without the involvement of a trusted third party. Some authors have proposed using Blockchain as the solution for this problem due to the matching of the security services it provides and the security requirements identified. Unfortunately, none of the Blockchain proposed solutions put attention to two of the key services that, according to NIST [53], a secure logging system must provide: access control and confidentiality.

With these limitations in mind, in this chapter we have presented a Blockchain based logging system without third party dependencies that provides log immutability, confidentiality and access control (both at the node and the user level), as well as deploying a prototype to validate that the proposed logging system is technically possible and provides all the intended functionalities.

8

Conclusions and Future Research Lines

8.1 Conclusions	101
8.1.1 Towards Self-Authenticable Wearable Devices	103
8.1.2 Lightweight Access Control System for Wearable Devices.....	103
8.1.3 Access Control System for interoperable distributed architectures.....	103
8.1.4 Modelling XACML Security Policies Using Graph Databases.....	104
8.1.5 Hybrid XACML-Graph Database Policy Decision Point.....	104
8.1.6 Secure Blockchain-based Logging System for Distributed Environments	105
8.2 Future Research Lines	105

8.1 Conclusions

This thesis faces AAA open challenges for future heterogenous environments. In particular, we started focusing on authentication and authorization of portable devices that, due to their limited computational capacities, cannot employ traditional access control protocols to protect the information they manage. Within this area of research, we have proposed an authentication protocol (Chapter 2), an authorization protocol (Chapter 3) and a complete XACML access control architecture (Chapter 4) for decentralized and heterogenous environments. Then, we directed our research to improving the performance limitations of XACML protocol implementations identified during the access control system deployment. To this matter, we have proposed two Graph database-based solutions which highly improve the performance of XACML access control when the number of policies increase. One based on a pure Graph database model (Chapter 5) and the other based on a hybrid approach (Chapter 6) for scenarios where changing the architecture needed for the previously proposed solution may not be an option. After that, we moved on to accounting and presented a proposal to cover the gap for registering logs in a distributed environment in a flexible and secure way using Blockchain

(Chapter 7). All these proposals have been prototyped as well as either integrated in a GCS demonstrator (authentication, authorization and complete access control) or simulated their integration (graph-based databases and blockchain logging network).

Having a look again (this image was also presented in the introduction of this thesis) to the image (Figure 42) of the evolution of the GCS architecture, we can identify where the presented solutions could be applied to selected parts of a future GCS architecture to provide a complete AAA.

Figure 42: *Distributed GCS Architecture*

Below, we describe with more detail these contributions and the conclusions of the research conducted during this thesis.

8.1.1 Towards Self-Authenticable Wearable Devices

Wearable devices communicate among themselves, but they also need to communicate with remote entities through the Internet in order to share information. Given the sensitivity of the information handled, authentication is needed to allow data access only to authorized parties. However, the existing authentication solutions for wearable devices are limited to scenarios where direct communication between the authenticating parties is possible.

With this in mind, we proposed an authentication protocol that enables secure mutual end-to-end authentication between a wearable device and any other entity such as another wearable device, a personal device (mobile phone), a remote server, or a user's application. Our design uses a point-to-point authentication protocol (end-to-end authentication) regardless whether other intermediate devices are trusted or not. Finally, we presented a security evaluation of the proposed authentication protocol.

8.1.2 Lightweight Access Control System for Wearable Devices

Wearable devices are being used in areas such as health and military environments where, due to information sensitivity, access control is essential. In these environments, it is necessary to be able to control the way the information is handled by the wearable device. However, current security solutions for wearable devices focus mostly on protecting (using encryption) information access from unauthorized parties and do not cover the access control over the information when this is handled by the wearable device itself.

With this in mind, we proposed an access control system that, in addition to protecting the information from unauthorized access, also allows defining (using a security policy) and enforcing (using a hardware and software solution) a set of restrictions about how the information should be handled into the wearable device. Finally, we presented a security evaluation of the proposed access control system and a prototype that validates the solution.

8.1.3 Access Control System for interoperable distributed architectures

This solution combines the authentication (Chapter 2) and authorization (Chapter 3) proposals to provide a complete access control system for portable devices. The resulting access control

system is able to be integrated in a corporate environment and to validate it, two real prototypes were developed for a GCS, one of them for the Command and Control System and the other one for the Monitoring System.

8.1.4 Modelling XACML Security Policies Using Graph Databases

XACML is a precise and complete access control language that defines an architecture to deploy access control services in a fine-grained way. However, when the number and complexity of policies increases, it suffers from performance problems. This problem has been analyzed by the research community and the solutions proposed in the literature, based their idea in changing the way of storing the security policies. Many of them do that with the representation of the XACML policies in a graph data structure. However, these solutions increase the performance but decrease drastically the functionality offered.

With this in mind, we developed a way of modelling and storing XACML policies within a graph database. One of the most striking features of this databases is the high performance offered in the operations over the data. Therefore, if the security policies are included in this database, the performance property is assured automatically. Besides, due to the power of the engines and connectors offered by this database, we also can assure that we could offer all the functions defined by XACML. Finally, in order to show the viability of our proposal we have designed a prototype.

8.1.5 Hybrid XACML-Graph Database Policy Decision Point

Previous chapter uses a graph database-based solution to model and validate XACML security policies. However, in some scenarios where there are services using a classical XACML implementation, changing the architecture needed for the previously proposed solution may not be an option.

For such scenarios, we defined a hybrid approach compatible with classical XACML implementations that minimizes the architecture modifications while still improving the system performance using a graph database. Finally, we presented a performance evaluation of the proposed hybrid system and a prototype to show the viability of our proposal.

8.1.6 Secure Blockchain-based Logging System for Distributed Environments

Traditional logging solutions are not flexible enough for providing secure logging in distributed environments without the involvement a trusted third party. Some authors have proposed using Blockchain as the solution for this problem due to the matching of the security services Blockchain provides and the security requirements identified. Unfortunately, none of the Blockchain proposed solutions put attention to two of the key services that a secure logging system must provide: access control and confidentiality.

With these limitations in mind, we have presented a Blockchain based logging system without third party dependencies that provides log immutability, confidentiality and access control (both at the node and the user level), as well as deploying a prototype to validate that the proposed logging system is technically possible and provides all the intended functionalities.

8.2 Future Research Lines

During the course of this thesis we have faced the AAA problem for heterogenous and distributed environments from different angles and provide solutions for the main security gaps identified. To design a specific security solution for all the possible heterogenous and distributed scenarios is a topic too broad to be addressed in a single thesis. However, the research already conducted and the proposed solutions opens various ways of future work, such as:

- Evaluate the flexibility of our Lightweight Access Control System (presented in chapter 3) for even more restricted (than wearables) IoT devices, e.g. sensors, and analyze if it is flexible enough to be integrated within an IoT architecture. Our access control system needs to attach a secure token to the IoT device and, as we have seen in the prototypes of chapters 2 and 3, they required a NFC connection or a SD card slot respectively. Therefore, the first step should validate if IoT sensors can physically integrate the secure token and if their firmware can integrate a secure application to manage the secured resources according to the format defined by our Lightweight Access Control System. Then, it would also be necessary to evaluate if it makes sense to use the designed architecture with the SP and IdP, or it needs to be adapted according to the different layers of the IoT architectures [106].

- Extending our MLS access control system to provide a hybrid role-based access control and attribute-based access control. There are some proposals, such as [107], which combines these two access control models to build a hybrid access control protocol. Therefore, the objective of this research would be to evolve the proposed access control protocol of our Lightweight Access Control System to include information related with users roles, to define how it can be integrated in the defined architecture and how it can be processed.
- The prototype of the pure graph database model (presented in chapter 5) covers a subset (comparison operators) of the XACML operations. Therefore, it would be interesting to extend this prototype to cover every XACML operations and carrying out a detailed performance analysis to validate the results obtained with our prototype.
- The Hybrid XACML presented solution (chapter 6) has been prototyped using the Balana library included into the WSO2 Identity Server. Due to the good performance results obtained, we think that it would be interested to evaluate the integration of this solution within the official WSO2 Identity Server release.
- The registry bucket (presented in chapter 7) is very similar to a Domain Name System (DNS) because it stores registered buckets to allow log operators to locate them. Therefore, it would be very interesting to explore the integration of the existing DNS solutions adapted to the Blockchain environment, such as Ethereum Name Service [108], as an alternative to the Registry Bucket.
- An important area in which blockchain is being used is the digital identity, which is known as self-sovereign identity [109]. It is an evolution of previous identity systems because the user identity information is under his control because there is no need of trusted third party to manage that information as it is done by a blockchain network. Therefore, as our logging solution (presented in chapter 7) needs to receive user information to evaluate the security policy, it would be interesting to integrate a self-sovereign identity solution to manage user information.

References

- [1] R. Ballagas, M. Rohs, J. G. Sheridan, and J. Borchers, “Byod: Bring your own device,” in *Proceedings of the Workshop on Ubiquitous Display Environments, Ubicomp*, 2004, vol. 2004.
- [2] B. Sosinsky, *Cloud Computing Bible*. Indianapolis (NY): John Wiley & Sons, 2011.
- [3] S. Greengard, *The Internet of Things*. Cambridge (MA): MIT Press, 2015.
- [4] C. Arthur, “Naked celebrity hack: security experts focus on iCloud backup theory,” *The Guardian*, 01-Sep-2014 [Online]. Available: <https://www.theguardian.com/technology/2014/sep/01/naked-celebrity-hack-icloud-backup-jennifer-lawrence>. [Accessed: 29-Feb-2020]
- [5] J. C. Wong, “Former Google self-driving car engineer charged with theft of trade secrets,” *The Guardian*, 27-Aug-2019 [Online]. Available: <https://www.theguardian.com/technology/2019/aug/27/anthony-levandowski-google-trade-secrets-theft>. [Accessed: 29-Feb-2020]
- [6] N. Lord, “‘Insider’ IP Theft Suit Ends in Prison Time, Hefty Fines,” *Digital Guardian*, 16-Aug-2017 [Online]. Available: <https://digitalguardian.com/blog/insider-ip-theft-suit-ends-prison-time-hefty-fines>. [Accessed: 29-Feb-2020]
- [7] E. MacAskill, G. Dance, F. Cage, and G. Chen, “NSA files decoded: Edward Snowden’s surveillance revelations explained,” *the Guardian*, 01-Nov-2013 [Online]. Available: <http://www.theguardian.com/world/interactive/2013/nov/01/snowden-nsa-files-surveillance-revelations-decoded>. [Accessed: 29-Feb-2020]
- [8] M. Billingham and T. Starner, “Wearable devices: new ways to manage information,” *Computer*, vol. 32, no. 1, pp. 57–64, Jan. 1999, doi: 10.1109/2.738305.
- [9] J. M. Franklin *et al.*, “Mobile Device Security Corporate-Owned Personally-Enabled (COPE),” National Institute of Standards and Technology, NIST SPECIAL PUBLICATION (1800): 21A, 2019 [Online]. Available: <https://www.nccoe.nist.gov/sites/default/files/library/sp1800/mdse-nist-sp1800-21-draft.pdf>. [Accessed: 29-Feb-2020]
- [10] K. P. Valavanis and G. J. Vachtsevanos, *Handbook of Unmanned Aerial Vehicles*, Edición: 2015. New York: Springer, 2014.
- [11] C. Metz, “AAA protocols: authentication, authorization, and accounting for the Internet,” *IEEE Internet Computing*, vol. 3, no. 6, pp. 75–79, Nov. 1999, doi: 10.1109/4236.807015.
- [12] E. Rescorla, “The Transport Layer Security (TLS) Protocol Version 1.3,” RFC Editor, RFC 8446, Aug. 2018 [Online]. Available: <https://www.rfc-editor.org/info/rfc8446>. [Accessed: 29-Feb-2020]
- [13] G. Pujolle and P. Urien, “EAP Support in Smartcard,” RFC Draft 26, Jul. 2014 [Online]. Available: <https://tools.ietf.org/html/draft-urien-eap-smartcard-26>. [Accessed: 29-Feb-2020]

- [14] Zhaoyang Zhang, Honggang Wang, A. V. Vasilakos, and Hua Fang, "ECG-Cryptography and Authentication in Body Area Networks," *IEEE Trans. Inform. Technol. Biomed.*, vol. 16, no. 6, pp. 1070–1078, Nov. 2012, doi: 10.1109/TITB.2012.2206115.
- [15] M. Shin, "Secure Remote Health Monitoring with Unreliable Mobile Devices," *Journal of Biomedicine and Biotechnology*, vol. 2012, pp. 1–5, 2012, doi: 10.1155/2012/546021.
- [16] P. R. Burnap, I. Spasić, W. A. Gray, J. C. Hilton, O. F. Rana, and G. Elwyn, "Protecting patient privacy in distributed collaborative healthcare environments by retaining access control of shared information," in *2012 International Conference on Collaboration Technologies and Systems (CTS)*, 2012, pp. 490–497, doi: 10.1109/CTS.2012.6261095.
- [17] S. Alshehri and R. K. Raj, "Secure Access Control for Health Information Sharing Systems," in *2013 IEEE International Conference on Healthcare Informatics*, 2013, pp. 277–286, doi: 10.1109/ICHI.2013.40.
- [18] P. DeShazo, J. Butterworth, and P. Secinaro, "Tactical information sharing: A wearable one-way transfer (WOWT) device," in *2010 - MILCOM 2010 MILITARY COMMUNICATIONS CONFERENCE*, 2010, pp. 896–899, doi: 10.1109/MILCOM.2010.5679594.
- [19] J. Kim and S. Yoo, "Design of Real-time Vital-Sign Encryption Module for Wearable Personal Healthcare Device," *Journal of the Institute of Electronics and Information Engineers*, vol. 50, Feb. 2013, doi: 10.5573/ieek.2013.50.2.221.
- [20] Y.-L. Tan and R. K. B.-M. Goi, "Real-Time/Store-and-Forward Telemedicine with Patients' Data Protection by KP-ABE Encryption," in *The International Conference on E-Technologies and Business on the Web (EBW2013)*, 2013, pp. 79–84.
- [21] "eXtensible Access Control Markup Language (XACML) Version 3.0," 22-Jan-2013. [Online]. Available: <http://docs.oasis-open.org/xacml/3.0/xacml-3.0-core-spec-os-en.html>. [Accessed: 29-Feb-2020]
- [22] V. C. Hu *et al.*, "Guide to Attribute Based Access Control (ABAC) Definition and Considerations," National Institute of Standards and Technology, NIST SP 800-162, Jan. 2014 [Online]. Available: <http://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-162.pdf>. [Accessed: 29-Feb-2020]
- [23] "XACML Architecture - Identity Server 5.1.0 - WSO2 Documentation." [Online]. Available: <https://docs.wso2.com/display/IS510/XACML+Architecture>. [Accessed: 29-Feb-2020]
- [24] Axiomatics, "Dynamic Authorization for Business Applications." [Online]. Available: <https://www.axiomatics.com/product/dynamic-authorization-applications/>. [Accessed: 29-Feb-2020]
- [25] A. X. Liu, F. Chen, J. Hwang, and T. Xie, "Xengine: a fast and scalable XACML policy evaluation engine," in *ACM SIGMETRICS Performance Evaluation Review*, 2008, vol. 36, pp. 265–276.
- [26] S. Pina Ros, M. Lischka, and F. Gómez Mármol, "Graph-based XACML evaluation," in *Proceedings of the 17th ACM symposium on Access Control Models and Technologies*, 2012, pp. 83–92.
- [27] D. Carasso, "Exploring Splunk: search processing language (SPL) primer and cookbook," 2014 [Online]. Available: <https://www.splunk.com/pdfs/exploring-splunk.pdf>. [Accessed: 29-Feb-2020]
- [28] Y. Gupta and R. K. Gupta, *Mastering Elastic Stack*. Packt Publishing, 2017.

- [29] “GrayLog Documentation (Official Website).” [Online]. Available: <https://docs.graylog.org/en/3.2/>. [Accessed: 29-Feb-2020]
- [30] J. Cucurull and J. Puiggali, “Distributed Immutabilization of Secure Logs,” in *Security and Trust Management*, 2016, pp. 122–137.
- [31] A. Sutton and R. Samavi, “Blockchain enabled privacy audit logs,” in *International Semantic Web Conference*, 2017, pp. 645–660.
- [32] W. Pourmajidi and A. Miranskyy, “Logchain: Blockchain-assisted log storage,” in *2018 IEEE 11th International Conference on Cloud Computing (CLOUD)*, 2018, pp. 978–982, doi: 10.1109/CLOUD.2018.00150.
- [33] W. Pourmajidi, L. Zhang, J. Steinbacher, T. Erwin, and A. Miranskyy, “Immutable log storage as a service,” in *2019 IEEE/ACM 41st International Conference on Software Engineering: Companion Proceedings (ICSE-Companion)*, 2019, pp. 280–281.
- [34] H. Wang, D. Yang, N. Duan, Y. Guo, and L. Zhang, “Medusa: Blockchain Powered Log Storage System,” in *2018 IEEE 9th International Conference on Software Engineering and Service Science (ICSESS)*, 2018, pp. 518–521, doi: 10.1109/ICSESS.2018.8663935.
- [35] A. Ahmad, M. Saad, and A. Mohaisen, “Secure and transparent audit logs with BlockAudit,” *Journal of Network and Computer Applications*, vol. 145, 2019, doi: 10.1016/j.jnca.2019.102406.
- [36] K. P. Arnold, “The UAV Ground Control Station: Types, Components, Safety, Redundancy, and Future Applications,” *International Journal of Unmanned Systems Engineering.*, vol. 4, no. 1, pp. 37–50, 2016, doi: 10.14323/ijuseng.2016.4.
- [37] G. Pardo-Castellote, “OMG Data-Distribution Service: architectural overview,” in *23rd International Conference on Distributed Computing Systems Workshops, 2003. Proceedings.*, Providence, Rhode Island, USA, 2003, pp. 200–206, doi: 10.1109/ICDCSW.2003.1203555.
- [38] “Predator RQ-1 / MQ-1 / MQ-9 Reaper UAV,” *Airforce Technology*. [Online]. Available: <https://www.airforce-technology.com/projects/predator-uav/>. [Accessed: 29-Feb-2020]
- [39] K. Mansfield, T. Eveleigh, T. H. Holzer, and S. Sarkani, “Unmanned aerial vehicle smart device ground control station cyber security threat model,” in *2013 IEEE International Conference on Technologies for Homeland Security (HST)*, 2013, pp. 722–728, doi: 10.1109/THS.2013.6699093.
- [40] ABI Research, “Body Area Networks for Sports and Healthcare,” ABI Research, 2012.
- [41] Oracle, “Java Card Technology (Official website).” [Online]. Available: <https://www.oracle.com/technetwork/java/embedded/javacard/overview/index.html>. [Accessed: 29-Feb-2020]
- [42] “NFC forum (Official website).” [Online]. Available: <https://nfc-forum.org/>. [Accessed: 29-Feb-2020]
- [43] H. Wilcox, “Mobile Ticketing for Transport Markets. Airlines, Rail, Metro & Bus 2011-2015,” Juniper Research, 2011.
- [44] “Identification cards — Integrated circuit cards — Part 4: Organization, security and commands for interchange,” International Organization for Standardization, Standard ISO/IEC 7816-4:2005, 2005.
- [45] J. Torres, A. Izquierdo, and J. M. Sierra, “Advances in Network Smart Cards Authentication,” *Computer Networks*, vol. 51, no. 9, pp. 2249–2261, Jun. 2007, doi: 10.1016/j.comnet.2007.01.010.
- [46] W. Simpson, “The Point-to-Point Protocol (PPP),” RFC Editor, RFC1661, Jul. 1994 [Online]. Available: <https://www.rfc-editor.org/info/rfc1661>. [Accessed: 29-Feb-2020]

- [47] B. Aboba, L. Blunk, J. Vollbrecht, J. Carlson, and H. Levkowetz, “Extensible Authentication Protocol (EAP),” RFC Editor, RFC3748, Jun. 2004 [Online]. Available: <https://www.rfc-editor.org/info/rfc3748>. [Accessed: 29-Feb-2020]
- [48] F. Stajano and R. Anderson, “The Resurrecting Duckling: Security Issues for Ad-hoc Wireless Networks,” in *Security Protocols*, vol. 1796, Berlin, Heidelberg: Springer Berlin Heidelberg, 2000, pp. 172–182 [Online]. Available: http://link.springer.com/10.1007/10720107_24. [Accessed: 27-Feb-2020]
- [49] C. Huang and J. Kaps, “An Overview of Rfid Technology, Application, and Security/privacy Threats and Solutions,” in *George Mason University*, 2009.
- [50] J. Torres Márquez, “Nuevo marco de autenticación para tarjetas inteligentes en red. Aplicación al pago electrónico en entornos inalámbricos,” Doctoral Thesis, Universidad Carlos III de Madrid, 2006 [Online]. Available: <https://e-archivo.uc3m.es/handle/10016/781>. [Accessed: 29-Feb-2020]
- [51] “Identification cards -- Contactless integrated circuit cards -- Proximity cards - Part 4: Transmission protocol,” International Organization for Standardization, Standard ISO/IEC 14443-4:2008, 2008.
- [52] D. Cooper, S. Santesson, S. Farrell, S. Boeyen, R. Housley, and W. Polk, “Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile,” RFC Editor, RFC 5280, May 2008 [Online]. Available: <http://www.rfc-editor.org/rfc/rfc5280.txt>. [Accessed: 29-Feb-2020]
- [53] F. X. Standaert, “Introduction to Side-Channel Attacks,” in *Secure Integrated Circuits and Systems*, Boston, MA: Springer US, 2010, pp. 27–42.
- [54] J. Moar, “Smart Wearables: Competitor Strategies, Opportunities & Forecasts 2018-2022,” Juniper Research, 2018.
- [55] D. Tam, “Pilot of the future: U.S. Army gets wearable tech for the battlefield,” 08-Jul-2012. [Online]. Available: <https://www.cnet.com/news/pilot-of-the-future-u-s-army-gets-wearable-tech-for-the-battlefield/>. [Accessed: 29-Feb-2020]
- [56] D. Halperin, T. S. Heydt-Benjamin, K. Fu, T. Kohno, and W. H. Maisel, “Security and Privacy for Implantable Medical Devices,” *IEEE Pervasive Computing*, vol. 7, no. 1, pp. 30–39, Jan. 2008, doi: 10.1109/MPRV.2008.16.
- [57] Microsoft, “Microsoft Information Rights Management (Official website).” [Online]. Available: <https://docs.microsoft.com/en-us/exchange/information-rights-management-exchange-2013-help>. [Accessed: 29-Feb-2020]
- [58] Adobe, “Adobe Digital Rights Management (Official Website).” [Online]. Available: <https://www.adobe.com/marketing/experience-manager-assets/digital-rights-management.html>. [Accessed: 29-Feb-2020]
- [59] Nymi, “Nymi Wristband (Official website),” *Nymi*. [Online]. Available: <https://nyimi.com/home>. [Accessed: 29-Feb-2020]
- [60] D. E. Bell and L. J. LaPadula, “Secure computer systems: Mathematical foundations,” MITRE CORP, Bedford (Massachusetts), 1973.
- [61] K. J. Biba, “Integrity considerations for secure computer systems,” MITRE CORP, Bedford (Massachusetts), 1977.
- [62] P. Anjali Arora and Saibal Kumar Pal, “A Survey of Cryptanalytic Attacks on Lightweight Block Ciphers,” presented at the IRACST - International Journal of Computer Science and Information Technology & Security (IJCSITS), 2012, vol. 2.

- [63] F. P. Diez, D. S. Touceda, J. M. S. Camara, and S. Zeadally, "Toward self-authenticable wearable devices," *IEEE Wireless Communications*, vol. 22, no. 1, pp. 36–43, Feb. 2015, doi: 10.1109/MWC.2015.7054717.
- [64] P. Gallagher and A. Director, "Secure hash standard (shs)," *FIPS PUB*, vol. 180, p. 183, 1995.
- [65] J. Keogh, *J2EE: The complete Reference*. New York: McGraw-Hill Education, 2002.
- [66] A. Turner, "Kingwear 18 Smartwatch." [Online]. Available: <https://www.androids4seniors.com/android-device-reviews/kingwear-kw18-smartwatch-review/>. [Accessed: 29-Feb-2020]
- [67] GO Trust, "GO-Trust microSD Java," 2014.
- [68] N. Elenkov, *Android Security Internals: An In-Depth Guide to Android's Security Architecture*, Edición: 1. San Francisco: No Starch Press, 2014.
- [69] S. Vermeulen, *SELinux Cookbook*. Packt Publishing, 2014.
- [70] G. Blokdyk, *SAML 2.0: A Clear and Concise Reference*. 5STARCook, 2018.
- [71] WSO2, "WSO2 (Official website)." [Online]. Available: <https://wso2.com/>. [Accessed: 29-Feb-2020]
- [72] J. Galbraith and O. Saarenmaa, "SSH File Transfer Protocol," IETF Secretariat, Internet-Draft draft-ietf-secsh-filexfer-13, Jul. 2006 [Online]. Available: <http://www.ietf.org/internet-drafts/draft-ietf-secsh-filexfer-13.txt>. [Accessed: 29-Feb-2020]
- [73] E. R. Harold, *Xml Bible*, 3rd edition. Indianapolis: John Wiley & Sons, 2004.
- [74] NATO, "International Programs Security Handbook: Chapter 10." [Online]. Available: https://fas.org/sgp/library/ipshbook/Chap_10.html. [Accessed: 29-Feb-2020]
- [75] "ISO 8601 Date and time format," International Organization for Standardization, Standard ISO 8601, 2004.
- [76] WSO2, "Entitlement with APIs." [Online]. Available: <https://docs.wso2.com/display/IS530/Entitlement+with+APIs>. [Accessed: 29-Feb-2020]
- [77] F. Turkmen and B. Crispo, "Performance evaluation of XACML PDP implementations," in *Proceedings of the 2008 ACM workshop on Secure web services*, 2008, pp. 37–44 [Online]. Available: <http://dl.acm.org/citation.cfm?id=1456499>. [Accessed: 12-Apr-2017]
- [78] C. Vicknair, M. Macias, Z. Zhao, X. Nan, Y. Chen, and D. Wilkins, "A Comparison of a Graph Database and a Relational Database: A Data Provenance Perspective," in *Proceedings of the 48th Annual Southeast Regional Conference*, New York, NY, USA, 2010, pp. 42:1–42:6, doi: 10.1145/1900008.1900067.
- [79] R. Anderson, F. Stajano, and J.-H. Lee, "Security policies," in *Advances in Computers*, vol. 55, M. V. Zelkowitz, Ed. Elsevier, 2002, pp. 185–235.
- [80] National Computer Security Center (US)., "A Guide to Understanding Discretionary Access Control in Trusted Systems." National Computer Security Center, 1987 [Online]. Available: <https://fas.org/irp/nsa/rainbow/tg003.htm>. [Accessed: 29-Feb-2020]
- [81] B. Thuraisingham, "Mandatory Access Control," *Encyclopedia of Database Systems*, pp. 1684–1685, 2009, doi: 10.1007/978-0-387-39940-9_214.
- [82] R. S. Sandhu, E. J. Coyne, H. L. Feinstein, and C. E. Youman, "Role-Based Access Control Models," *Computer*, vol. 29, no. 2, pp. 38–47, Feb. 1996, doi: 10.1109/2.485845.
- [83] I. Robinson, J. Webber, and E. Eifrem, *Graph databases: new opportunities for connected data*, 2nd ed. Beijing: O'Reilly Media, 2015.

- [84] S. Beis, S. Papadopoulos, and Y. Kompatsiaris, “Benchmarking Graph Databases on the Problem of Community Detection,” in *New Trends in Database and Information Systems II*, Springer, Cham, 2015, pp. 3–14.
- [85] S. Raj, *Neo4j High Performance*. Packt Publishing, 2015.
- [86] WSO2, “WSO2 Balana Implementation (Official repository),” 2019. [Online]. Available: <https://github.com/wso2/balana>. [Accessed: 29-Feb-2020]
- [87] Sun, “Official XACML Implementation,” 2006. [Online]. Available: <http://sunxacml.sourceforge.net/>. [Accessed: 29-Feb-2020]
- [88] NEO4J, “Neo4j Graph Platform,” 2019. [Online]. Available: <https://neo4j.com/>
- [89] A. Kuketayev, “XACML Version 2.0 Conformance Tests,” 13-Oct-2005. [Online]. Available: <https://www.oasis-open.org/committees/download.php/14877/ConformanceTests.html>. [Accessed: 29-Feb-2020]
- [90] K. Kent and M. P. Souppaya, “Guide to computer security log management,” National Institute of Standards and Technology, NIST SP 800-92, 2006 [Online]. Available: <https://nvlpubs.nist.gov/nistpubs/Legacy/SP/nistspecialpublication800-92.pdf>. [Accessed: 29-Feb-2020]
- [91] S. Nakamoto, “Bitcoin: A Peer-to-Peer Electronic Cash System.” 2008 [Online]. Available: <https://bitcoin.org/bitcoin.pdf>
- [92] A. M. Antonopoulos and G. Wood, *Mastering Ethereum: Building Smart Contracts and Dapps*, Edición: 1st. Sebastopol, CA: O’Reilly UK Ltd., 2018.
- [93] N. Gaur, L. Desrosiers, P. Novotny, V. Ramakrishna, A. O’Dowd, and S. A. Baset, *Hands-On Blockchain with Hyperledger: Building decentralized applications with Hyperledger Fabric and Composer*. Birmingham Mumbai: Packt Publishing, 2018.
- [94] M. Castro and B. Liskov, “Practical Byzantine Fault Tolerance and Proactive Recovery,” *ACM Transactions on Computer Systems*, vol. 20, no. 4, pp. 398–461, Nov. 2002, doi: 10.1145/571637.571640.
- [95] JPMorgan, “Quorum (Official Repository).” [Online]. Available: <https://github.com/jpmorganchase/quorum>. [Accessed: 29-Feb-2020]
- [96] A. Baliga, I. Subhod, P. Kamat, and S. Chatterjee, “Performance evaluation of the quorum blockchain platform,” 2018.
- [97] I. Bashir, *Mastering Blockchain: Distributed ledger technology, decentralization, and smart contracts explained, 2nd Edition*, 2ndn ed. Birmingham: Packt Publishing, 2018.
- [98] Corda, “Corda.” [Online]. Available: <https://www.corda.net/>. [Accessed: 29-Feb-2020]
- [99] JPMorgan, “Constellation.” [Online]. Available: <https://github.com/jpmorganchase/constellation>. [Accessed: 29-Feb-2020]
- [100] JPMorgan, “Tessera.” [Online]. Available: <https://github.com/jpmorganchase/tessera>. [Accessed: 29-Feb-2020]
- [101] D. Ongaro and J. Ousterhout, “In Search of an Understandable Consensus Algorithm,” in *2014 USENIX Annual Technical Conference (USENIX ATC 14)*, Philadelphia, PA, 2014, pp. 305–319 [Online]. Available: <https://www.usenix.org/conference/atc14/technical-sessions/presentation/ongaro>. [Accessed: 29-Feb-2020]
- [102] L. Lamport and others, “Paxos made simple,” *ACM Sigact News*, vol. 32, no. 4, pp. 18–25, 2001.
- [103] Y. Lin, “Istanbul Byzantine Fault Tolerance.” [Online]. Available: <https://github.com/ethereum/EIPs/issues/650>. [Accessed: 29-Feb-2020]

- [104] JPMorgan, “7 nodes (Official Website).” [Online]. Available: <https://github.com/jpmorganchase/quorum-examples>. [Accessed: 29-Feb-2020]
- [105] P. Namisiko Wanjala, *A Beginner’s Journey to Ethereum’s Smart Contracts: Engineering Smart Contracts and DApps in Solidity and Web3.Js*. 2018.
- [106] M. Wu, T.-J. Lu, F.-Y. Ling, J. Sun, and H.-Y. Du, “Research on the architecture of Internet of Things,” in *2010 3rd International Conference on Advanced Computer Theory and Engineering (ICACTE)*, 2010, vol. 5, pp. V5–484.
- [107] H. B. Attia, L. Kahloul, and S. Benharzallah, “A New Hybrid Access Control Model for Security Policies in Multimodal Applications Environments,” *Journal of Universal Computer Science*, vol. 24, no. 4, pp. 392–416, 2018.
- [108] N. Johnson, *Ethereum Name Service*. Ethereum Name Service, 2018 [Online]. Available: <https://github.com/ensdomains/ens>
- [109] H. Vescent, K. Young, K. H. Duffy, M. Sabadello, D. Zagidulin, and J. Caballero, *A Comprehensive Guide to Self Sovereign Identity*, 2nd ed. The Purple Tornado, 2019.